





ECA No. A272002, A273003 & 5854-7DSSDD

St. Edmunds Landfill Site: Annual Monitoring Report (2024)

Municipality of Northern Bruce Peninsula, Ontario

Submitted to:

Municipality of Northern Bruce Peninsula 56 Lindsay Road 5 Lion's Head, ON NOH 1W0

Submitted by:

GEI Consultants Canada Ltd. 1260 2nd Avenue East, Unit #1 Owen Sound, ON N4K 2J3 519.376.1805 April 30, 2025 Project No. 2402868



andrae Welson

Andrea Nelson Project Manager

Table of Contents

| 1. | INTRODUCTION | 1 |
|--------------------------------------|---|-----------------------|
| 2. | SITE USAGE | 1 |
| 3. 3.1. 3.2. | SITE LIFE EXPECTANCY Past Landfill Development | |
| 4. 4.1. 4.2. 4.3. | SITE DEVELOPMENT AND OPERATIONS Method of Operation | 3 3 |
| 5. 5.1. 5.2. 5.3. | LANDFILL MANAGEMENT Vector, Vermin and Wildlife Control Litter Control Public Complaints | 4 |
| 6. | BURNING OPERATIONS | 5 |
| 7.5. 7.6. 7.7. 7.8. 7.9. | RECYCLING AND WASTE REDUCTION Blue Box Materials | 6 7 7 8 8 |
| 8.1. | Summary of Hydrogeologic Setting | 9 9 .10 |
| 9. 9.1. 9.2. 9.3. | MONITORING REQUIREMENTS Monitoring Locations | . 10 . 10 . 11 |
| 10. 10.1. | DETERMINATION OF REASONABLE USE CRITERIA FOR THE SITE Determination of Action Levels | 12 |

| 10.2. | Background Water Quality | .13 |
|-------|---|-----|
| 10.3. | Calculation of Objective Levels | .14 |
| 10.4. | Surface Water – Provincial Water Quality Objectives | .14 |
| 11. | MONITORING RESULTS AND DISCUSSION | 15 |
| 11.1. | Leachate Generation | .15 |
| 11.2. | Leachate Characterization | .15 |
| 11.3. | Groundwater Migration and Compliance Assessment | .16 |
| | 11.3.1. Cross-gradient (Northeast) | |
| | 11.3.2. Cross-gradient (East) | .17 |
| | 11.3.3. Downgradient (South to Southeast) | |
| | 11.3.4. Cross-gradient (West) | |
| 11.4. | Groundwater Quality Summary | .19 |
| | SURFACE WATER QUALITY AND STORMWATER MANAGEMENT | 20 |
| | Surface Water Quality | |
| 12.2. | Stormwater Management: Trigger Levels | .21 |
| 12.3. | Review of Surface Water Monitoring Network and Trigger Levels | .22 |
| 13. | METHANE GAS PRODUCTION | 22 |
| 14. | CONCLUSIONS | 23 |
| 15. | RECOMMENDATIONS | 24 |

| List of Tak | oles [Em | bedded | in Re | port] |
|-------------|----------|--------|-------|-------|
| | | | | |

| Table 4-1. St. Edmunds Landfill Site – Hours of Operation | 4 |
|--|---|
| Table 7-1. Northern Bruce Peninsula – Population Proportions | |
| Table 7-2. Northern Bruce Peninsula – Diversion Estimates | 6 |
| Table 7-3. Summary of Waste Diversion (Tonnes) | 8 |
| Table 9-1. Water Quality Monitoring Program1 | 1 |
| Table 11-1. Groundwater Quality Summary - Categorization1 | 9 |
| Table 12-1. Trigger Parameters and Levels2 | 1 |
| Fable 15-1. Recommended Monitoring Program (2025)2 | 4 |
| Table 11-1. Groundwater Quality Summary - Categorization | |

Tables [End of Report]

Table 1: Landfill Volume Capacity

Table 2: Site Specific Background & Guideline B-7-1 RUC Determination (Overburden)

Table 3: Site Specific Background & Guideline B-7-1 RUC Determination (Bedrock)

Table 4: Overburden Groundwater Quality Summary - 2024

Table 5: Leachate Characterization

Table 6: Bedrock Groundwater Quality Summary - 2024Table 7: Summary of Surface Water Quality Results - 2024

Figures [End of Report]

Figure 1: Site Location Map

Figure 2: General Site Plan

Figure 3: Site Layout and Existing Conditions

Figure 4: Overburden Groundwater Flow

Figure 5: Bedrock Groundwater Flow

Figure 6: Final Contours

Figure 7: Chloride, Alkalinity and Potassium Concentrations

Figure 8: Surface Water Management Works – 2015 Air Photo

Appendices [End of Report]

Appendix A Environmental Compliance Approvals

Appendix B Correspondence

Appendix C Borehole Logs

Appendix D Cross-Sections

Appendix E Summary of Historical Groundwater Elevations

Appendix F Laboratory Analytical Reports

Appendix G Historical Groundwater Quality Results (Tables and Graphs)

Appendix H Historical Surface Water Quality Results (Tables and Graphs)

AN/MN:clw

1. INTRODUCTION

The St. Edmunds landfill site is located west of Provincial Highway No.6 and approximately 4.5 km southwest of Tobermory, at the intersection of Warner Bay Road and McArthur Road. The 82-hectare site is situated on Lots 46 and 47, Concession 3 West of Bury Road (W.B.R.), in the former Township of St. Edmunds, Municipality of Northern Bruce Peninsula, County of Bruce, where shown on Figure 1. Landfill operations are conducted under Provisional Certificates of Approval (CofA) No. 273002 and No. 272003. In addition, CofA No. 5854-7DSSDD was issued on July 11, 2008, for the stormwater management facility at the Site. Copies of the Approvals are provided in Appendix A.

Based on previous reports, the landfill was owned and operated by the Township of St. Edmunds from the late 1970's (i.e., sometime between 1977 and 1980) to 1999. The Municipality was formed in 1999 as the result of the amalgamation of the former Townships of Eastnor, Lindsay, and St. Edmunds, as well as the Village of Lion's Head. Prior to 1999 each respective township was serviced by a landfill, of which the Municipality assumed ownership upon amalgamation. As a result, the St. Edmunds landfill is one of three landfill sites that service the Municipality and is approved to accept non-hazardous municipal wastes generated from within its geographic boundaries.

Approval No. A273002 was issued by the Ministry of the Environment, Conservation and Parks (MECP) on March 14, 1980, and was amended on July 10, 1998. Under this Approval, the site has an approved useable area of 3.3 ha for landfilling within the 82-ha property. The Approval references the Plan of Development and Operation Report (Henderson, Paddon and Associates Ltd., July 1995), hereafter referred to as the PDO, under which a volume of 141,000 m³ for waste and daily cover is approved.

CofA No. A273003, which was issued in October 1993 and amended in July 1998, approves a stump disposal area of 2.02 ha with a volumetric capacity of 54,700 m³. This area is located to the north of the approved landfill footprint and within the 82-ha property. The limits of the approved landfill and stump disposal areas are shown on Figure 2.

The approval for municipal and private sewage works (i.e., CofA No. 5854-7DSSDD) approves an on-site stormwater management facility for a total drainage area of 10.2-ha consisting of the existing 3.33-ha municipal waste disposal area, the 2.02-ha stump disposal area, and a 4.67-ha area for the access road and recycling facility.

According to Condition 14 of CofA No. A273003, a monitoring report providing a yearly summary of the site monitoring and operations is required, and Condition 6(2) of CofA No.5854-7DSSDD requires that an annual performance report on the stormwater management works be completed by April 30th of each year. Although the stormwater management reports are only to be made available, upon request, to the District Manager, this annual monitoring and operations report summarizes the previous year's operations, waste quantities, and groundwater and surface water monitoring results and has been completed to meet the requirements of all the compliance approvals for the St. Edmunds Landfill Site.

2. SITE USAGE

According to Statistics Canada's 2021 census data, the Municipality of Northern Bruce Peninsula has a permanent population of 4,404 and a total of 5,101 dwellings, of which 2,206 are occupied by permanent residents. For the purpose of waste generation and usage of waste management services, the contributing population is more accurately estimated to be 5,610. This is based on the method adopted by Waste Diversion Ontario (WDO) where 6 seasonal households are equivalent to 1 permanent household and an average of 2.5 people per permanent household. The former Township of St. Edmunds is estimated to account for approximately 40% of the population in the Municipality of Northern Bruce Peninsula, which equates to approximately 2,245 persons.

The St. Edmunds landfill is currently one of three landfills approved for the disposal of solid non-hazardous waste that services the Municipality of Northern Bruce Peninsula. The landfill services the residential and industrial, commercial, and institutional (IC&I) sectors located within the Municipality.

As of January 2017, the entire Municipality is serviced by curb-side waste and recycling collection. Residents are limited to 2 bags per week. Although the Municipality provides waste collection services on a weekly basis to the residents of the former Township of St. Edmunds, waste from the curbside collection services is currently transported to the Eastnor landfill site for logistical reasons. A significant portion of the waste currently disposed of at the St. Edmunds landfill originates from the IC&I sector, some of the main users include the following:

- Parks Canada
- The Chi-Cheemaun Ferry Service
- The Ministry of Transportation
- Several campgrounds and small businesses

Activities that currently occur at the St. Edmunds landfill site include landfilling of residual waste and wood waste, burning of clean wood wastes, collection of blue box materials, electronic waste, and mattresses, stockpiling of scrap metal and tires, as appropriate, and goods exchange through their reuse building. According to Site records, an estimated 595 tonnes (metric) of waste was landfilled at the St. Edmunds landfill site during the reporting period.

3. SITE LIFE EXPECTANCY

3.1. Past Landfill Development

Area A

Area A has been filled and capped to final contours and is closed. According to the 2005 Annual Report prepared by H&P (2006), topsoil was placed on approximately 90 to 95% of this area and seeding was carried out in 1993/1994. According to the PDO, the total volume of waste, interim and final cover, and topsoil placed in this area was 45,100 m³, and the remaining 1,310 m³ of final cover and topsoil was applied in 2004. Based on the historic development of this area, it is unknown if a low permeability soil was applied to the base prior to waste placement.

Area B

In 2007, Area B was filled to capacity with waste and interim cover and was subsequently closed. Approximately half of Area B was capped with clay cover in 2004 and capping of the remainder of the area was completed in 2008. The application of final topsoil and seeding has yet to be completed for the latter half of Area B.

According to the PDO, a 600 mm thick clay/silt attenuation pad was placed at the base of Area B in 1993 prior to the initiation of landfill activities in this area. Due to the permeability of the soils, shallow bedrock, and relatively highwater table in the vicinity of the landfill, the base preparations were completed to aid in the attenuation of leachate generated from the landfill.

3.2. Active Landfilling Areas

In 2007, a topographic survey of the entire landfill area was completed to determine the remaining Site capacity following the closure of Area A and partial closure of Area B. Based on a comparison of the digital terrain models from the survey to the proposed final contours (Figure 6), the remaining capacity for waste and interim cover was determined to be approximately 40,500 m³ as of the end of 2007. In 2008, the Municipality completed the base

preparations of Area C which, similar to Area B, included the application of 600 mm of low permeability clay/silt soil to the landfill base.

Since then, the remaining capacity has been determined by subtracting the estimated volumetric capacity used derived from annual surveys of the active fill areas. Using the elevation difference between the December 2023 and December 2024 topographical surveys, a capacity of 2,095 m³ was calculated to have been used. Assuming 20% interim cover by volume, the amount of landfilled waste in 2024 is estimated to be 1,675 m³.

In 2024, landfilling operations continued within Area C, where shown on Figure 3. In consideration of the limited remaining capacity, a comprehensive survey of the entire landfill footprint was completed in 2023 to provide an updated and more accurate assessment of the remaining site life. The survey data was used in conjunction with the approved final contours outlined in the PDO (which account for waste and interim cover) to confirm the remaining airspace capacity and site life. In consideration of the comprehensive survey completed in 2023, as of the end of 2024 the St. Edmunds landfill site has a remaining capacity of about 3,600 m³, or a remaining site life of approximately 1.5 to 2 years. Although not required by the Approval, it is recommended that a Closure Plan be completed for submission to the MECP in 2025, prior to the anticipated Site closure in 2027.

Based on an average fill rate over the last five years of 2,180 m³, the remaining site life is approximately two years. It is noted that the volume for final cover and topsoil of 7,470 m³ remains unused. Based on the Long-Term Waste Management Plan for the Municipality, once the St. Edmunds Landfill reaches capacity, residual waste will be directed to the Eastnor Landfill Site. A summary of the estimated annual fill volumes (since 2018) is provided in Table 1.

4. SITE DEVELOPMENT AND OPERATIONS

4.1. Method of Operation

The approved landfill footprint has been divided into three areas, Areas A, B and C, as shown on Figure 2. The approved bottom elevation for disposal of waste in Area A is 201.8 metres above sea level (masl) and for Areas B and C is 202.2 masl. It is noted that, based on a survey completed in November 2022, these elevations presented have been lowered by 0.7 meters to suit the UTM derived coordinates.

The approved final contours for the landfill, including final cover, are shown on Figure 6. Based on the original Plan of Development and Operations prepared by Ainley and Associates (1978), the maximum elevation for waste disposal is 209.9 masl (or 209.2 masl when adjusted to suit the UTM derived coordinates). Side slopes of the approved final contours are approximately 4:1 with final top grades of approximately 5%. To date, landfill operations have generally occurred from the southwest to the northeast within the approved landfill footprint and Area A and Area B have been capped and closed. In 2024, landfilling operations continued progressing within Area C, where shown on Figure 3.

The Municipality currently uses the area-ramp method of landfilling and uses a packer to help maximize the waste density achieved at the Site. The area-ramp method is efficient with respect to space utilization and requires less cover material than other methods. Continued attention should be given to ensuring that waste within the active area of the landfill is sufficiently covered in a timely fashion with an adequate amount of material.

4.2. Periods of Operation – Landfill Hours

Currently the Site is open to the public/vehicles hauling waste during the following operating hours:

Table 4-1. St. Edmunds Landfill Site – Hours of Operation

| Date | Monday | Tuesday | Wednesday | Thursday | Friday | Saturday | Sunday |
|-------------------|--------|---------|--------------|----------|--------|-------------|--------|
| Nov 1 to March 31 | Closed | Closed | 10:00 – 4:00 | Closed | Closed | Closed | Closed |
| April 1 to Oct 31 | Closed | Closed | 9:00 - 5:00 | Closed | Closed | 9:00 - 5:00 | Closed |

A sign at the access gate notes the hours of operation. A site attendant is present during operating hours. When the site is closed to the public, a locked gate across the entrance road controls access to the site. Waste may be received outside the hours of operation, by appointment and under the supervision of a trained attendant.

4.3. Waste Receiving Station

In 2009, the Municipality completed the construction of a waste receiving station at each of their landfill sites (Eastnor, Lindsay, and St. Edmunds). The waste receiving station at the St. Edmunds Landfill Site is located approximately 150 m north of the landfill along the site access road. The waste receiving station includes a weigh scale and transfer bins for recyclables and waste to be landfilled. The collection bins are available to the public for waste drop-off and sorting. Access to the landfill area is limited to contractors and municipal employees.

5. LANDFILL MANAGEMENT

5.1. Vector, Vermin and Wildlife Control

At the St. Edmunds landfill site there are several types of vermin, vector and wildlife that have been identified as requiring some form of precautionary management plan, including bees/wasps, coyotes, gulls, turkey vultures, rodents, and black bears. Control can effectively be accomplished by applying cover material after each day of refuse deposition and through good housekeeping (i.e., daily litter pick-up, regular site inspection and proper waste segregation practices). An electric fence also lines the perimeter of the waste disposal area to discourage black bears and coyotes from entering the active area of the landfill. The 'Vector and Vermin Control/Management Plan' should be implemented should vermin, vector, and/or wildlife become a nuisance.

It is noted that the construction of the waste receiving station at the site entrance limits public access to the site which has resulted in improved waste segregation and refuse deposition practices.

5.2. Litter Control

Continued litter pick-up is recommended to help prevent fire hazards and unsightliness. The application of cover material each day the site is operational will help with litter control. According to the Municipality, litter pick-up is to occur on a regular basis, with a thorough pick-up scheduled at the end of every month.

5.3. Public Complaints

The Municipality reports that they did not receive any complaints regarding the existence or operations of the St. Edmunds landfill site during the year of 2024.

6. BURNING OPERATIONS

As per the PDO, the burning of clean wood and brush in accordance with the MECP Guideline "Burning at Landfill Sites" is allowed. Any brush, trees and clean wood material should be stockpiled separately. Before burning takes place, the Chief Fire Official must be notified of the date and time the burn is to take place, in accordance with the Municipality of Northern Bruce By-Law No. 2000-24, as amended.

Burning at the site is to be restricted to clean, dry wood wastes such as brush, trees, and lumber. These wood wastes are to be stockpiled in a designated burn area located on-site and be limited to an area no larger than 6 x 6 meters. Burning of designated wood waste is to be carried out in an area at least 30 meters away from the active landfilling area. Additionally, an area of 4.5 meters around the burn pit should be kept free of vegetation.

Burning is to occur only on clear, dry, windless days and should be conducted under the supervision of an attendant. The site attendant is responsible for the removal of any non-wood wastes from the pile prior to burning, as well as regularly removing cold ashes from the burn area for disposal in the active landfill area. The attendant must fully extinguish the fire at the end of the day.

In 2024, approximately 180 tonnes of clean wood waste and brush was reportedly received at the Site. This material was presumably burned.

7. RECYCLING AND WASTE REDUCTION

Currently, refuse segregation and recycling services are available at all three municipal landfill sites. Furthermore, to encourage blue-box recycling, this waste diversion stream is included in the curb-side collection services provided to the entire Municipality.

The site attendant/supervisor is responsible for the proper segregation and recycling of refuse at the Site. Waste segregation and recycling occurs in the waste transfer and receiving area for ease of access and supervision, where shown on Figure 3. It is important that the Municipality continue to remove stockpiles of recyclable goods on a regular basis to prevent clutter and to maintain an aesthetically acceptable site. The following goods are separated from the solid waste and stockpiled in designated areas that are clearly labelled.

7.1. Blue Box Materials

In addition to curbside collection of recyclable materials, the Municipality currently provides three depot locations for drop-off of recyclables, each associated with the existing Municipal Landfill Sites. The Municipality accepts mixed recyclables, meaning that all accepted recyclable materials can be placed into one bin at the Municipality's Recycling Depots/Facilities. Recyclables are then transferred to a Material Recovery Facility (MRF) in Mount Forest. This single-stream recyclable processing uses separation technologies specifically designed for a mixed recyclable stream. The current list of recyclable items accepted by the Municipality includes the following:

- glass
- steel paint cans
- aluminum cans, foil, and pie pans
- paper, boxboard and cartons
- various types of plastic including, but not limited to, PETE, HDPE, LDPE, PP, and PVC

Waste Management has provided an analysis of the blue box recyclables diverted from the Eastnor, Lindsay and St. Edmunds landfill sites located in the Municipality of Northern Bruce Peninsula for the 2024 calendar year. It is noted that the amount of blue box recyclables diverted, specifically from the former Township of St. Edmunds, is not available. However, an estimate has been completed based on the percentage of the estimated population contributing recyclables from within the former Township of St. Edmunds.

The estimated population contributing waste to each municipal landfill is as follows:

Estimated Contributing Population Site **Total Persons** Percent 45% Eastnor 2,545 Lindsay 840 15% St. Edmunds 2,245 40% **Total** 100% 5,610

Table 7-1. Northern Bruce Peninsula – Population Proportions

Based on the estimated proportion of the municipal population in each of the former Townships, the estimated recyclables diverted from each of the municipal landfills (in tonnes) for the 2024 calendar year is presented below:

| Landfill Site | Total Diverted (Tonnes) |
|---------------|-------------------------|
| Eastnor | 217.8 |
| Lindsay | 72.6 |
| St. Edmunds | 193.6 |
| Total | 484.00 |

Table 7-2. Northern Bruce Peninsula – Diversion Estimates

The total combined amount of blue box recyclables collected in 2024 by Waste Management for the Municipality was 484 tonnes. Based on the proportion of the Municipality's population serviced by the St. Edmunds landfill (i.e., 40%), an estimated 194 tonnes of the blue box recyclables were diverted from the St. Edmunds landfill.

7.2. Used Tires

In January 2019, tires were the first material to be moved to the individual producer responsibility (IPR) framework under the recent waste diversion legislation, the Waste-Free Ontario Act. The Municipality continues to collect and stockpile used tires at all three of its landfills. As a registered collector, the Municipality accepts used tires from residents. These tires are recycled by tire producers (or Producer Responsibility Organizations), who are now directly responsible and accountable for meeting mandatory collection and recycling targets for used tires. According to the site records, 204 tires weighing an estimated 2.65 tonnes were received at the St. Edmunds landfill in 2024.

According to O.Reg.347 s.6(3), there must be fewer than 5,000 tire units at any given time. The volume of tires within an individual stockpile should not exceed 300 m³. There must be greater than 15 meters between the stockpile and the property line, buildings, and the active area of the landfill, and greater than 30 meters separation between the tire pile and the burn pile. Tires should be stockpiled in an area where there is no vegetation within 4.5 meters. Individual stockpiles should be separated from each other and from other waste piles by a minimum of 6 meters.

7.3. Scrap Metal and White Goods

The Municipality accepts scrap metal at the Site, including propane tanks and both chlorofluorocarbon (CFC)-containing (i.e., air conditioners, dehumidifiers, freezers, refrigerators, and water coolers) and non-CFC-containing white goods. White goods and marketable scrap metals should be stockpiled separately. Site records indicate that 22.8 tonnes of scrap metal (including propane tanks and white goods) was diverted from the waste stream at the St. Edmunds landfill site in 2024. Scrap metal and white goods are periodically removed from the Site for recycling.

Propane Tanks

Empty propane tanks should be stored on the ground surface in a segregated area. Tanks should be stored in a manner that minimizes the potential for cylinder valves to be damaged or broken (i.e., single layer and upright position).

White Goods

In compliance with Ontario Regulation 463/10, CFC-containing white goods are to be properly drained by a certified technician and then tagged to indicate that the CFC's have been removed, prior to the removal of white goods from the site. White goods and scrap metal are collected by a hauler on an as needed basis for salvage.

7.4. Automotive Batteries

Batteries are to be stored in a single layer under a roof in order to prevent precipitation from coming in contact with the batteries and in a manner that provides secondary containment in the event of leakage. Currently, batteries are stored in a site shed to prevent spills or weathering. According to the Site operational records, no battery units were received at the site during the reporting period.

7.5. Electronic Waste

The Municipality has been collecting electronic waste since 2010. Initially the electronic waste diversion program was operated by the Ontario Electronic Stewardship (OES) who was responsible for electronics recycling in Ontario on behalf of the electronics industry. In January 2021, Electrical and Electronic Equipment (EEE), specifically information technology, telecommunications, and audio-visual equipment (ITT/AV), became the third material to be moved to the individual producer responsibility (IPR) framework under the Waste-Free Ontario Act. OES did not operate a program for lighting; however, the producer responsibility for lighting equipment came into effect in January 2023.

The Municipality continues to collect and stockpile electronic waste at all three of its landfills. Electronic waste can be dropped off free of charge. At the St. Edmunds landfill site electronic waste is stored and locked in a steel shipping container. The municipality reported receiving 9.2 tonnes of electronic waste at the site in 2024.

7.6. Mattresses

In 2012, the Municipality began diverting mattresses as an additional waste diversion stream. According to the Site operational records 126 mattresses, totaling approximately 1.89 tonnes, were received at the St. Edmunds landfill in 2024. These mattresses are stored in a dry storage area at the Site and are removed periodically for recycling by Recyc-matelas Inc.

7.7. Reuse Building

Reuse buildings are located at the St. Edmunds and Eastnor landfill sites for exchange of re-usable goods. In 2024, the Municipality recorded receiving 9.1 tonnes of re-usable goods at the St. Edmunds landfill site. These goods are free for residents to access for their use.

7.8. Hazardous and Special Products (HSP)

In October 2021, Hazardous and Special Products transitioned to the individual producer responsibility framework. The HSP program for the Municipality is operated by Bruce County through the Orange Drop Program. In the Municipality of Northern Bruce Peninsula, the County typically provides two to three collection events per year. Under the Orange Drop program residents can drop-off hazardous materials free of charge.

Based on the Household Hazardous Waste Program summary of materials reportedly received by the County, the amount of HSP collected through the Orange Drop Program was estimated to be 15.3 tonnes during the reporting period. Based on the proportion of the Municipality's population serviced by the St. Edmunds landfill (i.e., 40%), an estimated 6.12 tonnes of HSP was diverted from the St. Edmunds landfill through the Orange Drop Program.

7.9. Leaf and Yard Waste

Although the Municipality promotes home composting for wet organics through the distribution of backyard composting bins, a leaf and yard waste composting pile is maintained at the Site. The municipality reported receiving approximately 106 tonnes of leaf and yard waste at the site in 2024. This pile should be turned on a regular basis. Surface water run-off generated from this pile should be either prevented or managed. If the pile becomes odorous, it should be placed in the active face of the landfill and immediately covered. Topsoil generated from this service can be used for placement over the final cover.

7.10. Waste Reduction Summary

Based on the sum of the diversion programs at the St. Edmunds landfill site and local depot, approximately 342 tonnes of material was diverted from the landfill in 2024. A summary of the quantity of materials diverted since 2016 is provided below:

| Table | 7-3 | Summary | of Waste | Diversion | (Tonnes) |
|-------|------|------------|-----------|-----------|------------|
| lable | 7-3. | Sullillary | UI VVaste | Diversion | (lullies) |

| Materials Diverted | 2016 | 2017 | 2018 | 2019 | 2020 | 2021 | 2022 | 2023 | 2024 |
|-------------------------|-------|-------|-------|-------|-------|-------|-------|--------|-------|
| Blue Box Recyclables | 173.7 | 208.4 | 220.3 | 194.8 | 208.8 | 227.4 | 212.2 | 180.2 | 193.6 |
| Tires | 1.0 | 1.3 | 2.2 | 1.5 | 1.7 | 2.6 | 2.5 | 11.42* | 2.65 |
| Scrap Metal/White Goods | 29.6 | 29.3 | 36.4 | 36.1 | 64.2 | 59.3 | 35.6 | 25.7 | 22.8 |
| Automotive Batteries | 0.07 | 0.05 | 0.02 | 0.11 | 0 | 0.23 | 0.13 | 0 | 0 |
| Bale Wrap | 22.6 | 1.7 | 1.1 | 0 | 0 | 0.14 | 0 | 0 | 0 |
| Electronic Waste | 8.3 | 3.65 | 14.0 | 8.12 | 4.94 | 5.32 | 3.31 | 1.65 | 9.22 |
| Mattresses | 1.4 | 1.2 | 1.65 | 1.77 | 2.4 | 3.0 | 2.3 | 1.97 | 1.89 |
| HSP | 5.62 | 8.02 | 8.53 | 6.77 | 3.54 | 6.2 | 6.3 | 6.34 | 6.12 |
| Leaf and Yard Waste | 11.9 | 130 | 25.4 | 37.9 | 40.4 | 60.3 | 34.0 | 246 | 106 |
| Total | 254.2 | 383.6 | 309.6 | 287.1 | 326.0 | 364.5 | 296.3 | 473.3 | 342.3 |

Note: All values are presented in tonnes. NA = Not Available. * Tires removed from the site

The variability in diversion is primarily attributed to the leaf and yard waste contribution. It is noted that the quantity of diverted materials does not account for the clean wood and brush (i.e., burnable) that is also diverted.

8. SITE SETTING

8.1. Summary of Hydrogeologic Setting

The St. Edmunds landfill site is located within the physiographic region known as the Bruce Peninsula (Chapman and Putnam, 1984). The region is characterized by generally flat topography with shallow overburden and abundant bedrock exposed at ground surface. Regionally, the bedrock dips gradually to the south-west towards Lake Huron. The upper bedrock is of the Guelph Formation and primarily consists of dolomite. The exposed bedrock surfaces in the area are scoured from glacial activity and are typically irregular due to weathering.

Based on the Hydrogeologic Investigation (H&P et al, 1989), the overburden at the site ranges in thickness from approximately 1.4 m to 3.7 m and generally consists of two units including (i) sand and gravel and (ii) silt-till. According to the borehole logs for the monitoring wells installed as part of the Hydrogeologic Investigation, the sand and gravel unit is generally found to the northwest and in close proximity to the landfill while the silt till soils are generally associated with the low-lying areas to the south, east, and west of the landfill. The underlying bedrock is generally described as poorly fractured dolostone. Copies of the borehole logs for wells O-1 to O-9 and B-1 to B-5 are provided in Appendix C and cross-sections are provided in Appendix D. It is noted that borehole logs for piezometers P-1 through P-3 and wells W-1 to W3-03 are not available for inclusion in this report. Efforts by the Municipality to locate/obtain the borehole logs have been unsuccessful.

The topography at the site generally slopes gradually towards the south/southwest. Based on groundwater elevations in the monitoring wells, groundwater flow through the shallow overburden and bedrock is inferred to be in a south to south-westerly direction towards Lake Huron (Figure 4 and Figure 5).

8.2. Existing Surface Water Features at the Site

8.2.1. Regional Drainage System

Generally, drainage from upgradient lands is intercepted by the ditch system along McArthur Road, which directs stormwater in a southeasterly direction to Warner Bay Road, then southwesterly towards Warner Bay. This drainage area upstream from the landfill is approximately 222-ha.

As shown on Figure 2, drainage from the landfill site is generally directed in a southerly direction towards Warner Bay Road. At the confluence point between the upgradient drainage system and the site drainage system, stormwater is channeled into two separate ditches, herein referred to as the 'north ditch' and 'south ditch', which continue to flow southwesterly along Warner Bay Road.

Two ponds are located at the southwest portion of the landfill site property, and approximately 800 meters from the landfill footprint. The historical extraction of cover material from a borrow pit (licensed by the Ministry of Natural Resources) resulted in the formation of these ponds, herein referred to as the 'borrow pit ponds' or 'BPP1 and BPP2'. The north ditch along Warner Bay Road drains into BBP2. Discharge water from BBP2 discharges via a drainage ditch that connects to the south drainage ditch of Warner Bay Road and flows towards Lake Huron.

8.2.2. Site Stormwater Drainage System

According to the PDO, stormwater drainage was generally characterized by sheet flow in a south/southwesterly direction prior to site development. However, in 1993/1994 drainage improvements were made to enable landfill operations to take place in Areas B and C, and to relocate an existing ditch system away from the toe of the landfill footprint.

Currently, drainage from the landfill area is directed to a ditch system constructed to the south of the landfill footprint (Figure 8). When this drainage system was constructed, stormwater flow into this area was mixed with regional flow from the northeast. However, with consultation from the MECP and consistent with the Approval for stormwater management, regional surface water drainage from the northeast has been redirected to the southeast along McArthur Road. Run-off from the landfill area is directed to the south towards Warner Bay Road, which is located 400 m from the southern limit of the landfill footprint. It then mixes with water from the northern ditch and discharges to the Borrow Pit Pond (BPP2).

8.2.3. Municipal Sewage Works Approval No. 5854-7DSSDD

On July 11, 2008, an Approval for Municipal Sewage Works (i.e., CofA No.5854-7DSSDD) was issued for the stormwater management works for the site. The drainage area of the stormwater management works consists of 10.2-ha, which includes the landfill area, the stump disposal area, and an additional 4.67-ha for access roads and the recycling area. As part of the CofA, several modifications to the existing drainage system were required, which are described in the 'Surface Water Management Report, St. Edmunds Landfill Site, Municipality of Northern Bruce Peninsula' (G&M, August 2007). Construction of these modifications to the stormwater management works was completed in about 2011.

9. MONITORING REQUIREMENTS

9.1. Monitoring Locations

9.1.1. Groundwater

Groundwater and surface water quality monitoring has been completed at the site since 1988. In recent years the sampling program has consisted of sampling twice annually, in the spring and the fall, from 11 overburden monitoring locations including wells O-1, O-2, O-3, O-4, O-6, O-7, O-8, O-9, W-1, W-2, and W-3/03, and from seven bedrock monitoring points at five different locations, including wells B-2, B-3, B-4 and B-5, and the bedrock piezometer nest (i.e. P-1, P-2, and P-3). During the reporting period, samples could not be collected from P-1 or P-2 due to the presence of an obstruction. Further efforts to re-establish these monitoring locations will be made in 2025.

It is noted that monitoring wells B-1 and O-5 have not been sampled since 1998 and 1993, respectively, and are assumed to be destroyed. There are no plans to replace these wells as the existing monitoring network continues to sufficiently monitor site compliance.

9.1.2. Surface Water

While surface water quality monitoring was first completed at the Site in 1988 (i.e., SW-1 only), a more comprehensive sampling program was initiated in 1995. Currently, surface water quality monitoring is completed at five (5) locations to support the requirements of the Approvals for both Waste Disposal and Stormwater Management. The surface water sampling program for the Site includes the following:

- **<u>S-1:</u>** Located in the external drainage ditch east of the landfill footprint. Representative of background surface water flowing from McArthur Road.
- <u>S-6:</u> Located in the stormwater management pond immediately southwest of the landfill footprint. Representative of surface water directly downgradient of the landfill.
- <u>S-6A:</u> Located downstream of the confluence of ditches draining surface water from the stormwater management pond and McArthur Road. Representative of surface water downgradient of the landfill after mixing with background water.
- **<u>S-8:</u>** Located in the north ditch prior to discharging into the borrow pit pond (i.e. BPP2).
- <u>S-9:</u> Located in the outlet creek west of BPP2. Represents surface water discharging from the site.

It is noted that surface water sampling from S-1, S-6 and S-9 is required under the CofA for Municipal Sewage Works. The additional locations are sampled to support the assessment of potential impacts and attenuation at the site. Surface water sampling locations are presented on Figure 2 and Figure 8.

9.2. Monitoring Program

Water quality monitoring at the Site has been completed since 1988. The current monitoring program frequency of twice annual sampling in the spring and fall was initiated in 2006. The sampling program currently consists of sampling from eleven (11) shallow overburden wells, seven (7) bedrock monitoring locations and five (5) surface water sampling locations and is summarized as follows:

Table 9-1. Water Quality Monitoring Program

| SAMPLIN | G LOCATI | ONS | ANALYTICAL PARAMETERS | | | | |
|---|---|----------------------|--|--|--|--|--|
| | GROUNDWATER (Spring and Fall) | | | | | | |
| O-1 * O-2 * O-3 O-4 B2 B3 B4 | O-6 * O-7 * O-8 O-9 P1 P2 P3 | W-1 W-2 W-3/03 | Alkalinity, Hardness, Conductivity, pH, Ammonia, Nitrate, Nitrite, DOC, Chloride, Sulphate, Iron, Sodium and Potassium Calcium and Magnesium Leachate Indicator Parameter Additions: Boron *Leachate wells* (as of 2020) Spring: Same as the indicator list outlined above | | | | |
| B5 | | | <u>Fall:</u> Schedule 5: Column 1 (i.e., Comprehensive list for groundwater and leachate) which includes field parameters (i.e., pH and Conductivity) | | | | |
| | SURFACE WATER (Spring and Fall) | | | | | | |
| | S-1 S-6 S-6A S-8 S-9 | | Alkalinity, Hardness, Conductivity, pH, Total Ammonia, Nitrate, Nitrite, TKN, DOC, CBOD ₅ , Chloride, Sulphate, Phenols, Total Phosphorus, Iron, Boron and Zinc (Na, K, Ca, and Mg *) Field Parameters: pH, Conductivity, and Temperature | | | | |

It is noted that to address the MECP comments outlined in correspondence dated February 12th, 2019, a revised sampling program was proposed. The sampling program provided herein reflects MECP recommendations. Correspondence is included in Appendix B.

9.3. Sampling Procedures

For the groundwater sampling, the static groundwater level and well depth are measured in each monitoring well prior to purging three casing volumes of stagnant water from each well. Field personnel also check to ensure that all monitoring wells are properly secured and in compliance with O.Reg.903. After purging, monitoring wells are allowed to recharge with fresh groundwater before sampling occurs. Groundwater purging and sampling is conducted using dedicated Waterra™ tubing and inertial-type pumps. Samples are collected in laboratory supplied containers and are kept chilled following completion of the sampling program and sent within 24 hours of the sampling event to an accredited laboratory for analysis. Under the site-specific program, samples collected for indicator metals are placed in laboratory supplied containers without preservative and are filtered and preserved prior to analysis. Samples collected for metals under the comprehensive list are filtered in the field and placed in laboratory supplied containers with preservative.

Surface water samples are collected by submerging the appropriate sample container into the water body and removing the container when a sufficient volume of sample has been collected. During collection, contact with the bottom sediment is avoided to prevent stirring-up sediment. When collecting surface water samples, direct dipping of the sample bottle is acceptable unless the bottle contains preservative. For those samples requiring preservative, a clean unpreserved bottle is used to obtain the sample, which is then transferred into the appropriate preserved bottle. The temperature, conductivity and pH of the surface water is measured with a YSI multi-parameter field meter and recorded at the time of sampling.

The groundwater and surface water samples are kept chilled following completion of the sampling program and sent within 24 hours of the sampling event to the accredited laboratory for analysis. Copies of the 2024 laboratory analytical reports are provided in Appendix F.

10. DETERMINATION OF REASONABLE USE CRITERIA FOR THE SITE

10.1. Determination of Action Levels

MECP Guideline B-7 establishes the basis for determining what constitutes the reasonable use of groundwater on properties adjacent to landfill sites. This approach uses both the provincial maximum concentrations identified in the Ontario Drinking Water Standards (ODWS), revised June 2006, and the site-specific background values, to calculate acceptable concentrations at the Site boundary. By applying the RUC, the potential use of groundwater for domestic consumption will almost always provide the lowest allowable concentration limits, referred to as the objective levels. MECP Procedure B-7-1 provides technical details for the application of the reasonable use approach. A change in the quality of groundwater on an adjacent property, where the reasonable use is determined to be for drinking water, will be acceptable only where:

- i. Quality is not degraded by more than 50% of the difference between background concentrations and the Ontario Drinking Water Standards for non-health related parameters, and
- ii. Quality is not degraded by more than 25% of the difference between background concentrations and the Ontario Drinking Water Standards for health-related parameters.

Background concentrations are considered to be the quality of the groundwater prior to any contamination from landfill activities.

10.2. Background Water Quality

Background concentrations are the site-specific values that represent the quality of groundwater prior to any contamination from landfill activities. The background water quality was determined using data from overburden monitoring well O-1 and bedrock well B5, which are located cross-gradient from the landfill, where shown on Figure 4 and Figure 5. Groundwater quality results collected from these monitoring locations between 1988 and November 2017, provided in Appendix G, were used to calculate the average and 95th-percentile background concentrations for each indicator parameter to aid in the determination of RUC values for groundwater in the shallow overburden and the bedrock. The 95th-percentile concentration was used to reflect the RUC background concentrations for parameters with background concentrations that exceed the ODWS, including hardness. The background concentration ranges, averages, and resulting RUC values (i.e., objective levels) for the indicator parameters monitored at the Site are summarized in Table 2 and Table 3.

Overburden

In the past, monitoring location O-7 was used to assess the background concentrations in shallow groundwater at the Site. However, due to the elevated and highly variable concentrations of sulphate and hardness, a re-assessment of the background water quality was completed in 2017 using monitoring location O-1. Monitoring well O-1 is situated approximately 65 m west of the western corner of the landfill footprint and approximately 210 m from the northern property boundary.

Based on the analytical data for well O-1, the shallow background groundwater chemistry for the Site can generally be described as having low concentrations of chloride, typically less than 15 mg/L, a slightly basic pH of approximately 8.0, and an average conductivity in the range 590 μ S/cm. The average hardness and alkalinity concentrations are approximately 330 mg/L and 325 mg/L, respectively, which is representative of a carbonate-rich groundwater system. Consideration should continue to be given to the different variables that may influence the overall geochemical characteristics of the groundwater which result in a natural variability in background groundwater quality across the Site.

As demonstrated by the historical water quality results and trends noted at well O-1, the background groundwater quality shows naturally elevated hardness and sulphate concentrations, and elevated conductivity. While the concentrations of other parameters remain relatively stable, the conductivity and the concentrations of sulphate and hardness are highly variable and are typically greater in the fall. These parameter-specific fluctuations are interpreted to be the result of the shallow nature of the overburden wells that may consequently be influenced, to some degree, by 'widespread' surface water infiltration during precipitation events and/or the influence of the finer grained silty soils on the groundwater quality downgradient of the landfill. Based on this assessment, conductivity, hardness, and sulphate alone are not considered good leachate indicator parameters at the St. Edmunds landfill site. This is discussed in more detail in the following Sections of this Report.

Bedrock

The background groundwater quality within the bedrock unit was determined using data collected from well B5 during the period up to and including 2017. This well is located approximately 30 m southeast of the landfill footprint. In general, the shallow background groundwater quality within the bedrock can be described as having low concentrations of chloride (i.e., less than 15 mg/L), a slightly basic pH in the range of 8.0, and conductivity typically in the range of 400 to 1,000 μ S/cm. The average hardness and alkalinity concentrations are approximately 380 mg/L and 260 mg/L, respectively, which is representative of a carbonate-rich groundwater system.

It is noted that in the Fall of 2022, the chloride concentration at B5 spiked to 170 mg/L, exceeding the RUC of 130 mg/L, however, concentrations in 2023 returned to historical concentrations. Chloride concentrations again spiked in 2024, with concentrations measured to be 306 mg/L in the fall. Increased concentrations may be related to landfill operations occurring upgradient of this monitoring location.

10.3. Calculation of Objective Levels

Table 2 and Table 3 identify the concentrations of groundwater quality indicator parameters in overburden and bedrock, respectively, used for evaluating the acceptable level of contaminant concentrations at the site boundary. Background concentrations (Cb) are the site-specific values (discussed in the previous section). The provincial maximum concentrations (Cr) are identified in the Technical Support Document for Ontario Drinking Water Standards Objectives and Guidelines (June 2006), referred to herein as the ODWS. Acceptable concentrations at the site boundary (Cm), referred to as the Reasonable Use Criteria (RUC), are calculated from MECP Procedure B-7-1 using the following formula.

$$Cm = Cb + x(Cr - Cb)$$

Where:

Cm = Maximum concentration acceptable in groundwater beneath an adjacent property.

Cb = Background concentration.

Cr = Maximum concentration that should be present in groundwater for domestic consumption according to the ODWS.

X = 0.5 for non-health related parameters (AO/OG) and 0.25 for health-related parameters (MAC & IMAC).

AO = Aesthetic Objective

OG = Operational Guideline

(I)MAC = (Interim) Maximum Acceptable Concentration, Parameters Related to Health

It should be noted that if background concentrations exceed the ODWS, the objective level is set at the background concentration, as outlined by Procedure B-7-1. A summary of the 2024 analytical results, compared to the RUC and ODWS, is provided in Table 4 and Table 6.

To determine if leachate is impacting groundwater, individual indicator parameters were evaluated in conjunction with other indicator parameters and concentration trends. Wells with elevated and stable concentrations of the identified naturally elevated constituents, that show no increases in other leachate indicator parameters, are deemed un-impacted by landfill leachate. Additionally, comparison of known leachate impacted groundwater is compared to the groundwater chemistry at locations with naturally elevated concentrations to determine if leachate contributes to the elevated concentrations measured.

10.4. Surface Water – Provincial Water Quality Objectives

The purpose of surface water quality management at the Site is to achieve the requirements established in the Provincial Water Quality Objectives (PWQO) set out by the MECP. The PWQO were established to ensure that surface waters are of a quality, which is satisfactory for aquatic life and recreation. Areas that have water quality surpassing the PWQO requirements are to be maintained at or above the applicable objectives. Areas that have water quality that does not presently meet the PWQO are not to be degraded any further and are to be upgraded if practical. The 2024 surface water quality results compared to the PWQO are presented in Table 7.

For the evaluation of surface water quality at the St. Edmunds landfill site, consideration is given to the site-specific conditions within the local sub-watershed. Therefore, water quality at the site is monitored at a background location (i.e., S-1) to characterize the surface water quality entering the Site, prior to potential impacts from landfill leachate. Based on a review of the analytical data, the background surface water can be characterized as having low levels of nutrients and metals and average concentrations of conductivity, hardness, and alkalinity of approximately 615 μ S/cm, 310 mg/L and 255 mg/L, respectively. In general, chloride concentrations at this location have historically ranged between 1.7 mg/L and 60 mg/L. Elevated chloride concentrations are likely due to road salting activities along McArthur Road.

11. MONITORING RESULTS AND DISCUSSION

11.1. Leachate Generation

Leachate is produced when surface water percolates down through refuse resulting in impacted water that has the potential to migrate along the surface or in the ground. Landfill derived leachate that enters into the groundwater is often attenuated by natural mechanisms along the water migration pathway. The attenuation of leachate can occur by dilution, biologic activity, and geochemical mechanisms.

To determine the presence of potential impacts from leachate, several indicator parameters are monitored, and a trend analysis is conducted to determine changes in water quality over time. The following sections discuss the potential impacts to groundwater and surface water, with a focus on the water quality crossing the property boundaries and compliance with the RUC and PWQO. The results of the most recent groundwater monitoring and compliance with the RUC are provided in Table 4 and Table 6. The results of the most recent surface water quality monitoring and compliance with the PWQO are summarized in Table 7. Historical groundwater and surface water sampling results and graphical trends of indicator parameters are included in Appendix G and H, respectively.

11.2. Leachate Characterization

Leachate production is typically greatest directly beneath the landfill and at the perimeter of the landfilled area. Wells O-2 and O-6 are located at the downgradient edge of the landfill footprint and are within 25 meters of one another. As would be expected due to the proximity of well O-2 to the fill area, this monitoring location has historically shown the greatest influence from landfill leachate. However, it is noted that although well O-6 is also situated within close proximity to the landfill footprint, the magnitude of impacts has historically been significantly less at this location when compared to O-2.

Based on a review of the borehole logs, the difference in the magnitude of impacts historically noted between O-2 and O-6 is likely attributable to the differing geologic conditions of the two wells. Borehole logs show that well O-2 is reportedly screened in a fine to medium sand with occasional stones, while well O-6 is reportedly screened in a sandy silt till with some clay. Based on these conditions, it is reasonable to expect that preferential groundwater flow and leachate migration would be through the coarser soils where O-2 is located. As a result, the groundwater at O-2 has historically been most impacted by leachate and is considered a leachate characterization well.

As is typical for leachate-impacted groundwater, relative to background concentrations, groundwater at O-2 has consistently been noted to have high conductivity, averaging approximately 1,800 μ S/cm, and elevated concentrations of hardness, alkalinity, chloride, sodium, potassium, ammonia, and DOC. Furthermore, in contrast to several of these indicator parameters, concentrations of alkalinity and potassium appear to be solely influenced by landfill leachate-derived impacts. As a result, while hardness, alkalinity, chloride, sodium, potassium, ammonia, and DOC are all considered to be primary leachate indicator parameters for the Site, alkalinity and potassium are considered key leachate indicators. The concentrations of chloride, potassium, and alkalinity for 2024 are presented on Figure 7.

Since about 2023, leachate indicator parameter concentrations at O-2 have decreased significantly. This likely reflects the transition of the active area of the site to the northerly portion of the landfill footprint, providing for a greater separation distance between this monitoring location and operations. In 2024, RUC exceedances were noted for hardness, alkalinity, and DOC. While exceedances of iron are periodically reported, iron concentrations do not appear to directly correlate with the degree of leachate influence, as indicated by other more prominent leachate indicators. Therefore, iron concentrations in the shallow groundwater are interpreted to be naturally occurring and are not considered to reflect leachate influence and/or strength. In addition, it is noted that nitrate,

nitrite, and sulphate concentrations did not historically increase at this monitoring location along with other leachate indicator parameters, suggesting that these parameters are not indicators of landfill-leachate derived impacts at the Site.

Recommended Revisions to the Monitoring Program

In response to MECP comments provided in correspondence dated February 12th, 2019, the list of required parameters for wells O-2 and O-7 was revised to be based on the parameters listed in Schedule 5: Column 1 (i.e., comprehensive list for groundwater and leachate) during the fall monitoring event. Groundwater quality results are summarized in Table 5. Based on a review of the monitoring results from the supplemental sampling completed, and as per MECP recommendations (correspondence dated August 12, 2022), it is thought that the addition of boron as a leachate-indicator parameter to the established monitoring program may be beneficial. This recommendation is reflected in the updated monitoring program presented in Section 15 of this report.

11.3. Groundwater Migration and Compliance Assessment

11.3.1. Cross-gradient (Northeast)

The northeastern property boundary, along McArthur Road, is upgradient from the landfill. As shown on Figure 2, the approved landfill footprint is located approximately 175 m southwest of McArthur Road. Based on the distance to the northeastern property boundary and the groundwater flow direction, generally to the south-southwest (Figure 4), off-site impacts related to landfill leachate are not anticipated at the northeastern compliance limit.

Compliance Well W-1

Well W-1 is located approximately 225 m east of the landfill and 10 m west of McArthur Road and could be considered to be a background well based on its location. However, when compared to background well O-1, there was a more limited data set available as this well could not be sampled between 2004 and 2012 due to insufficient water. In 2012, sediment was successfully removed from the well, which was contributing to the difficulty of obtaining a sample from this location. As would be expected, the groundwater quality reported for this monitoring location is generally similar to background. Consistent with historical results, RUC exceedances are reported for DOC, with RUC exceedances for iron occurring periodically. These are interpreted to be naturally occurring.

Monitoring Well O-7

Monitoring well O-7 is located approximately 30 meters cross-gradient and to the east of the landfill footprint. As previously discussed, historical water quality results suggest that groundwater quality at the site can be influenced by different variables that may influence the overall geochemical characteristics of the groundwater.

Available data from well O-7 suggests that the groundwater quality in the shallow overburden is highly variable with respect to conductivity, hardness, and sulphate concentrations (refer to trend graph provided in Appendix G). At well O-7, conductivity, hardness, and sulphate concentrations have generally ranged between 380 and 2,500 μ S/cm, 170 and 1,900 mg/L, and 10 and 1,520 mg/L, respectively. Other leachate indicator parameters remain relatively stable and similar to background, including chloride, potassium, and alkalinity. Therefore, conductivity, hardness and sulphate alone are not considered good leachate indicator parameters at the St. Edmunds landfill site.

Based on a review of historic analytical data, it appears that the elevated concentrations of conductivity, hardness and sulphate may be due to the natural mineralogy of the parent material from which the soils were derived. Based on the ratios of dissolved calcium and magnesium to sulphate in groundwater, it is estimated that the dissolution of gypsum and/or anhydrite minerals are the primary contributing factor to these naturally elevated concentrations. The occurrence of these evaporate minerals is relatively common in the bedrock of the area. The elevated hardness and conductivity appear to be a direct result of the dissolved calcium, magnesium, and sulphate ions.

11.3.2. Cross-gradient (East)

The eastern limit of the approved landfill footprint is situated greater than 400 meters from the compliance limit to the east towards the intersection of MacArthur Road and Warner Bay Road. Groundwater quality is monitored at overburden monitoring wells W-2 and O-8, which are located approximately 75 m cross-gradient and to the east of the landfill. The well depths are reported to be approximately 2.5 m and 1.4 m below ground surface, respectively.

In recent years, the groundwater quality at these two shallow overburden monitoring locations has exhibited similar groundwater quality results and trends. The concentrations of naturally elevated parameters, including hardness and sulphate, when apparent, are generally greater in the fall. Concentrations of primary leachate indicator parameters are similar to background indicating that leachate impacts are not occurring within the shallow overburden in this area of the Site.

At well O-8, RUC exceedances are typically noted for DOC, however in the absence of other leachate indicators, the slightly elevated DOC concentrations at this location are considered to be naturally occurring. In the fall of 2024, slight RUC exceedances for alkalinity were also noted at O-8 and W-2.

11.3.3. Downgradient (South to Southeast)

Overburden Wells - Downgradient from Landfill

Wells W-3/03, O-3 and O-4 are located between 50 to 75 m downgradient of the landfill and, based on the south to southwesterly groundwater flow direction, are inferred to intersect groundwater flow from the landfilled area. In general, the groundwater quality at these monitoring locations is noted to be geochemically similar to that noted at well O-7, as indicated by the elevated sulphate and hardness concentrations and associated concentration trends. These are considered to be naturally occurring at the Site.

With respect to potential impacts from the landfill, groundwater quality results indicate that a similar suite of leachate indicator parameters exists at both W-3/03 and O-3. However, consistent with their location further downgradient from the landfill than leachate well O-2, concentrations have historically been lower and, more recently, similar to those reported at O-2, exhibiting minor leachate influence (Table 4). A generally stable concentration trend for leachate-indicator parameters has typically been exhibited at both locations, however a slightly increasing concentration trend has more recently been noted at well O-3. In conjunction with increased alkalinity at wells W-3/03 and O-3, typically in the range of 300 mg/L to 700 mg/L, chloride concentrations have averaged 28 mg/L and 19 mg/L and potassium concentrations have averaged 13.6 mg/L and 5.5 mg/L, respectively. Similar to well O-2, RUC exceedances for hardness, alkalinity, DOC, and periodically iron, are often noted.

Consistent with the limited impacts noted at well O-6, and the additional separation distance of greater than 50 meters from the landfill footprint, the shallow groundwater further downgradient from well O-6 at well O-4 generally does not exhibit impacts from landfill leachate. This suggests that leachate-impacted groundwater has naturally attenuated between these two monitoring locations.

In summary, it appears that leachate impacted groundwater is having minor influence at O-3 and W-3/03, and a minimal to negligible influence at well O-4. Based on the degree of leachate influence and the downgradient distance to the compliance limits to the southeast and southwest of the landfill (i.e., over 500 m), off-site impacts are not anticipated in the shallow overburden.

Bedrock Wells

The bedrock wells considered to be downgradient of the landfill include wells B2, B3 and B4. Wells B2 and B4 are located directly southwest and southeast of the landfill, respectively, and well B-3 is located approximately 100 m to the south. In general, the background groundwater quality at these locations is influenced by the naturally

elevated sulphate and hardness concentrations. In closer proximity to the landfill the sulphate concentrations are generally less, averaging approximately 50 mg/L directly downgradient of the landfill, and averaging approximately 1,000 mg/L further downgradient at well B3.

Bedrock well B2 is located adjacent to leachate well O-2. Based on the water level elevations (Appendix E), a downward hydraulic gradient is apparent at this location and generally exists in the vicinity of the landfill footprint (Figure 4 and Figure 5). While leachate impacts have been evident in overburden well O-2, the magnitude of impacts noted at depth within the bedrock, is minimal. Average chloride concentrations are reported to be in the range of 13 mg/L and 28 mg/L at wells B2 and B4, respectively, and concentrations of other leachate indicators suggest limited to minor impacts to the bedrock unit directly downgradient of the landfill. Since 2023, chloride concentrations noted at well B4 show an increasing trend with concentrations reported to be greater than 100 mg/L in 2024. Consistent with historical results, in 2024 RUC exceedances for DOC were noted at wells B2, B3 and B4.

Further downgradient at bedrock well B3, the combination of chloride, alkalinity, and potassium concentrations, which are all slightly elevated, suggests minor leachate impacts at depth. A review of key leachate indicator parameter trends suggests that a relatively stable concentration trend exists at this time. In 2024, RUC exceedances noted at well B3 included hardness, alkalinity, sulphate, and iron of which alkalinity and, in part, hardness may be considered to be related to landfill leachate-derived impacts.

In general, it appears that landfill leachate may be having minimal impacts to groundwater at well B2, with impacts more recently apparent at bedrock well B4. Minor leachate influence is evident at well B3, which is located approximately 100 meters downgradient of the landfill footprint. Based on the water quality results and the distance to the compliance limit to the southeast of greater than 500 m, off-site impacts via groundwater migration through the bedrock are not anticipated.

11.3.4. Cross-gradient (West)

Groundwater quality cross-gradient and to the west of the landfill is monitored at two overburden wells (well O-1 and O-9) and a bedrock piezometer nest (P1, P2, and P3). Monitoring well O-1, which is considered the background well for the Site, is situated approximately 65 m west of the western corner of the landfill footprint. Well O-9 is located approximately 180 m to the southwest of the landfill and approximately 350 m from the compliance limit to the southwest. Piezometers P1, P2 and P3 are situated approximately 50 m west of the landfill and greater than 200 m from the property boundary to the northwest.

Overburden Well

Monitoring well O-9 is located in a low-lying wet 'swampy' area to the southwest of the landfill. With the exception of sulphate and DOC concentrations, which are elevated at O-9 relative to that in background well O-1, the water quality at O-9 is similar to background and does not exhibit leachate impacts. The high DOC concentrations at this location are attributed to the characteristically nutrient-rich and organic swampy area in the vicinity of well O-9. Historically, DOC concentrations have been highest at this monitoring location with concentrations consistently exceeding the RUC.

Piezometer Nest

Groundwater levels measured at the bedrock piezometer nest, P3 (shallow), P1 (intermediate) and P2 (deep) suggest that a downward hydraulic gradient exists at this location. In general, groundwater quality at these piezometers is similar to the background well B5. However, consistent with the absence of elevated sulphate and hardness concentrations in the overburden wells in this area of the Site (i.e., O-1), these parameter concentrations do not appear to be naturally elevated in this area.

Chloride concentrations have fluctuated over time and most recently were reported to be in the range of 20 to 55 mg/L in wells P1 and P2. Based on the location of the piezometer nest (next to the access road and potentially downgradient of former excess snow storage areas), the chloride response appears to be related to road salt and/or the periodic application of dust suppressant along the access road in the summer and fall. Overall, chloride concentrations may decrease over time due to limited road salt associated with the construction of a transfer station at the site entrance (limiting winter road maintenance requirements to active area) and the suspension of excess snow storage practices at the landfill site. However, it is noted that the periodic application of dust suppressant along this access road in the summer and fall may continue to influence the groundwater quality to some degree.

11.4. Groundwater Quality Summary

Groundwater quality at the site can be divided into five different categories, each representing different geochemical characteristics and potential influences. This is likely due to the shallow nature of the overburden wells that may consequently be influenced, to some degree, by the infiltration of surface water across the site during periods of precipitation. Some wells exhibit the combined influence from two or more of these categories. The groundwater at the site can be classified as follows:

Table 11-1. Groundwater Quality Summary - Categorization

| Category | Defining Feature | Potential Source | Well No's |
|----------|---|--|---|
| 1 | 'Normal' | Concentrations within range, typically observed in the area. | O-1 B2 B5 |
| 2 | High sulphate, alkalinity, conductivity, and hardness | Likely associated with the native soils/bedrock and natural geochemistry. | O-3 O-4 O-7 W-2 B3 |
| 3 | High DOC | Likely associated with groundwater derived from organic-rich swampy areas. DOC concentrations are similar to those measured in surface water. | O-8 O-9 W-1 W-3/03 |
| 4 | Elevated chloride and hardness only | Elevated chloride concentrations. Other leachate indicator parameters are similar to background. May be associated with road salt and/or dust suppressant. | P1 P2 P3 |
| 5 | Elevated chloride, potassium, hardness, and alkalinity. | Influenced by landfill derived leachate to varying degrees. | O-2 O-3 O-6 W-3/03 B2 B3 B4 |

As noted in the Table above, it appears that overburden wells O-2, O-3, O-6, and W-3/03 are being influenced by leachate. In addition, it appears that landfill leachate may be having minimal impacts to groundwater at bedrock well B2, with leachate influence more evident at wells B3 and B4. Bedrock well B3 is located approximately 100 meters downgradient of the landfill footprint.

Based on the location of these wells, it appears that the leachate plume is migrating in a southerly to southwesterly direction through the overburden soils and bedrock. It is noted that the degree of leachate influence in the wells

19

downgradient from O-2 and O-6 (i.e., O-3, W-3/03, and B3) is not considered to be significant at this time and is estimated to be limited to within 100 m of the landfill. Therefore, considering the level of attenuation and the distance between the surrounding property boundaries and the landfill footprint, off-site impacts above the RUC from landfill leachate are not anticipated.

12. SURFACE WATER QUALITY AND STORMWATER MANAGEMENT

12.1. Surface Water Quality

As per the CofA for the stormwater management facility, surface water quality samples are collected from a background monitoring location (S-1), from the stormwater management pond (S-6), and from the outlet creek west of Pond BPP2 (S-9). Monitoring location S-9 is representative of surface water discharging from the site. Two additional locations are sampled to support the assessment of potential impacts and attenuation at the site including S-8, which is collected from surface water flowing along Warner Bay Road in the north ditch, and S-6A which is located downgradient of S-6. Surface water sampling locations are shown on Figure 2 and Figure 8.

As would be expected due to the proximity of S-6 to the landfill footprint and consistent with the characteristics of the leachate-impacted groundwater, the surface water quality at this location exhibits elevated concentrations of hardness, alkalinity, chloride, sodium, potassium, and ammonia. Therefore, leachate impacts to surface water are apparent within the stormwater management pond.

Monitoring location S-6A is located downstream of the confluence of ditches draining surface water from the stormwater management pond (i.e., S-6) and McArthur Road (i.e., S-1) and is representative of surface water downgradient of the landfill after mixing with background surface water. As would be expected, while a similar suite of leachate indicator parameters is typically noted at this location, the magnitude of leachate impacts is, at times, less than that observed directly downgradient of the landfill (i.e., at S-6). This suggests that some dilution of the surface water from the stormwater management pond is periodically occurring.

Correspondence from the MECP dated June 21, 2018, requested clarification with respect to the source of leachate contamination at S-6/S-6A. As provided in a response issued to the MECP on July 3, 2018, the source of leachate is considered to be groundwater that is being intercepted by the perimeter swale constructed along the west side of the landfill. A more detailed discussion is provided in the following Section 12.2. Correspondence is included in Appendix B.

Consistent with historical results, phosphorus concentrations were noted to exceed the PWQO at monitoring location S-6 in the spring only (i.e., 0.05 mg/L) and at S-6A (0.04 mg/L), slightly exceeding the PWQO for phosphorus of 0.02 mg/L. However, it is noted that comparison to background concentrations at S-1 suggests that phosphorus concentrations of up to 0.06 mg/L have been measured in background surface water. Therefore, the periodic exceedance of the PWQO for phosphorus is not likely directly attributable to landfill leachate. PWQO exceedances for iron were reported at these locations in the fall. PWQO exceedances for boron are also commonly reported at these surface water sampling locations situated in closer proximity to the landfill and were reported in 2024.

Further downgradient, along Warner Bay Road, the surface water quality at S-8 and S-9 is similar to background and does not appear to be influenced by landfill leachate, suggesting that adequate attenuation of impacts to surface water is occurring before water is discharged from the Site. It is noted that in 2024, PWQO exceedances were noted for phenol and phosphorus at S-8 and S-9. Based on the leachate characteristics and the historical surface water quality at these locations, which show infrequent exceedances of various parameters (i.e., phosphorus, iron, and phenol), exceedances reported are not attributed to landfill-leachate derived impacts.

The surface water chemistry at S-6 and to a lesser degree at S-6A, situated immediately downgradient of the landfill area, indicates that impacts from landfill leachate are occurring within the stormwater management pond. However, based on the water quality noted at S-8 and S-9, the attenuation of the impacts from landfill leachate is occurring within the sewage works and before reaching potential sensitive receptors (i.e., Borrow Pit Pond BPP2).

12.2. Stormwater Management: Trigger Levels

As per Condition 5(2) of the Approval for the stormwater management facility, monitoring results for sampling location S-6 are to be compared to the trigger levels (as provided in the table below) to identify leachate contamination to stormwater.

| Trigger Parameters Trigger Location: S-6 (SWM Pond) | | | | | | | | |
|---|-------|-------|--|--|--|--|--|--|
| Parameter Units Trigger Level | | | | | | | | |
| Ammonia (Un-ionized) | mg/L | 0.06 | | | | | | |
| Chloride | mg/L | 60 | | | | | | |
| Conductivity | uS/cm | 2.200 | | | | | | |

Table 12-1. Trigger Parameters and Levels

As per the requirements of the Approval, a "Stormwater Management Contingency and Remedial Action Plan" was completed by GMBP and submitted to the MECP in 2009, hereafter referred to as the Contingency Plan. The report describes the conditions (i.e., trigger levels and locations) under which contingency measures may be required and recommends the corresponding contingency and remedial action plans for the Site. The primary goal of the Contingency Plan is to provide a course of action in the event that the monitoring program indicates a potential for off-site impacts related to the production and migration of leachate.

It is noted that in 2011, exceedances of the trigger levels were reported for unionized ammonia and contingency measures were implemented including the following:

- A review of the potential for off-site impacts: This concluded that attenuation of the impacts from landfill leachate was occurring within the sewage works and before reaching potential sensitive receptors (i.e., Borrow Pit Pond BPP2).
- ii. A visual inspection for leachate seeps within the stormwater management works: This indicated that groundwater impacted with landfill leachate was discharging into the drainage ditch located west of the landfill in the vicinity of well O-2. As this drainage ditch appeared to have intersected the groundwater table, mitigative measures were undertaken in 2011 and 2012. These measures included raising the base grade of the drainage ditch with a low permeability soil to limit leachate seepage into the drainage ditch and planting of cattails (i.e., Typha spp.) at the outlet of the ditch.

Since 2013, the cattails have become more established and the surface water within the pond has been observed to be much clearer relative to previous years. The reported ammonia concentrations continue to exhibit improvement relative to pre-2012 conditions. Since 2014, un-ionized ammonia concentrations have ranged between 0.002 and 0.03 mg/L, remaining below the trigger level of 0.06 mg/L. It is anticipated that concentrations of un-ionized ammonia will continue to remain low as the vegetation has become well established within the drainage ditches and ponds. In addition, since 2019, chloride concentrations at S-6 have generally remained below the trigger level of 60 mg/L. As previously discussed, surface water quality results suggest that adequate attenuation of impacts from landfill leachate is occurring within the sewage works and prior to reaching potential sensitive receptors (i.e., Borrow Pit Pond BPP2).

12.3. Review of Surface Water Monitoring Network and Trigger Levels

As noted in the Contingency Plan, the trigger levels established for the Site were intended to provide an indicator of when potential impacts outside the sewage works may occur. Trigger levels were estimated based on the analytical results from S-6 that were available at that time (i.e., 2009) and prior to the modifications of the stormwater works. As a result, it was noted that due to the limited data available, particularly for ammonia, and the change in the condition associated with the trigger location, the trigger levels could only be estimated. Consequently, it was recognized that the trigger levels may need to be adjusted as performance data for the stormwater works became available.

This was recognized in the CofA under Condition 5(5), which allows for the trigger levels and parameters to be updated after two years of monitoring (with permission from the MECP District Manager). Based on the modifications made to the sewage works in 2012/2013, it is recommended that the water quality within the sewage works continue to be closely monitored. At this time, it is recognized that attenuation of impacts is being achieved in the sewage works. In MECP correspondence dated December 14, 2021, it was recognized that continued sampling prior to the finalization of trigger levels would be reasonable.

Further, the mitigative measures previously implemented have improved surface water quality at trigger location S-6. However, as previously noted, leachate influence continues to be present at this location. The surface water quality at S-6 and the vegetative state of the ditches and surface water pond will continue to be closely monitored as it is anticipated that surface water quality may continue to improve as vegetation becomes more established. It should be noted that based on the location of S-6 in relation to the landfill, it is anticipated that a level of leachate influence will continue to persist at this location.

13. METHANE GAS PRODUCTION

Landfill gas is primarily produced by the bacterial decomposition of organic materials after the capping and closure of a landfill has been completed and is combustible if it accumulates to concentrations greater than the lower explosive limit (LEL). Landfill gas tends to migrate laterally from the landfill area when the gas is unable to escape vertically through the ground surface via dry relatively permeable soils, commonly due to an overlying low permeability geologic stratum or when the ground surface is frozen.

Soils in the vicinity of the St. Edmunds landfill site are limited in thickness (i.e., less than 3.7 meters) and have a moderate to high permeability that would permit the venting of gases to the atmosphere, greatly reducing the potential for lateral migration of landfill gas. In addition, the landfill is primarily constructed above grade and the vadose zone around the perimeter of the waste is relatively thin, limiting the potential pathway for methane gas migration. Therefore, at the St. Edmunds Landfill site methane gas is vented passively to the surrounding atmosphere. It is further noted that the closest receptor of methane gas is located greater than 500 m from the Site and the re-use storage building and operator weigh scale building are both sufficiently separated from the landfill footprint.

In summary, due to the existence of a thin vadose zone and the moderately permeable overburden soils, combined with the distance of the landfill from the site boundaries and any structures, the generation and migration of landfill gas at the site is not considered to be of concern at the Site.

14. CONCLUSIONS

Presented below is a summary of conclusions for the landfill operations, recycling programs, and environmental monitoring for the year 2024.

- Based on the annual topographical surveys of the active area, it is estimated that a volume of 2,095 m³ was used during the reporting period. The remaining capacity for waste and daily cover is estimated to be about 3,600 m³.
- 2. The average fill rate over the last five years is approximately 2,180 m³/yr. At the five-year average fill rate, the remaining site life is estimated to be approximately 1.5 to 2 years.
- 3. In 2024, an estimated 342 tonnes of material were diverted from the St. Edmunds landfill through Municipal programs.
- 4. Different variables influence the overall geochemical characteristics of the groundwater resulting in a natural variability in background groundwater quality across the Site. This is demonstrated by the historical water quality results and trends noted at well O-7, which shows naturally elevated hardness and sulphate concentrations, and elevated conductivity.
- 5. It is noted that the groundwater quality at the site, particularly in the overburden, fluctuates to a significant degree. This appears to be directly related to seasonal variations where parameters are typically higher in the fall and lower in the spring. Lower concentrations in the spring are likely due to the higher proportion of surface water infiltration (i.e., snow melt and rain) resulting in a level of dilution.
- 6. It appears that past road salt usage and/or excess snow storage at the site may have historically influenced chloride concentrations at a number of bedrock monitoring locations at the site. Parameters including chloride and hardness in select bedrock wells continue to appear to be influenced by site operations (i.e., the application of road salt and/or dust suppressant on access roads).
- 7. DOC concentrations are noted to be generally elevated at monitoring wells located in organic rich swampy areas.
- 8. Due to the variability in groundwater chemistry at the site, various leachate indicators that are normally used to assess leachate migration are not considered to be reliable. Based on the site-specific scenario, the key leachate indicators for groundwater are found to be alkalinity and potassium. Although chloride concentrations can be influenced by other factors, such as road salt and dust suppressants, chloride is also considered to be a reliable indicator of leachate when assessed in conjunction with other leachate indicator parameters.
- 9. Based on the analytical results for groundwater, it appears that the leachate plume is migrating in a southerly to southwesterly direction through the overburden soils and bedrock. It is noted that the degree of leachate influence in the downgradient wells is not considered to be significant at this time. Considering the level of attenuation being demonstrated in the groundwater and the distance between the surrounding property boundaries and the landfill footprint, offsite impacts from leachate are not anticipated.
- 10. Based on the analytical results for surface water, it appears that influence from leachate continues to occur at S-6. However, water quality has improved at these locations following the mitigation efforts undertaken in 2011 and 2012. The surface water chemistry at S-8 and S-9, located downstream of S-6, is similar to background conditions and does not exhibit influence from leachate. Therefore, attenuation of leachate impacted surface water appears to be occurring onsite within the sewage works and prior to entering sensitive surface water receptors.

15. RECOMMENDATIONS

Based on the findings of this report and the Conditions of the Approvals, the following recommendations are provided:

- 1. The Municipality continues to employ the area ramp method to achieve optimal compaction and reduce litter.
- 2. Given that Area B has reached capacity and clay capping has been completed, it is recommended that the application of topsoil and seed be completed to provide protection of the cover material from erosion, promote evapotranspiration, and enhance the site aesthetics.
- 3. In consideration of the limited remaining capacity, a comprehensive survey of the entire landfill footprint was completed in 2023 to provide an updated and more accurate assessment of the remaining site life. The survey data was used in conjunction with the approved final contours outlined in the PDO (which account for waste and interim cover) to confirm the remaining airspace capacity and site life. Based on the comprehensive survey, the St. Edmunds landfill site had a remaining capacity of 5,700 m³ at the end of 2023. Although not required by the Approval, it is recommended that a Closure Plan be completed for submission to the MECP in 2025.
- 4. Cover material be applied on regular basis to inhibit leachate generation and prevent litter and scavenging.
- 5. Based on previous revisions, it is recommended that the monitoring program for 2024 include the locations and parameters outlined in Table 15-1.

Table 15-1. Recommended Monitoring Program (2025)

| SAMPLIN | G LOCATI | ONS | ANALYTICAL PARAMETERS | | | |
|-------------------------------------|-------------------------------------|----------------------|---|--|--|--|
| | GROUNDWATER (Spring and Fall) | | | | | |
| O-1 * O-2 * O-3 O-4 | O-6 * O-7 * O-8 O-9 | W-1 W-2 W-3/03 | Alkalinity, Hardness, Conductivity, pH, Ammonia, Nitrate, Nitrite, DOC, Chloride, Sulphate, Iron, Sodium and Potassium Calcium and Magnesium Leachate Indicator Parameter Addition: Boron | | | |
| B2 B3 B4 B5 | P1 P2 P3 | | *Leachate wells* (as of 2020) *Spring: Same as the indicator list outlined above *Fall: Schedule 5: Column 1 (i.e., Comprehensive list for groundwater and leachate) which includes field parameters (i.e., pH and Conductivity) | | | |
| | SURFACE WATER (Spring and Fall) | | | | | |
| | S-1 S-6 S-6A S-8 S-9 | | Alkalinity, Hardness, Conductivity, pH, Total Ammonia, Nitrate, Nitrite, TKN, DOC, CBOD₅, Chloride, Sulphate, Phenols, Total Phosphorus, Iron, Boron and Zinc (Na, K, Ca, and Mg) Field Parameters: pH, Conductivity, and Temperature | | | |

- 6. Groundwater level elevations should continue to be monitored in the spring and fall from all monitoring locations.
- 7. Under Condition 5(5) of the Approval for Municipal Sewage Works, the trigger levels and parameters may be updated with approval from the MECP District Manager. Based on the modifications made to the sewage works in 2012/2013, it is recommended that the water quality within the sewage works continue to be closely monitored. At this time, it is recognized that attenuation of impacts continues to be achieved in the sewage works.

Tables

| Table | 1: | Landfill | Volume | Capacity |
|--------------|----|----------|--------|----------|
| | | | | |

- Table 2: Site Specific Background & Guideline B-7-1 RUC Determination (Overburden)
- Table 3: Site Specific Background & Guideline B-7-1 RUC Determination (Bedrock)
- Table 4: Overburden Groundwater Quality Summary 2024
- **Table 5: Leachate Characterization**
- Table 6: Bedrock Groundwater Quality Summary 2024
- Table 7: Summary of Surface Water Quality Results 2024

TABLE 1
LANDFILL VOLUME CAPACITY (m³)

| | <u>2019</u> | 2020 | <u>2021</u> | 2022 | 2023 | <u>2024</u> |
|--|-------------|---------|-------------|---------|---------|-------------|
| Total Approved Capacity | | | | | | |
| Total Capacity for Waste and Daily Cover | 141,100 | 141,100 | 141,100 | 141,100 | 141,100 | 141,100 |
| Total Capacity for Topsoil | 3,510 | 3,510 | 3,510 | 3,510 | 3,510 | 3,510 |
| Total Capacity for Final Cover | 21,020 | 21,020 | 21,020 | 21,020 | 21,020 | 21,020 |
| Total Air Space Capacity | 165,630 | 165,630 | 165,630 | 165,630 | 165,630 | 165,630 |
| Capacity Used During Year | | | | | | |
| Capacity Used for Waste and Daily Cover | 820 | 1,750 | 1,750 | 2,650 | 2,660 | 2,095 |
| Volume of Topsoil Used | - | _ | - | - | - | - |
| Capacity Used for Final Cover | - | _ | - | _ | - | - |
| Total Capacity Used | 820 | 1,750 | 1,750 | 2,650 | 2,660 | 2,095 |
| Volume Filled at End of Year | | | | | | |
| Volume of Waste and Daily Cover | 128,605 | 130,355 | 132,105 | 134,755 | 137,415 | 139,510 |
| Volume of Topsoil | 1,650 | 1,650 | 1,650 | 1,650 | 1,650 | 1,650 |
| Volume of Final Cover | 15,410 | 15,410 | 15,410 | 15,410 | 15,410 | 15,410 |
| Total Volume Filled | 145,665 | 147,415 | 149,165 | 151,815 | 154,475 | 156,570 |
| Remaining Capacity at End of Year | | | | | | i i |
| Capacity for Waste and Daily Cover | 12,495 | 10,745 | 8,995 | 6,345 | 5700* | 3,605 |
| Capacity for Topsoil | 1,860 | 1,860 | 1,860 | 1,860 | 1,860 | 1,860 |
| Capacity for Final Cover | 5,610 | 5,610 | 5,610 | 5,610 | 5,610 | 5,610 |
| Total Remaining Capacity | 19,965 | 18,215 | 16,465 | 13,815 | 13,170 | 13,170 |
| | | | | | | |
| Remaining Site Life | | | | | | |
| At 5-Year Average Fill Rate (2180 m³/year) | 5.7 | 4.9 | 4.1 | 2.9 | 2.6 | 1.7 |
| At 5-Year Max Fill Rate (3,000 m³/year) | 4.2 | 3.6 | 3.0 | 2.1 | 1.9 | 1.9 |

Notes:

Project No.: 2402869 St.Edmunds Landfill Site

^{1.} Remaining capacity for the landfill is calculated using a volumetric comparison of the landfill area to final contours completed using elevation data from the fall of 2007 less annual fill volumes.

^{2.} Annual fill volumes are calculated using elevations obtained from topographic surveys of the active landfill areas completed in the fall of each year.

^{3.} In consideration of the limited remaining capacity, a comprehensive survey of the entire landfill footprint was completed in 2023 to provide an updated and more accurate assessment of the remaining site life. The survey data was used in conjunction with the approved final contours outlined in the PDO (which account for waste and interim cover) to confirm the remaining airspace capacity and site life. Based on the comprehensive survey, the St. Edmunds landfill site has a remaining capacity of 5,700 m³.

TABLE 2 SITE SPECIFIC BACKGROUND CONCENTRATIONS AND GUIDELINE B-7-1 RUC DETERMINATION OVERBURDEN GROUNDWATER

| | GROUNDWATER INDICATOR PARAMETERS ST. EDMUNDS LANDFILL SITE | | | | | | | | | | | | | |
|----------------------|--|-----------|--------------------|--------------|------------|---------------|------------|--|--|--|--|--|--|--|
| | ODV | | BACKGROUN | D CONCEN | TRATION | Average | | | | | | | | |
| | Maxin | num | Overbu | rden Well: (| D-1 | Background | Objective | | | | | | | |
| | Concentra | ition and | Range [n] | Avorago | 95th | Concentration | Level | | | | | | | |
| Parameter (mg/L) | Classifi | cation | Kange [n] | Average | Percentile | (Cb) | (Cm) | | | | | | | |
| Conductivity (uS/cm) | NV | NV | 335 - 1180 [38] | 569 | 912 | 569 | NV | | | | | | | |
| pH (no units) | 6.5 to 8.5 | OG | 7.73 - 8.41 [23] | 8.03 | 8.32 | 8.03 | 6.5 to 8.5 | | | | | | | |
| Hardness* | 80 to 100 | OG | 178 - 664 [39] | 322 | 527 | 527 | 527 | | | | | | | |
| Alkalinity | 500 | OG | 173 - 641 [23] | 308 | 502 | 308 | 404 | | | | | | | |
| Chloride | 250 | AO | 0.34 - 21.1 [38] | 5.4 | 12.7 | 5.4 | 128 | | | | | | | |
| Nitrate | 10 | MAC | 0.05 - 6.96 [23] | 1.10 | 4.37 | 1.10 | 3.33 | | | | | | | |
| Nitrite | 1.0 | MAC | <0.25 [23] | NA | NA | NA | 0.25 | | | | | | | |
| Sulphate | 500 | AO | 1.74 - 35.8 [23] | 10.8 | 25.5 | 10.8 | 255 | | | | | | | |
| Sodium | 200 | AO | 0.92 - 6.31 [23] | 2.93 | 5.68 | 2.93 | 101 | | | | | | | |
| Potassium | NV | NV | 0.37 - 4.31 [22] | 1.21 | 2.69 | 1.21 | NV | | | | | | | |
| Ammonia | NV | NV | <0.05 [23] | NA | NA | NA | NV | | | | | | | |
| Iron | 0.3 | AO | <0.005 - 0.59 [36] | 0.037 | 0.14 | 0.037 | 0.17 | | | | | | | |
| DOC | 5.0 | AO | <1.0 - 20.5 [37] | 4.74 | 13.8 | 4.74 | 4.87 | | | | | | | |

Notes:

- 1. [n] = number of data points used to determine the average background concentration.
- 2. Available data from O-1, up to and including November 2017, was used to calculate background concentrations.
- 3. mg/L = milligrams per litre; uS/cm = microsiemens per centimetre; NV = No Value.
- 4. AO = Aesthetic Objective; OG = Operational Guideline

MAC = Maximum Acceptable Concentration, Parameters Related to Health

IMAC = Interim Maximum Acceptable Concentration, Parameters Related to Health

MOECC Procedure B-7-1

Cm = Cb + x(Cr - Cb)

Where:

Cm = Maximum concentration acceptable in groundwater beneath an adjacent property.

Cb = Background concentration.

Cr = Maximum concentration that should be present in groundwater for domestic consumption according to the Ontario Drinking Water Standards (ODWS).

x = 0.5 for non-health related parameters and 0.25 for health related parameters.

5. For parameters in which the background concentration (i.e. the average concentration) exceeds the ODWS, the average of the 95th percentiles is used to represent the RUC for the Site. These parameters are shaded and shown in **BOLD**.

Project No.: 2402869 St.Edmunds Landfill GEI Consultants Canada Ltd.

TABLE 3 SITE SPECIFIC BACKGROUND CONCENTRATIONS AND GUIDELINE B-7-1 RUC DETERMINATION BEDROCK GROUNDWATER

| | GROUNDWATER INDICATOR PARAMETERS ST. EDMUNDS LANDFILL SITE | | | | | | | | | | | | | |
|----------------------|--|-----------|-------------------|-------------|------------|---------------|------------|--|--|--|--|--|--|--|
| | ODV | | BACKGROUN | D CONCEN | TRATION | Average | | | | | | | | |
| | Maxin | | Bedro | ck Well: B- | 5 | Background | Objective | | | | | | | |
| | Concentra | ition and | Range [n] | Average | 95th | Concentration | Level | | | | | | | |
| Parameter (mg/L) | Classifi | cation | Kange [ii] | Average | Percentile | (Cb) | (Cm) | | | | | | | |
| Conductivity (uS/cm) | NV | NV | 354 - 1110 [38] | 663 | 947 | 663 | NV | | | | | | | |
| pH (no units) | 6.5 to 8.5 | OG | 7.78 - 8.30 [24] | 8.02 | 8.18 | 8.02 | 6.5 to 8.5 | | | | | | | |
| Hardness* | 80 to 100 | OG | 172 - 598 [38] | 365 | 543 | 543 | 543 | | | | | | | |
| Alkalinity | 500 | OG | 130 - 300 [24] | 250 | 284 | 250 | 375 | | | | | | | |
| Chloride | 250 | AO | 0.30 - 42.8 [38] | 10.5 | 32.7 | 10.5 | 130 | | | | | | | |
| Nitrate | 10 | MAC | <0.25 [24] | NA | NA | NA | 2.50 | | | | | | | |
| Nitrite | 1.0 | MAC | <0.25 [24] | NA | NA | NA | 0.25 | | | | | | | |
| Sulphate | 500 | AO | 18.2 - 338 [24] | 147 | 298 | 147 | 324 | | | | | | | |
| Sodium | 200 | AO | 1.52 - 15.8 [24] | 4.26 | 6.82 | 4.26 | 102 | | | | | | | |
| Potassium | NV | NV | 0.66 - 1.62 [23] | 1.27 | 1.55 | 1.27 | NV | | | | | | | |
| Ammonia | NV | NV | <0.02 - 0.21 [24] | 0.06 | 0.13 | 0.06 | NV | | | | | | | |
| Iron | 0.3 | AO | <0.01 - 1.97 [37] | 0.17 | 0.60 | 0.17 | 0.24 | | | | | | | |
| DOC | 5.0 | AO | 0.70 - 11.0 [36] | 3.60 | 7.3 | 3.60 | 4.30 | | | | | | | |

Notes:

- 1. [n] = number of data points used to determine the average background concentration.
- 2. Available data from B-5, up to and including November 2017, was used to calculate background concentrations.
- 3. mg/L = milligrams per litre; uS/cm = microsiemens per centimetre; NV = No Value.
- 4. AO = Aesthetic Objective; OG = Operational Guideline

MAC = Maximum Acceptable Concentration, Parameters Related to Health

IMAC = Interim Maximum Acceptable Concentration, Parameters Related to Health

MOECC Procedure B-7-1

Cm = Cb + x(Cr - Cb)

Where:

Cm = Maximum concentration acceptable in groundwater beneath an adjacent property.

Cb = Background concentration.

Cr = Maximum concentration that should be present in groundwater for domestic consumption according to the Ontario Drinking Water Standards (ODWS).

x = 0.5 for non-health related parameters and 0.25 for health related parameters.

5. For parameters in which the background concentration (i.e. the average concentration) exceeds the ODWS, the average of the 95th percentiles is used to represent the RUC for the Site. These parameters are shaded and shown in **BOLD**.

Project No.: 2402869 St.Edmunds Landfill GEI Consultants Canada Ltd.

TABLE 4
OVERBURDEN GROUNDWATER QUALITY SUMMARY - 2024

| | | | | | North | east (Upgra | dient) | Ea | st (Crossgrad | dient) | N ₁ | orthwest (C | rossgradier | nt) | | | | | | |
|----------------------|------|-----------|------|---------|-----------|-------------|-----------|-----------|---------------|-----------|----------------|-------------|-------------|-----------|-----|--------|--------|--------|------|--------|
| Parameter | Bkgd | OD' | We | RUC | 0-7 | W | -1 | O-8 | ٧ | V-2 | 0 | -1 | 0 | -9 | | | | | | |
| Description | Dryu | a ODVVS | | ODVIS | | ODWS | | ODVIS | | NOC | Silt till | N | A | Silt till | Sil | t till | Sand 8 | gravel | Silf | t till |
| Sampling Date | | | | | 30-Apr-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 | | | | | | |
| Conductivity (uS/cm) | 569 | NV | NV | NV | 396 | 507 | 616 | 764 | 672 | 790 | 662 | 831 | 548 | 742 | | | | | | |
| pH (Unitless) | 8.03 | 6.5-8.5 | OG | 6.5-8.5 | 7.76 | 7.85 | 7.90 | 7.53 | 7.80 | 7.95 | 7.69 | 7.58 | 7.66 | 7.77 | | | | | | |
| Hardness | 527 | 80-100 | OG | 527 | 221 | 288 | 292 | 431 | 374 | 374 | 327 | 532 | 292 | 402 | | | | | | |
| Alkalinity | 308 | 30-500 | OG | 404 | 228 | 306 | 392 | 475 | 411 | 421 | 373 | 513 | 330 | 433 | | | | | | |
| Chloride | 5.4 | 250 | AO | 128 | 0.53 | 3.12 | 4.07 | 3.96 | 1.72 | 7.52 | 4.44 | 6.94 | 6.42 | 8.16 | | | | | | |
| Nitrate | 1.10 | 10.0 | MAC | 3.33 | 0.91 | 0.06 | 0.10 | < 0.05 | < 0.05 | 0.13 | 0.86 | 0.57 | < 0.05 | 0.12 | | | | | | |
| Nitrite | ND | 1.0 | MAC | 0.25 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | <0.05 | | | | | | |
| Sulphate | 10.8 | 500 | AO | 255 | 14.8 | 10.7 | 24.6 | 0.55 | 4.0 | 48.7 | 7.2 | 8.1 | 2.7 | 8.4 | | | | | | |
| Sodium | 2.93 | 200 | AO | 101 | 2.55 | 3.45 | 3.42 | 3.86 | 1.24 | 2.68 | 4.24 | 5.85 | 3.98 | 3.89 | | | | | | |
| Potassium | 1.21 | NV | NA | NV | 0.90 | 0.65 | 0.76 | < 0.50 | 0.71 | 1.29 | 1.11 | 2.76 | 3.89 | 5.90 | | | | | | |
| Calcium | ND | NV | NA | NV | 67.0 | 84.7 | 92.8 | 132 | 116 | 115 | 92.1 | 153 | 76.7 | 114 | | | | | | |
| Magnesium | ND | NV | NA | NV | 13.0 | 18.5 | 14.6 | 24.7 | 20.4 | 21.0 | 23.5 | 36.4 | 24.4 | 28.4 | | | | | | |
| Ammonia | ND | NV | NA | NV | 0.55 | 0.08 | 0.11 | 0.02 | 0.02 | < 0.02 | < 0.02 | < 0.02 | 0.06 | 0.07 | | | | | | |
| Iron | 0.04 | 0.3 | AO | 0.17 | <0.020 | 0.34 | 0.05 | <0.020 | <0.020 | <0.020 | < 0.020 | <0.020 | 0.47 | 0.15 | | | | | | |
| Boron | 0.01 | 5 | IMAC | 1.25 | <0.010 | <0.010 | 0.015 | <0.010 | < 0.010 | 0.022 | 0.046 | 0.075 | 0.015 | 0.052 | | | | | | |
| DOC | 4.74 | 5.0 | AO | 4.87 | 7.4 | 33.9 | 28.5 | 9.2 | 4.8 | 4.6 | 2.8 | 8.3 | 26.2 | 27.2 | | | | | | |

| | | | | | | | South (D | owngradien | it) | | | South - Edg | e of Landfil | l |
|----------------------|------|---------|------|---------|-----------|-----------|-----------|------------|-----------|-----------|-----------|-------------|--------------|------------|
| Parameter | Bkgd | OD | WC | RUC | W3 | -03 | 0 | -3 | C |)-4 | 0 | -2 | 0 | -6 |
| Description | Dkyu | 00 | WS | NUC | N. | /A | Silt | till | Sand | l & silt | Sa | ınd | Sand&G | ravel/Silt |
| Sampling Date | | | | | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 |
| Conductivity (uS/cm) | 569 | NV | NV | NV | 1040 | 975 | 1970 | 1970 | 765 | 836 | 1370 | 1390 | 1430 | 1400 |
| pH (Unitless) | 8.03 | 6.5-8.5 | OG | 6.5-8.5 | 7.52 | 7.75 | 7.43 | 7.53 | 7.76 | 7.83 | 7.20 | 7.12 | 7.05 | 7.17 |
| Hardness | 527 | 80-100 | OG | 527 | 416 | 382 | 985 | 957 | 382 | 387 | 570 | 520 | 600 | 535 |
| Alkalinity | 308 | 30-500 | OG | 404 | 529 | 590 | 476 | 506 | 302 | 385 | 749 | 808 | 836 | 838 |
| Chloride | 5.4 | 250 | AO | 128 | 19.1 | 17.6 | 39.0 | 41.3 | 0.42 | 15.4 | 30.6 | 39.0 | 16.9 | 23.8 |
| Nitrate | 1.10 | 10.0 | MAC | 3.33 | < 0.05 | 0.27 | < 0.07 | < 0.07 | < 0.05 | < 0.05 | < 0.05 | <0.05 | < 0.05 | 0.81 |
| Nitrite | ND | 1.0 | MAC | 0.25 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 |
| Sulphate | 10.8 | 500 | AO | 255 | 12.8 | 4.5 | 589 | 571 | 142 | 118 | 4.08 | 2.33 | 7.0 | 10.2 |
| Sodium | 2.93 | 200 | AO | 101 | 21.7 | 18.3 | 18.8 | 19.3 | 1.64 | 10.1 | 36.1 | 57.3 | 24.0 | 20.3 |
| Potassium | 1.21 | NV | NA | NV | 14.0 | 13.2 | 4.20 | 5.29 | < 0.50 | 1.33 | 21.7 | 26.7 | 21.0 | 20.6 |
| Calcium | ND | NV | NA | NV | 113 | 109 | 263 | 259 | 105 | 106 | 152 | 131 | 160 | 150 |
| Magnesium | ND | NV | NA | NV | 32.4 | 26.6 | 79.8 | 75.4 | 29.1 | 29.6 | 46.3 | 46.9 | 48.7 | 38.9 |
| Ammonia | ND | NV | NA | NV | 8.08 | 9.12 | 0.04 | 0.08 | <0.02 | < 0.02 | 23.8 | 26.2 | 24.9 | 24.2 |
| Iron | 0.04 | 0.3 | AO | 0.17 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | 0.34 | 1.47 | < 0.020 | 0.03 |
| Boron | 0.01 | 5 | IMAC | 1.25 | 0.36 | 0.36 | 0.018 | 0.044 | <0.010 | 0.060 | 0.39 | 0.64 | 0.28 | 0.28 |
| DOC | 4.74 | 5.0 | AO | 4.87 | 11.3 | 12.7 | 4.5 | 3.5 | 3.0 | 2.4 | 17.5 | 23.2 | 14.6 | 19.5 |

- 1. ODWS = Ontario Drinking Water Standards (June 2003, Revised June 2006).
- 2. AO: Aesthetic Objective; OG = Operational Guideline; MAC = Maximum Acceptable Concentration.
- 3. NV = No Value specified; NA = Not Applicable; ISW = Insufficient Water
- 4. Background concentrations calculated using data collected between 1988 through 2017 from monitoring well O-1.
- 5. Values in bold represent results greater than the ODWS.
- 6. Shaded values represent results greater than the Reasonable Use Criteria (RUC).
- 7. Samples analyzed by an accredited laboratory.
- 8. Results presented in mg/L (milligrams per litre) unless otherwise specified.

TABLE 5 SUMMARY OF LEACHATE CHARACTERIZATION

| Monitoring Location | | | | 0-2 | 0-2 | 0-2 |
|-------------------------------------|---------|-----------|-----------|----------|----------|----------|
| Sampling Date | UNITS | odws | RUC | 09-22-22 | 11-28-23 | 11-12-24 |
| INORGANICS | | | | | | |
| Alkalinity | mg/L | 30 - 500 | 404 | 911 | 917 | 855 |
| Total Ammonia-N | mg/L | NV | NV | 33.4 | 34.4 | 30.6 |
| Arsenic (As) | mg/L | 0.01 | N/A | 0.007 | <0.001 | <0.001 |
| Barium (Ba) | mg/L | 1 | N/A | 0.11 | 0.052 | 0.065 |
| Boron (B) | mg/L | 5 | N/A | 0.35 | 0.19 | 0.42 |
| Cadmium (Cd) | mg/L | 0.005 | N/A | <0.0001 | <0.0001 | <0.0001 |
| Calcium (Ca) | mg/L | NV | NV | 184 | 172 | 148 |
| Chloride (Cl-) | mg/L | 250 | 128 | 65.1 | 29.7 | 61.7 |
| Chromium (Cr) | mg/L | 0.05 | N/A | <0.002 | <0.002 | <0.002 |
| Conductivity | umho/cm | NV | NV | 1970 | 1610 | 1570 |
| Copper (Cu) | mg/L | 1.0 | N/A | 0.002 | 0.003 | 0.002 |
| Hardness (CaCO3) | mg/L | 80-100 | 527 | 643 | 579 | 548 |
| Iron (Fe) | mg/L | 0.3 | 0.17 | 22.5 | 0.53 | 0.02 |
| Lead (Pb) | mg/L | 0.01 | N/A | <0.0005 | <0.0005 | <0.0005 |
| Magnesium (Mg) | mg/L | NV | NV | 44.6 | 36.4 | 43.5 |
| Manganese (Mn) | mg/L | NV | NV | 0.66 | 0.20 | 0.37 |
| Mercury (Hg) | mg/L | 0.001 | N/A | <0.0001 | <0.0001 | |
| Nitrate (N) | mg/L | 10 | 3.33 | <0.07 | 1.22 | <0.05 |
| Nitrite (N) | mg/L | 1 | 0.25 | 1.98 | <0.05 | <0.05 |
| Total Kjeldahl Nitrogen (TKN) | mg/L | NV | NV | 35.4 | 34.6 | 31.8 |
| pH | рН | 6.5 - 8.5 | 6.5 - 8.5 | 7.27 | 7.17 | 7.43 |
| Total Phosphorus | mg/L | NV | NV | 0.05 | 0.12 | 0.14 |
| Potassium (K) | mg/L | NV | NV | 17.8 | 5.9 | 18.6 |
| Sodium (Na) | mg/L | 200 | 101 | 30 | 9.5 | 52.8 |
| Total Dissolved Solids | mg/L | 500 | N/A | 840 | 742 | 892 |
| Sulphate (SO4) | mg/L | 500 | 255 | <0.19 | 3.41 | 1.62 |
| Zinc (Zn) | mg/L | 5 | N/A | <0.005 | 0.008 | <0.005 |
| OTHER ORGANICS | | | | | | |
| Total BOD | mg/L | NV | NV | 4 | 5 | <20 |
| Total Chemical Oxygen Demand (COD) | mg/L | NV | NV | 60 | 40 | 46 |
| Dissolved Organic Carbon | mg/L | 5 | 4.9 | 24 | 11 | 18.5 |
| Phenols-4AAP | mg/L | NV | NV | 0.072 | 0.013 | 0.001 |
| VOLATILE ORGANICS | | | | | | |
| Benzene | mg/L | 0.001 | N/A | 0.0017 | 0.0014 | 0.0012 |
| 1,4-Dichlorobenzene | mg/L | 0.001 | N/A | <0.0002 | <0.001 | <0.0001 |
| Methylene Chloride(Dichloromethane) | mg/L | 0.05 | N/A | <0.0006 | <0.003 | <0.03 |
| Toluene | mg/L | 0.024 | N/A | <0.0004 | <0.002 | <0.0002 |
| Vinyl Chloride | mg/L | 0.001 | N/A | <0.0004 | <0.002 | <0.0002 |

- 1. ODWS = Ontario Drinking Water Standards (June 2003, Revised June 2006)
- 2. NV = No value specified
- 3. NM = Not Measured; N/A = Not Available
- 4. Values in bold represent results greater than the ODWS
- 5. Shaded values represent results greater than the Reasonable Use Criteria
- 6. Samples analyzed by Bureau Veritas.
- 7. Analytical parameters based on Schedule 5, Column 1 Comprehensive List for Groundwater and Leachate (O.Reg. 232/98, Rev. January 2012).

TABLE 6
BEDROCK GROUNDWATER QUALITY SUMMARY - 2024

| | Bkgd | ODV | vs | RUC | North (Up | gradient) | | est radient) |
|----------------------|-------|---------|------|---------|--------------|-----------|-----------|------------------|
| Parameter | Diigu | | | | В | 5 | P3 | P3 |
| Sampling Date | | | | | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 |
| Conductivity (uS/cm) | 663 | NV | NA | NV | 1260 | 1870 | 642 | 733 |
| pH (Unitless) | 8.02 | 6.5-8.5 | OG | 6.5-8.5 | 7.73 | 7.84 | 7.99 | 7.94 |
| Hardness | 543 | 80-100 | OG | 543 | 642 | 375 | 308 | 273 |
| Alkalinity | 250 | 30-500 | OG | 375 | 345 | 414 | 321 | 332 |
| Chloride | 10.5 | 250 | AO | 130 | 15.1 | 306 | 8.42 | 49.8 |
| Nitrate | ND | 10.0 | MAC | 2.5 | < 0.05 | < 0.07 | 0.24 | 0.44 |
| Nitrite | ND | 1.0 | MAC | 0.25 | < 0.05 | < 0.05 | < 0.05 | <0.05 |
| Sulphate | 147 | 500 | AO | 324 | 318 | 71.3 | 13.7 | 16.6 |
| Sodium | 4.26 | 200 | AO | 102 | 10.7 | 173 | 3.75 | 22.8 |
| Potassium | 1.27 | NV | NA | NV | 1.39 | 1.44 | 0.59 | <0.50 |
| Calcium | ND | NV | NA | NV | 173 | 106 | 84.6 | 72.3 |
| Magnesium | ND | NV | NA | NV | 50.9 | 26.8 | 23.6 | 22.5 |
| Ammonia | 0.06 | NV | NA | NV | 0.09 <0.02 | | <0.02 | <0.02 |
| Iron | 0.17 | 0.3 | AO | 0.24 | 0.026 <0.020 | | <0.020 | <0.020 |
| Boron | 0.01 | 5 | IMAC | 1.25 | 0.034 0.18 | | <0.010 | 0.023 |
| DOC | 3.6 | 5.0 | AO | 4.3 | 5.3 | 3.4 | 2.9 | 1.6 |

| | | | | | | | South (Dov | vngradient) | | |
|----------------------|------|---------|------|---------|-----------|-----------|------------|-------------|-----------|-----------|
| Parameter | Bkgd | ODV | VS | RUC | В | 2 | В | 13 | В | 34 |
| Sampling Date | - | | | | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 | 30-Apr-24 | 12-Nov-24 |
| Conductivity (uS/cm) | 663 | NV | NA | NV | 688 | 653 | 2690 | 2460 | 1560 | 1450 |
| pH (Unitless) | 8.02 | 6.5-8.5 | OG | 6.5-8.5 | 7.81 | 7.93 | 7.40 | 7.59 | 7.55 | 7.63 |
| Hardness | 543 | 80-100 | OG | 543 | 333 | 288 | 1310 | 1230 | 542 | 532 |
| Alkalinity | 250 | 30-500 | OG | 375 | 309 | 326 | 463 | 502 | 578 | 631 |
| Chloride | 10.5 | 250 | AO | 130 | 10.3 | 15.0 | 16.0 | 16.0 | 115 | 129 |
| Nitrate | ND | 10.0 | MAC | 2.50 | < 0.05 | < 0.05 | <0.14 | <0.14 | < 0.05 | < 0.05 |
| Nitrite | ND | 1.0 | MAC | 0.25 | < 0.05 | < 0.05 | <0.11 | <0.11 | < 0.05 | < 0.05 |
| Sulphate | 147 | 500 | AO | 324 | 50.2 | 39.1 | 983 | 888 | 53.9 | 58.5 |
| Sodium | 4.26 | 200 | AO | 102 | 10.6 | 12.1 | 16.0 | 19.7 | 72.1 | 69.0 |
| Potassium | 1.27 | NV | NA | NV | 1.45 | 1.30 | 3.17 | 3.35 | 5.63 | 7.13 |
| Calcium | ND | NV | NA | NV | 84.1 | 72.0 | 359 | 329 | 119 | 128 |
| Magnesium | ND | NV | NA | NV | 29.9 | 26.2 | 100 | 99.2 | 59.5 | 51.6 |
| Ammonia | 0.06 | NV | NA | NV | 0.20 | 0.29 | 0.12 | 0.16 | 2.92 | 4.16 |
| Iron | 0.17 | 0.3 | AO | 0.24 | <0.020 | <0.020 | 0.53 | 0.65 | <0.020 | <0.020 |
| Boron | 0.01 | 5 | IMAC | 1.25 | 0.048 | 0.054 | 0.047 | 0.069 | 0.22 | 0.27 |
| DOC | 3.6 | 5 | AO | 4.3 | 6.2 | 5.7 | 5.3 | 4.2 | 18.0 | 17.2 |

- 1. ODWS = Ontario Drinking Water Standards (June 2003, Revised June 2006).
- 2. RUC = Reasonable Use Criteria
- 3. AO = Aesthetic Objective; OG = Operational Guideline; MAC = Maximum Acceptable Concentration.
- 4. NV = No Value specified; NA = Not Applicable
- 5. Background concentrations calculated using data collected from 1988 through 2017 from monitoring well B-5.
- 6. Values in bold represent results greater than the ODWS.
- 7. Shaded values represent results greater than the Reasonable Use Criteria (RUC).
- 8. Samples analyzed by AGAT Laboratories, Ltd.
- 9. Results presented in mg/L (milligrams per litre) unless otherwise specified.

TABLE 7 SUMMARY OF SURFACE WATER QUALITY RESULTS - 2024

| Parameter | Units | PWQO | Trigger Level | S-1: Bac | kground | s | -6 | S- | 6A | S | -8 | s | -9 |
|--------------------|----------|------------|------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Sampling Date | | | (S-6) | 30-Apr-24 | 12-Nov-24 |
| CBOD ₅ | mg/L | NV | NV | <2 | <20 | <2 | <20 | <2 | <20 | <2 | <20 | <2 | <20 |
| Conductivity | uS/cm | NV | 2200 | 593 | 804 | 921 | 1000 | 825 | 977 | 363 | 492 | 328 | 471 |
| pH | unitless | 6.5 to 8.5 | NV | 8.14 | 7.73 | 8.05 | 7.81 | 8.06 | 7.85 | 8.15 | 7.97 | 8.16 | 7.91 |
| Hardness | mg/L | NV | NV | 220 | 410 | 351 | 414 | 321 | 409 | 193 | 277 | 176 | 269 |
| Alkalinity | mg/L | Note 5 | NV | 248 | 345 | 381 | 431 | 374 | 438 | 214 | 297 | 204 | 270 |
| Chloride | mg/L | NV | 60 | 42.2 | 34.0 | 31.3 | 81.4 | 28.7 | 80.2 | 4.31 | 6.88 | 0.69 | 5.68 |
| Nitrate | mg/L | NV | NV | 0.08 | < 0.05 | 1.48 | 0.65 | 1.60 | 0.51 | 0.05 | < 0.05 | < 0.05 | <0.05 |
| Nitrite | mg/L | NV | NV | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 | < 0.05 |
| Sulphate | mg/L | NV | NV | 4.43 | 81.3 | 41.8 | 27.7 | 38.0 | 29.6 | 2.98 | 12.4 | 0.75 | 10.8 |
| Ammonia | mg/L | NV | NV | 0.02 | < 0.02 | 1.11 | 0.18 | 0.82 | <0.02 | 0.03 | < 0.02 | 0.03 | <0.02 |
| DOC | mg/L | NV | NV | 14.2 | 13.1 | 15.4 | 12.0 | 15.0 | 11.3 | 17.1 | 16.7 | 7.8 | 17.4 |
| Phenols | mg/L | 0.001 | NV | 0.001 | <0.001 | 0.001 | <0.001 | 0.001 | <0.001 | <0.001 | <0.001 | 0.002 | <0.001 |
| TKN | mg/L | NV | NV | 0.26 | 0.24 | 2.31 | 0.40 | 1.78 | 0.46 | 0.20 | <0.10 | <0.10 | 0.18 |
| Phosphorus | mg/L | 0.02 | NV | 0.06 | < 0.02 | 0.05 | < 0.02 | 0.04 | 0.04 | 0.04 | < 0.02 | 0.05 | < 0.02 |
| Boron | mg/L | 0.2 | NV | 0.015 | <0.010 | 0.36 | 0.37 | 0.36 | 0.36 | 0.031 | 0.021 | 0.017 | 0.017 |
| Zinc | mg/L | 0.03 | NV | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 |
| Iron | mg/L | 0.3 | NV | < 0.050 | 0.22 | 0.20 | 2.29 | 0.13 | 1.15 | 0.068 | 0.079 | < 0.050 | 0.083 |
| Sodium | mg/L | NV | NV | 30.9 | 25.4 | 34.3 | 66.2 | 35.8 | 63.1 | 4.16 | 5.49 | 1.78 | 4.94 |
| Potassium | mg/L | NV | NV | 0.84 | 1.76 | 12.5 | 13.2 | 11.6 | 13.2 | 1.01 | 2.26 | 1.69 | 2.07 |
| Un-ionized Ammonia | mg/L | 0.02 | 0.06 | 0.0005 | <0.001 | 0.036 | 0.005 | 0.031 | <0.001 | 0.002 | <0.001 | 0.0012 | <0.001 |
| Field Conductivity | uS/cm | NV | 2200 | 737 | 920 | 838 | 1140 | 560 | 990 | 349 | 540 | 357 | 540 |
| Field pH | unitless | 6.5 to 8.5 | NV | 8.04 | 8.04 | 8.16 | 8.16 | 8.24 | 8.24 | 8.34 | 8.34 | 8.22 | 8.22 |
| Field Temperature | °C | NV | NV | 10.0 | 10.0 | 10.3 | 10.3 | 9.9 | 9.9 | 10.9 | 10.9 | 11.7 | 11.7 |

- 1. Analytical results presented in mg/L (milligrams per litre) unless otherwise specified.
- 2. PWQO = Provincial Water Quality Objectives (July 1994).
- 3. NV = No Value specified; NM = Not Monitored
- 4. Un-ionized ammonia calculated using pH and temperature per PWQO Guidelines.5. Alkalinity should not be decreased by more than 25% of the natural concentration.
- 6. Values that are in bold indicate an exceedance of the PWQO.
- 7. Values that are shaded indicate an exceedance of the Trigger Level.
- 8. Samples analyzed by an accredited laboratory.

ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Figures

Figure 1: Site Location Map

Figure 2: General Site Plan

Figure 3: Site Layout and Existing Conditions


Figure 4: Overburden Groundwater Flow


Figure 5: Bedrock Groundwater Flow

Figure 6: Final Contours

Figure 7: Chloride, Alkalinity and Potassium Concentrations

Figure 8: Surface Water Management Works – 2015 Air Photo





2402869

St. Edmund's Annual Report Part Lots 46 & 47, Conc. 3 W.B.R. Municipality of Northern Bruce Peninsula



LEGEND

 APPROXIMATE LIMIT OF EXISTING LANDFILL

EXISTING DITCH, SWALE

TREELINE

ACTIVE SURFACE WATER MONITORING STATION

FORMER SURFACE WATER MONITORING STATION

MONITORING WELL - OVERBURDEN BEDROCK PIEZOMETER

NOTES:

- 1. SURFACE DRAINAGE FEATURES WERE SURVEYED BY GAMSBY AND MANNEROW LIMITED ON APRIL 25, 2007.
- 2. THE INFORMATION SHOWN HERE WAS OBTAINED FROM A DRAWING BY HENDERSON PADDON AND ASSOCIATES LIMITED, DATED JUNE 2005.
- 3. LOCATION OF PROPERTY LINES ARE APPROXIMATE ONLY.
- 4. FIGURES WERE ADJUSTED IN 2022 TO SUIT UTM DERIVED COORDINATES AND THE ELEVATIONS ACROSS THE SITE WERE LOWERED BY $0.7 \mathrm{m}$.

SCALE = 1:2,500 APRIL 2025

SITE LAYOUT & EXISTING CONDITIONS


ST. EDMUNDS WASTE DISPOSAL SITE

Figure No. 3



VED BY: Kenboe3954, 4/29/2025 12:22:58 PM PLOTTED BY:Boers, Ken 4/29/2025 12:24:30 PM

C:AutoCAD Drawings/Z40z869 St Edmunds Afrik Figures.awg LATOUT:FIG 6 SAVED BY:Kenboe3954, 4/29/2025 12:22:58 PM PLOTTED BY:Boers. Ken 4/29/2025 12:24



2402869

St. Edmund's Annual Report Part Lots 46 & 47, Conc. 3 W.B.R. Municipality of Northern Bruce Peninsula



LEGEND

APPROXIMATE LIMIT OF EXISTING LANDFILL EXISTING DITCH, SWALE

FORMER SURFACE WATER MONITORING STATION MONITORING WELL - OVERBURDEN

BEDROCK PIEZOMETER

ALKALINITY SPRING/FALL (mg/L) POTASSIUM CONCENTRATION SPRING/FALL (mg/L)

SPRING VALUE / FALL VALUE

- THE INFORMATION SHOWN HERE WAS OBTAINED FROM A DRAWING BY HENDERSON PADDON AND ASSOCIATES LIMITED, DATED
- 2. LOCATION OF PROPERTY LINES ARE APPROXIMATE ONLY
- PARAMETER CONCENTRATIONS PRESENTED WERE MEASURED DURING THE SPRING & FALL OF 2021.
- 4. FIGURES WERE ADJUSTED IN 2022 TO SUIT UTM DERIVED COORDINATES AND THE ELEVATIONS ACROSS THE SITE WERE LOWERED BY 0.7m.

SCALE = 1:2,500 **APRIL 2025**

CHLORIDE, ALKALINITY & POTASSIUM CONCENTRATIONS

ST. EDMUNDS WASTE DISPOSAL SITE

Figure No. 7



2402869

St. Edmund's Annual Report Part Lots 46 & 47, Conc. 3 W.B.R. Municipality of Northern Bruce Peninsula



LEGEND

ACTIVE SURFACE WATER MONITORING STATION

EXISTING DITCH, SWALE

MUNICIPAL PROPERTY BOUNDARY

SCALE = 1:2,000 APRIL 2025

SURFACE WATER MANAGEMENT WORKS-2015 AIR PHOTO

ST. EDMUNDS WASTE DISPOSAL SITE

Figure No. 8



ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix A Environmental Compliance Approvals



Ministry of the Environment

PROVISIONAL CERTIFICATE OF APPROVAL WASTE DISPOSAL SITE

Under The Environmental Protection Act, 1971 and the regulations and subject to the immitations thereof, this Provisional Certificate of Approval is issued to:

Township of St. Edmunds Box 70 Tobermory, Ontario NOH 2RO

for the use and operation of a 3.2 hectare landfilling site within a total area of 45 hectares

all in accordance with the following plans and specifications: Report entitled "Sanitary Landfill Utilization Report File 1 77283" prepared jointly by Ainley and Associates Limited, Consulting Engineers and Planners, and by Ian D. Wilson Associates Limited, Consulting Hydrogeologists, dated August, 1978. Located:

Lot 47 and Part Lot 46, Concession 3 W.B.R. Township of St. Edmunds

which includes the use of the six only for the disposal of the following categories of waste (NOTE: Use of the six for additional categories of wastes requires a new application and amendments to the Provisional Certificate of Approval) Domestic, Commercial and 22 other limited to brush and lumber

and subject to the following conditions:

In this condition shall be carried out at the site after sixty days from this condition becoming enforceable unless this Certificate Including the reasons for this condition has been registered by the applicant as an instrument in the appropriate Land Registry Office against title to the site and a duplicate registered copy thereof has been returned by the applicant to the Director.

Dated this 14 day of March, 1980

Director, Section 39, The Environmental Protection Act, 1971

8]

. .



Ministry of the Environment

Ministère de l'Environnement

The Corporation of the Township of St. Edmunds P.O. Box 70
Tobermory, Ontario
NOH 2R0

You are hereby notified that the Provisional Certificate of Approval No. A 273002 dated March 14, 1980, is hereby amended as follows:

A. The first page of the Certificate of Approval is amended to read:

for the use and operation of a 3.33 hectare landfilling site within a
total are of 82 hectares

all in accordance with the following plans and specifications:

- Application for Approval of a Waste Disposal Site (to amend the existing Certificate of Approval) dated January 11, 1996 with a cover letter from Ross Slaughter, P.Eng., of Henderson, Paddon & Associates Limited, to Mr. Jim Janse of the Ministry of the Environment, dated January 16, 1996.
- Document entitled "Plan of Development and Operation, Township of St, Edmunds Landfill", revised July 1995.
- Drawing entitled "Present Landuse, Figure 1" and drawing entitled "Site Plan and Buffer Area Landfill, Township of St. Edmunds, Figure 2", dated March 21, 1991.

All other conditions on the original Provisional Certificate of Approval, dated March 14, 1980, and as amended, not affected by this amendment, remain in effect.

This Notice shall constitute part of the approval issued under Certificate of Approval No. A 273002 dated March 14, 1980.

In accordance with Section 139 of the Environmental Protection Act, R.S.O. 1990, Chapter E-19, may by written notice served upon me, the Environmental Appeal Board and the Environmental ommissioner, Environmental Bill of Rights, S.O. 1993, Chapter 28, within 15 days after receipt of this Notice, quire a hearing by the Board. Section 142 of the Environmental Protection Act, as amended provides that the Notice requiring a hearing shall state:



Ministry. of the

Ministère

de

Environment

l'Environnement

The portions of the approval or each term or condition in the approval in respect of which the hearing is

The grounds on which you intend to rely at the hearing in relation to each portion appealed.

In addition to these legal requirements, the Notice should also include:

The name of the appellant;

The address of the appellant;

The Certificate of Approval number;

The date of the Certificate of Approval;

The name of the Director;

The municipality within which the waste disposal site is located;

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

The Secretary, fronmental Appeal Board, JOO Yonge St., 12th Fl., O. Box 2382 oronto, Ontario. M4P 1E4

The Environmental Commissioner, 1075 Bay Street, Suite 605, 6th Floor, Toronto, Ontario. M5S 2W5

The Director, Section 39, Environmental Protection Act, Ministry of the Environment, 250 Davisville Avenue, 3rd Floor, Toronto, Ontario. M4S 1H2

This instrument is subject to Section 38 of the Environmental Bill of Rights, that allows residents Ontario to seek leave to appeal the decision on this instrument. Residents of Ontario may seek to appeal for 15 days from the date this decision is placed on the Environmental Registry. By accessing the Environmental Registry, you can determine when the leave to appeal period ends.

DATED AT TORONTO this 10th day of July, 1998.

P. Eng. A. Dominski,

Director Section 39

Environmental Protection Act

District Manager, Barrie



Ministry of the

nistry Ministère

ne de

Environment l'Environnement

PROVISIONAL CERTIFICATE OF APPROVAL FOR A WASTE DISPOSAL SITE (LANDFILL)

NO. A273003 PAGE 1 OF 7

Under the Environmental Protection Act and the regulations and subject to the limitations thereof, this Provisional Certificate of Approval is issued to:

The Corporation of the Township of St. Edmunds P.O. Box 70
Tobermory, Ontario
NOH 2R0

for the use and operation of a Waste Disposal Site (Landfill)

all in accordance with the following plans and specifications:

the application for a Certificate of Approval for a Waste Disposal Site (Landfill) dated March 23, 1993, and the supporting information found in Schedule A.

Located:

Lot 47, Concession III W.B.R. Township of St. Edmunds County of Bruce

which includes the use of the site only for the final disposal by landfilling of the following category of waste (Note: Use of the site or additional categories of wastes requires a new application and am iments to the Provisional Certificate of Approval)

STUMPS

and subject to the following conditions:

A. Definitions

- 1. For the purpose of this Provisional Certificate of Approval:
 - a. "Act" means the <u>Environmental Protection Act</u>, R.S.O. 1990, C.E-19 as amended;
 - b. "Certificate" means Provisional Certificate of Approval for a Waste Disposal Site (Landfill);
 - c. "Director" means the Regional Director, Southwestern Region, Ontario Ministry of the Environment and Energy;

ורפונטי פלפן

- d. "District Office" means the Owen Sound District Office, Southwestern Region, Ontario Ministry of the Environment and Energy;
- e. "District Officer" means the District Officer of the Owen Sound District Office, Ontario Ministry of the Environment and Energy;
- f. "Minister" means the Minister of the Ontario Ministry of the Environment and Energy;
- g. "Ministry" means the Ontario Ministry of the Environment and Energy;
- h. "Proponent" means The Corporation of the Township of St. Edmunds;
- i. "Regional Office" means the London Regional Office of the Ontario Ministry of the Environment and Energy;
- j. "Site" means Lot 47, Concession III W.B.R., St. Edmunds Township, Bruce County.

General

Except as otherwise provided by the Special Terms and Conditions set out in this Certificate, the Waste Disposal Site (Landfill) shall be operated in accordance with the application for a Certificate of Approval for the Waste Disposal Site (Landfill) dated March 23, 1993, and the documents as listed under Schedule "A" attached.

Where there is a conflict between a provision of any document referred to in Condition (2) and the Conditions of this Certificate, the Conditions in this Certificate shall take precedence.

Requirements specified in this Certificate are the requirements under the Act. Issuance of this Certificate in no way abrogates the Proponent's legal obligations to take all reasonable steps to avoid violating other applicable provisions of the Act and other legislation and regulations.

Requirements of this Certificate are severable. If any requirement of this Certificate, or the application of any requirement of this Certificate to any circumstance, is held invalid, the application of such requirement to other circumstances and the remainder of this Certificate shall not be affected thereby.

The Proponent must ensure compliance with all terms and Conditions of this Certificate. Any non-compliance constitutes a violation of the Act and is grounds for enforcement.

PROVISIONAL CERTIFICATE OF APPROVAL FOR A WASTE DISPOSAL SITE (LANDFILL) NO. A273003 PAGE 3 OF 7

Any information relating to this Certificate and contained in Ministry files may be made available to the public in accordance with the provisions of the <u>Freedom of Information and Protection of Privacy Act</u>, R.S.O. 1990, C. F-31.

The Proponent shall notify the District Officer in writing of any of the following changes within thirty (30) days of the change occurring:

- a. i. change of Owner or operator of the Site or both;
 - ii. change of address or address of the new Owner;
 - iii. change of partners where the Owner or operator is or at any time becomes a partnership, and a copy of the most recent declaration filed under the <u>Business Names Act</u>, 1991 shall be included in the notification to the District Officer;
 - iv. any change of name of the corporation where the Owner or operator is or at any time becomes a corporation, and a copy of the most current "Initial Notice or Notice of Change" (form 1 or 2 of O. Reg. 182, Chapter C-39, R.R.O. 1990 as amended from time to time), filed under the <u>Corporations</u> <u>Information Act</u> shall be included in the notification to the District Officer;
 - v. change in directors or officers of the corporation where the Owner or operator is or at any time becomes a corporation, and a copy of the most current "Initial Notice or Notice of Change" as referred to in 8(a)(iv), supra;
- b. In the event of any change in ownership of the Site, the Owner shall notify in writing the succeeding owner of the existence of this Certificate, and a copy of such notice shall be forwarded to the District Officer.
- If any changes to the Site are contemplated, application shall be made to the Ministry for approval, and such changes shall not be made until approval has been granted by the Director.
- 10. This Certificate shall be registered on the title to the lands comprising the waste disposal site. No operation shall be carried out at the site after sixty days from the date of this Certificate unless this Certificate including the reasons for this condition have been registered by the proponent as an instrument in the appropriate Land Registry Office against title to the site and a duplicate registered copy thereof returned by the applicant to the Director and District Officer.

site Operations

- a. The amount of waste to accepted at this Site may not exceed 200 cubic metres per day.
 - b. This Site is limited to a maximum filling capacity of 35,800 cubic metres.
- 12. The disposal of any waste, other than Stumps is prohibited at this Site.
- 13. The burning of wastes is prohibited at this Site.

b: Annual Report

£ .

Ĺā

- The annual report for the St. Edmunds Township Landfill, Provisional Certificate of Approval for a Waste Disposal Site (Landfill) Number A273002, shall include but not be limited to the following information as it pertains to the stump disposal site approved under this Certificate:
 - a. a yearly summary of the volumes of wastes received at the Site;
 - any environmental and operational problems encountered during the operation of the Site and any mitigative actions taken;
 - a statement as to compliance with all Conditions of approval and with the inspection and reporting requirements of the Conditions; and
 - any recommendations to minimize impacts and improve Site operations.

PROVISIONAL CERTIFICATE OF APPROVAL FOR A WASTE DISPOSAL SITE (LANDFILL) NO. A273003 PAGE 5 OF 7

4.3

. .

SCHEDULE "A"

This Schedule "A" forms part of Provisional Certificate of Approval: A

- Hydrogeological Investigation Landfill Site St. Edmunds Township by Henderson, Paddon & Associates & Morrison Beatty Ltd., October 1989.
- Plan of Development and Operation Township of St. Edmunds Landfill, June 1992.
- Engineering Plan Drawing No. 9048-01 Existing conditions, bottom elevations and final contours, Waste Disposal Site, Township of St. Edmunds, Revised March 1993.
- 4. Engineering Plan Drawing No. 9048-02 Site Development Plan, Waste Disposal Site, Township of St. Edmunds, Revised March 1993, Stump Disposal Site.
- 5. Extract from Bruce County Official Plan.
 - Extract from Zoning By-Law 1986-12.
- 7. By-Law No. 78-34.
- Figure No. 2A showing landfill area and stump dump area and buffer owned by Township of St. Edmunds.

PROVISIONAL CERTIFICATE OF APPROVAL FOR A WASTE DISPOSAL SITE (LANDFILL) NO. A273003 PAGE 6 OF 7

The reasons for the imposition of these Conditions are as follows:

1.1

μ.

L. .

2.

The reason for Condition 1 is to simplify the wording of the subsequent Conditions and to define the specific meaning of terms as used in this Certificate.

The reason for Conditions 2, 11, 12 and 13 is to ensure that the Waste Disposal Site (Landfill) is operated in accordance with the application, supporting information, the Certificate of Approval and the Act.

The reason for Conditions 3, 4, 5, 6, 7, 8 and 9 is to clarify the legal rights and obligations of this Certificate of Approval.

The reason for Condition 10 requiring registration of the Certificate, is that Section 46 of the Act, prohibits any use being made of the lands after they cease to be used for waste disposal purposes within a period of twenty five years from the year in which such land ceased to be used, unless approval of the Minister for the proposed use has been given. The purpose of this prohibition is to protect future occupants of the site and the environment from any hazards which might occur as a result of waste being disposed of on the site. This prohibition and potential hazard should be drawn to the attention of future owners and occupants by the Certificate being registered on title.

The reason for Condition 14 is to ensure that the Proponent submits a yearly summary of the Site operations to this Ministry.

PROVISIONAL CERTIFICATE OF APPROVAL FOR A WASTE DISPOSAL SITE (LANDFILL) NO. A2 73003 PAGE 7 OF 7

You may by written notice served upon me and the Environmental Appeal Board within 15 days after receipt of this Notice, require a hearing by the Board. Section 142 of the Environmental Protection Act, R.S.O. 1990 c. E-19, as amended, provides that the Notice requiring the hearing shall state:

The portions of the approval or each term or condition in the approval in respect of which the hearing is required, and;

The grounds on which you intend to rely at the hearing in relation to each portion appealed.

In addition to these legal requirements, the Notice should also include:

The name of to appellant;

The address of the appellant;

The Certificate of Approval number;

The date of the Certificate of Approval;

The name of the Director;

The municipality within which the waste disposal site is located;

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

The Secretary, Environmental Appeal Board, 12 St. Clair Avenue West, Juite 502, to, Ontario,

Te

14 - 1N3

AND

The Director, Section 39, Environmental Protection Act, Ministry of the Environment and Energy, 985 Adelaide Street South London, Ontario, N6E 1 V3

| DATED | AT LONDON this | 15+ | day of | Cctober | 1002 |
|-------|------------------|-----|------------|---------------|---------|
| | III LONDON IIIIS | | _ auy oj _ | 0 0 0 0 0 0 0 | , 1993. |

Director,

Section 39,

Environmental Protection Act



Ministry of the Environment

de l'Environnement

Ministère

The Corporation of the Township of St. Edmunds P.O. Box 70
Tobermory, Ontario
NOH 2R0

You are hereby notified that the Provisional Certificate of Approval No. A 273003 dated October 1, 1993, is hereby amended as follows:

A. The first page of the Certificate of Approval is amended to read:

for the use and operation of a 2.02 hectare Waste Disposal Site (stump disposal) within a total area of 82 hectares

- 8. Condition 11 is hereby revoked and replaced with the following:
 - 11. (a) The amount of waste to be accepted at this Site may not exceed 200 cubic metres per day; and
 - (b) This Site is limited to a final volumetric capacity of 54,700 cubic metres.
- The Schedule "A" attached to the original Provisional Certificate of Approval No. A 273003, dated October 1, 1993, is hereby amended to add, in addition to those articles already listed, the following:
 - 9. Application for Approval of a Waste Disposal Site (to amend the existing Certificate of Approval) dated December 7, 1995 with a cover letter from Ross Slaughter, P.Eng., of Henderson, Paddon & Associates Limited, to Mr Todd Fleet of the Ministry of the Environment, dated December 14, 1995.
 - Document entitled "Plan of Development and Operation, Township of St. Edmunds Landfill", revised July 1995.
 - 11. Drawing entitled "Present Landuse, Figure 1" and drawing entitled "Site Plan and Buffer Area Landfill, Township of St. Edmunds, Figure 2", dated March 21, 1991.
 - 12. Engineering Plan Drawing No. 9048-01 existing conditions, bottom elevations and final contours, Waste Disposal Site, Township of St. Edmunds, revised July 1994.
 - Engineering Plan Drawing No. 9048-02A Stump Dump Disposal Plan, Waste Disposal Site, Township of St. Edmunds, revised December 1995.

.ll other conditions on the original Provisional Certificate of Approval, dated October 1, 1993, and as amended, not affected by this amendment, remain in effect.

This Notice shall constitute part of the approval issued under Certificate of Approval No. A 273003 dated October 1, 1993.



Ministry of the Environment

Ministère de

l'Environnement

NOTICE Page 2 of 2

In accordance with Section 139 of the Environmental Protection Act, R.S.O. 1990, Chapter E-19, you may by written notice served upon me, the Environmental Appeal Board and the Environmental Commissioner, Environmental Bill of Rights, S.O. 1993, Chapter 28, within 15 days after receipt of this Notice, require a hearing by the Board. Section 142 of the Environmental Protection Act, as amended provides that the Notice requiring a hearing shall state:

- The portions of the approval or each term or condition in the approval in respect of which the hearing is 1.
- The grounds on which you intend to rely at the hearing in relation to each portion appealed. 2.

In addition to these legal requirements, the Notice should also include:

- The name of the appellant;
- The address of the appellant;
- The Certificate of Approval number; 5.
- The date of the Certificate of Approval; 6.
- The name of the Director; 7.
- The municipality within which the waste disposal site is located; 8.

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

The Secretary,

Environmental Appeal Board, 2300 Yonge St., 12th Fl.,

P.O. Box 2382

Toronto, Ontario.

₩4P1E4

The Environmental Commissioner,

1075 Bay Street,

Suite 605,

6th Floor, Toronto, Ontario.

M5S 2W5

The Director,

Section 39, Environmental Protection Act, Ministry of the Environment,

250 Davisville Avenue, 3rd Floor,

Toronto, Ontario.

M4S 1H2

This instrument is subject to Section 38 of the Environmental Bill of Rights, that allows residents of Ontario to seek leave to appeal the decision on this instrument. Residents of Ontario may seek to appeal for 15 days from the date this decision is placed on the Environmental Registry. By accessing the Environmental Registry, you can determine when the leave to appeal period ends:

DATED AT TORONTO this 10th day of July, 1998.

A. Dominski, P. Eng.

Director

Section 39 Environmental Protection Act

TF/st cc: District Manager, Barrie





Ministry of the Environment Ministère de l'Environnement

CERTIFICATE OF APPROVAL MUNICIPAL AND PRIVATE SEWAGE WORKS

NUMBER 5854-7DSSDD Issue Date: July 11, 2008

The Corporation of the Municipality of Northern Bruce Peninsula 56 Lindsay Road 5
Rural Route, No. 2, Lions Head
Northern Bruce Peninsula, Ontario
N0H 1W0

Site Location:

St. Edmunds Waste Disposal Site Lot 46 & 47, Concession 3 WBR

Northern Bruce Peninsula Municipality, County of Bruce

You have applied in accordance with Section 53 of the Ontario Water Resources Act for approval of:

a stormwater management facility for a total drainage area of 10.2 ha consisting of an existing 3.33 ha for municipal waste disposal, an existing 2.02 ha for tree stump disposal, and remaining 4.67 ha for access roads and recycling area, located within a total of 82 ha landfill property of the St. Edmunds Landfill Site which is located in the Municipality of Northern Bruce Peninsula, County of Bruce, designed to attenuate stormwater runoff from storm events up to 1:100 year return frequency to predevelopment levels, consisting of the following:

External Drainage Ditch (EDD)

one (1) triangular drainage ditch approximately 900 m long with depths ranging from 0.2 m to 1.5 m and side slopes of 3H:1V, running from McArthur Road in a westerly direction through a proposed new diversion drainage ditch, designed to separate non-contact stormwater runoff from stormwater runoff originating from the approved landfill footprint, then in a southerly direction to a drainage ditch along the north side of Warner Bay Road, discharging to an existing Borrow Pit Pond (BPP2) described below;

Northwest Perimeter Drainage Ditch (NWPDD)

 one (1) triangular drainage ditch approximately 300 m long with depths ranging from 0.2 m to 1.5 m, 0.5% grades, and side slopes of 3H:1V, running along the north side of the landfill site in a westerly direction and then in a southerly direction conveying stormwater runoff from western portion of the approved landfill footprint, discharging to a forebay of a proposed stormwater management pond (SWM Pond) described below;

Northeast Perimeter Drainage Ditch (NEPDD)

one (1) triangular drainage ditch approximatell 380 m long with depths ranging from 0.2 m to 1.5 m, 0.5% grades, and side slopes of 3H:1V, running along the north side of the landfill site in an easterly direction and then in a southerly direction conveying stormwater runoff from eastern portion of the approved landfill footprint, discharging to a forebay of a proposed stormwater management pond (SWM Pond) described below;

Stormwater Management Pond (SWM Pond)

one (1) 215 m long and 15.0 m wide wet extended detention stormwater management pond with a maximum depth of 1.5 m and 5H:1V side slopes, providing a maximum storage capacity of 2,365 m³, located at the southern part of the landfill footprint, equipped with two (2) 70 m³ storage capacity shallow forebays at each end of the pond, receiving stormwater runoff from the approved landfill footprint only, equipped with a 20 m long 375 mm diameter PVC discharge control outlet pipe, discharging to an existing west drainage ditch described above;

Borrow Pit Pond (BPP2)

- one (1) stormwater management pond located at the southwest corner of the 82 ha landfill site property and approximately 800 m from the approved landfill footprint, created as a result of cover material extraction activities, having an approximate dimensions of 80 m long, 50 m wide, and 2.5 m deep, providing a total storage capacity of 10,000 m³, receiving stormwater flows from the drainage ditches described above, discharging to Warner Bay Road roadside ditch and eventually through Hopkins Bay to Lake Huron;
- all associated controls and appurtenances.

all in accordance with the Application for Approval of Municipal and Private Sewage Works submitted by The Municipality of Northern Bruce Peninsula dated August 21, 2007 and engineering drawings and design specifications prepared by Gamsby and Mannerow Limited, Owen Sound, Ontario, and the following documents:

- "Certificate of Approval Application, St. Edmunds Landfill Site, Municipality of Northern Bruce Peninsula" dated May 2007, prepared by Gamsby and Mannerow Limited, Consulting Professional Engineers, Owen Sound.
- 2. "Plan of Development and Operation Township of St. Edmunds Landfill" revised July 1995, prepared by Henderson Paddon & Associates Limited, Owen Sound, Ontario.

 "Surface Water Management Report, St. Edmunds Landfill Site, Municipality of Northern Bruce Peninsula" dated August 2007, prepared by Gamsby and Mannerow Limited, Consulting Professional Engineers, Owen Sound.

For the purpose of this Certificate of Approval and the terms and conditions specified below, the following definitions apply:

"Act" means the Ontario Water Resources Act, R.S.O. 1990, Chapter 0.40, as amended;

"Certificate" means this entire certificate of approval document, issued in accordance with Section 53 of the Act, and includes any schedules;

"Director" means any Ministry employee appointed by the Minister pursuant to section 5 of the Act;

"District Manager" means the District Manager of the Owen Sound District Office of the Ministry;

"Ministry " means the Ontario Ministry of the Environment;

"Owner" means The Municipality of Northern Bruce Peninsula and includes its successors and assignees;

"Works" means the sewage works described in the Owner's application, this Certificate and in the supporting documentation referred to herein, to the extent approved by this Certificate.

You are hereby notified that this approval is issued to you subject to the terms and conditions outlined below:

TERMS AND CONDITIONS

1. GENERAL PROVISIONS

- (1) The Owner shall ensure that any person authorized to carry out work on or operate any aspect of the Works is notified of this Certificate and the conditions herein and shall take all reasonable measures to ensure any such person complies with the same.
- (2) Except as otherwise provided by these Conditions, the Owner shall design, build, install, operate and maintain the Works in accordance with the description given in this Certificate, the application for approval of the works and the submitted supporting documents and plans and specifications as listed in this Certificate.
- (3) Where there is a conflict between a provision of any submitted document referred to in this Certificate and the Conditions of this Certificate, the Conditions in this Certificate

shall take precedence, and where there is a conflict between the listed submitted documents, the document bearing the most recent date shall prevail.

- (4) Where there is a conflict between the listed submitted documents, and the application, the application shall take precedence unless it is clear that the purpose of the document was to amend the application.
- (5) The requirements of this *Certificate* are severable. If any requirement of this *Certificate*, or the application of any requirement of this *Certificate* to any circumstance, is held invalid or unenforceable, the application of such requirement to other circumstances and the remainder of this certificate shall not be affected thereby.

2. EXPIRY OF APPROVAL

The approval issued by this Certificate will cease to apply to those parts of the Proposed Works which have not been constructed within five (5) years of the date of this Certificate.

CHANGE OF OWNER

- (1) The Owner shall notify the District Manager and the Director, in writing, of any of the following changes within 30 days of the change occurring:
 - (a) change of Owner;
 - (b) change of address of the Owner;
 - (c) change of partners where the *Owner* is or at any time becomes a partnership, and a copy of the most recent declaration filed under the <u>Business Names Act</u>, R.S.O. 1990, c.B17 shall be included in the notification to the *District Manager*; and
 - (d) change of name of the corporation where the *Owner* is or at any time becomes a corporation, and a copy of the most current information filed under the <u>Corporations Information Act</u>, R.S.O. 1990, c. C 39 shall be included in the notification to the *District Manager*.
- (2) In the event of any change in ownership of the Works, other than a change to a successor municipality, the Owner shall notify in writing the succeeding owner of the existence of this Certificate, and a copy of such notice shall be forwarded to the District Manager and the Director.

4. MONITORING AND RECORDING

The Owner shall carry out the following monitoring program:

- (1) All samples and measurements taken for the purposes of this *Certificate* are to be taken at a time and in a location characteristic of the quality and quantity of the effluent stream over the time period being monitored.
- (2) The Owner shall collect at least three (3) stormwater grab samples at a semi-annual frequency during spring and fall period from the designated sampling locations and analyse for the parameters listed in Table 1.

| Table Sampling Locations: | e 1 - Surface Water Monitori S-1 (EDD), S-6 (SWM Pond) | ng and S-9 (BPP 2) |
|---------------------------|---|-----------------------|
| Parameter | Parameter | Field Parameter |
| Alkalinity | CBOD5 | pH |
| Hardness | Chloride | Temperature |
| Conductivity | Boron | Conductivity |
| pН | Phenols | |
| Total Ammonia | Total Phosphorus | - |
| Nitrate | Sulphate | |
| Nitrite | Iron | |
| TKN | Zinc | |
| DOC | | |

- * Note: Samples shall be collected as soon as practically possible after a rainfall event resulting in a stormwater discharge from the pond during spring and fall period.
- (3) The methods and protocols for sampling, analysis and recording shall conform, in order of precedence, to the methods and protocols specified in the following:
 - (a) the Ministry's Procedure F-10-1, "Procedures for Sampling and Analysis Requirements for Municipal and Private Sewage Treatment Works (Liquid Waste Streams Only), as amended from time to time by more recently published editions;
 - (b) the Ministry's publication "Protocol for the Sampling and Analysis of Industrial/Municipal Wastewater" (January 1999), ISBN 0-7778-1880-9, as amended from time to time by more recently published editions; and
 - (c) the publication "Standard Methods for the Examination of Water and Wastewater" (21st edition), as amended from time to time by more recently published editions.
- (4) The measurement frequencies specified in subsection (2) in respect to any parameter are minimum requirements which may, after two (2) years of monitoring in accordance with this Condition, be modified by the *District Manager* in writing from time to time.

(5) The Owner shall retain for a minimum of three (3) years from the date of their creation, all records and information related to or resulting from the monitoring activities required by this Certificate.

5. OPERATION AND MAINTENANCE

- (1) Within six (6) months of the issuance date of this Certificate, the Owner shall prepare a "Stormwater Management Contingency and Remedial Action Plan" for the Works and submit it for approval to the District Manager.
- (2) The Owner shall compare monitoring results for sampling location S-6 (SWM Pond) obtained under Section 4 (2) with the corresponding trigger level of each parameter listed in Table 2 to identify any leachate contamination of stormwater.

| to a contract of the contract | able 2 Parameters |
|---|---------------------------------------|
| Parameter | Trigger Level (mg/L unless indicated) |
| Ammonia (Un-ionized) | 0.06 |
| Chloride | 60 |
| Conductivity (uS/cm) | 2,200 |

- (3) In the event of an exceedence of a trigger level for any of the trigger parameters, the Owner shall implement the "Stormwater Management Contingency and Remedial Action Plan" approved under Condition 5 (1) to identify the cause of contamination and implement remedial measures.
- (4) The Owner shall maintain a record of all trigger level exceedence events identified under Condition 5 (3). The Owner shall report all trigger level exceedence events and all contingency and remedial measures implemented in the annual monitoring report prepared under Condition 6 (2).
- (5) After two years of monitoring in accordance with Condition 4 (2), the Owner may submit to the District Manager an assessment report and a proposal to modify the list of trigger parameters and corresponding trigger levels stipulated under Condition 5 (2). Any modification to the list of trigger parameters and corresponding trigger levels shall be approved by the District Manager in writing from time to time.
- (6) The Owner shall inspect the Works at least once a year and, if necessary, clean and maintain the Works to prevent the excessive build-up of sediments and/or vegetation.
- (7) The Owner shall maintain a logbook to record the results of these inspections and any

cleaning and maintenance operations undertaken, and shall keep the logbook at the site and/or Owner's operational headquarter for inspection by the Ministry. The logbook shall include the following:

- (a) the name of the Works;
- (b) the date and results of each inspection, maintenance and cleaning, including an estimate of the quantity of any materials removed; and
- (c) the volume of contaminated stormwater disposed off-site, the date, and the name of the receiving sewage treatment plant.

6. REPORTING

- The Owner shall, upon request, make all manuals, plans, records, data, procedures and supporting documentation available to Ministry staff.
- (2) The Owner shall prepare, and submit to the District Manager upon request, a performance report, on an annual basis, by April 30th following the end of the period being reported upon. The first such report shall cover the first annual period following the commencement of operation of the Works and subsequent reports shall be submitted to cover successive annual periods following thereafter. The reports shall contain, but shall not be limited to, the following information:
 - a summary of all monitoring results undertaken in the reporting period including sampling locations and dates;
 - (b) a description of any operating problems encountered and corrective actions taken; and
 - (c) a summary of all maintenance carried out on any major structure or thing forming part of the Works.

The reasons for the imposition of these terms and conditions are as follows:

- 1. Condition 1 is imposed to ensure that the Works are built and operated in the manner in which they were described for review and upon which approval was granted. This condition is also included to emphasize the precedence of Conditions in the Certificate and the practice that the Approval is based on the most current document, if several conflicting documents are submitted for review. The condition also advises the Owners their responsibility to notify any person they authorized to carry out work pursuant to this Certificate the existence of this Certificate.
- 2. Condition 2 is included to ensure that, when the Works are constructed, the Works will

meet the standards that apply at the time of construction to ensure the ongoing protection of the environment.

- 3. Condition 3 is included to ensure that the *Ministry* records are kept accurate and current with respect to the approved works and to ensure that subsequent owners of the *Works* are made aware of the *Certificate* and continue to operate the *Works* in compliance with it.
- 4. Condition 4 is included to enable the *Owner* to evaluate and demonstrate the performance of the *Works*, on a continual basis, so that the *Works* are properly operated and maintained at a level which is consistent with the design objectives specified in the *Certificate* and that the *Works* does not cause any impairment to the receiving watercourse.
- 5. Condition 5 is included to require that the Works be properly operated, maintained, funded, staffed and equipped such that the environment is protected and deterioration, loss, injury or damage to any person or property is prevented. As well, the inclusion of a comprehensive operations manual governing all significant areas of operation, maintenance and repair is prepared, implemented and kept up-to-date by the owner and made available to the Ministry.
- 6. Condition 6 is included to provide a performance record for future references, to ensure that the *Ministry* is made aware of problems as they arise, and to provide a compliance record for all the terms and conditions outlined in this *Certificate*, so that the *Ministry* can work with the *Owner* in resolving any problems in a timely manner.

In accordance with Section 100 of the <u>Ontario Water Resources Act</u>, R.S.O. 1990, Chapter 0.40, as amended, you may by written notice served upon me and the Environmental Review Tribunal within 15 days after receipt of this Notice, require a hearing by the Tribunal. Section 101 of the <u>Ontario Water Resources Act</u>, R.S.O. 1990, Chapter 0.40, provides that the Notice requiring the hearing shall state:

- 1. The portions of the approval or each term or condition in the approval in respect of which the hearing is required, and;
- The grounds on which you intend to rely at the hearing in relation to each portion appealed.

The Notice should also include:

- 3. The name of the appellant;
- The address of the appellant;
- 5. The Certificate of Approval number;
- 6. The date of the Certificate of Approval;
- The name of the Director;
- The municipality within which the works are located;

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

The Secretary*

The Director

. . .

Environmental Review Tribunal 655 Bay Street, 15th Floor Toronto, Ontario M5G 1E5

AND

Section 53, Ontario Water Resources Act Ministry of the Environment 2 St. Clair Avenue West, Floor 12A Toronto, Ontario M4V 1L5

* Further information on the Environmental Review Tribunal's requirements for an appeal can be obtained directly from the Tribunal at: Tel: (416) 314-4600, Fax: (416) 314-4506 or www.ert.gov.on.ca

The above noted sewage works are approved under Section 53 of the Ontario Water Resources Act.

DATED AT TORONTO this 11th day of July, 2008

ON July 17 2008 N-P (Signed)

Mansoor Mahmood, P.Eng.

Director

Section 53, Ontario Water Resources Act

SH/c:

District Manager, MOE Owen Sound
John Slocombe, Gamsby and Mannerow Engineers ✓

ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix B Correspondence

Ministry of the Environment and Climate Change

Southwestern Region Owen Sound District Office 3rd Flr 101 17th St Owen Sound ON N4K 0A5 Fax: (519) 371-2905 Tel: (519) 371-6191 Ministère de l'Environnement et de l'Action en matière de changement climatique

Direction régionale du Sud-Ouest Bureau du district d'Owen Sound 101 rue 17th, 3ème étage Owen Sound ON N4K 0A5 Télécopieur: (519) 371-2905 Tél:(519) 371-6191



June 21, 2018

Mr. Troy Cameron Municipality of Northern Bruce Peninsula R.R. # 2 56 Lindsay Rd. 5 Lion's Head, ON N0H 1W0

Dear Mr. Cameron,

RE: St Edmunds Landfill Site, 2017 Annual Report

We have received a copy of the report titled "Municipality of Northern Bruce Peninsula, 2017 Annual Monitoring Report – St Edmunds Landfill," dated February 2018 and prepared by GM BluePlan Engineering Limited. Our regional surface water specialist reviewed the report and provides the following comments:

Section 12 of the report notes that surface water sample location S-6 is impacted by landfill leachate. The report goes on to state "S-6....is consistent with the characteristics of the leachate impacted groundwater, the surface water quality at this location exhibits elevated concentrations of hardness, alkalinity, chloride, sodium, potassium, and ammonia." (page 19). The report does not clarify the source of leachate contamination. If the source is leachate impacted groundwater movement to the pond, our surface water reviewer may be willing to accept an attenuation argument for mitigation given there is only 6 years left of active landfilling at the site (page 3). However if leachate impact is surface water runoff associated with the open face of the landfill, then the Municipality should take steps to improve site operations to contain surface water leachate generation.

Water quality results provided in appendix G. suggest water quality results for all surface water monitoring sites are remaining within historical norms (save for S-6 discussed above), accordingly there are no other surface water comments associated with the site. No changes are recommended to the surface water monitoring program.

Please provide the undersigned with a response concerning the source of impacts to S-6 discussed above. If you have any questions concerning this letter, please contact the undersigned at (519) 371-6191.

Yours truly,

Ian Mitchell, P.Eng. District Engineer

Owen Sound District Office

an Mitchell



July 3, 2018 Our File: M-1555

MOECC Owen Sound District Office 101-17th Street East Owen Sound, ON N4K 0A5

Attention: Mr. Ian Mitchell

Re:

Annual Monitoring Report (2017) Surface Water Comments St. Edmunds Landfill Site

ECA No. A273002, A273003 and

5854-7DSSDD

Dear lan,

This letter is being provided in response to the comments you provided in correspondence dated June 21, 2018.


With respect to the water quality at S-6, the source of leachate influence is considered to be groundwater that was intercepted during construction of the perimeter swale along the west side of the landfill. This has been documented in Annual Monitoring Reports (AMRs) starting in 2012 (i.e., monitoring year 2011) and carried forward since that the time. A more fulsome discussion of the issue is provided in Section 12.2 of the 2017 AMR.

It is noted that in 2011, exceedances of the trigger levels were reported for un-ionized ammonia and contingency measures were implemented including the following:

- A review of the potential for off-site impacts: This concluded that attenuation of the impacts from landfill leachate was occurring within the sewage works and before reaching potential sensitive receptors (i.e., Borrow Pit Pond BPP2).
- ii. A visual inspection for leachate seeps within the stormwater management works: This indicated that groundwater impacted with landfill leachate was discharging into the drainage ditch located west of the landfill in the vicinity of well O-2. As this drainage ditch appeared to have intersected the groundwater table, mitigative measures were undertaken in 2011 and 2012. These measures included raising the base grade of the drainage ditch with a low permeability soil to limit leachate seepage into the drainage ditch and planting of cattails (i.e. Typha spp.) at the outlet of the ditch which have become well established since that time.

Since 2013, the cattails have become more established and the surface water within the pond has been observed to be much clearer relative to previous years. The reported ammonia concentrations continue to exhibit improvement relative to pre-2012 conditions. Since 2014, un-ionized ammonia concentrations have ranged between 0.002 and 0.03 mg/L, remaining below the trigger level of 0.06 mg/L. It is anticipated that concentrations of un-ionized ammonia will continue improve as the vegetation becomes further established within the drainage ditches and ponds.

Since 2012, chloride concentrations at S-6 have typically exceeded the trigger level of 60 mg/L during the fall sampling event. In the fall of 2017 a concentration of 131 mg/L was reported. It is noted that during the fall sampling event water levels were noted to be very low, with little to no flow (i.e., stagnant conditions). As previously discussed, surface water quality results suggest that adequate attenuation of impacts from landfill leachate is occurring within the sewage works and prior to reaching potential sensitive receptors (i.e., Borrow Pit Pond BPP2).





In recent years, groundwater discharge to the swale along the west side of the landfill is observed under wet conditions (typically spring), with significantly less quantity than prior to remedial efforts and with apparently better quality.

Based on landfill inspections during the monitoring program, and discussions with the Municipality, there has not been evidence of surface water run-off or leachate break-out in the active area. During the 2018 spring monitoring program (under wet conditions) there was no evidence of impacted surface water migration from the active area and the swale in this area was observed to be generally under "stagnant" flow conditions. Consequently, it appears that the impacts at S-6 are primarily related to shallow groundwater, as opposed to surface water migrating from the active area further to the east.

As the site progress landfilling progresses towards the boundaries of the footprint, and closer to the stormwater swales, it is noted that a clayey soil berm will be placed at the perimeter. This is standard practice and allows the operator a limit of fill boundary with which to work waste into lifts. The berm will mitigate the potential for contact stormwater from directly entering the swale by limiting migration and forcing infiltration.

In the meantime, the operators will continue to monitor the active area to ensure leachate impacted surface water is managed appropriately and is not directly entering the stormwater swale. Our team will also continue to provide specific inspection during the twice-annual monitoring program.

Yours truly,

GM BLUEPLAN ENGINEERING LIMITED

Per:

Matthew Nelson, P.Eng., P.Geo.

MN/mz

cc: Troy Cameron, Municipality of Northern Bruce Peninsula

File No. M-1555

Ministry of the Environment, Conservation and Parks

Southwestern Region Owen Sound District Office 3rd Flr 101 17th St Owen Sound ON N4K 0A5 Fax: (519) 371-2905 Tel: (519) 371-6191

Ministère de l'Environnement, de la Protection de la nature et des Parcs

Direction régionale du Sud-Ouest Bureau du district d'Owen Sound 101 rue 17th, 3ème étage Owen Sound ON N4K 0A5 Télécopieur: (519) 371-2905 Tél:(519) 371-6191



February 12, 2019

Mr. Troy Cameron Municipality of Northern Bruce Peninsula R.R. # 2 56 Lindsay Rd. 5 Lion's Head, ON N0H 1W0

Dear Mr. Cameron,

RE: St Edmunds Landfill Site, 2017 Annual Report

Further to my letter to you dated June 21, 2018, containing surface water comments for the St Edmunds Landfill 2017 Annual Monitoring Report, our regional hydrogeologist has reviewed the annual report and provides comments in the attached memorandum.

In addition, the annual report states that the generation and migration of landfill gas at the site is not considered to be of concern. The consultant should comment specifically on whether or not methane monitors should be installed in on site buildings or the attendants shack.

If you have any questions concerning this letter, please contact the undersigned at (519) 371-6191.

Yours truly,

Ian Mitchell, P.Eng.

District Engineer

Owen Sound District Office

File Storage Number: SI BR NB C2 610

a Mithell

enclosure

cc. H. Pfeiffer, MECP, Owen Sound

Helene Pierard, MECP, London

M.D. Nelson, GM BluePlan, Owen Sound

Ministry of the Environment, Conservation and Parks

Southwestern Region Technical Support Section Water Resources 733 Exeter Rd London ON N6E 1L3 Fax: (519) 873-5020 Tel: (519) 873-5034 Ministère de l'Environnement, de la Protection de la nature et des Parcs

Direction régionale du Sud-Ouest Secteur du Soutien Technique 733 Exeter Rd London ON N6E 1L3 Télécopieur: (519) 873-5020 Tél:(519) 873-5034



February 8th, 2019

Mr. Ian Mitchell, P.Eng.
District Engineer
Ministry of the Environment, Conservation and Parks
Owen Sound District Office
101 17th Street. East
Owen Sound, ON N4K 0A5

Dear Ian

RE: St. Edmunds Landfill (ECA A273002) - 2017 Annual Monitoring Report - Groundwater Comments Lots 46 & 47, Concession 3 WBR, Northern Bruce Peninsula (formerly St. Edmunds), Bruce County Reference Numbers 2447-AVQLPV (2017) and 8028-ALZL7Z (2016)

I reviewed the "2017 Annual Monitoring Report - St. Edmunds Landfill - ECA No. A273002, A273003 and 5854-7DSSDD" prepared by GM Blue Plan Engineering and dated February 2018.

The site is located on lots 46 and 47, concession 3 WBR, in the former township of St. Edmunds, now municipality of the Northern Bruce Peninsula in the County of Bruce. The waste disposal area occupies an area of approximately 3.33 hectares on a 82 hectare site.

The purpose of the report is to document site activities under 3 different Environmental Compliance Approvals. The purpose of my review is to assess the hydrogeological aspect of the site and determine site compliance with the Reasonable Use Guideline (Policy B-7). My comments are the following:

- The Consultant has commented on the 'natural variability' and the significant fluctuation in
 the groundwater chemistry at the site. The Consultant should explain the possible causes of
 this variation. There should also be some consideration for the inspection and repair and/or
 replacement of some of the monitoring wells to ensure that the groundwater collected from
 the monitoring wells is representative of the groundwater quality at the site.
- 2. In addition to the potential well issues, especially relating to the sealing of the annular space, the fact that some of the wells, including some bedrock wells, have been assumed to be

destroyed, may add to the connectivity between the hydrogeological units. Efforts should be made to find and properly abandon these destroyed wells. If the wells cannot be found at all, the Municipality should retain a professional geoscientist or professional engineer to prepare a report regarding the risk caused by not finding the wells. Given the current land use, it would be appropriate for the qualified person to focus on contaminants of concerns and potential receptors.

- 3. Cross-Sections The existing cross-sections should be expanded to include all the wells along the segment. For example, cross-section A-A' should include wells O-9 and the W-3 series. Water levels should also be noted on the cross-sections. Additional cross-sections for the site would help understand the hydrogeological conditions.
- 4. Are the 2 overburden units (the sand and gravel and the silt till) and the waste acting as one hydrogeological unit? It would be helpful for the "groundwater elevation table" to indicate the hydrogeological unit in which the wells are completed. It would also be helpful to have a visual aid on the figures to distinguish the wells from the different hydrogeological units. A discussion on the potential influence of the ditches and other surface water features on groundwater flow should be included in the report.
- 5. Leachate Characterization Currently, the leachate at the site is characterized by the leachate chemistry of monitoring well O-2 which is near the oldest part of the landfill and is reported to be unlined. Since Area B is now closed and capped, it would be helpful to add another leachate well in Area B to not only better characterize newer waste, but also as a representative of a well with a silty/clay base. I also recommend that the list of analytical parameters for the leachate wells be revised to follow that of the long list of Schedule 5 of the Landfill Standard Guideline document. A better characterization of the leachate will also allow for a more comprehensive list of the key and/or primary leachate indicators for the site.
- 6. Similarly to the leachate characterization, it would be helpful to add parameters such as boron to the list of groundwater chemistry for all the wells on the site. If the leachate characterization offers additional key or primary leachate indicators, they should also be added to the analytical list of groundwater sampling.
- 7. The Consultant should provide additional information on the type of dust suppressant that is used at the site?
- 8. Interpretation of overburden groundwater chemistry Table 4 should have the hydrogeological unit indicated for each well. By doing so, it would be easier to determine if the groundwater chemistry in the sand and gravel is significantly different than that of the till overburden wells. Even if the groundwater flow pattern is similar in the different overburden units, the attenuation of leachate may be different depending on what unit it is in.
- 9. Nitrate & Sulphate On page 15 of the report, the Consultant has suggested that nitrate, nitrate and sulphate do not appear to be indicators of leachate impact on groundwater. Considering that the geochemistry of the leachate of monitoring well O-2 suggests that anaerobic conditions are present in the waste, nitrate and sulphate may not currently be present in that form in the waste mound, however they might as oxidation conditions develop.

10. Based on my current knowledge of the site and the information before me, no Reasonable Use compliance issues require immediate action. The site characterization and the groundwater monitoring, however, needs to be enhanced to increase the confidence in the information.

Please let me know if you have any questions.

Yours truly,

Helene Pierard P.Geo

Hydrogeologist

Southwestern Region

File Storage Number: SI BR NB C3 610

File Storage Number:

Limitations: The purpose of the preceding review is to provide advice to the Ministry of the Environment, Conservation and Parks regarding subsurface conditions based on the information provided in the above referenced documents. The conclusions, opinions and recommendations of the reviewer are based on information provided by others, except where otherwise specifically noted. The Ministry cannot guarantee that the information that has been provided by others is accurate or complete. A lack of specific comment by the reviewer is not to be construed as endorsing the content or views expressed in the reviewed material.

Ministry of the Environment, Conservation & Parks

Owen Sound District Office 101 17th Street East, 3rd Floor Owen Sound ON N4K 0A5 **Tel.**: 519-371-2901

Tel.: 519-371-2901 **Fax**.: 519-371-2905

Ministère de l'Environnement, de la Protection de la nature et des Parcs

Bureau de district d'Owen Sound 101 17ème rue Est, 3e étage Owen Sound ON N4K 0A5 Tél. 519-371-2901

Téléc. : 519-371-2905



December 14, 2021

Mr. Troy Cameron Municipality of Northern Bruce Peninsula R.R. # 2 56 Lindsay Rd. 5 Lion's Head, ON N0H 1W0

Via email: pwmanager@northernbruce.ca

Dear Mr. Cameron

Re: St Edmunds Landfill Site, 2020 Annual Report

MOE File: SI BR NB C2 610

We have received a copy of the report titled "Municipality of Northern Bruce Peninsula, 2020 Annual Monitoring Report – St Edmunds Landfill," dated March 2021 and prepared by GM BluePlan Engineering Limited. Our regional surface water specialist reviewed the report and provides the following comments:

ECA 5854-7DSSDD indicates that semi-annual sampling is required at surface water locations S-1, S-6, S-8 and S-9 and Point 8 in the recommendations section also lists spring and fall sampling. However, it appears that sampling in 2020 was only done in the fall with the exception of S-9 in April. The annual report should explain why S-1, S-6, S-6a and S-8 were not sampled in April as well. Is it expected that sampling will return to the approved semi-annual frequency moving forward?

The sampling results from fall 2020 indicate acceptable unionized ammonia concentrations and only slight exceedances of phenols which is also seen in background conditions.

The recommendation for continued sampling prior to trigger finalization is reasonable given the most recent sampling results.

If you have any questions concerning this letter, please contact the undersigned at (519) 374-1388.

Yours truly,

Ian Mitchell
District Engineer
Owen Sound District

for Mitchell

cc. Alison Munro, MECP, London MD Nelson, GM BluePlan, Owen Sound, <u>matthew.nelson@gmblueplan.ca</u> Kim Pietz, MECP, Owen Sound Ministry of the Environment, Conservation and Parks Southwestern Region Technical Support Section Water Resources

733 Exeter Rd London ON N6E 1L3 Fax: (519) 873-5020 Tel: (519) 873-5034 Ministère de l'Environnement de la Protection de la nature et des Parcs Direction régionale du Sud-Ouest Secteur du Soutien Technique



733 Exeter Rd London ON N6E 1L3 Télécopieur: (519) 873-5020 Tél: (519) 873-5034

Memorandum

Date: August 12th, 2022

To: Kimberley Pietz – Senior Environmental Officer – Southwestern Region

From: Gloria Suarez – Hydrogeologist – Southwestern Region – Technical Support Section

Re: Review of the 2020 and 2021 Annual Monitoring Reports - St. Edmund's landfill,

Municipality of Northern Bruce Peninsula, Ontario

Groundwater Technical Review Request, Reference Number: 1-107841506

In preparation of this memorandum, I have reviewed the following documents:

- 1. 2020 Annual Monitoring Report St. Edmund's landfill, Municipality of Northern Bruce Peninsula, Ontario by GM BluePlan Engineering Dated March 2021, and signed by M. D. Nelson MSc, PEng, PGeo.
- 2. 2021 Annual Monitoring Report St. Edmund's landfill, Municipality of Northern Bruce Peninsula, Ontario by GM BluePlan Engineering Dated March 2022, and signed by M. D. Nelson MSc, PEng, PGeo.
- 3. Amended Certificates of Approval (CofA) No A273002; issued on July 10th, 1998.
- 4. Amended Certificates of Approval (CofA) No A273003; issued on July 10th, 1998.

Background

As requested, I have reviewed the 2020 and 2021 Annual Monitoring Reports for the St. Edmunds Landfill (Site) located in lots 46 & 47, Concession 3 WBR Northern Bruce Peninsula prepared by GM BluePlan Engineering (Consultant) on behalf of the Municipality of Northern Bruce Peninsula (Municipality). According to Site records, an estimated 1,750 m³ of waste was landfilled in 2021 with a remaining capacity for waste and daily cover estimated to be 9,010 m³. The 82-hectare non-hazardous waste Site opened in 1970 and operates under the following instruments:

- 1. Amended Certificates of Approval (CofA) No A273002; issued on July 10th, 1998.
- 2. Amended Certificates of Approval (CofA) No A273003; issued on July 10th, 1998.

The Site generally slopes towards the south/southwest with an inferred groundwater flow south to south-westerly (overburden and bedrock). Based on the hydrogeologic investigation, the overburden at the Site is $\sim 1,4$ to 3.7 m of sand and gravel and silt till. The underlying bedrock is a poorly fractured dolostone.

The Municipality conducts a site-wide groundwater monitoring program which includes: spring and fall sampling (alkalinity, hardness, conductivity, pH, ammonia, nitrate, nitrite, DOC, chloride, sulphate, iron, sodium & potassium) from eleven (11) overburden wells (O-1, O-2, O-3, O-4, O-6,O-7, O-8, 0-9, W-1,W-2 & W-3/03), seven (7) bedrock wells at five (5) different locations (B-2, B-3, B-4 & B-5) and the bedrock piezometer (P-1, P-2 & P-3). A revised sampling program was proposed to address MECP comments dated February 8th, 2019, calcium and magnesium were added to the list of leachate characterization for the analytical list of groundwater sampling in 2020. A preliminary review of results will be provided in the 2022 annual report.

Included in Appendix G of each of the 2020 and 2021 annual reports, is a Groundwater Monitoring Review report. These reports included the detailed technical evaluation of the monitoring data and an annual determination of the adequacy of the monitoring program and contingency measures. These reports were the primary focus of my review.

The purpose of my review was to evaluate whether there is potential for offsite groundwater impacts and to provide conclusions and recommendations, if any, from a hydrogeological perspective. It is noted that I did not complete an exhaustive review of historical data for the site.

My review following the Reasonable Use Criteria (RUC) and Contaminant Attenuation Zone was to determine if the Site meets RUC at property boundary for landfill contaminants of concern:

- 1. Guideline B-7 Incorporation of the Reasonable Use Concept into MOEE Groundwater Management Activities, and
- 2. Guideline B-7-1 Determination of Contaminant Limits and Attenuation Zones (CAZ)

Based on my review, I offer the following comments and recommendations which may be forwarded to the technical consultant.

Comments

Monitoring wells were constructed to intersect the shallow groundwater within the overburden that has less than 4 m thickness. The historical shallow groundwater results and trends show naturally elevated hardness and sulphate concentrations and elevated conductivity. Iron is naturally presented in shallow groundwater. Nitrate, nitrite, and sulphate concentrations have not increased, suggesting these parameters are not leachate indicators. While the concentrations of other parameters remain relatively stable, conductivity, sulphate and hardness are highly variable and are typically greater in the fall. However, historical water quality can be influenced by surface water infiltration that may influence the geochemical characteristics of the groundwater.

1. <u>Leachate Characterization</u> – Wells O-2 & O-7 (2020) have been selected as leachate wells. O-2 results show high concentration of hardness, alkalinity, chloride, sodium, potassium, ammonia, and DOC and these parameters are primary leachate indicators for the Site. Because of historical water quality variability, only chloride, alkalinity, and potassium are reliable as leachate indicators. O-7 results indicate elevated concentrations of conductivity,

hardness, and sulphate. It could be caused by dissolved calcium, magnesium, and sulphate ions in groundwater.

2. Reasonable Use Criteria and Contamination Attenuation Zone (CAZ): the areas in which the site is divided for discussion purposes are northeastern, east, south to southeast (downgradient) and west to northwest (upgradient and considered background). Groundwater flow direction is generally towards the south-southwest. Based on the groundwater flow direction, the main area of the site where there is concern for the off-site migration of landfill-impacted groundwater are overburden and bedrock downgradient south to southeast. Overburden wells W-3/03, O-3 and O-4 indicate minor increased alkalinity, chloride, and potassium (W-3/03 & O-3) with exceedances for RUC hardness, alkalinity, and DOC. Bedrock downgradient wells B2, B3, & B4 show naturally elevated hardness and sulphate concentrations. B2 does not show impacts even though the depth within the bedrock is minimal. B3 located ~100 m downgradient indicates chloride, alkalinity, and potassium slightly elevated concentrations, suggesting minor leachate impacts at bedrock. 2021 RUC exceedances in B3 for hardness, alkalinity, sulphate, iron, and DOC; and in B2 & B4 for DOC and alkalinity.

Overburden wells O-2, O-3, O-6 & W-3/03 and bedrock B3 & B4 are being influenced by leachate. Plume is migrating in southerly to southwesterly direction through overburden soils and bedrock. However, leachate influence is not considered to be greater than 100 m. Because of level of attenuation and distance to property boundaries, off-site impacts above the RUC from landfill leachate are not anticipated.

Downgradient wells O-4 & O-6 do not show landfill leachate impacts suggesting that leachate impacted groundwater has naturally attenuated between these two wells.

3. Methane Gas Management: gas is not monitored. Gas is venting passively to the atmosphere. Soils have moderate to high permeability that would permit the venting of gases to the atmosphere. Therefore, landfill gas at the site is not considered to be of concern at this time.

Conclusions and Recommendations

I concur with the consultant; Area B has reached capacity and should be capped. I recommend adding another leachate well in area B to characterize newer waste and a representative of a well with silty/clay base. I disagree with using O-7 as a leachate well of the active Area C of landfilling. The well is located ~ 30 m cross-gradient and to the east of landfill footprint.

Wells O-5 & B-1 were destroyed in 1994 and 1999 respectively. It is recommended, abandonment of these wells in accordance with O. Reg 903.

I noted that calcium and magnesium were added as analytical parameters in 2020 to address the MECP comments dated February 8th, 2019, for a revised sampling program. However, they were not sampled during 2020 & 2021. I recommend adding boron as a parameter to leachate characterization for all wells on the site.

| SAMPLI | NG LOCATI | ONS | ANALYTICAL PARAMETERS |
|-------------------------------------|------------------------------------|----------------------|--|
| | | | GROUNDWATER (Spring and Fall) |
| 0-1 * 0-2 * 0-3 0-4 | O-6 * O-7* O-8 O-9 | W-1 W-2 W-3/03 | Alkalinity, Hardness, Conductivity, pH, Ammonia, Nitrate, Nitrite, DOC, Chloride, Sulphate, Iron, Sodium and Potassium |
| B2 B3 B4 B5 | P1 P2 P3 | | Calcium and Magnesium (add in 2020) *Leachate wells* (as of 2020) <u>Spring:</u> Same as the indicator list outlined above <u>Fall:</u> Schedule 5: Column 1 (i.e. Comprehensive list for groundwater an leachate) which includes field parameters (i.e. pH and Conductivity) |
| | , | | SURFACE WATER (Spring and Fall) |
| | S-1 S-6 S-6A S-8 S-9 | | Alkalinity, Hardness, Conductivity, pH, Total Ammonia, Nitrate, Nitrite, TKN, DOC, CBODs, Chloride, Sulphate, Phenols, Total Phosphorus, Iron, Boron and Zinc (Na, K, Ca and Mg*) Field Parameters: pH, Conductivity, and Temperature |

It appears that the leachate plume is migrating in a southerly to southwesterly direction through the overburden and bedrock. Considering natural attenuation and distance to property boundaries and the landfill footprint, offsite impacts from leachate are not anticipated at this time.

The site has developed stable leachate mounds and a stable leachate plume (size and concentrations). Seasonal and annual water levels and water quality fluctuations are well understood. There are no trigger values with contingency plans or site remedial actions.

However, hardness, conductivity, chloride, and alkalinity increasing trend concentrations since 2006 have been noted in the southeast downgradient bedrock well B-4. A detailed follow-up of this well is recommended in future monitoring reports.

Groundwater level elevations should continue to be monitored in the spring and fall from all monitoring locations.

Limitations:

The purpose of the preceding review is to provide advice to the Ministry of the Environment regarding subsurface conditions based on the information provided in the above referenced documents. The conclusions, opinions and recommendations of the reviewer are based on information provided by others, except where otherwise specifically noted. The Ministry cannot guarantee that the information that has been provided by others is accurate or complete. A lack of specific comment by the reviewer is not to be construed as endorsing the content or views expressed in the reviewed material.

I trust that this hydrogeological review is sufficient for your purposes. If you have any further comments or questions, please feel free to contact me by phone at (289) 659-4007 or by e-mail at gloria.suarez@ontario.ca.

Gloria Suarez, M.Sc., P.Geo.

Hydrogeologist – TSS – SWR

cc: B. Harman

ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix C Borehole Logs

APPENDIX C SUMMARY OF BOREHOLE LOGS AND MONITORING WELL INSTALLATION DETAILS

| | 1 | I | | Details | | | | Sc | reen Inte | rval | | Top of S | Sandpack | | 1 | Dept | h Interval | of Each | Unit | |
|-----------|----------------------|--------|--------|------------------|--------|--------|--------|--------|-----------|--------|----------------|----------|----------|--------------------------|---------|------|------------|---------|----------------|---|
| Well ID | | ļ | | | вн в | ottom | Bot | tom | T | ор | | Elevatio | n (mbgs) | Well Screen | Unit ID | From | То | From | То | |
| (Drilled) | Installation Date | Ground | тос | Stick up (±mags) | (mbgs) | (masl) | (mbgs) | (masl) | (mbgs) | (masl) | Length (ft) | (mbgs) | (masl) | and Sandpack Interval | | mb | gs | me | ters | Description of Unit Encountered |
| 0-1 | 1988 | 202.1 | 203.31 | 1.2 | 1.52 | 200.59 | 1.52 | 200.59 | 1.20 | 200.91 | 1 | 1.0 | 201.1 | | Topsoil | 0 | | | | Topsoil: Black, organic, sandy |
| | | | | | | | | | | | | | | O-1 | S/G | 0.3 | | | 200.59 | SAND AND GRAVEL: Brown, medium to coarse. |
| | | | | | | | | | | | | | | | [Bdrk] | 1.52 | | 200.59 | | Refusal: Interpreted bedrock surface |
| 0-2 | 1988 | 203.0 | 204.07 | 1.1 | 2.13 | 200.84 | 2.0 | 200.97 | 0.75 | 202.22 | 4 | 0.6 | 202.4 | | Sand | 0 | 120002 | 202.97 | - 100 E.C.C. C | SAND: Brown, fine to medium, occasional stones |
| | | | | | | | | | | | | | | O-2 | Sand | 1.8 | | | 200.84 | SAND: Brown, coarse, dense |
| | | | | | | | | | | | | | | | [Bdrk] | 2.13 | | 200.84 | | Refusal: Interpreted bedrock surface |
| O-3 | 1988 | 201.1 | 202.20 | 1.1 | 2.44 | 198.66 | 2.3 | 198.80 | 1.1 | 200.00 | 4 | 0.95 | 200.2 | | Topsoil | 0 | | | | Topsoil: Black, organic, sandy |
| | | | | | | | | | | | | | | O-3 | Till | 0.2 | | 200.90 | 198.66 | SILT: Grey, some sand and clay, occasional stones (TILL) |
| | | | | | | | | | | | | | | | [Bdrk] | 2.44 | | 198.66 | | Refusal: Interpreted bedrock surface |
| 0-4 | 1988 | 201.8 | 202.75 | 1.0 | 3.60 | 198.15 | 3.50 | 198.25 | 2.00 | 199.75 | 5 | 1.25 | 200.5 | 0-4 | Till | 0 | | | 198.15 | Sandy SILT: Brown to grey, fine, some clay, occasional stones, dense |
| | | | | | | | | | | | | | | | [Bdrk] | 3.6 | | 198.15 | | Refusal: Interpreted bedrock surface |
| O-5 | 1988 | 202.9 | 203.62 | 0.75 | 4.42 | 198.45 | 2.60 | 200.27 | 1.10 | 201.77 | 5 | 1.0 | 201.9 | | Topsoil | 0 | | 202.87 | | Topsoil: Black, organic, sandy |
| | | | | | | | | | | | | | | O-5 | Sand | 0.3 | | 202.57 | | SAND: grey, medium, occasional small stones |
| | | | | | | | | | | | | | | 0 0 | Till | 1.95 | | 200.92 | | SILT: Grey, some sand and clay, occasional stones (TILL) |
| | | | | | | | | | | | | | | | Bdrk | 3.8 | 4.42 | 199.07 | | DOLOSTONE: weathered, interbedded with fine grey sand |
| O-6 | 1988 | 202.30 | 203.45 | 1.15 | 3.66 | 198.64 | 2.25 | 200.05 | 1.05 | 201.25 | 4 | 0.65 | 201.7 | | S/G | 0 | | 202.30 | | SAND AND GRAVEL: Grey, medium to coarse. |
| | | | | | | | | | | | | | | OW-6 | Till | 1.25 | | 201.05 | 198.64 | Sandy SILT: grey, fine, some clay, soft (TILL) |
| | | | | | | | | | | | | | | | [Bdrk] | 3.7 | | 198.64 | | Refusal: Interpreted bedrock surface |
| 0-7 | 1988 | 202.23 | 203.38 | 1.15 | 1.37 | 200.86 | 1.37 | 200.86 | 0.75 | 201.48 | 2 | 0.65 | 201.6 | | Topsoil | 0 | | | | Topsoil: Black, organic, sandy |
| | | | | | | | | | | | | | | O-7 | Till | 0.3 | | 201.93 | 200.86 | SILT: Grey-brown, some sand and clay, occasional small stones (TILL) |
| | | | | | | | | | | | | | | | [Bdrk] | 1.37 | | 200.86 | | Refusal: Interpreted bedrock surface |
| O-8 | 1988 | 202.16 | 203.26 | 1.10 | 1.37 | 200.79 | 1.37 | 200.79 | 1.05 | 201.11 | 1 | 0.65 | 201.5 | | Topsoil | 0 | 0.4 | 202.16 | 201.76 | Topsoil: Black, organic, sandy |
| | | | | | | | | | | | | | | O-8 | Till | 0.4 | 1.37 | 201.76 | 200.79 | SILT: Grey-brown, some sand and clay, occasional small stones (TILL) |
| | | | | | | | | | | | | | | | [Bdrk] | 1.37 | | 200.79 | | Refusal: Interpreted bedrock surface |
| O-9 | 1988 | 201.90 | 202.65 | 0.75 | 2.40 | 199.50 | 2.40 | 199.50 | 0.90 | 201.00 | 5 | 0.75 | 201.2 | | Topsoil | 0 | 0.6 | 201.90 | | Topsoil: Black, organic, sandy |
| | | | | | | | | | | | | | | O-9 | Till | 0.6 | 2.40 | 201.30 | 199.50 | SILT: Grey, some sand and clay, occasional stones, dense (TILL) |
| | | | | | | | | | | | | | | | [Bdrk] | 2.40 | | 199.50 | | Refusal: Interpreted bedrock surface |
| B-1 | 1988 | 205.32 | 206.32 | 1.0* | 13.4 | 191.92 | 13.40 | 191.92 | 3.10 | 202.22 | 10.3 | N/A | N/A | | S/G | 0 | 0.7 | 205.32 | 204.62 | SAND AND GRAVEL: Brown |
| | | | | Assumed | | | | | | | Open Hole | | | B-1 | Bdrk | 0.7 | 13.4 | 204.62 | 191.92 | Dolostone: finely crystalline, buff grey |
| B-2 | 1988 | 204.35 | 205.15 | 0.80 | 12.81 | 191.54 | 12.81 | 191.54 | 4.50 | 199.85 | 8.31 | N/A | N/A | | Sand | 0 | 1.9 | 204.35 | | SAND: Brown, fine to medium, occasional stones |
| | | | | | | | | | | | Open Hole | | | 1 | Sand | 1.9 | 2.30 | 202.45 | 202.05 | SAND: Brown, coarse, dense |
| | | | | | | | | | | | | | | | S.Sand | 2.3 | 4.30 | 202.05 | 200.05 | Silty SAND: grey with weathered dolostone pieces |
| | | | | | | | | | | | | | | B-2 | Bdrk | 4.3 | | 200.05 | | Dolostone: buff grey, poorly fractured |
| B-3 | 1988 | 201.38 | 201.66 | 0.28 | 12.34 | 189.04 | 12.34 | 189.04 | 3.10 | 198.28 | 9.24 | N/A | N/A | | Till | 0 | 1.75 | 201.38 | 199.63 | Sandy SILT: Brown to grey, fine, some clay, occasional stones, dense (TILL) |
| | | | | | | | | | | | Open Hole | | | B-3 | Bdrk | 1.75 | 3.00 | 199.63 | 198.38 | Dolostone: Weathered, interbedded with fine sand |
| | | | | | | | | | | | | | | D-3 | Bdrk | 3.0 | 12.34 | 198.38 | 189.04 | Dolostone: buff grey, poorly fractured |
| B-4 | 1988 | 202.91 | 203.41 | 0.50 | 15.85 | 187.06 | 15.85 | 187.06 | 5.00 | 197.91 | 10.85 | N/A | N/A | | Sand | 0 | 1.95 | 202.91 | 200.96 | SAND: grey, medium, occasional small stones |
| | | | | | | | | | | | Open Hole | | | | Till | 1.95 | | 200.96 | | SILT: Grey, some sand and clay, occasional stones (TILL) |
| | | | | | | | | | | | | | | B-4 | Bdrk | 3.9 | | | | Dolostone: finely crystalline, buff grey |
| B-5 | 1988 | 202.27 | 203.17 | 0.90 | 12.19 | 190.08 | 12.19 | 190.08 | 2.00 | 200.27 | 10.19 | N/A | N/A | | Sand | 0 | 0.3 | | | SAND: grey, medium, occasional small stones |
| | | | | | | | | | | 0.000 | Open Hole | | | | Till | 0.3 | - | | | SILT: Grey, some sand and clay, occasional stones (TILL) |
| | | | | | | | | | | | | | | B-5 | Bdrk | 1.7 | 12.19 | | | Dolostone: finely crystalline, buff grey |

- 1. mbgs = meters below ground surface.
- Though a line let's below ground surface.
 TOC = top of PVC pipe (i.e. measuring point); BH btm = Bottom of Borehole.
 Information presented for wells OW-1 through OW-4 was obtained from borehole logs prepared by AMEC.
 Borehole logs and well installation details for P1, P2, P3, W-1, W-2 and W-0-3/03 are not available.
- 5. In November 2022 the site was surveyed to reflect UTM derived coordinates and the elevation across the Site was lowered by 0.7 meters. Elevation have been adjusted to reflect this survey.



4000 diale reed, ite, mississesses, emerie (4is) 624 - 9100

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY DATE COMPLETED NOVEMBER 22,1988 GDP GEOLOGIST/ENGINEER_ SAMPLE N" REMARKS DEPTH WELL DESCRIPTION BLOWS PER FOOT DETAIL type metres feet 10 20 30 40 50 60 70 80 90 square steel protective casing TOPSOIL, sandy, cement/bentonite organic, black. surface seal 0.0 SAND & GRAVEL, medium to coarse compact, 0 bentonite seal SS 1 brown, saturated. ..0 0:0 50mm Ø PVC flush threaded riser pipe 0 silica sand filter . a 5 SS 2 END OF HOLE 1.52m 50mm Ø PVC #10 slot Auger Refusal well screen 3 10 15 6 20 WATER LEVEL "N" BLOWS PER FOOT GS- GRAB SAMPLE SS - SPLIT SPOON ST-'SHELBY TUBE



morrison beatty limited consulting engineers and hydrogeologists 4500 diete rood, IZe,mississenge,sestrio (416) 624 - 9300

0 - 2

FILE NO. 646-881 CLIENT ST. EDMUNDS TOWNSHIP LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY GEOLOGIST/ ENGINEER ___GDP DATE COMPLETED NOVEMBER 21, 1988 SAMPLE "N" REMARKS DEPTH WELL DESCRIPTION BLOWS PER FOOT metres feet DETAIL no. 10 20 30 40 50 60 70 80 90 square steel protective casing cement/pentonite SAND, fine to medium, surface seal occasional stones, bentonite seal brown, saturated. 50mm Ø PVC flush SS 1 threaded riser 50mm Ø PVC #10 slot well screen silica sand 2 SS filter pack SS 3. SAND, coarse, dense, brown, saturated. END OF HOLE 2.13m Auger Refusal 10 15 5 20 WATER LEVEL V ST-'SHELBY TUBE "N" BLOWS PER FOOT GS- GRAB SAMPLE SS - SPLIT SPOON



4500 diele reed, illa,missionengo,amerio (416) 824 - 9300

0 - 3

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY **NOVEMBER 17, 1988** GDP DATE COMPLETED. GEOLOGIST/ENGINEER___ SAMPLE N" REMARKS WELL DEPTH DESCRIPTION DETAIL BLOWS PER FOOT type metres fest no. 10 20 30 40 50 60 70 80 90 square steel protective casing cement/bentonite TOPSOIL, sandy, organic, surface seal black. SILT, some sand and clay, occasional stones, bentonite seal SS 1 grey, wet (TILL). 50mm Ø flush threaded PVC riser 50mm Ø PVC #10 slot well screen 2 SS silica sand filter pack 3 SS END OF HOLE \$.44m Auger Refusal 3 10 15 6 20 WATER LEVEL V "N" BLOWS PER FOOT GS- GRAB SAMPLE ST-'SHELBY TUBE SS - SPLIT SPOON



0-4

| CLIENT ST. EDMUNDS | TOWNS | SHIP | | | | FILE NO646-881 |
|---|--------|----------------------|----------|----------|------------|---|
| PROJECT HYDROGEOLO | GIC ' | YOUTS | | N TOBER | | EMBER 10, 1000 |
| GEOLOGIST/ENGINEER | GD | | DATE C | OMPLETE | | FMBER 18, 1988 |
| DESCRIPTION | | DEPTH metres feet | na. 1 | APLE | WELL | REMARKS BLOWS PER FOOT |
| | | | | | | 10 20 30 40 50 60 70 80 90 |
| | | | | | | square steel protective casing |
| Sandy <u>SILT</u> , fine, some clay, occasional stones, brown to grey, dense, saturated (TILL). | | 5 | . 2 | SS SS | 111 | cement/bentonite surface seal bentonite seal 50mm Ø PVC flush threaded riser silica sand filter pack |
| | | 3 10. | . 4 | SS | | 50mm Ø PVC #10 slot well screen |
| END OF HOLE 3.60m Auger Refusal | | 4 15 _5 | | | | |
| CS- GRAB SAMPLE SS-SI | I IT S | POON ST | - SHELBY | CTUBE "N | I" BLOWS F | PER FOOT WATER LEVEL V |



0 - 5

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY NOVEMBER 17, 1988 GDP DATE COMPLETED GEOLOGIST/ENGINEER_ SAMPLE N" REMARKS WELL DEPTH DESCRIPTION BLOWS PER FOOT metres feet no. 10 20 30 40 50 60 70 80 90 square steel protective casing TOPSOIL, sandy, organic, bentonite black. surface seal SAND, medium, occasional 50mm Ø PVC flush small stones, grey, wet. SS 1 threaded riser silica sand 5 filter pack 2 SS 50mm Ø #10 slot PVC well screen SILT, some sand and SS 3 clay, occasional stones, grey, saturated (TILL). 3 10 SS 4 - native backfill SS 5 DOLOSTONE, weathered, interbedded with fine grey sand. 15 END OF HOLE 4.42m 5 20 WATER LEVEL V "N" BLOWS PER FOOT GS- GRAB SAMPLE SS - SPLIT SPOON ST-'SHELBY TUBE



0 - 6

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY NOVEMBER 20, 1988 GEOLOGIST/ ENGINEER __ GDP DATE COMPLETED. SAMPLE "N" WELL REMARKS DEPTH DESCRIPTION BLOWS PER FOOT metres feet no. 10 20 30 40 50 60 70 80 90 square steel protective casing cement/bentonite 0.0 SAND & GRAVEL, medium surface seal 0. to coarse, grey, bentonite seal saturated. . 0. 0 50mm Ø PVC flush ò SS 1 threaded riser 0. 0 silica sand filter pack Sandy SILT, some clay, 5 50mm Ø PVC #10 2 SS soft, grey, wet (TILL). slot well screen 3 SS — native backfill 3 10 4 SS END OF HOLE 3.66m Auger REfusal 15 5 6 20 WATER LEVEL V "N" BLOWS PER FOOT ST-'SHELBY TUBE GS- GRAB SAMPLE SS - SPLIT SPOON



4500 disle roud, (Ze, mississes qu, emerie (418) ag4 - anan

0 - 7

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 PROJECT ___TEST_DRILLING LOCATION ST. EDMUNDS TOWNSHIP LANDFILL GEOLOGIST/ ENGINEER _ GDP DATE COMPLETED NOVEMBER 14, 1988 SAMPLE "N" DESCRIPTION DEPTH WELL REMARKS metres feet DETAIL no. BLOWS PER FOOT 10 20 30 40 50 60 70 80 90 square steel protective casing TOPSOIL, sandy, organic, cement/bentonite 1 SS surface seal SILT, some clay and 50mm Ø flush sand, occasioanal small threaded PVC riser stones, grey brown, 2 SS saturated (TILL). bentonite seal silica sand filter 50mm Ø PVC #10 slot END OF HOLE 1.37m well screen Auger Refusal 3 10 15 20 GS- GRAB SAMPLE ST-'SHELBY TUBE SS - SPLIT SPOON "N" BLOWS PER FOOT WATER LEVEL V



0-8

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY NOVEMBER 15, 1988 GEOLOGIST/ENGINEER GDP DATE COMPLETED. SAMPLE "N" REMARKS DEPTH WELL DESCRIPTION BLOWS PER FOOT metres feet DETAIL no. 10 20 30 40 50 60 70 80 90 square steel protective casing TOPSOIL, sandy, black, bentonite seal organic. SS 1 50mm Ø PVC flush SILT, some clay and threaded riser sand, occasional small 2 SS silica sand filter stones, grey brown, pack saturated (TILL). 50mm Ø PVC #10 slot well screen 5 END OF HOLE 1.37m Auger Refusal 3 10 15 5 6 20 WATER LEVEL V "N" BLOWS PER FOOT ST-'SHELBY TUBE GS- GRAB SAMPLE SS - SPLIT SPOON



0 - 9

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881 LOCATION TOBERMORY PROJECT HYDROGEOLOGIC STUDY NOVEMBER 24, 1988 GDP DATE COMPLETED. GEOLOGIST/ENGINEER_ SAMPLE N" REMARKS WELL DEPTH DESCRIPTION BLOWS PER FOOT metres feet 10 20 30 40 50 60 70 80 90 square steel protective casing cement/bentonite TOPSOIL, sandy, black, surface seal organic. bentonite seal SILT, some clay and 50mm Ø PVC flush threaded riser sand, occasional stones, dense, grey, silica sand saturated (TILL). filter pack 5 50mm Ø PVC #10 slot well screen END OF HOLE 2.4m Auger Refusal 3 10 15 6 20 WATER LEVEL V "N" BLOWS PER FOOT GS- GRAB SAMPLE SS - SPLIT SPOON ST-'SHELBY TUBE



morrison beatty limited consulting engineers and hydrogeologists 4500 dinie road, 12e, mierienenge, enterie (416) 624 - 9308

B-1

CLIENT__ST. EDMUNDS TOWNSHIP 646-881 FILE NO. . PROJECT HYDROGEOLOGIC STUDY LOCATION ____TOBERMORY JSC DATE COMPLETED NOVEMBER 24, 1988 GEOLOGIST/ENGINEER. SAMPLE N" WELL DESCRIPTION REMARKS DEPTH metres feet type BLOWS PER FOOT no. 10 20 30 40 50 60 70 80 90 square steel protective casing cement/bentonite SAND& GRAVEL, brown, surface seal 0 moist. native backfill DOLOSTONE, finely crystalline, buff grey, 50mm Ø PVC flush trace thin shaley threaded riser partings, poorly defined fossils, vugular with quartz bentonite seal 10 crystals. -PVC "o" ring 15 -3 7/8" open hole 6 20 25 30 10 35 12 40 45 END OF HOLE 43.8m "N" BLOWS PER FOOT WATER LEVEL ST- SHELBY TUBE SS - SPLIT SPOON GS- GRAB SAMPLE



B-2

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. 646-881

PROJECT HYDROGEOLOGIC STUDY LOCATION TOBERMORY

| DESCRIPTION | DEPTH metres feet | SAMPLE no. type "N" | WELL DETAIL | REMARKS BLOWS PER FOOT |
|---|---------------------------|------------------------|----------------|---|
| | | | | square steel protective casing |
| SAND, coarse, dense, brown, saturated. | 5 2 | | | cement/bentonite surface seal native backfill 50mm Ø PVC flush threaded riser |
| Silty SAND, grey with weathered dolostone pieces (TILL). DOLOSTONE, buff grey, poorly fractured. | 4 15 5 620 | | | bentonite seal PVC "o" ring |
| | 7 25 8 | | | 3 7/8" open hole |
| | 9 30 10 35 | | | |
| END OF HOLE 12.81m | 12 ₄₀ | | | |
| | 15 50 16 | | | |
| | 17 18 60 | | | |



morrison beatty limited

consulting engineers and hydrogeologists

B-3

CLIENT ST. EDMUNDS TOWNSHIP 646-881 FILE NO. PROJECT _ HYDROGEOLOGIC STUDY LOCATION ____ TOBERMORY DATE COMPLETED NOVEMBER 17, 1988 GEOLOGIST/ ENGINEER __GDP_ SAMPLE "N" DESCRIPTION DEPTH WELL REMARKS DETAIL metres test BLOWS PER FOOT 10 20 30 40 50 60 70 80 90 square steel protective vasing cement/bentonite Sandy SILT, fine, some SS surface seal 1 clay, occasional native backfill stones, brown to grey, SS 50mm Ø PVC flush dense, saturated threaded riser (TILL). DOLOSTONE, weathered, 3 - bentonite seal 10 interbedded with fine sand. PVC "o" ring DOLOSTONE, buff grey, 15 poorly fractured. -3 7/8" open hole 620 930 10 12 40 END OF HOLE 12.34m 13 15 50 16 55 17 18 60 GS- GRAB SAMPLE "N" BLOWS PER FOOT SS - SPLIT SPOON ST- SHELBY TUBE WATER LEVEL



morrison beatty limited

consulting engineers and hydrogeologists

B-4

CLIENT ST. EDMUNDS TOWNSHIP 646-881 FILE NO. _ PROJECT HYDROGEOLOGIC STUDY LOCATION TOBERMORY DATE COMPLETED NOVEMBER 20, 1988 GEOLOGIST/ ENGINEER GDP SAMPLE N" DESCRIPTION DEPTH WELL REMARKS metres feet DETAIL BLOWS PER FOOT 10 20 30 40 50 60 70 80 90 SAND, medium, ccasional small stones, grey, wet 6 5/8" I.J. steel casing bentonite grout SILT, some sand and clay, occasional 310 stones, grey, saturated (TILL). DOLOSTONE . finely crystalline, buff grey, trace thin shaley partings, poorly 620 defined fossils, -5 7/8" open hole vugular with quartz crystals. 25 930 10 35 12 40 13 45 15 50 16 END OF HOLE 15.85m 18 60 GS- GRAB SAMPLE SS - SPLIT SPOON WATER LEVEL V ST - SHELBY TUBE "N" BLOWS PER FOOT



consulting engineers and hydrogeologists

B-5

CLIENT ST. EDMUNDS TOWNSHIP FILE NO. __646-881 PROJECT _ HYDROGEOLOGIC STUDY LOCATION_ **TOBERMORY** GEOLOGIST/ENGINEER __GDP DATE COMPLETED NOVEMBER 14, 1988 DESCRIPTION SAMPLE Type "N" DEPTH WELL REMARKS metres feet DETAIL BLOWS PER FOOT 10 20 30 40 50 60 70 80 90 square steel protective casing TOPSOIL, sandy, organic, SS cement/bentonite black. surface seal 2 SS SILT, some clay and sand, occasional small native backfill 3 SS bentonite seal stones, grey brown, -PVC "o" ring saturated (TILL). Ю DOLOSTONE, buff grey, poorly fractured. 620 -3 7/8" open rock hole 25 12 40 END OF HOLE 12.19m 45 14 15 50 16 55 17 18 GS- GRAB SAMPLE SS - SPLIT SPOON "N" BLOWS PER FOOT ST - SHELBY TUBE WATER LEVEL V

ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix D Cross-Sections



ACTIVE SURFACE WATER MONITORING STATION FORMER SURFACE WATER MONITORING STATION

- THE INFORMATION SHOWN HERE WAS OBTAINED FROM A DRAWING BY HENDERSON PADDON AND ASSOCIATES LIMITED, DATED
- SURFACE WATER DRAINAGE FEATURES WERE SURVEYED BY GAMSBY
- 4, FIGURES WERE ADJUSTED IN 2022 TO SUIT UTM DERIVED COORDINATES AND THE ELEVATIONS ACROSS THE SITE WERE LOWERED BY 0.7m.


SCALE = 1:2,500 JANUARY 2024

CROSS-SECTION LOCATION PLAN

ST. EDMUNDS WASTE DISPOSAL SITE

Appendix D





HORIZ. = 1:1,500 VERT. = 1:150

NOTE:

IN NOVEMBER 2022 THE SITE WAS SURVEYED TO REFLECT UTM DERIVED COORDINATES AND THE ELEVATION ACROSS THE SITE WAS LOWERED BY 0.7 METERS.


JANUARY 2024

CROSS-SECTION A-A'

ST. EDMUNDS WASTE DISPOSAL SITE

Appendix D1





NOTE:

IN NOVEMBER 2022 THE SITE WAS SURVEYED TO REFLECT UTM DERIVED COORDINATES AND THE ELEVATION ACROSS THE SITE WAS LOWERED BY 0.7 METERS

JANUARY 2024


CROSS-SECTION B-B'

ST. EDMUNDS WASTE DISPOSAL SITE

Appendix D2



HORIZ. = 1:1,500 VERT. = 1:150



HORIZ. = 1:1,500 VERT. = 1:150

NOTE:

IN NOVEMBER 2022 THE SITE WAS SURVEYED TO REFLECT UTM DERIVED COORDINATES AND THE ELEVATION ACROSS THE SITE WAS LOWERED BY 0.7 METERS.


JANUARY 2024

CROSS-SECTION C-C'

ST. EDMUNDS WASTE DISPOSAL SITE

Appendix D3





HORIZ. = 1:1,500 VERT. = 1:150

NOTE:

IN NOVEMBER 2022 THE SITE WAS SURVEYED TO REFLECT UTM DERIVED COORDINATES AND THE ELEVATION ACROSS THE SITE WAS LOWERED BY 0.7 METERS.

CROSS-SECTION D-D'

ST. EDMUNDS WASTE DISPOSAL SITE

Appendix D4



ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix E Summary of Historical Groundwater Elevations

| | l | Reference | Well Depth | 12-D€ | ec-88 | 30-Ja | ın-89 | 13-D | ec-89 | 7-Ma | ır-90 | 13-Ja | ın-93 | 25-Ja | n-94 |
|----------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| - Ei | Well ID | Elevation | from | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation |
| | 0-1 | 204.01 | 2.73 | 1.47 | 202.54 | 1.34 | 202.67 | 1.53 | 202.48 | 1.56 | 202.45 | Frozen | | 1.70 | 202.31 |
| 1 | O-2 | 204.77 | 3.25 | 2.24 | 202.53 | 2.11 | 202.66 | 2.27 | 202.50 | 2.22 | 202.55 | 2.15 | 202.62 | 2.42 | 202.35 |
| 1 | O-3 | 202.90 | 3.42 | 1.30 | 201.60 | 1.19 | 201.71 | 1.245 | 201.66 | 1.25 | 201.65 | Frozen | | 1.30 | 201.60 |
| lے | 0-4 | 203.45 | 4.50 | 1.55 | 201.90 | 1.16 | 202.29 | 1.50 | 201.95 | 1.45 | 202.00 | 1.42 | 202.03 | 1.35 | 202.10 |
| 용 | O-5 | 204.32 | 3.33 | 1.83 | 202.49 | 1.65 | 202.67 | 1.74 | 202.58 | 1.75 | 202.57 | 1.65 | 202.67 | Destr | oyed |
| verburde | O-6 | 204.15 | 3.46 | 1.75 | 202.40 | 1.59 | 202.56 | 1.72 | 202.43 | 1.73 | 202.42 | 1.41 | 202.74 | NM | |
| 15 | O-7 | 204.08 | 2.60 | DRY | | 1.17 | 202.91 | 1.425 | 202.66 | 1.40 | 202.68 | Frozen | | Frozen | |
| Ιš | O-8 | 203.96 | 2.32 | DRY | | 1.19 | 202.77 | Frozen | | 1.39 | 202.57 | Frozen | | Frozen | 1 |
| I۲ | O-9 | 203.35 | 3.16 | 1.40 | 202.51 | 1.30 | 202.61 | 1.47 | 202.44 | 1.44 | 202.47 | Frozen | | 1.55 | 202.36 |
| 1 | W-1 | NA | 1.65 | 1.04 | NA | 0.96 | NA | 1.00 | NA | 0.98 | NA | Frozen | NA | Frozen | NA |
| 1 | W-2 | 203.97 | 3.52 | 1.35 | 202.62 | 1.21 | 202.76 | Frozen | | 1.33 | 202.64 | Frozen | | Frozen | |
| | W-3 | 202.86 | 1.91 | 1.14 | 201.72 | 1.00 | 201.86 | 1.15 | 201.71 | 1.13 | 201.73 | 1.05 | 201.81 | 1.12 | 201.74 |
| | B-1 | 207.02 | 13.37 | 6.35 | 200.67 | 6.07 | 200.95 | 6.30 | 200.72 | 6.30 | 200.72 | 6.05 | 200.97 | 6.32 | 200.70 |
| 1 | B-2 | 204.85 | 13.61 | 4.60 | 200.25 | 4.46 | 200.39 | 4.70 | 200.15 | 4.63 | 200.22 | 4.54 | 200.31 | 4.65 | 200.20 |
| 농 | B-3 | 202.36 | 11.70 | 1.70 | 200.66 | 1.96 | 200.40 | 2.20 | 200.16 | 2.14 | 200.22 | 2.08 | 200.28 | 2.18 | 200.18 |
| ١ě | B-4 | 204.11 | 15.61 | 3.96 | 200.15 | 3.65 | 200.46 | 3.18 | 200.93 | 3.27 | 200.84 | 3.58 | 200.53 | 3.86 | 200.25 |
| edro | B-5 | 203.87 | 12.80 | 0.99 | 202.88 | 0.90 | 202.97 | Frozen | | 0.92 | 202.95 | Frozen | | Frozen | () |
| m | P-1 | 205.36 | 17.58 | NI | | NI | | NI | | NI | | 3.21 | 202.15 | 3.52 | 201.84 |
| 1 | P-2 | 205.36 | 31.89 | NI | | NI | | NI | | NI | | 5.27 | 200.09 | 5.68 | 199.68 |
| | P-3 | 205.35 | 9.12 | NI | | NI | 7 | NI | | NI | (| 3.12 | 202.23 | 3.36 | 201.99 |

| | | Reference | Well Depth | 16-No | ov-94 | 30-O | ct-95 | 17-D | ec-96 | 15-0 | ct-97 | 28-O | ct-98 | 9-No | v-99 |
|------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| Unit | Well ID | Elevation | from | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation |
| Г | 0-1 | 204.01 | 2.73 | 1.54 | 202.47 | 1.45 | 202.56 | 1.21 | 202.80 | 1.55 | 202.46 | 2.00 | 202.01 | 1.36 | 202.65 |
| 1 | O-2 | 204.77 | 3.25 | 2.31 | 202.46 | 2.25 | 202.52 | 2.10 | 202.67 | 2.30 | 202.47 | 2.70 | 202.07 | 2.21 | 202.56 |
| 1 | O-3 | 202.90 | 3.42 | 1.31 | 201.59 | 1.26 | 201.64 | 1.20 | 201.70 | 1.31 | 201.59 | 2.00 | 200.90 | 1.24 | 201.66 |
| rden | 0-4 | 203.45 | 4.50 | 1.40 | 202.05 | 1.28 | 202.17 | 1.24 | 202.21 | 1.36 | 202.09 | 2.90 | 200.55 | 1.62 | 201.83 |
| 5 | O-6 | 204.15 | 3.46 | 1.84 | 202.31 | 1.47 | 202.68 | 1.40 | 202.75 | 1.56 | 202.59 | 2.00 | 202.15 | 1.40 | 202.75 |
| erbu | O-7 | 204.08 | 2.60 | 1.38 | 202.70 | 1.35 | 202.73 | 1.30 | 202.78 | 1.39 | 202.69 | NM | | 1.37 | 202.71 |
| ē | O-8 | 203.96 | 2.32 | 1.42 | 202.54 | 1.35 | 202.61 | 1.34 | 202.62 | 1.45 | 202.51 | NM | | 1.43 | 202.53 |
| Ó | O-9 | 203.35 | 3.16 | 1.30 | 202.61 | 1.38 | 202.53 | 1.35 | 202.56 | 1.43 | 202.48 | 2.22 | 201.69 | 1.48 | 202.43 |
| 1 | W-1 | NA | 1.65 | 1.32 | NA | 1.17 | NA | 1.14 | NA | 1.25 | NA | 1.31 | NA | 1.23 | NA |
| 1 | W-2 | 203.97 | 3.52 | 1.33 | 202.64 | 1.23 | 202.74 | 1.21 | 202.76 | 1.33 | 202.64 | | 203.97 | 1.28 | 202.69 |
| | W-3 | 202.86 | 1.91 | 1.09 | 201.77 | 1.03 | 201.83 | 1.01 | 201.85 | 1.11 | 201.75 | 1.30 | 201.56 | 1.22 | 201.64 |
| | B-1 | 207.02 | 13.37 | NM | | 4.63 | 202.39 | 5.58 | 201.44 | 6.17 | 200.85 | 6.80 | 200.22 | Destr | |
| 1 | B-2 | 204.85 | 13.61 | 4.64 | 200.21 | 4.60 | 200.25 | 4.55 | 200.30 | 4.65 | 200.20 | 5.50 | 199.35 | 4.61 | 200.24 |
| 농 | B-3 | 202.36 | 11.70 | 2.12 | 200.24 | 2.12 | 200.24 | 2.50 | 199.86 | 2.16 | 200.20 | 3.05 | 199.31 | 2.16 | 200.20 |
| 1 2 | B-4 | 204.11 | 15.61 | 3.86 | 200.25 | 3.71 | 200.40 | 3.68 | 200.43 | 3.86 | 200.25 | 4.65 | 199.46 | 3.81 | 200.30 |
| eq | B-5 | 203.87 | 12.80 | 1.05 | 202.82 | 0.95 | 202.92 | 0.82 | 203.05 | 0.98 | 202.89 | 1.22 | 202.65 | 0.88 | 202.99 |
| | P-1 | 205.36 | 17.58 | 2.02 | 203.34 | 1.93 | 203.43 | 1.95 | 203.41 | 1.71 | 203.65 | 3.00 | 202.36 | 3.11 | 202.25 |
| 1 | P-2 | 205.36 | 31.89 | 5.48 | 199.88 | 5.40 | 199.96 | 5.17 | 200.19 | 5.07 | 200.29 | 6.33 | 199.03 | 5.35 | 200.01 |
| | P-3 | 205.35 | 9.12 | 2.98 | 202.37 | 2.52 | 202.83 | 2.94 | 202.41 | 2.93 | 202.42 | 3.89 | 201.46 | 3.72 | 201.63 |

| | | Reference | Well Depth | 27-0 | ct-00 | 1-No | v-01 | 12-N | ov-02 | 23-O | ct-03 | 10-No | ov-04 | 1-No | v-05 |
|----------|---------|------------|------------|----------|-----------|----------|--------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| Lit | Well ID | Elevation | from | Water | Level | Water | Level | Water | Level | Water | Level | Water | Level | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation | Measured | Elevation | Measured | Elevation | Measured | Elevation | Measured | Elevation | Measured | Elevation |
| Г | 0-1 | 204.01 | 2.73 | 1.68 | 202.33 | 1.53 | 202.48 | 1.57 | 202.44 | 1.75 | 202.26 | 1.92 | 202.09 | 1.34 | 202.67 |
| | 0-2 | 204.77 | 3.25 | 2.47 | 202.30 | 2.15 | 202.62 | 2.32 | 202.45 | 2.44 | 202.33 | 2.56 | 202.21 | 2.22 | 202.55 |
| | O-3 | 202.90 | 3.42 | 1.45 | 201.45 | 1.28 | 201.62 | 1.33 | 201.57 | 1.46 | 201.44 | 1.55 | 201.35 | 1.23 | 201.67 |
| I۰ | 0-4 | 203.45 | 4.50 | 2.20 | 201.25 | 1.68 | 201.77 | 1.75 | 201.70 | 1.67 | 201.78 | 1.96 | 201.49 | 1.59 | 201.86 |
| erburden | O-6 | 204.15 | 3.46 | 1.66 | 202.49 | 1.32 | 202.83 | 1.56 | 202.59 | 1.82 | 202.33 | 1.85 | 202.30 | 1.63 | 202.52 |
| ۱ş | 0-7 | 204.08 | 2.60 | 2.00 | 202.08 | 1.36 | 202.72 | 1.40 | 202.68 | 2.11 | 201.97 | DRY | | 1.35 | 202.73 |
| ΙË | O-8 | 203.96 | 2.32 | 2.20 | 201.76 | 1.42 | 202.54 | 1.44 | 202.52 | DRY | | DRY | | 1.38 | 202.58 |
| ۱š | O-9 | 203.35 | 3.16 | 1.68 | 202.23 | 1.53 | 202.38 | 1.59 | 202.32 | 1.91 | 202.00 | 1.39 | 201.96 | 0.95 | 202.40 |
| I۲ | W-1 | NA | 1.65 | 1.28 | NA | 1.20 | NA | 1.23 | NA | 1.27 | NA | 1.35 | NA | 0.95 | NA |
| | W-2 | 203.97 | 3.52 | 2.03 | 201.94 | 1.20 | 202.77 | 1.37 | 202.60 | 2.71 | 201.26 | 2.76 | 201.21 | 0.83 | 203.14 |
| | W-3 | 202.86 | 1.91 | Plug | ged | Plug | ged | Plug | ged | Plug | ged | Plug | ged | Plug | ged |
| | W-3/03 | 202.96 | 2.14 | Not In: | stalled | Not Ins | stalled | Not In | stalled | 0.87 | 202.09 | 0.89 | 202.07 | 0.74 | 202.22 |
| | B-2 | 204.85 | 13.61 | 4.90 | 199.95 | 2.27 | 202.58 | 4.82 | 200.03 | 5.16 | 199.69 | 5.36 | 199.49 | 4.79 | 200.06 |
| ٦٠ | B-3 | 202.36 | 11.70 | 2.42 | 199.94 | 4.72 | 197.64 | 2.33 | 200.03 | 2.70 | 199.66 | 2.87 | 199.49 | 2.34 | 200.02 |
| Ιğ | B-4 | 204.11 | 15.61 | 4.11 | 200.00 | NM | 57 <u></u> 5 | 4.04 | 200.07 | 4.45 | 199.66 | 4.55 | 199.56 | 4.00 | 200.11 |
| 18 | B-5 | 203.87 | 12.80 | 1.20 | 202.67 | 0.95 | 202.92 | 0.97 | 202.90 | 1.18 | 202.69 | 1.33 | 202.54 | 0.90 | 202.97 |
| Bedrock | P-1 | 205.36 | 17.58 | 3.40 | 201.96 | 3.10 | 202.26 | 3.28 | 202.08 | 3.57 | 201.79 | 4.22 | 201.14 | 3.35 | 202.01 |
| 1 | P-2 | 205.36 | 31.89 | 5.66 | 199.70 | 5.20 | 200.16 | 5.44 | 199.92 | 6.24 | 199.12 | 6.28 | 199.08 | 5.62 | 199.74 |
| | P-3 | 205.35 | 9.12 | 3.55 | 201.80 | 2.90 | 202.45 | 3.06 | 202.29 | 3.30 | 202.05 | 3.40 | 201.95 | 2.97 | 202.38 |

| L | | Reference | Well Depth | 18-Ap | or-06 | 31-0 | ct-06 | 19-A | pr-07 | 20-No | ov-07 | 15-Ap | or-08 | 7-Oc | t-08 |
|----------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| L Lit | Well ID | Elevation | from | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation |
| Г | 0-1 | 204.01 | 2.73 | 1.46 | 202.55 | 1.51 | 202.50 | 1.45 | 202.56 | 1.58 | 202.43 | 1.25 | 202.76 | 1.93 | 202.08 |
| 1 | 0-2 | 204.77 | 3.25 | 2.18 | 202.59 | 2.27 | 202.50 | 2.18 | 202.59 | 2.30 | 202.47 | 2.07 | 202.70 | 2.56 | 202.21 |
| 1 | O-3 | 202.90 | 3.42 | 1.39 | 201.51 | 1.34 | 201.56 | 1.35 | 201.55 | 1.32 | 201.58 | 1.29 | 201.61 | 1.93 | 200.97 |
| Iے | 0-4 | 203.45 | 4.50 | 1.75 | 201.70 | 1.77 | 201.68 | 1.76 | 201.69 | 1.72 | 201.73 | 1.66 | 201.79 | 2.87 | 200.58 |
| ē | O-6 | 204.15 | 3.46 | 1.36 | 202.79 | 1.57 | 202.58 | 1.30 | 202.85 | 1.61 | 202.54 | 1.32 | 202.83 | 1.83 | 202.32 |
| ۱š | O-7 | 204.08 | 2.60 | 1.38 | 202.70 | 1.42 | 202.66 | 1.34 | 202.74 | 1.40 | 202.68 | 1.80 | 202.28 | Dry | NA |
| 무 | O-8 | 203.96 | 2.32 | 1.42 | 202.54 | 1.35 | 202.61 | 1.43 | 202.53 | 1.34 | 202.62 | 1.43 | 202.53 | Dry | NA |
| ۱ž | O-9 | 203.35 | 3.16 | 0.95 | 202.40 | 0.99 | 202.36 | 1.00 | 202.35 | 1.04 | 202.31 | 0.95 | 202.40 | 1.63 | 201.72 |
| I۲ | W-1 | NA | 1.65 | 1.00 | NA | 1.07 | NA | 1.06 | NA | 1.06 | NA | Dry | NA | 1.29 | NA |
| 1 | W-2 | 203.97 | 3.52 | 0.89 | 203.08 | 0.89 | 203.08 | 0.98 | 202.99 | 0.89 | 203.08 | 1.04 | 202.93 | 1.76 | 202.21 |
| 1 | W-3 | 202.86 | 1.91 | 1.06 | 201.80 | 1.21 | 201.65 | 1.18 | 201.68 | | | 1.12 | 201.74 | 1.45 | 201.41 |
| | W-3/03 | 202.96 | 2.14 | 0.76 | 202.20 | 0.81 | 202.15 | 0.78 | 202.18 | 0.77 | 202.19 | 0.74 | 202.22 | 1.00 | 201.96 |
| | B-2 | 204.85 | 13.61 | 4.87 | 199.98 | 4.87 | 199.98 | 4.93 | 199.92 | 4.91 | 199.94 | 4.85 | 200.00 | 5.47 | 199.38 |
| ٦٧ | B-3 | 202.36 | 11.70 | 2.38 | 199.98 | 2.42 | 199.94 | 2.50 | 199.86 | 2.46 | 199.90 | 2.41 | 199.95 | 3.03 | 199.33 |
| 支 | B-4 | 204.11 | 15.61 | 4.03 | 200.08 | 4.01 | 200.10 | 4.20 | 199.91 | 4.17 | 199.94 | 4.15 | 199.96 | 4.71 | 199.40 |
| edro | B-5 | 203.87 | 12.80 | 0.92 | 202.95 | 0.95 | 202.92 | 0.98 | 202.89 | 1.10 | 202.77 | 1.69 | 202.18 | 1.58 | 202.29 |
| lä | P-1 | 205.36 | 17.58 | 3.94 | 201.42 | 4.09 | 201.27 | 4.02 | 201.34 | 3.48 | 201.88 | 3.92 | 201.44 | 4.22 | 201.14 |
| 1 | P-2 | 205.36 | 31.89 | 5.81 | 199.55 | 5.82 | 199.54 | 5.97 | 199.39 | 9.10 | 196.26 | 5.64 | 199.72 | 6.50 | 198.86 |
| | P-3 | 205.35 | 9.12 | 4.50 | 200.85 | 3.16 | 202.19 | 3.53 | 201.82 | 6.33 | 199.02 | 3.45 | 201.90 | 3.57 | 201.78 |

| | | Reference | Well Depth | 20-A | or-09 | 11-No | ov-09 | 7-Ap | r-10 | 12-No | ov-10 | 14-A | or-11 | 1-No | v-11 |
|----------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|--------------------|-----------------|
| Lit | Well ID | Elevation | from | Water | Level | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation | Measured | Elevation |
| | 0-1 | 204.01 | 2.73 | 1.40 | 202.61 | 1.60 | 202.41 | 1.95 | 202.06 | 2.06 | 201.95 | 1.40 | 202.61 | 1.54 | 202.47 |
| | 0-2 | 204.77 | 3.25 | 2.16 | 202.61 | 2.26 | 202.51 | 2.64 | 202.13 | 2.75 | 202.02 | 2.52 | 202.25 | 2.38 | 202.39 |
| | O-3 | 202.90 | 3.42 | 1.23 | 201.67 | 1.30 | 201.60 | 1.21 | 201.69 | 1.51 | 201.39 | 1.28 | 201.62 | 1.36 | 201.54 |
| _ | 0-4 | 203.45 | 4.50 | 1.83 | 201.62 | 1.78 | 201.68 | 1.64 | 201.81 | 2.09 | 201.36 | 1.65 | 201.80 | 1.71 | 201.74 |
| verburde | O-6 | 204.15 | 3.46 | 1.37 | 202.78 | 1.48 | 202.67 | 1.50 | 202.65 | 1.94 | 202.21 | 1.31 | 202.84 | 1.50 | 202.65 |
| Ιž | O-7 | 204.08 | 2.60 | 1.68 | 202.40 | 1.85 | 202.23 | 1.60 | 202.48 | 2.18 | 201.90 | 1.80 | 202.28 | 1.82 | 202.26 |
| 무 | O-8 | 203.96 | 2.32 | 1.51 | 202.45 | dry | NA | 1.43 | 202.53 | 1.85 | 202.11 | 1.80 | 202.16 | 1.79 | 202.17 |
| Ĭš | O-9 | 203.35 | 3.16 | 0.94 | 202.41 | 0.97 | 202.38 | 1.27 | 202.08 | 1.47 | 201.88 | 0.97 | 202.38 | 1.03 | 202.32 |
| I۲ | W-1 | NA | 1.65 | 1.02 | NA | 1.07 | NA | NA | NA | 1.10 | NA | 1.03 | NA | | |
| | W-2 | 203.97 | 3.52 | 0.92 | 203.05 | 2.15 | 201.82 | 1.15 | 202.82 | 1.38 | 202.59 | 1.38 | 202.59 | 1.41 | 202.56 |
| | W-3 | 202.86 | 1.91 | 1.10 | 201.76 | 1.2 | 201.66 | 1.14 | 201.72 | 1.3 | 201.56 | | | (mam) | 1 - |
| | W-3/03 | 202.96 | 2.14 | 0.74 | 202.22 | 0.79 | 202.17 | 0.78 | 202.18 | 1.04 | 201.92 | 0.80 | 202.16 | 0.82 | 202.14 |
| | B-2 | 204.85 | 13.61 | 4.85 | 200.00 | 4.90 | 199.95 | 5.24 | 199.61 | 5.36 | 199.49 | 4.80 | 200.05 | 4.82 | 200.03 |
| ٦٦ | B-3 | 202.36 | 11.70 | 2.40 | 199.96 | 2.47 | 199.89 | 2.51 | 199.85 | 2.89 | 199.47 | 2.43 | 199.93 | 2.43 | 199.93 |
| 18 | B-4 | 204.11 | 15.61 | 4.06 | 200.05 | 4.16 | 199.95 | 4.20 | 199.91 | 4.61 | 199.50 | 4.05 | 200.06 | 4.10 | 200.01 |
| ۱ĕ | B-5 | 203.87 | 12.80 | 1.17 | 202.70 | 2.46 | 201.41 | 1.54 | 202.33 | 1.57 | 202.30 | 1.70 | 202.17 | 1.72 | 202.15 |
| Bedrock | P-1 | 205.36 | 17.58 | 3.60 | 201.76 | 3.90 | 201.46 | 4.43 | 200.93 | 4.25 | 201.11 | 4.20 | 201.16 | 4.05 | 201.31 |
| 1 | P-2 | 205.36 | 31.89 | 5.66 | 199.70 | 5.94 | 199.42 | 5.96 | 199.40 | 6.39 | 198.97 | 5.75 | 199.61 | 5.79 | 199.57 |
| L | P-3 | 205.35 | 9.12 | 3.60 | 201.75 | 3.30 | 202.05 | 4.41 | 200.94 | 3.63 | 201.72 | 3.17 | 202.18 | 3.70 | 201.65 |

| | | Reference | Well Depth | 11-A | or-12 | 1-No | v-12 | 15-A | pr-13 | 14-No | ov-13 | 12-Ma | ay-14 | 29-0 | ct-14 |
|-------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| Chit | Well ID | Elevation | from | Water | Level |
| Ľ | | TOC (masl) | TOC (masl) | Measured | Elevation |
| | 0-1 | 204.01 | 2.73 | 1.71 | 202.30 | 1.80 | 202.21 | 1.21 | 202.80 | 1.52 | 202.49 | 1.45 | 202.56 | 1.46 | 202.55 |
| 1 | O-2 | 204.77 | 3.25 | 2.44 | 202.33 | 2.55 | 202.22 | 2.00 | 202.77 | 2.21 | 202.56 | 2.30 | 202.47 | 2.20 | 202.57 |
| 1 | O-3 | 202.90 | 3.42 | 1.37 | 201.53 | 1.36 | 201.54 | 1.26 | 201.64 | 1.36 | 201.54 | 1.31 | 201.59 | 1.25 | 201.65 |
| I٠ | 0-4 | 203.45 | 4.50 | 1.91 | 201.54 | 1.64 | 201.81 | 1.60 | 201.85 | 1.72 | 201.73 | 1.77 | 201.68 | 1.62 | 201.83 |
| urde | O-6 | 204.15 | 3.46 | 1.59 | 202.56 | 1.85 | 202.30 | 1.27 | 202.88 | 1.45 | 202.70 | 1.38 | 202.77 | 1.44 | 202.71 |
| Į Š | O-7 | 204.08 | 2.60 | 2.03 | 202.05 | 1.91 | 202.17 | 1.70 | 202.38 | 1.84 | 202.24 | 1.80 | 202.28 | 1.69 | 202.39 |
| erp | O-8 | 203.96 | 2.32 | 1.96 | 202.00 | 1.58 | 202.38 | 1.54 | 202.42 | 1.74 | 202.22 | 1.61 | 202.35 | 1.40 | 202.56 |
| ۱ž | O-9 | 203.35 | 3.16 | 1.05 | 202.30 | 1.15 | 202.20 | 0.96 | 202.39 | 1.00 | 202.35 | 0.98 | 202.37 | 0.96 | 202.39 |
| I۲ | W-1 | NA | 1.65 | 1.06 | NA | 1.05 | NA | 1.01 | NA | 1.07 | NA | 1.06 | NA | 1.03 | NA |
| 1 | W-2 | 203.97 | 3.52 | 1.50 | 202.47 | 1.39 | 202.58 | 1.27 | 202.70 | 1.33 | 202.64 | 1.16 | 202.81 | 1.05 | 202.92 |
| 1 | W-3 | 202.86 | 1.91 | (marie) | | 1.27 | 201.59 | 1.21 | 201.65 | 1.13 | 201.73 | 1.09 | 201.77 | 1.02 | 201.84 |
| | W-3/03 | 202.96 | 2.14 | 0.82 | 202.14 | 0.90 | 202.06 | 0.73 | 202.23 | 0.78 | 202.18 | 0.76 | 202.20 | 0.77 | 202.19 |
| | B-2 | 204.85 | 13.61 | 4.99 | 199.86 | 5.21 | 199.64 | 4.81 | 200.04 | 4.86 | 199.99 | 4.85 | 200.00 | 4.80 | 200.05 |
| L | B-3 | 202.36 | 11.70 | 2.56 | 199.80 | 2.78 | 199.58 | 2.37 | 199.99 | 2.45 | 199.91 | 2.44 | 199.92 | 2.36 | 200.00 |
| Įģ | B-4 | 204.11 | 15.61 | 4.23 | 199.88 | 4.37 | 199.74 | 4.40 | 199.71 | 4.3 | 199.81 | 4.80 | 199.31 | 4.04 | 200.07 |
| drock | B-5 | 203.87 | 12.80 | 1.70 | 202.17 | 1.68 | 202.19 | 1.77 | 202.10 | 1.64 | 202.23 | 1.34 | 202.53 | 1.38 | 202.49 |
| å | P-1 | 205.36 | 17.58 | 4.24 | 201.12 | 4.35 | 201.01 | 4.00 | 201.36 | 3.72 | 201.64 | 4.33 | 201.03 | 4.25 | 201.11 |
| 1 | P-2 | 205.36 | 31.89 | 5.99 | 199.37 | 9.25 | 196.11 | 5.71 | 199.65 | 5.86 | 199.50 | 5.73 | 199.63 | 5.89 | 199.47 |
| | P-3 | 205.35 | 9.12 | 3.54 | 201.81 | 2.16 | 203.19 | 3.1 | 202.25 | 2.8 | 202.55 | 2.8 | 202.55 | 2.66 | 202.69 |

| | | Reference | Well Depth | 23-A | or-15 | 29-O | ct-15 | 21-A | pr-16 | 1-No | v-16 | 25-Ap | or-17 | 14-No | v-17 |
|-----------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| Ŀ E | Well ID | Elevation | from | Water | Level |
| Ľ | | TOC (masl) | TOC (masl) | Measured | Elevation |
| Г | 0-1 | 204.01 | 2.73 | 1.32 | 202.69 | 2.23 | 201.78 | 1.35 | 202.66 | 1.93 | 202.08 | 1.47 | 202.54 | 1.83 | 202.18 |
| 1 | O-2 | 204.77 | 3.25 | 2.11 | 202.66 | 2.65 | 202.12 | 2.10 | 202.67 | 2.57 | 202.20 | 2.12 | 202.65 | 2.47 | 202.30 |
| 1 | O-3 | 202.90 | 3.42 | 1.27 | 201.63 | 1.74 | 201.16 | 1.28 | 201.62 | 1.43 | 201.47 | 1.33 | 201.57 | 1.32 | 201.58 |
| ᡖ | 0-4 | 203.45 | 4.50 | 1.61 | 201.84 | 4.28 | 199.17 | 1.74 | 201.71 | 2.03 | 201.42 | 1.70 | 201.75 | 1.70 | 201.75 |
| rerburden | O-6 | 204.15 | 3.46 | 1.30 | 202.85 | 1.96 | 202.19 | 1.28 | 202.87 | 1.83 | 202.32 | 1.36 | 202.79 | 1.74 | 202.41 |
| ١ã | O-7 | 204.08 | 2.60 | 1.60 | 202.48 | 2.43 | 201.65 | 1.67 | 202.41 | 2.09 | 201.99 | 2.00 | 202.08 | 1.86 | 202.22 |
| ē | O-8 | 203.96 | 2.32 | 1.39 | 202.57 | 1.56 | 202.40 | 1.42 | 202.54 | 2.08 | 201.88 | 1.95 | 202.01 | 1.94 | 202.02 |
| Ó | O-9 | 203.35 | 3.16 | 0.96 | 202.39 | 2.00 | 201.35 | 0.95 | 202.40 | 1.49 | 201.86 | 0.99 | 202.36 | 1.03 | 202.32 |
| 1 | W-1 | NA | 1.65 | 1.03 | NA | 1.06 | NA | 1.05 | NA | 1.12 | NA | 1.04 | NA | 1.06 | NA |
| 1 | W-2 | 203.97 | 3.52 | 0.95 | 203.02 | 1.32 | 202.65 | 0.95 | 203.02 | 1.64 | 202.33 | 1.57 | 202.40 | 1.56 | 202.41 |
| | W-3/03 | 202.96 | 2.14 | 0.79 | 202.17 | 0.80 | 202.16 | 0.59 | 202.37 | 1.30 | 201.66 | 0.76 | 202.20 | 0.86 | 202.10 |
| | B-2 | 204.85 | 13.61 | 4.75 | 200.10 | 5.94 | 198.91 | 4.80 | 200.05 | 5.57 | 199.28 | 4.86 | 199.99 | 5.14 | 199.71 |
| ٦٦ | B-3 | 202.36 | 11.70 | 2.37 | 199.99 | 3.55 | 198.81 | 2.44 | 199.92 | 3.15 | 199.21 | 2.51 | 199.85 | 2.73 | 199.63 |
| 支 | B-4 | 204.11 | 15.61 | 4.06 | 200.05 | 5.09 | 199.02 | 4.28 | 199.83 | 4.68 | 199.43 | 4.14 | 199.97 | 4.38 | 199.73 |
| 1 5 | B-5 | 203.87 | 12.80 | 1.19 | 202.68 | 1.78 | 202.09 | 1.20 | 202.67 | 1.90 | 201.97 | 1.87 | 202.00 | 1.85 | 202.02 |
| Bedro | P-1 | 205.36 | 17.58 | 4.43 | 200.93 | 6.25 | 199.11 | 4.50 | 200.86 | 5.90 | 199.46 | 4.87 | 200.49 | 4.57 | 200.79 |
| | P-2 | 205.36 | 31.89 | 5.68 | 199.68 | 6.94 | 198.42 | 5.67 | 199.69 | 6.63 | 198.73 | 5.73 | 199.63 | 6.23 | 199.13 |
| _ | P-3 | 205.35 | 9.12 | 3.80 | 201.55 | 3.88 | 201.47 | 2.95 | 202.40 | 3.18 | 202.17 | 3.14 | 202.21 | 2.98 | 202.37 |

| | | Reference | Well Depth | 8-Ma | y-18 | 20-No | ov-18 | 16-A | pr-19 | 22-0 | ct-19 | 25-Ap | or-20 | 28-O | ct-20 |
|------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| Unit | Well ID | Elevation | from | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation |
| Г | 0-1 | 204.01 | 2.73 | 1.29 | 202.72 | 1.55 | 202.46 | 1.23 | 202.78 | 1.66 | 202.35 | 1.68 | 202.33 | 1.61 | 202.40 |
| 1 | 0-2 | 204.77 | 3.25 | 2.03 | 202.74 | 2.18 | 202.59 | 1.97 | 202.80 | 2.34 | 202.43 | 2.26 | 202.51 | 2.30 | 202.47 |
| 1 | O-3 | 202.90 | 3.42 | 1.29 | 201.61 | 1.30 | 201.60 | 1.27 | 201.63 | 1.31 | 201.59 | 1.30 | 201.60 | 1.29 | 201.61 |
| 딞 | 0-4 | 203.45 | 4.50 | 1.67 | 201.78 | 1.68 | 201.77 | 1.55 | 201.90 | 1.65 | 201.80 | 1.43 | 202.02 | 1.67 | 201.78 |
| nrd | O-6 | 204.15 | 3.46 | 1.24 | 202.91 | 1.42 | 202.73 | NM | NM | 1.62 | 202.53 | 1.50 | 202.65 | 1.53 | 202.62 |
| erbu | O-7 | 204.08 | 2.60 | 1.84 | 202.24 | 1.84 | 202.24 | 1.66 | 202.42 | 1.77 | 202.31 | 1.94 | 202.14 | 1.78 | 202.30 |
| Ιē | O-8 | 203.96 | 2.32 | 1.89 | 202.07 | 1.65 | 202.31 | 1.40 | 202.56 | 1.74 | 202.22 | 2.03 | 201.93 | 1.64 | 202.32 |
| Ó | O-9 | 203.35 | 3.16 | 0.96 | 202.39 | 0.97 | 202.38 | 0.96 | 202.39 | 0.97 | 202.38 | 0.99 | 202.36 | 1.00 | 202.35 |
| 1 | W-1 | NA | 1.65 | 0.99 | NA | 1.02 | NA | 1.01 | NA | 1.03 | NA | 1.03 | NA | 1.02 | NA |
| 1 | W-2 | 203.97 | 3.52 | 1.52 | 202.45 | 1.48 | 202.49 | 1.25 | 202.72 | 1.42 | 202.55 | 1.61 | 202.36 | 1.43 | 202.54 |
| L | W-3/03 | 202.96 | 2.14 | 0.79 | 202.17 | 0.80 | 202.16 | 0.78 | 202.18 | 0.84 | 202.12 | 0.79 | 202.17 | 0.81 | 202.15 |
| | B-2 | 204.85 | 13.61 | 4.81 | 200.04 | 4.90 | 199.95 | 4.71 | 200.14 | 5.03 | 199.82 | 4.95 | 199.90 | 4.93 | 199.92 |
| ٦٦ | B-3 | 202.36 | 11.70 | 2.40 | 199.96 | 2.50 | 199.86 | 2.36 | 200.00 | 2.65 | 199.71 | 2.52 | 199.84 | 2.52 | 199.84 |
| 支 | B-4 | 204.11 | 15.61 | 4.08 | 200.03 | 4.15 | 199.96 | 4.03 | 200.08 | 4.33 | 199.78 | 4.19 | 199.92 | 4.21 | 199.90 |
| ۱ŧ | B-5 | 203.87 | 12.80 | 1.83 | 202.04 | 1.86 | 202.01 | 1.79 | 202.08 | 1.86 | 202.01 | 1.82 | 202.05 | 1.83 | 202.04 |
| lä | P-1 | 205.36 | 17.58 | 4.23 | 201.13 | 4.38 | 200.98 | 4.17 | 201.19 | 2.71 | 202.65 | 4.30 | 201.06 | 4.27 | 201.09 |
| | P-2 | 205.36 | 31.89 | 5.62 | 199.74 | 5.89 | 199.47 | 5.68 | 199.68 | 6.01 | 199.35 | 5.99 | 199.37 | 5.93 | 199.43 |
| | P-3 | 205.35 | 9.12 | 2.74 | 202.61 | 2.64 | 202.71 | 2.51 | 202.84 | 2.70 | 202.65 | 2.88 | 202.47 | 2.93 | 202.42 |

SUMMARY OF HISTORICAL GROUNDWATER LEVEL ELEVATIONS

| Ţ | | Reference | Well Depth | 4-Ma | y-21 | 6-Oc | t-21 |
|------------|---------|------------|------------|----------|-----------|----------|-----------|
| Jnit | Well ID | Elevation | from | Water | Level | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation | Measured | Elevation |
| | 0-1 | 204.01 | 2.73 | 1.28 | 202.73 | 1.84 | 202.17 |
| | O-2 | 204.77 | 3.25 | 2.10 | 202.67 | 2.40 | 202.37 |
| | O-3 | 202.90 | 3.42 | 1.20 | 201.70 | 1.37 | 201.53 |
| ᇣ | 0-4 | 203.45 | 4.50 | 1.87 | 201.58 | 2.30 | 201.15 |
| ě | O-6 | 204.15 | 3.46 | 1.28 | 202.87 | 1.65 | 202.50 |
| Overburden | O-7 | 204.08 | 2.60 | 1.49 | 202.59 | 2.50 | 201.58 |
| ě | O-8 | 203.96 | 2.32 | 2.25 | 201.71 | 2.12 | 201.84 |
| Ó | O-9 | 203.35 | 3.16 | 0.94 | 202.42 | 1.10 | 202.25 |
| | W-1 | NA | 1.65 | 0.94 | N/A | 1.29 | N/A |
| | W-2 | 203.97 | 3.52 | 1.14 | 202.83 | 1.64 | 202.33 |
| | W-3/03 | 202.96 | 2.14 | 0.78 | 202.18 | 0.84 | 202.12 |
| | B-2 | 204.85 | 13.61 | 4.76 | 200.09 | 5.07 | 199.78 |
| J | B-3 | 202.36 | 11.70 | 2.36 | 200.00 | 2.62 | 199.74 |
| 호 | B-4 | 204.11 | 15.61 | 3.95 | 200.16 | 4.30 | 199.81 |
| Bedrock | B-5 | 203.87 | 12.80 | 1.76 | 202.11 | 1.83 | 202.04 |
| Be | P-1 | 205.36 | 17.58 | 4.44 | 200.92 | 4.62 | 200.74 |
| | P-2 | 205.36 | 31.89 | 5.80 | 199.56 | 6.10 | 199.26 |
| | P-3 | 205.35 | 9.12 | 2.78 | 202.57 | 3.06 | 202.29 |

| | | Reference | Well Depth | 26-Ap | or-22 | 22-Se | p-22 | 21-A | pr-23 | 28-No | ov-23 | 30-Ap | or-24 | 12-No | v-24 |
|------|---------|------------|------------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| Unit | Well ID | Elevation | from | Water | Level |
| | | TOC (masl) | TOC (masl) | Measured | Elevation |
| Г | 0-1 | 203.31 | 2.73 | 1.33 | 201.98 | 1.64 | 201.67 | 1.60 | 201.71 | 1.62 | 201.69 | 1.30 | 202.01 | 1.85 | 201.46 |
| | O-2 | 204.07 | 3.25 | 2.00 | 202.07 | 2.56 | 201.51 | 2.12 | 201.95 | 2.22 | 201.85 | 2.01 | 202.06 | 2.45 | 201.62 |
| | O-3 | 202.20 | 3.42 | 1.28 | 200.92 | 1.75 | 200.45 | 1.26 | 200.94 | 1.25 | 200.95 | 1.23 | 200.97 | 1.31 | 200.89 |
| 등 | 0-4 | 202.75 | 4.50 | 1.61 | 201.14 | NM | N/A | 1.70 | 201.05 | 1.72 | 201.03 | 1.56 | 201.19 | 1.84 | 200.91 |
| Ē | O-6 | 203.45 | 3.46 | 1.24 | 202.21 | 1.84 | 201.61 | 1.32 | 202.13 | 1.40 | 202.05 | NM | N/A | NM | N/A |
| ᇋ | O-7 | 203.38 | 2.60 | 1.75 | 201.63 | DRY | N/A | 1.62 | 201.76 | DRY | N/A | 1.50 | 201.88 | 1.94 | 201.44 |
| Įě | O-8 | 203.26 | 2.32 | 1.57 | 201.69 | 2.10 | 201.16 | 1.38 | 201.88 | 1.64 | 201.62 | 1.35 | 201.91 | 1.89 | 201.37 |
| ΙÓ | O-9 | 202.65 | 3.16 | 0.95 | 201.70 | 1.53 | 201.12 | 0.95 | 201.70 | 0.95 | 201.70 | 0.94 | 201.71 | 1.02 | 201.63 |
| | W-1 | N/A | 1.65 | 1.04 | N/A | 1.38 | N/A | 1.05 | N/A | 1.06 | N/A | 0.99 | N/A | 1.08 | N/A |
| | W-2 | 203.27 | 3.52 | 1.02 | 202.25 | 1.54 | 201.73 | 0.93 | 202.34 | 1.15 | 202.12 | 0.93 | 202.34 | 1.41 | 201.86 |
| | W-3/03 | 202.26 | 2.14 | 0.81 | 201.45 | 0.96 | 201.30 | 0.79 | 201.47 | 0.80 | 201.46 | 0.73 | 201.53 | 0.82 | 201.44 |
| | B-2 | 204.15 | 13.61 | 4.77 | 199.38 | 5.59 | 198.56 | 4.85 | 199.30 | 4.95 | 199.20 | 4.93 | 199.22 | 5.14 | 199.01 |
| L | B-3 | 201.66 | 11.70 | 2.42 | 199.24 | 3.17 | 198.49 | 2.41 | 199.25 | 2.50 | 199.16 | 2.48 | 199.18 | 2.70 | 198.96 |
| 支 | B-4 | 203.41 | 15.61 | 3.99 | 199.42 | 4.83 | 198.58 | 4.10 | 199.31 | 4.17 | 199.24 | 4.50 | 198.91 | 4.38 | 199.03 |
| 15 | B-5 | 203.17 | 12.80 | 1.26 | 201.91 | 1.69 | 201.48 | 1.20 | 201.97 | 1.35 | 201.82 | 1.18 | 201.99 | 1.60 | 201.57 |
| æ | P-1 | 204.66 | 17.58 | 4.31 | 200.35 | 5.04 | 199.62 | 4.21 | 200.45 | NM | N/A | NM | N/A | NM | N/A |
| 1 | P-2 | 204.66 | 31.89 | NM | N/A |
| | P-3 | 204.65 | 9.12 | 2.30 | 202.35 | 3.21 | 201.44 | 2.52 | 202.13 | 2.51 | 202.14 | 2.83 | 201.82 | 3.07 | 201.58 |

^{**} In November 2022 the site was surveyed to reflect UTM derived coordinates and the elevation across the Site was lowered by 0.7 meters.

ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix F Laboratory Analytical Reports



CLIENT NAME: GM BLUEPLAN

1260 Second Avenue East, Unit 1 OWEN SOUND, ON N4K2J3

(519) 376-1805

ATTENTION TO: Jessica Weller

PROJECT: M1555

AGAT WORK ORDER: 24T144991

WATER ANALYSIS REVIEWED BY: Yris Verastegui, Inorganic Team Lead

DATE REPORTED: May 13, 2024

PAGES (INCLUDING COVER): 12 VERSION*: 1

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

| *Notes | | | |
|--------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Disclaimer:

- All work conducted herein has been done using accepted standard protocols, and generally accepted practices and methods. AGAT test methods may
 incorporate modifications from the specified reference methods to improve performance.
- All samples will be disposed of within 30 days after receipt unless a Long Term Storage Agreement is signed and returned. Some specialty analysis may
 be exempt, please contact your Client Project Manager for details.
- AGAT's liability in connection with any delay, performance or non-performance of these services is only to the Client and does not extend to any other
 third party. Unless expressly agreed otherwise in writing, AGAT's liability is limited to the actual cost of the specific analysis or analyses included in the
 services.
- . This Certificate shall not be reproduced except in full, without the written approval of the laboratory.
- The test results reported herewith relate only to the samples as received by the laboratory.
- Application of guidelines is provided "as is" without warranty of any kind, either expressed or implied, including, but not limited to, warranties of
 merchantability, fitness for a particular purpose, or non-infringement. AGAT assumes no responsibility for any errors or omissions in the guidelines
 contained in this document.
- All reportable information as specified by ISO/IEC 17025:2017 is available from AGAT Laboratories upon request.
- For environmental samples in the Province of Quebec: The analysis is performed on and results apply to samples as received. A temperature above 6°C upon receipt, as indicated in the Sample Reception Notification (SRN), could indicate the integrity of the samples has been compromised if the delay between sampling and submission to the laboratory could not be minimized.

AGAT Laboratories (V1)

Page 1 of 12

Member of: Association of Professional Engineers and Geoscientists of Alberta (APEGA)

Western Enviro-Agricultural Laboratory Association (WEALA) Environmental Services Association of Alberta (ESAA) AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. Measurement Uncertainty is not taken into consideration when stating conformity with a specified requirement.



Certificate of Analysis

AGAT WORK ORDER: 24T144991

PROJECT: M1555

ATTENTION TO: Jessica Weller

FAX (905)712-5122 http://www.agatlabs.com

TEL (905)712-5100

5835 COOPERS AVENUE

MISSISSAUGA, ONTARIO CANADA L4Z 1Y2

CLIENT NAME: GM BLUEPLAN
SAMPLING SITE:St. Edmunds

SAMPLED BY:

| | | | | | CBOD |)5 | | | |
|--|------|------------|-----------|------------|------------|------------|------------|------------|---------------------------|
| DATE RECEIVED: 2024-05-01 | | | | | | | | | DATE REPORTED: 2024-05-13 |
| | | SAMPLE DES | CRIPTION: | S-1 | S-6 | S-6A | S-8 | S-9 | |
| | | SAMI | PLE TYPE: | Water | Water | Water | Water | Water | |
| | | DATE S | SAMPLED: | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 | |
| Parameter | Unit | G/S | RDL | 5831075 | 5831087 | 5831088 | 5831089 | 5831090 | |
| Biochemical Oxygen Demand, Carbonaceous | mg/L | | 2 | <2 | <2 | <2 | <2 | <2 | |
| | | | | | | | | | |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

5831087-5831090 Un-ionized Ammonia detection limit is a calculated RDL. The calculation of Un-ionized Ammonia is based on the field temperature and pH. Values are reported as calculated.

Dilution required, RDL has been increased accordingly.

Analysis performed at AGAT Halifax (unless marked by *)

Certified By:





CLIENT NAME: GM BLUEPLAN

SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T144991

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

Groundwater Package

| DATE RECEIVED: 2024-05-01 | | | | | | | DATE REPORTED: 2024-05-13 | | | | |
|----------------------------------|----------|----------|------------------------------------|----------------------------|----------------------------|----------------------------|----------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| | | 250 0000 | CRIPTION: PLE TYPE: SAMPLED: | O-1 Water 2024-04-30 | O-2 Water 2024-04-30 | O-3 Water 2024-04-30 | O-4 Water 2024-04-30 | O-6 Water 2024-04-30 | O-7 Water 2024-04-30 | O-8 Water 2024-04-30 | O-9 Water 2024-04-30 |
| Parameter | Unit | G/S | RDL | 5831020 | 5831047 | 5831048 | 5831049 | 5831050 | 5831051 | 5831052 | 5831053 |
| Electrical Conductivity | uS/cm | | 2 | 662 | 1370 | 1970 | 765 | 1430 | 396 | 764 | 548 |
| рН | pH Units | | NA | 7.69 | 7.20 | 7.43 | 7.76 | 7.05 | 7.76 | 7.53 | 7.66 |
| Hardness (as CaCO3) (Calculated) | mg/L | | 0.5 | 327 | 570 | 985 | 382 | 600 | 221 | 431 | 292 |
| Alkalinity (as CaCO3) | mg/L | | 5 | 373 | 749 | 476 | 302 | 836 | 228 | 475 | 330 |
| Chloride | mg/L | | 0.10 | 4.44 | 30.6 | 39.0 | 0.42 | 16.9 | 0.53 | 3.96 | 6.42 |
| Nitrate as N | mg/L | | 0.05 | 0.86 | <0.05 | < 0.07 | < 0.05 | <0.05 | 0.91 | <0.05 | < 0.05 |
| Nitrite as N | mg/L | | 0.05 | < 0.05 | <0.05 | <0.05 | <0.05 | <0.05 | < 0.05 | < 0.05 | < 0.05 |
| Sulphate | mg/L | | 0.10 | 7.20 | 4.08 | 589 | 142 | 7.04 | 14.8 | 0.55 | 2.67 |
| Ammonia as N | mg/L | | 0.02 | <0.02 | 23.8 | 0.04 | <0.02 | 24.9 | 0.55 | 0.02 | 0.06 |
| Dissolved Organic Carbon | mg/L | | 0.5 | 2.8 | 17.5 | 4.5 | 3.0 | 14.6 | 7.4 | 9.2 | 26.2 |
| Dissolved Calcium | mg/L | | 0.05 | 92.1 | 152 | 263 | 105 | 160 | 67.0 | 132 | 76.7 |
| Dissolved Magnesium | mg/L | | 0.05 | 23.5 | 46.3 | 79.8 | 29.1 | 48.7 | 13.0 | 24.7 | 24.4 |
| Dissolved Potassium | mg/L | | 0.50 | 1.11 | 21.7 | 4.20 | < 0.50 | 21.0 | 0.90 | <0.50 | 3.89 |
| Dissolved Sodium | mg/L | | 0.05 | 4.24 | 36.1 | 18.8 | 1.64 | 24.0 | 2.55 | 3.86 | 3.98 |
| Dissolved Iron | mg/L | | 0.020 | <0.020 | 0.341 | <0.020 | <0.020 | <0.020 | <0.020 | <0.020 | 0.467 |
| Dissolved Boron | mg/L | | 0.010 | 0.046 | 0.388 | 0.018 | <0.010 | 0.282 | <0.010 | <0.010 | 0.015 |
| Lab Filtration DOC | | | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Lab Filtration Metals | | | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

Certified By:



CLIENT NAME: GM BLUEPLAN

SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T144991

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

Groundwater Package

| DATE RECEIVED: 2024-05-01 | | | | | | | | Γ | DATE REPORT | ED: 2024-05-13 | |
|----------------------------------|----------|------------|------------------------|--------------|--------------|-----------------|-------------|-------------|-------------|----------------|-------------|
| | | SAMPLE DES | CRIPTION: PLE TYPE: | W-1 Water | W-2 Water | W-3/03 Water | B2 Water | B3 Water | B4 Water | B5 Water | P3 Water |
| | | DATE | SAMPLED: | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 | 2024-04-30 |
| Parameter | Unit | G/S | RDL | 5831054 | 5831055 | 5831056 | 5831057 | 5831058 | 5831059 | 5831060 | 5831061 |
| Electrical Conductivity | uS/cm | | 2 | 507 | 672 | 1040 | 688 | 2690 | 1560 | 1260 | 642 |
| рН | pH Units | | NA | 7.85 | 7.80 | 7.52 | 7.81 | 7.40 | 7.55 | 7.73 | 7.99 |
| Hardness (as CaCO3) (Calculated) | mg/L | | 0.5 | 288 | 374 | 416 | 333 | 1310 | 542 | 642 | 308 |
| Alkalinity (as CaCO3) | mg/L | | 5 | 306 | 411 | 529 | 309 | 463 | 578 | 345 | 321 |
| Chloride | mg/L | | 0.10 | 3.12 | 1.72 | 19.1 | 10.3 | 16.0 | 115 | 15.1 | 8.42 |
| Nitrate as N | mg/L | | 0.05 | 0.06 | < 0.05 | < 0.05 | < 0.05 | <0.14 | < 0.05 | < 0.05 | 0.24 |
| Nitrite as N | mg/L | | 0.05 | <0.05 | < 0.05 | < 0.05 | < 0.05 | <0.11 | < 0.05 | <0.05 | <0.05 |
| Sulphate | mg/L | | 0.10 | 10.7 | 4.00 | 12.8 | 50.2 | 983 | 53.9 | 318 | 13.7 |
| Ammonia as N | mg/L | | 0.02 | 0.08 | 0.02 | 8.08 | 0.20 | 0.12 | 2.92 | 0.09 | < 0.02 |
| Dissolved Organic Carbon | mg/L | | 0.5 | 33.9 | 4.8 | 11.3 | 6.2 | 5.3 | 18.0 | 5.3 | 2.9 |
| Dissolved Calcium | mg/L | | 0.05 | 84.7 | 116 | 113 | 84.1 | 359 | 119 | 173 | 84.6 |
| Dissolved Magnesium | mg/L | | 0.05 | 18.5 | 20.4 | 32.4 | 29.9 | 100 | 59.5 | 50.9 | 23.6 |
| Dissolved Potassium | mg/L | | 0.50 | 0.65 | 0.71 | 14.0 | 1.45 | 3.17 | 5.63 | 1.39 | 0.59 |
| Dissolved Sodium | mg/L | | 0.05 | 3.45 | 1.24 | 21.7 | 10.6 | 16.0 | 72.1 | 10.7 | 3.75 |
| Dissolved Iron | mg/L | | 0.020 | 0.342 | <0.020 | <0.020 | <0.020 | 0.530 | <0.020 | 0.026 | <0.020 |
| Dissolved Boron | mg/L | | 0.010 | <0.010 | <0.010 | 0.363 | 0.048 | 0.047 | 0.218 | 0.034 | < 0.010 |
| Lab Filtration DOC | | | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Lab Filtration Metals | | | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

5831020-5831061 Metals analysis completed on a filtered sample.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:



CLIENT NAME: GM BLUEPLAN

SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T144991

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

Surface Water Package

| | | | 0 | illuoc viato | i i donage | | | | | |
|----------------------------------|-----------|---|---------------------------------------|--------------|---------------------------------------|--|----------|---------------------------------------|---------------------------------------|--|
| DATE RECEIVED: 2024-05-01 | | | | | | | | DATE REPORTI | ED: 2024-05-13 | |
| Parameter | S Unit | AMPLE DESCRIPTION: SAMPLE TYPE: DATE SAMPLED: G/S RDL | S-1 Water 2024-04-30 5831075 | RDL | S-6 Water 2024-04-30 5831087 | S-6A Water 2024-04-30 5831088 | RDL | S-8 Water 2024-04-30 5831089 | S-9 Water 2024-04-30 5831090 | |
| Electrical Conductivity | uS/cm | 2 | 593 | 2 | 921 | 825 | 2 | 363 | 328 | |
| рН | pH Units | NA | 8.14 | NA | 8.05 | 8.06 | NA | 8.15 | 8.16 | |
| Hardness (as CaCO3) (Calculated) | mg/L | 0.5 | 220 | 0.5 | 351 | 321 | 0.5 | 193 | 176 | |
| Alkalinity (as CaCO3) | mg/L | 5 | 248 | 5 | 381 | 374 | 5 | 214 | 204 | |
| Chloride | mg/L | 0.10 | 42.2 | 0.12 | 31.3 | 28.7 | 0.10 | 4.31 | 0.69 | |
| Nitrate as N | mg/L | 0.05 | 80.0 | 0.05 | 1.48 | 1.60 | 0.05 | 0.05 | <0.05 | |
| Nitrite as N | mg/L | 0.05 | <0.05 | 0.05 | < 0.05 | <0.05 | 0.05 | < 0.05 | < 0.05 | |
| Sulphate | mg/L | 0.10 | 4.43 | 0.10 | 41.8 | 38.0 | 0.10 | 2.98 | 0.75 | |
| Total Phosphorus | mg/L | 0.02 | 0.06 | 0.02 | 0.05 | 0.04 | 0.02 | 0.04 | 0.05 | |
| Ammonia-Un-ionized (Calculated) | mg/L | 0.000002 | 0.000486 | 0.000002 | 0.0362 | 0.0310 | 0.000002 | 0.00153 | 0.00124 | |
| Ammonia as N | mg/L | 0.02 | 0.02 | 0.02 | 1.11 | 0.82 | 0.02 | 0.03 | 0.03 | |
| Total Kjeldahl Nitrogen | mg/L | 0.10 | 0.26 | 0.10 | 2.31 | 1.78 | 0.10 | 0.20 | <0.10 | |
| Dissolved Organic Carbon | mg/L | 0.5 | 14.2 | 0.5 | 15.4 | 15.0 | 0.5 | 17.1 | 7.8 | |
| Phenols | mg/L | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | <0.001 | 0.002 | |
| Total Calcium | mg/L | 0.20 | 68.2 | 0.20 | 103 | 88.3 | 0.20 | 51.3 | 51.1 | |
| Total Magnesium | mg/L | 0.10 | 12.0 | 0.10 | 22.9 | 24.5 | 0.10 | 15.8 | 11.8 | |
| Total Potassium | mg/L | 0.50 | 0.84 | 0.50 | 12.5 | 11.6 | 0.50 | 1.01 | 1.69 | |
| Total Sodium | mg/L | 0.10 | 30.9 | 0.10 | 34.3 | 35.8 | 0.10 | 4.16 | 1.78 | |
| Total Boron | mg/L | 0.010 | 0.015 | 0.010 | 0.361 | 0.358 | 0.010 | 0.031 | 0.017 | |
| Total Iron | mg/L | 0.050 | < 0.050 | 0.050 | 0.202 | 0.131 | 0.050 | 0.068 | <0.050 | |
| Total Zinc | mg/L | 0.020 | <0.020 | 0.020 | <0.020 | <0.020 | 0.020 | <0.020 | <0.020 | |
| Lab Filtration DOC | | | 1 | | 1 | 1 | | 1 | 1 | |
| Field Temperature | Deg C | | 10.0 | | 10.3 | 9.9 | | 10.9 | 11.7 | |
| Field pH | pH Units | NA | 8.04 | NA | 8.16 | 8.24 | NA | 8.34 | 8.22 | |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

5831075-5831090 Dilution required, RDL has been increased accordingly.

Un-ionized Ammonia detection limit is a calculated RDL. The calculation of Un-ionized Ammonia is based on the field temperature and pH. Values are reported as calculated.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:



Quality Assurance

CLIENT NAME: GM BLUEPLAN

PROJECT: M1555

AGAT WORK ORDER: 24T144991 ATTENTION TO: Jessica Weller

SAMPLED BY:

SAMPLING SITE:St. Edmunds

Water Analysis DUPLICATE REFERENCE MATERIAL METHOD BLANK SPIKE RPT Date: May 13, 2024 MATRIX SPIKE Method Acceptable Acceptable Acceptable Sample Blank Limits Limits Limits Dup #2 **PARAMETER** Batch Dup #1 RPD Recovery Recover Value Lower Upper Lower Upper Lower Upper **Groundwater Package** 931 **Electrical Conductivity** 941 < 2 96% 80% 120% 5832463 1.1% 5832463 8.04 8.11 0.9% NA 100% 90% 110% Alkalinity (as CaCO3) 5832463 422 428 1.4% < 5 106% 80% 120% Chloride 5831048 5831048 39.0 38.6 1.0% < 0.10 94% 70% 130% 100% 80% 120% 103% 70% 130% Nitrate as N 5831048 5831048 < 0.07 < 0.07 < 0.05 93% 70% 94% 80% 120% 95% 70% 130% NA 130% Nitrite as N 5831048 5831048 < 0.05 < 0.05 95% 70% 96% 80% 120% 70% 130% < 0.05 NA 130% 95% Sulphate 5831048 5831048 589 580 1.5% < 0.10 92% 70% 130% 95% 80% 120% NA 70% 130% Ammonia as N 5820946 0.02 0.02 NA < 0.02 105% 70% 130% 103% 80% 120% 92% 70% 130% Dissolved Organic Carbon 5831020 5831020 2.8 2.7 3.6% < 0.5 102% 90% 110% 100% 90% 110% 100% 80% 120% **Dissolved Calcium** < 0.05 103% 104% 70% 130% 5830045 155 158 1.9% 70% 130% 80% 120% 107% 5830045 23.2 2.2% < 0.05 103% 70% 130% 104% 80% 120% 108% 70% 130% Dissolved Magnesium 22.7 70% 104% Dissolved Potassium 5830045 0.56 < 0.50 101% 130% 80% 120% 106% 70% 130% 0.52 NA 3.0% 70% 130% Dissolved Sodium 5830045 2.61 2.69 < 0.05 103% 130% 104% 80% 120% 106% 70% Dissolved Iron 5830045 1.54 1.44 6.7% < 0.010 105% 70% 130% 103% 80% 120% 101% 70% 130% Dissolved Boron 5830045 < 0.010 < 0.010 NA < 0.010 101% 70% 130% 112% 80% 120% 114% 70% 130% Surface Water Package **Electrical Conductivity** 5831056 5831056 1040 1040 0.0% < 2 97% 80% 120% pH 5831056 5831056 7.52 7.52 0.0% NA 99% 90% 110% Alkalinity (as CaCO3) 5831056 5831056 529 525 0.8% < 5 110% 80% 120% Chloride 5831048 5831048 39.0 38.6 1.0% < 0.10 94% 70% 130% 100% 80% 120% 103% 70% 130% Nitrate as N < 0.07 70% 94% 80% 120% 95% 130% 5831048 5831048 < 0.07 < 0.05 93% 130% 70% NA Nitrite as N 5831048 5831048 < 0.05 < 0.05 < 0.05 95% 70% 96% 80% 120% 95% 70% 130% NA 130% 1.5% 70% Sulphate 5831048 5831048 589 580 < 0.10 92% 130% 95% 80% 120% NA 70% 130% 96% Total Phosphorus 70% 106% 70% 130% 5835439 0.05 0.05 NA < 0.02 100% 130% 80% 120% Ammonia as N 5831057 5831057 0.20 0.20 0.0% < 0.02 105% 70% 130% 103% 80% 120% 100% 70% 130% Total Kjeldahl Nitrogen 5822121 3.37 3.22 4.6% < 0.10 102% 70% 130% 100% 80% 120% 93% 70% 130% Dissolved Organic Carbon 5831020 5831020 2.8 2.7 3.6% < 0.5 102% 90% 110% 100% 90% 110% 100% 80% 120% **Phenols** 5830056 0.002 0.002 NA < 0.001 97% 90% 110% 100% 90% 110% 98% 80% 120% 70% **Total Calcium** 5835439 230 234 1.7% < 0.20 95% 130% 102% 80% 120% NA 70% 130% **Total Magnesium** 5835439 130 124 4.7% < 0.10 101% 70% 130% 111% 80% 120% 109% 70% 130% **Total Potassium** 5835439 5.20 5.02 3.5% < 0.50 105% 70% 130% 109% 80% 120% 85% 70% 130% **Total Sodium** 5835439 218 225 3.2% < 0.10 110% 70% 130% 108% 80% 120% 119% 70% 130% **Total Boron** 102% 99% 130% 5835439 0.478 0.468 2.1% < 0.010 70% 130% 80% 120% 89% 70% Total Iron 0.260 70% 97% 94% 130% 5835439 0.240 NA < 0.050 97% 130% 80% 120% 70%

Comments: NA signifies Not Applicable.

Duplicate NA: results are under 5X the RDL and will not be calculated.

5835439

Matrix spike NA: Spike level < native concentration. Matrix spike acceptance limits do not apply and are not calculated.

0.044

CBOD5

Total Zinc

AGAT QUALITY ASSURANCE REPORT (V1)

Page 6 of 12

130%

70%

92%

AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. RPDs calculated using raw data. The RPD may not be reflective of duplicate values shown, due to rounding of final results.

NA

0.032

96%

< 0.020

70%

130%

95%

80%

120%



AGAT WORK ORDER: 24T144991

Quality Assurance

CLIENT NAME: GM BLUEPLAN

PROJECT: M1555 ATTENTION TO: Jessica Weller

SAMPLING SITE:St. Edmunds SAMPLED BY:

| | Water Analysis (Continued) | | | | | | | | | | | | | | |
|------------------------|----------------------------|--------------|--------|---------|-----|-----------------|----------|----------------------|--------|----------|-------|----------------|----------|----------|----------------|
| RPT Date: May 13, 2024 | | | E | UPLICAT | E | | REFEREN | ICE MA | TERIAL | METHOD | BLANK | SPIKE | MAT | RIX SPII | KE |
| PARAMETER | R Batch | Batch Sample | Dup #1 | Dup #2 | RPD | Method Blank | Measured | Acceptable Limits | | Recovery | Lin | ptable nits | Recovery | | ptable nits |
| | | ld | | | | | Value | Lower | Upper | | Lower | Upper | | Lower | Upper |

Biochemical Oxygen Demand, 5831823 <6 <6 NA <2 113% 70% 130%

Carbonaceous

Comments: If the RPD value is NA, the results of the duplicates are under 5X the RDL and will not be calculated.

Certified By:

Iris Verástegui

Method Summary

CLIENT NAME: GM BLUEPLAN

PROJECT: M1555

AGAT WORK ORDER: 24T144991 ATTENTION TO: Jessica Weller

SAMPLING SITE:St. Edmunds SAMPLED BY:

| PARAMETER | AGAT S.O.P | LITERATURE REFERENCE | ANALYTICAL TECHNIQUE |
|--|---------------|--|--------------------------|
| Water Analysis | | | |
| Biochemical Oxygen Demand, Carbonaceous | INOR-121-6023 | SM 5210 B | INCUBATOR |
| Electrical Conductivity | INOR-93-6000 | SM 2510 B | PC TITRATE |
| pH | INOR-93-6000 | modified from SM 4500-H+ B | PC TITRATE |
| Hardness (as CaCO3) (Calculated) | MET-93-6105 | modified from EPA SW-846 6010C & 200.7 & SM 2340 B | CALCULATION |
| Alkalinity (as CaCO3) | INOR-93-6000 | Modified from SM 2320 B | PC TITRATE |
| Chloride | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Nitrate as N | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Nitrite as N | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Sulphate | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Ammonia as N | INOR-93-6059 | modified from SM 4500-NH3 H | LACHAT FIA |
| Dissolved Organic Carbon | INOR-93-6049 | modified from SM 5310 B | SHIMADZU CARBON ANALYZER |
| Dissolved Calcium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP/MS |
| Dissolved Magnesium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Dissolved Potassium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP/MS |
| Dissolved Sodium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP/MS |
| Dissolved Iron | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Boron | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Lab Filtration DOC | SR-78-9001 | | FILTRATION |
| Lab Filtration Metals | SR-78-9001 | | FILTRATION |
| Total Phosphorus | INOR-93-6022 | modified from SM 4500-P B and SM 4500-P E | SPECTROPHOTOMETER |
| Ammonia-Un-ionized (Calculated) | | MOE REFERENCE, PWQOs Tab 2 | CALCULATION |
| Total Kjeldahl Nitrogen | INOR-93-6048 | modified from EPA 351.2 and SM 4500-NORG D | LACHAT FIA |
| Phenols | INOR-93-6072 | modified from SM 5530 D | LACHAT FIA |
| Total Calcium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Magnesium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Potassium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Sodium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Boron | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP-MS |
| Total Iron | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP-MS |
| Total Zinc | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP-MS |
| Field Temperature | | | N/A |
| Field pH | | | N/A |



CLIENT NAME: GEI CONSULTANTS

1260 Second Avenue East, Unit 1 OWEN SOUND, ON N4K2J3

(519) 376-1805

ATTENTION TO: Jessica Weller

PROJECT: M1555

AGAT WORK ORDER: 24T220815

TRACE ORGANICS REVIEWED BY: Neli Popnikolova, Senior Chemist WATER ANALYSIS REVIEWED BY: Yris Verastegui, Inorganic Team Lead

DATE REPORTED: Nov 26, 2024

PAGES (INCLUDING COVER): 16 VERSION*: 1

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

| *Notes | |
|--------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

Disclaimer.

- All work conducted herein has been done using accepted standard protocols, and generally accepted practices and methods. AGAT test methods may
 incorporate modifications from the specified reference methods to improve performance.
- All samples will be disposed of within 30 days after receipt unless a Long Term Storage Agreement is signed and returned. Some specialty analysis may
 be exempt, please contact your Client Project Manager for details.
- AGAT's liability in connection with any delay, performance or non-performance of these services is only to the Client and does not extend to any other
 third party. Unless expressly agreed otherwise in writing, AGAT's liability is limited to the actual cost of the specific analysis or analyses included in the
 services.
- This Certificate shall not be reproduced except in full, without the written approval of the laboratory.
- The test results reported herewith relate only to the samples as received by the laboratory.
- Application of guidelines is provided "as is" without warranty of any kind, either expressed or implied, including, but not limited to, warranties of
 merchantability, fitness for a particular purpose, or non-infringement. AGAT assumes no responsibility for any errors or omissions in the guidelines
 contained in this document.
- All reportable information is available on request from AGAT Laboratories, in accordance with ISO/IEC 17025:2017, ISO/IEC 17025:2005 (Quebec), DR-12-PALA and/or NELAP Standards.
- This document is signed by an authorized signatory who meets the requirements of the MELCCFP, CALA, CCN and NELAP.
- For environmental samples in the Province of Quebec: The analysis is performed on and results apply to samples as received. A temperature above 6°C upon receipt, as indicated in the Sample Reception Notification (SRN), could indicate the integrity of the samples has been compromised if the delay between sampling and submission to the laboratory could not be minimized.

AGAT Laboratories (V1)

Page 1 of 16

Member of: Association of Professional Engineers and Geoscientists of Alberta (APEGA)

Western Enviro-Agricultural Laboratory Association (WEALA) Environmental Services Association of Alberta (ESAA) AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. Measurement Uncertainty is not taken into consideration when stating conformity with a specified requirement.



Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

Volatile Organic Compounds in Water

| SAMPLE DESCRIPTION: 0-2 | | | | | | | | | | | |
|---------------------------|------------|--------------------|------------|---------------------------|--|--|--|--|--|--|--|
| DATE RECEIVED: 2024-11-14 | | | | DATE REPORTED: 2024-11-26 | | | | | | | |
| | SA | AMPLE DESCRIPTION: | O-2 | | | | | | | | |
| | | SAMPLE TYPE: | Water | | | | | | | | |
| | | DATE SAMPLED: | 2024-11-12 | | | | | | | | |
| Parameter | Unit | G/S RDL | 6321627 | | | | | | | | |
| Vinyl Chloride | μg/L | 0.17 | <0.17 | | | | | | | | |
| Benzene | μg/L | 0.20 | 1.23 | | | | | | | | |
| Dichloromethane | mg/L | 0.030 | < 0.030 | | | | | | | | |
| Toluene | μg/L | 0.20 | <0.20 | | | | | | | | |
| 1,4-Dichlorobenzene | μg/L | 0.10 | <0.10 | | | | | | | | |
| Surrogate | Unit | Acceptable Limits | | | | | | | | | |
| Toluene-d8 | % Recovery | 50-140 | 98 | | | | | | | | |
| 4-Bromofluorobenzene | % Recovery | 50-140 | 61 | | | | | | | | |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

Analysis performed at AGAT Toronto (unless marked by *)

CLIENT NAME: GEI CONSULTANTS

SAMPLING SITE:St. Edmunds

Certified By:





Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

5835 COOPERS AVENUE

MISSISSAUGA, ONTARIO CANADA L4Z 1Y2

http://www.agatlabs.com

TEL (905)712-5100 FAX (905)712-5122

ATTENTION TO: Jessica Weller

SAMPLED BY:

BOD5

DATE RECEIVED: 2024-11-14 DATE REPORTED: 2024-11-26

SAMPLE DESCRIPTION: 0-2
SAMPLE TYPE: Water

SAMPLE TIPE. Water

DATE SAMPLED: 2024-11-12 G / S RDL 6321627

 Parameter
 Unit
 G / S
 RDL
 6321627

 Biochemical Oxygen Demand, Total
 mg/L
 20
 <20</td>

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

6321627 RDL for BOD is raised due to insufficient DO depletion at selected dilution levels.

Analysis performed at AGAT Halifax (unless marked by *)

CLIENT NAME: GEI CONSULTANTS

SAMPLING SITE:St. Edmunds

Certified By:



SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

St. Edmunds Groundwater Package

| DATE RECEIVED: 2024-11-14 | | | | | | | D | ATE REPORT | ED: 2024-11-26 | |
|----------------------------------|----------|---|----------------------------|-------|----------------------------|-------|----------------------------|------------|----------------------------|--|
| | SA | AMPLE DESCRIPTION: SAMPLE TYPE: DATE SAMPLED: | O-1 Water 2024-11-12 | | O-2 Water 2024-11-12 | | O-3 Water 2024-11-12 | | O-4 Water 2024-11-12 | |
| Parameter | Unit | G/S RDL | 6321571 | RDL | 6321580 | RDL | 6321581 | RDL | 6321582 | |
| Electrical Conductivity | uS/cm | 2 | 831 | 2 | 1390 | 2 | 1970 | 2 | 836 | |
| рН | pH Units | NA | 7.58 | NA | 7.12 | NA | 7.53 | NA | 7.83 | |
| Hardness (as CaCO3) (Calculated) | mg/L | 0.5 | 532 | 0.5 | 520 | 0.5 | 957 | 0.5 | 387 | |
| Alkalinity (as CaCO3) | mg/L | 5 | 513 | 5 | 808 | 5 | 506 | 5 | 385 | |
| Chloride | mg/L | 0.12 | 6.94 | 0.12 | 39.0 | 0.24 | 41.3 | 0.12 | 15.4 | |
| Nitrate as N | mg/L | 0.05 | 0.57 | 0.05 | <0.05 | 0.07 | <0.07 | 0.05 | < 0.05 | |
| Nitrite as N | mg/L | 0.05 | < 0.05 | 0.05 | < 0.05 | 0.05 | < 0.05 | 0.05 | <0.05 | |
| Sulphate | mg/L | 0.10 | 8.10 | 0.10 | 2.33 | 0.19 | 571 | 0.10 | 118 | |
| Ammonia as N | mg/L | 0.02 | < 0.02 | 0.06 | 26.2 | 0.02 | 0.08 | 0.02 | <0.02 | |
| Dissolved Organic Carbon | mg/L | 0.5 | 8.3 | 0.5 | 23.2 | 0.5 | 3.5 | 0.5 | 2.4 | |
| Dissolved Calcium | mg/L | 0.05 | 153 | 0.05 | 131 | 0.05 | 259 | 0.05 | 106 | |
| Dissolved Magnesium | mg/L | 0.05 | 36.4 | 0.05 | 46.9 | 0.05 | 75.4 | 0.05 | 29.6 | |
| Dissolved Potassium | mg/L | 0.50 | 2.76 | 0.50 | 26.7 | 0.50 | 5.29 | 0.50 | 1.33 | |
| Dissolved Sodium | mg/L | 0.05 | 5.85 | 0.05 | 57.3 | 0.05 | 19.3 | 0.05 | 10.1 | |
| Dissolved Boron | mg/L | 0.010 | 0.075 | 0.010 | 0.636 | 0.010 | 0.044 | 0.010 | 0.060 | |
| Dissolved Iron | mg/L | 0.020 | < 0.020 | 0.020 | 1.47 | 0.020 | <0.020 | 0.020 | <0.020 | |
| Lab Filtration DOC | | | Υ | | Υ | | Υ | | Υ | |
| Lab Filtration Metals | | | Υ | | Υ | | Υ | | Υ | |

Certified By:



SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

St. Edmunds Groundwater Package

| DATE RECEIVED: 2024-11-14 | | | | | | | | Ē | ATE REPORT | ED: 2024-11-26 | |
|----------------------------------|----------|--|-------|---------------------------------------|-------|---------------------------------------|---------------------------------------|---------------------------------------|------------|--|--|
| Parameter | Unit | SAMPLE DESCRI SAMPLE DATE SAM G/S | TYPE: | O-6 Water 2024-11-12 6321583 | RDL | O-9 Water 2024-11-12 6321584 | W-1 Water 2024-11-12 6321585 | W-2 Water 2024-11-12 6321586 | RDL | W-3/03 Water 2024-11-12 6321587 | |
| Electrical Conductivity | uS/cm | 65° 80° 960° 5 | 2 | 1400 | 2 | 742 | 616 | 790 | 2 | 975 | |
| pH | pH Units | | NA | 7.17 | NA | 7.77 | 7.90 | 7.95 | NA | 7.75 | |
| Hardness (as CaCO3) (Calculated) | mg/L | | 0.5 | 535 | 0.5 | 402 | 292 | 374 | 0.5 | 382 | |
| Alkalinity (as CaCO3) | mg/L | | 5 | 838 | 5 | 433 | 392 | 421 | 5 | 590 | |
| Chloride | mg/L | | 0.12 | 23.8 | 0.10 | 8.16 | 4.07 | 7.52 | 0.12 | 17.6 | |
| Nitrate as N | mg/L | 1 | 0.05 | 0.81 | 0.05 | 0.12 | 0.10 | 0.13 | 0.05 | 0.27 | |
| Nitrite as N | mg/L | | 0.05 | < 0.05 | 0.05 | < 0.05 | < 0.05 | < 0.05 | 0.05 | <0.05 | |
| Sulphate | mg/L | | 0.10 | 10.2 | 0.10 | 8.35 | 24.6 | 48.7 | 0.10 | 4.49 | |
| Ammonia as N | mg/L |) | 0.06 | 24.2 | 0.02 | 0.07 | 0.11 | <0.02 | 0.03 | 9.12 | |
| Dissolved Organic Carbon | mg/L | | 0.5 | 19.5 | 0.5 | 27.2 | 28.5 | 4.6 | 0.5 | 12.7 | |
| Dissolved Calcium | mg/L | į | 0.05 | 150 | 0.05 | 114 | 92.8 | 115 | 0.05 | 109 | |
| Dissolved Magnesium | mg/L | | 0.05 | 38.9 | 0.05 | 28.4 | 14.6 | 21.0 | 0.05 | 26.6 | |
| Dissolved Potassium | mg/L | | 0.50 | 20.6 | 0.50 | 5.90 | 0.76 | 1.29 | 0.50 | 13.2 | |
| Dissolved Sodium | mg/L | | 0.05 | 20.3 | 0.05 | 3.89 | 3.42 | 2.68 | 0.05 | 18.3 | |
| Dissolved Boron | mg/L | (| 0.010 | 0.278 | 0.010 | 0.052 | 0.015 | 0.022 | 0.010 | 0.362 | |
| Dissolved Iron | mg/L | 0 | 0.020 | 0.030 | 0.020 | 0.151 | 0.045 | <0.020 | 0.020 | <0.020 | |
| Lab Filtration DOC | | | | Υ | | Υ | Υ | Υ | | Υ | |
| Lab Filtration Metals | | | | Υ | | Υ | Υ | Υ | | Υ | |

Certified By:



SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

St. Edmunds Groundwater Package

| DATE RECEIVED: 2024-11-14 | | | | | | | D | ATE REPORT | ΓED: 2024-11-26 | |
|----------------------------------|----------|--|---------|-------|---------------------------|-------|---------------------------|------------|---------------------------|--|
| | S | AMPLE DESCRIPTION SAMPLE TYPE DATE SAMPLED | : Water | | B3 Water 2024-11-12 | | B4 Water 2024-11-12 | | B5 Water 2024-11-12 | |
| Parameter | Unit | G/S RDL | 6321588 | RDL | 6321589 | RDL | 6321590 | RDL | 6321591 | |
| Electrical Conductivity | uS/cm | 2 | 653 | 2 | 2460 | 2 | 1450 | 2 | 1870 | |
| рН | pH Units | NA | 7.93 | NA | 7.59 | NA | 7.63 | NA | 7.84 | |
| Hardness (as CaCO3) (Calculated) | mg/L | 0.5 | 288 | 0.5 | 1230 | 0.5 | 532 | 0.5 | 375 | |
| Alkalinity (as CaCO3) | mg/L | 5 | 326 | 5 | 502 | 5 | 631 | 5 | 414 | |
| Chloride | mg/L | 0.10 | 15.0 | 0.49 | 16.0 | 0.12 | 129 | 0.24 | 306 | |
| Nitrate as N | mg/L | 0.05 | < 0.05 | 0.14 | <0.14 | 0.05 | <0.05 | 0.07 | <0.07 | |
| Nitrite as N | mg/L | 0.05 | < 0.05 | 0.11 | <0.11 | 0.05 | < 0.05 | 0.05 | < 0.05 | |
| Sulphate | mg/L | 0.10 | 39.1 | 0.38 | 888 | 0.10 | 58.5 | 0.19 | 71.3 | |
| Ammonia as N | mg/L | 0.02 | 0.29 | 0.02 | 0.16 | 0.02 | 4.16 | 0.02 | <0.02 | |
| Dissolved Organic Carbon | mg/L | 0.5 | 5.7 | 0.5 | 4.2 | 0.5 | 17.2 | 0.5 | 3.4 | |
| Dissolved Calcium | mg/L | 0.05 | 72.0 | 0.05 | 329 | 0.05 | 128 | 0.05 | 106 | |
| Dissolved Magnesium | mg/L | 0.05 | 26.2 | 0.05 | 99.2 | 0.05 | 51.6 | 0.05 | 26.8 | |
| Dissolved Potassium | mg/L | 0.50 | 1.30 | 0.50 | 3.35 | 0.50 | 7.13 | 0.50 | 1.44 | |
| Dissolved Sodium | mg/L | 0.05 | 12.1 | 0.05 | 19.7 | 0.05 | 69.0 | 0.05 | 173 | |
| Dissolved Boron | mg/L | 0.010 | 0.054 | 0.010 | 0.069 | 0.010 | 0.268 | 0.010 | 0.179 | |
| Dissolved Iron | mg/L | 0.020 | <0.020 | 0.020 | 0.654 | 0.020 | <0.020 | 0.020 | <0.020 | |
| Lab Filtration DOC | | | Υ | | Υ | | Υ | | Υ | |
| Lab Filtration Metals | | | Υ | | Υ | | Υ | | Y | |
| | | | | | | | | | | |

Certified By:



SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

St. Edmunds Groundwater Package

| | | | Ot. Lam | unds Crodinawater r dekage |
|----------------------------------|----------|--|-----------|----------------------------|
| DATE RECEIVED: 2024-11-14 | | | | DATE REPORTED: 2024-11-26 |
| | S | AMPLE DESCRIPTION SAMPLE TY DATE SAMPL | PE: Water | |
| Parameter | Unit | G/S RDI | 6321592 | |
| Electrical Conductivity | uS/cm | 2 | 733 | |
| рН | pH Units | NA | 7.94 | |
| Hardness (as CaCO3) (Calculated) | mg/L | 0.5 | 273 | |
| Alkalinity (as CaCO3) | mg/L | 5 | 332 | |
| Chloride | mg/L | 0.10 | 49.8 | |
| Nitrate as N | mg/L | 0.05 | 0.44 | |
| Nitrite as N | mg/L | 0.05 | < 0.05 | |
| Sulphate | mg/L | 0.10 | 16.6 | |
| Ammonia as N | mg/L | 0.02 | < 0.02 | |
| Dissolved Organic Carbon | mg/L | 0.5 | 1.6 | |
| Dissolved Calcium | mg/L | 0.05 | 72.3 | |
| Dissolved Magnesium | mg/L | 0.05 | 22.5 | |
| Dissolved Potassium | mg/L | 0.50 | < 0.50 | |
| Dissolved Sodium | mg/L | 0.05 | 22.8 | |
| Dissolved Boron | mg/L | 0.01 | 0.023 | |
| Dissolved Iron | mg/L | 0.02 | 0 <0.020 | |
| Lab Filtration DOC | | | Υ | |
| Lab Filtration Metals | | | Υ | |
| | | | | |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

6321571-6321592 Metals analysis completed on a filtered sample.

Dilution required, RDL has been increased accordingly.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:



SAMPLING SITE:St. Edmunds

Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

ATTENTION TO: Jessica Weller

SAMPLED BY:

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

St. Edmunds Groundwater Package (Fall)

| DATE RECEIVED: 2024-11-1 | 4 | | | DATE REPORTED: 2024-11-26 |
|--------------------------|----------|--------------------|------------|---------------------------|
| | | AMPLE DESCRIPTION: | O-2 | |
| | - | SAMPLE TYPE: | Water | |
| | | DATE SAMPLED: | 2024-11-12 | |
| Parameter | Unit | G/S RDL | 6321627 | |
| Electrical Conductivity | uS/cm | 2 | 1570 | |
| pH | pH Units | NA | 7.43 | |
| Total Dissolved Solids | mg/L | 10 | 892 | |
| Total Suspended Solids | mg/L | 10 | 126 | |
| Alkalinity (as CaCO3) | mg/L | 5 | 855 | |
| Chloride | mg/L | 0.12 | 61.7 | |
| Nitrate as N | mg/L | 0.05 | <0.05 | |
| Nitrite as N | mg/L | 0.05 | <0.05 | |
| Sulphate | mg/L | 0.10 | 1.62 | |
| Ammonia as N | mg/L | 0.06 | 30.6 | |
| Chemical Oxygen Demand | mg/L | 5 | 46 | |
| PhenoIs | mg/L | 0.001 | 0.001 | |
| otal Kjeldahl Nitrogen | mg/L | 0.10 | 31.8 | |
| otal Phosphorus | mg/L | 0.02 | 0.14 | |
| Dissolved Organic Carbon | mg/L | 0.5 | 18.5 | |
| Dissolved Calcium | mg/L | 0.05 | 148 | |
| Dissolved Magnesium | mg/L | 0.05 | 43.5 | |
| Dissolved Potassium | mg/L | 0.50 | 18.6 | |
| Dissolved Sodium | mg/L | 0.05 | 52.8 | |
| Dissolved Arsenic | mg/L | 0.001 | <0.001 | |
| Dissolved Barium | mg/L | 0.002 | 0.065 | |
| Dissolved Boron | mg/L | 0.010 | 0.417 | |
| Dissolved Cadmium | mg/L | 0.0001 | < 0.0001 | |
| Dissolved Chromium | mg/L | 0.002 | <0.002 | |
| Dissolved Copper | mg/L | 0.001 | 0.002 | |
| Dissolved Iron | mg/L | 0.010 | 0.016 | |
| Dissolved Lead | mg/L | 0.0005 | <0.0005 | |
| Dissolved Manganese | mg/L | 0.002 | 0.365 | |
| Dissolved Zinc | mg/L | 0.005 | < 0.005 | |
| Lab Filtration DOC | | | Υ | |

Certified By:



Certificate of Analysis

AGAT WORK ORDER: 24T220815

PROJECT: M1555

5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GEI CONSULTANTS

SAMPLING SITE:St. Edmunds

Parameter

ATTENTION TO: Jessica Weller

SAMPLED BY:

St. Edmunds Groundwater Package (Fall)

DATE RECEIVED: 2024-11-14 DATE REPORTED: 2024-11-26

> SAMPLE DESCRIPTION: 0-2

> > SAMPLE TYPE: Water

DATE SAMPLED: 2024-11-12 G/S RDL 6321627

Unit Lab Filtration Metals

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

Metals & DOC analysis completed on a filtered sample. 6321627

Dilution required, RDL has been increased accordingly.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:

Yris Verástegui



Quality Assurance

CLIENT NAME: GEI CONSULTANTS

PROJECT: M1555

AGAT WORK ORDER: 24T220815
ATTENTION TO: Jessica Weller

SAMPLING SITE:St. Edmunds SAMPLED BY:

| SAMPLING SITE.St. Edition | 13 | | | | | | | MINIT | LDB | 1. | | | | | |
|-------------------------------|---------|---------|--------|---------|------|-----------------|----------|--------|----------------|----------|-------|----------------|----------|---------|-----------------|
| | | | Trac | e Or | gani | cs Ar | nalysi | is | | | | | | | |
| RPT Date: Nov 26, 2024 | | | | UPLICAT | E | | REFEREN | ICE MA | TERIAL | METHOD | BLANK | SPIKE | MAT | RIX SPI | KE |
| PARAMETER | Batch | Sample | Dup #1 | Dup #2 | RPD | Method Blank | Measured | | ptable nits | Recovery | Lin | ptable nits | Recovery | 1:0 | eptable nits |
| | | ld | | | | | Value | Lower | Upper | | Lower | Upper | | Lower | Upper |
| Volatile Organic Compounds in | Water | | | | | | | | | | | | | | |
| Vinyl Chloride | 6321627 | 6321627 | <0.17 | < 0.17 | NA | < 0.17 | 60% | 50% | 140% | 101% | 50% | 140% | 91% | 50% | 140% |
| Benzene | 6321627 | 6321627 | 1.23 | 1.14 | 7.6% | < 0.20 | 97% | 50% | 140% | 119% | 60% | 130% | 93% | 50% | 140% |
| Dichloromethane | 6321627 | 6321627 | <0.030 | < 0.030 | NA | < 0.030 | 117% | 50% | 140% | 106% | 60% | 130% | 85% | 50% | 140% |
| Toluene | 6321627 | 6321627 | <0.20 | <0.20 | NA | < 0.20 | 96% | 50% | 140% | 113% | 60% | 130% | 85% | 50% | 140% |
| 1,4-Dichlorobenzene | 6321627 | 6321627 | <0.10 | < 0.10 | NA | < 0.10 | 95% | 50% | 140% | 101% | 60% | 130% | 89% | 50% | 140% |

Comments: When the average of the sample and duplicate results is less than 5x the RDL, the Relative Percent Difference (RPD) will be indicated as Not Applicable (NA).

Certified By:



Quality Assurance

CLIENT NAME: GEI CONSULTANTS

PROJECT: M1555

SAMPLING SITE:St. Edmunds

AGAT WORK ORDER: 24T220815
ATTENTION TO: Jessica Weller

SAMPLED BY:

| | | | Wate | er Ar | nalys | is | | | | | | | | |
|----------------------------|-----------------|----------|-----------|-------|-----------------|----------|--------|-----------------|------------|-------|-----------------|------------|--------|----------------|
| RPT Date: Nov 26, 2024 | | 1 | DUPLICATI | | | REFEREN | NCE MA | TERIAL | METHOD | BLAN | (SPIKE | MAT | RIX SP | KE |
| PARAMETER | Batch Samp | e Dup #1 | Dup #2 | RPD | Method Blank | Measured | | eptable mits | Recovery | Lie | eptable mits | Recovery | | ptable nits |
| TAIVAMETER | Daten Id | Dup " | Bup #2 | 111 5 | | Value | Lower | Upper | ricoore, j | Lower | Upper | ricoording | Lower | Upper |
| St. Edmunds Groundwater Pa | ckage | • | | | | | | | | | | | | |
| Electrical Conductivity | 6321459 | 23 | 22 | 4.4% | < 2 | 110% | 80% | 120% | | | | | | |
| рН | 6321459 | 5.95 | 5.52 | 7.5% | NA | 100% | 90% | 110% | | | | | | |
| Alkalinity (as CaCO3) | 6321459 | 12 | 7 | NA | < 5 | 114% | 80% | 120% | | | | | | |
| Chloride | 6321571 632157 | 6.94 | 6.92 | 0.3% | < 0.10 | 98% | 70% | 130% | 101% | 80% | 120% | 100% | 70% | 130% |
| Nitrate as N | 6321571 632157 | 0.57 | 0.58 | 1.7% | < 0.05 | 94% | 70% | 130% | 98% | 80% | 120% | 96% | 70% | 130% |
| Nitrite as N | 6321571 632157 | <0.05 | < 0.05 | NA | < 0.05 | 96% | 70% | 130% | 102% | 80% | 120% | 94% | 70% | 130% |
| Sulphate | 6321571 632157 | 8.10 | 8.39 | 3.5% | < 0.10 | 96% | 70% | 130% | 98% | 80% | 120% | 96% | 70% | 130% |
| Ammonia as N | 6346351 | < 0.02 | < 0.02 | NA | < 0.02 | 104% | 70% | 130% | 113% | 80% | 120% | 107% | 70% | 130% |
| Dissolved Organic Carbon | 6323085 | 13.0 | 13.9 | 6.7% | < 0.5 | 101% | 90% | 110% | 94% | 90% | 110% | NA | 80% | 120% |
| Dissolved Calcium | 6322924 | 82.2 | 79.4 | 3.5% | < 0.05 | 98% | 70% | 130% | 82% | 80% | 120% | 93% | 70% | 130% |
| Dissolved Magnesium | 6322924 | 39.1 | 37.4 | 4.4% | < 0.05 | 98% | 70% | 130% | 90% | 80% | 120% | 114% | 70% | 130% |
| Dissolved Potassium | 6322924 | 1.70 | 1.73 | NA | < 0.50 | 115% | 70% | 130% | 81% | 80% | 120% | 80% | 70% | 130% |
| Dissolved Sodium | 6322924 | 11.5 | 10.6 | 8.1% | < 0.05 | 99% | 70% | 130% | 81% | 80% | 120% | 101% | 70% | 130% |
| Dissolved Boron | 6322924 | 0.279 | 0.270 | 3.3% | < 0.010 | 98% | 70% | 130% | 103% | 80% | 120% | 104% | 70% | 130% |
| Dissolved Iron | 6322924 | <0.020 | <0.020 | NA | < 0.010 | 102% | 70% | 130% | 100% | 80% | 120% | 91% | 70% | 130% |
| St. Edmunds Groundwater Pa | ckage (Fall) | | | | | | | | | | | | | |
| Electrical Conductivity | 6321581 632158 | 1970 | 1970 | 0.0% | < 2 | 105% | 80% | 120% | | | | | | |
| pH | 6321581 632158 | 7.53 | 7.58 | 0.7% | NA | 100% | 90% | 110% | | | | | | |
| Total Dissolved Solids | 6321423 | 112 | 118 | 5.2% | < 10 | 98% | 80% | 120% | | | | | | |
| Total Suspended Solids | 6321627 6321627 | 126 | 134 | 6.2% | < 10 | 104% | 80% | 120% | | | | | | |
| Alkalinity (as CaCO3) | 6321581 632158 | 506 | 519 | 2.5% | < 5 | 108% | 80% | 120% | | | | | | |
| Chloride | 6321571 632157 | 6.94 | 6.92 | 0.3% | < 0.10 | 98% | 70% | 130% | 101% | 80% | 120% | 100% | 70% | 130% |
| Nitrate as N | 6321571 632157 | 0.57 | 0.58 | 1.7% | < 0.05 | 94% | 70% | 130% | 98% | 80% | 120% | 96% | 70% | 130% |
| Nitrite as N | 6321571 632157 | < 0.05 | < 0.05 | NA | < 0.05 | 96% | 70% | 130% | 102% | 80% | 120% | 94% | 70% | 130% |
| Sulphate | 6321571 632157 | 8.10 | 8.39 | 3.5% | < 0.10 | 96% | 70% | 130% | 98% | 80% | 120% | 96% | 70% | 130% |
| Ammonia as N | 6321588 6321588 | 0.29 | 0.28 | 3.5% | < 0.02 | 104% | 70% | 130% | 113% | 80% | 120% | 109% | 70% | 130% |
| Chemical Oxygen Demand | 6320083 | <5 | <5 | NA | < 5 | 99% | 80% | 120% | 98% | 90% | 110% | 97% | 70% | 130% |
| Phenols | 6321392 | < 0.001 | < 0.001 | NA | < 0.001 | 102% | 90% | 110% | 101% | 90% | 110% | 93% | 80% | 120% |
| Total Kjeldahl Nitrogen | 6320061 | < 0.10 | < 0.10 | NA | < 0.10 | 92% | 70% | 130% | 94% | 80% | 120% | 84% | 70% | 130% |
| Total Phosphorus | 6322924 | 0.06 | 0.06 | NA | < 0.02 | 101% | 70% | 130% | 104% | 80% | 120% | 113% | 70% | 130% |
| Dissolved Organic Carbon | 6321583 6321583 | 19.5 | 20.3 | 4.0% | < 0.5 | 103% | 90% | 110% | 105% | 90% | 110% | NA | 80% | 120% |
| Dissolved Calcium | 6322924 | 82.2 | 79.4 | 3.5% | < 0.05 | 98% | 70% | 130% | 82% | 80% | 120% | 93% | 70% | 130% |
| Dissolved Magnesium | 6322924 | 39.1 | 37.4 | 4.4% | < 0.05 | 98% | 70% | 130% | 90% | 80% | 120% | 114% | 70% | 130% |
| Dissolved Potassium | 6322924 | 1.70 | 1.73 | NA | < 0.50 | 115% | 70% | | 81% | 80% | 120% | 80% | 70% | 130% |
| Dissolved Sodium | 6322924 | 11.5 | 10.6 | 8.1% | < 0.05 | 99% | 70% | | 81% | 80% | 120% | 101% | | 130% |
| Dissolved Arsenic | 6322924 | 0.002 | <0.001 | NA | < 0.001 | 93% | | 130% | 110% | | 120% | 108% | | 130% |
| Dissolved Barium | 6322924 | 0.024 | 0.022 | 8.7% | < 0.002 | 103% | 70% | 130% | 106% | 80% | 120% | 102% | 70% | 130% |
| Dissolved Boron | 6322924 | 0.279 | 0.270 | 3.3% | < 0.010 | | 70% | | 103% | 80% | 120% | 104% | | 130% |
| Dissolved Cadmium | 6322924 | < 0.0001 | <0.0001 | NA | < 0.0001 | | | 130% | 99% | | 120% | 103% | | 130% |

AGAT QUALITY ASSURANCE REPORT (V1)

Page 11 of 16

AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. RPDs calculated using raw data. The RPD may not be reflective of duplicate values shown, due to rounding of final results.



Quality Assurance

CLIENT NAME: GEI CONSULTANTS

PROJECT: M1555

Dissolved Manganese

Dissolved Zinc

AGAT WORK ORDER: 24T220815
ATTENTION TO: Jessica Weller

SAMPLING SITE:St. Edmunds SAMPLED BY:

| | | V | Vate | ^r Ana | lysis | (Cor | ntinu | ed) | | | | | | | |
|------------------------|---------|--------|---------|------------------|-------|-----------------|----------|--------|----------------|----------|-------|----------------|----------|---------|----------------|
| RPT Date: Nov 26, 2024 | | | | UPLICAT | E | | REFEREN | NCE MA | TERIAL | METHOD | BLANK | SPIKE | MAT | RIX SPI | KE |
| PARAMETER | Batch | Sample | Dup #1 | Dup #2 | RPD | Method Blank | Measured | | ptable nits | Recovery | Lin | ptable nits | Recovery | Lin | ptable nits |
| | | ld | | | | | Value | Lower | Upper | • | Lower | Upper | | Lower | Upper |
| Dissolved Chromium | 6322924 | | <0.002 | <0.002 | NA | < 0.002 | 97% | 70% | 130% | 99% | 80% | 120% | 94% | 70% | 130% |
| Dissolved Copper | 6322924 | | 0.001 | 0.002 | NA | < 0.001 | 99% | 70% | 130% | 100% | 80% | 120% | 94% | 70% | 130% |
| Dissolved Iron | 6322924 | | <0.020 | <0.020 | NA | < 0.010 | 102% | 70% | 130% | 100% | 80% | 120% | 91% | 70% | 130% |
| Dissolved Lead | 6322924 | | <0.0005 | < 0.0005 | NA | < 0.0005 | 95% | 70% | 130% | 101% | 80% | 120% | 93% | 70% | 130% |

< 0.002

< 0.005

95%

99%

70% 130%

70% 130%

107%

98%

80% 120%

80% 120%

100%

99%

70% 130%

70% 130%

Comments: NA signifies Not Applicable.

Duplicate NA: results are under 5X the RDL and will not be calculated.

6322924

6322924

Matrix spike NA: Spike level < native concentration. Matrix spike acceptance limits do not apply and are not calculated.

BOD5

Biochemical Oxygen Demand, Total 6323205 6323205 1820 1890 3.8% < 2 91% 70% 130%

0.003

< 0.005

0.004

< 0.005

Comments: If RPD value is NA, the results of the duplicates are less than 5x the RDL and the RPD will not be calculated.

Certified By:

Inis Verástegui

Method Summary

CLIENT NAME: GEI CONSULTANTS

PROJECT: M1555

AGAT WORK ORDER: 24T220815 **ATTENTION TO: Jessica Weller**

| SAMPLING SITE:St. Edmunds | | SAMPLED BY: | |
|---------------------------|-------------|-------------------------------------|----------------------|
| PARAMETER | AGAT S.O.P | LITERATURE REFERENCE | ANALYTICAL TECHNIQUE |
| Trace Organics Analysis | | | |
| Vinyl Chloride | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |
| Benzene | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |
| Dichloromethane | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |
| Toluene | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |
| 1,4-Dichlorobenzene | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |
| Toluene-d8 | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |
| 4-Bromofluorobenzene | VOL-91-5001 | modified from EPA 5030B & EPA 8260D | (P&T)GC/MS |

Method Summary

CLIENT NAME: GEI CONSULTANTS

PROJECT: M1555

AGAT WORK ORDER: 24T220815
ATTENTION TO: Jessica Weller
SAMPLED BY:

SAMPLING SITE:St. Edmunds

| PARAMETER | AGAT S.O.P | LITERATURE REFERENCE | ANALYTICAL TECHNIQUE |
|----------------------------------|---------------|---|--------------------------|
| Water Analysis | | | • |
| Biochemical Oxygen Demand, Total | INOR-121-6023 | SM 5210 B | INCUBATOR |
| Electrical Conductivity | INOR-93-6000 | SM 2510 B | PC TITRATE |
| pH | INOR-93-6000 | modified from SM 4500-H+ B | PC TITRATE |
| Hardness (as CaCO3) (Calculated) | MET-93-6105 | modified from EPA SW-846 6010C & 200.7 & SM 2340 B | CALCULATION |
| Alkalinity (as CaCO3) | INOR-93-6000 | Modified from SM 2320 B | PC TITRATE |
| Chloride | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Nitrate as N | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Nitrite as N | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Sulphate | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Ammonia as N | INOR-93-6059 | modified from SM 4500-NH3 H | LACHAT FIA |
| Dissolved Organic Carbon | INOR-93-6049 | modified from SM 5310 B | SHIMADZU CARBON ANALYZER |
| Dissolved Calcium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP/MS |
| Dissolved Magnesium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Dissolved Potassium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP/MS |
| Dissolved Sodium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP/MS |
| Dissolved Boron | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Iron | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Lab Filtration DOC | SR-78-9001 | | FILTRATION |
| Lab Filtration Metals | SR-78-9001 | modified from EDA 1694 ON MOECC | FILTRATION |
| Total Dissolved Solids | INOR-93-6028 | modified from EPA 1684,ON MOECC E3139,SM 2540B,C,D | BALANCE |
| Total Suspended Solids | INOR-93-6028 | modified from EPA 1684,ON MOECC E3139,SM 2540B,C,D | BALANCE |
| Chemical Oxygen Demand | INOR-93-6042 | modified from SM 5220 A and SM 5220 D | SPECTROPHOTOMETER |
| PhenoIs | INOR-93-6072 | mod from SM 510C, EPA 420.2, ISO 3696, ASTM D1193 | SEGMENTED FLOW ANALYSIS |
| Total Kjeldahl Nitrogen | INOR-93-6048 | modified from EPA 351.2 and SM 4500-NORG D | LACHAT FIA |
| Total Phosphorus | INOR-93-6057 | modified from LACHAT 10-115-01-3A | LACHAT FIA |
| Dissolved Arsenic | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Barium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Cadmium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Chromium | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Copper | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Lead | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Manganese | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |
| Dissolved Zinc | MET-93-6103 | modified from EPA 200.8 and EPA 3005A | ICP-MS |



CLIENT NAME: GEI CONSULTANTS

1260 Second Avenue East, Unit 1 OWEN SOUND, ON N4K2J3

(519) 376-1805

ATTENTION TO: Jessica Weller

PROJECT: M1555 - St Edmunds

AGAT WORK ORDER: 24T220818

WATER ANALYSIS REVIEWED BY: Yris Verastegui, Inorganic Team Lead

DATE REPORTED: Nov 25, 2024

PAGES (INCLUDING COVER): 6 VERSION*: 1

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

| | *Notes |
|---|--------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| ļ | |

Disclaimer:

- All work conducted herein has been done using accepted standard protocols, and generally accepted practices and methods. AGAT test methods may
 incorporate modifications from the specified reference methods to improve performance.
- All samples will be disposed of within 30 days after receipt unless a Long Term Storage Agreement is signed and returned. Some specialty analysis may
 be exempt, please contact your Client Project Manager for details.
- AGAT's liability in connection with any delay, performance or non-performance of these services is only to the Client and does not extend to any other
 third party. Unless expressly agreed otherwise in writing, AGAT's liability is limited to the actual cost of the specific analysis or analyses included in the
 services.
- This Certificate shall not be reproduced except in full, without the written approval of the laboratory.
- The test results reported herewith relate only to the samples as received by the laboratory.
- Application of guidelines is provided "as is" without warranty of any kind, either expressed or implied, including, but not limited to, warranties of
 merchantability, fitness for a particular purpose, or non-infringement. AGAT assumes no responsibility for any errors or omissions in the guidelines
 contained in this document.
- All reportable information is available on request from AGAT Laboratories, in accordance with ISO/IEC 17025:2017, ISO/IEC 17025:2005 (Quebec), DR-12-PALA and/or NELAP Standards.
- This document is signed by an authorized signatory who meets the requirements of the MELCCFP, CALA, CCN and NELAP.
- For environmental samples in the Province of Quebec: The analysis is performed on and results apply to samples as received. A temperature above 6°C upon receipt, as indicated in the Sample Reception Notification (SRN), could indicate the integrity of the samples has been compromised if the delay between sampling and submission to the laboratory could not be minimized.

AGAT Laboratories (V1)

Page 1 of 6

Member of: Association of Professional Engineers and Geoscientists of Alberta (APEGA)

Western Enviro-Agricultural Laboratory Association (WEALA) Environmental Services Association of Alberta (ESAA) AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation. Measurement Uncertainty is not taken into consideration when stating conformity with a specified requirement.



Certificate of Analysis

AGAT WORK ORDER: 24T220818 PROJECT: M1555 - St Edmunds 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GEI CONSULTANTS

SAMPLING SITE:

ATTENTION TO: Jessica Weller

SAMPLED BY:

| | | | | | СВОГ |)5 | | | |
|--|------|------------|-----------|------------|------------|------------|------------|------------|---------------------------|
| DATE RECEIVED: 2024-11-14 | | | | | | | | ľ | DATE REPORTED: 2024-11-25 |
| | | SAMPLE DES | CRIPTION: | S-1 | S-6 | S-6A | S-8 | S-9 | |
| | | SAM | PLE TYPE: | Water | Water | Water | Water | Water | |
| | | DATE | SAMPLED: | 2024-11-12 | 2024-11-12 | 2024-11-12 | 2024-11-12 | 2024-11-12 | |
| Parameter | Unit | G/S | RDL | 6321392 | 6321394 | 6321395 | 6321396 | 6321397 | |
| Biochemical Oxygen Demand, Carbonaceous | mg/L | | 20 | <20 | <20 | <20 | <20 | <20 | |
| | | | | | | | | | |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

Analysis performed at AGAT Halifax (unless marked by *)

Certified By:





Certificate of Analysis

AGAT WORK ORDER: 24T220818 PROJECT: M1555 - St Edmunds 5835 COOPERS AVENUE MISSISSAUGA, ONTARIO CANADA L4Z 1Y2 TEL (905)712-5100 FAX (905)712-5122 http://www.agatlabs.com

CLIENT NAME: GEI CONSULTANTS

SAMPLING SITE:

ATTENTION TO: Jessica Weller SAMPLED BY:

St. Edmunds Surface Water Package

| DATE RECEIVED: 2024-11-14 | | | | | | | | ĺ | DATE REPORTED: | 2024-11-25 |
|----------------------------------|----------|--------|---------------------|----------------------------|----------------------------|-----------------------------|-------|----------------------------|----------------------------|------------|
| | | DATE S | LE TYPE: AMPLED: | S-1 Water 2024-11-12 | S-6 Water 2024-11-12 | S-6A Water 2024-11-12 | | S-8 Water 2024-11-12 | S-9 Water 2024-11-12 | |
| Parameter | Unit | G/S | RDL | 6321392 | 6321394 | 6321395 | RDL | 6321396 | 6321397 | |
| Electrical Conductivity | uS/cm | | 2 | 804 | 1000 | 977 | 2 | 492 | 471 | |
| pH | pH Units | | NA | 7.73 | 7.81 | 7.85 | NA | 7.97 | 7.91 | |
| Hardness (as CaCO3) (Calculated) | mg/L | | 0.5 | 410 | 414 | 409 | 0.5 | 277 | 269 | |
| Alkalinity (as CaCO3) | mg/L | | 5 | 345 | 431 | 438 | 5 | 297 | 270 | |
| Chloride | mg/L | | 0.12 | 34.0 | 81.4 | 80.2 | 0.10 | 6.88 | 5.68 | |
| Nitrate as N | mg/L | | 0.05 | <0.05 | 0.65 | 0.51 | 0.05 | <0.05 | <0.05 | |
| Nitrite as N | mg/L | | 0.05 | <0.05 | <0.05 | <0.05 | 0.05 | <0.05 | <0.05 | |
| Sulphate | mg/L | | 0.10 | 81.3 | 27.7 | 29.6 | 0.10 | 12.4 | 10.8 | |
| Total Phosphorus | mg/L | | 0.02 | < 0.02 | < 0.02 | 0.04 | 0.02 | < 0.02 | < 0.02 | |
| Ammonia as N | mg/L | | 0.02 | < 0.02 | 0.18 | <0.02 | 0.02 | < 0.02 | <0.02 | |
| Total Kjeldahl Nitrogen | mg/L | | 0.10 | 0.24 | 0.40 | 0.46 | 0.10 | < 0.10 | 0.18 | |
| Dissolved Organic Carbon | mg/L | | 0.5 | 13.1 | 12.0 | 11.3 | 0.5 | 16.7 | 17.4 | |
| PhenoIs | mg/L | | 0.001 | < 0.001 | < 0.001 | <0.001 | 0.001 | < 0.001 | <0.001 | |
| Total Calcium | mg/L | | 0.20 | 133 | 112 | 107 | 0.20 | 77.9 | 74.0 | |
| Total Magnesium | mg/L | | 0.10 | 19.0 | 32.6 | 34.4 | 0.10 | 20.1 | 20.5 | |
| Total Potassium | mg/L | | 0.50 | 1.76 | 13.2 | 13.2 | 0.50 | 2.26 | 2.07 | |
| Total Sodium | mg/L | | 0.10 | 25.4 | 66.2 | 63.1 | 0.10 | 5.49 | 4.94 | |
| Total Boron | mg/L | | 0.010 | <0.010 | 0.368 | 0.360 | 0.010 | 0.021 | 0.017 | |
| Total Iron | mg/L | | 0.050 | 0.223 | 2.29 | 1.15 | 0.050 | 0.079 | 0.083 | |
| Total Zinc | mg/L | | 0.020 | <0.020 | <0.020 | <0.020 | 0.020 | <0.020 | <0.020 | |
| Lab Filtration DOC | | | | Y | Y | Y | | Y | Υ | |

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard 6321392-6321397 Dilution required, RDL has been increased accordingly.

Analysis performed at AGAT Toronto (unless marked by *)

Certified By:



Quality Assurance

CLIENT NAME: GEI CONSULTANTS PROJECT: M1555 - St Edmunds

AGAT WORK ORDER: 24T220818 ATTENTION TO: Jessica Weller

| SAMPLING SITE: | | | | | | , | SAMP | LED B | Y: | | | | | |
|------------------------------|----------------|------------|----------|-------|-----------------|----------|----------------------|--------|----------|-------------------------|-------|------|--------|-----------------|
| | | | Wate | er Ar | nalys | is | | | | | | | | |
| RPT Date: Nov 25, 2024 | | | DUPLICAT | E | | REFERE | NCE MA | TERIAL | METHOD | BLANK | SPIKE | MAT | RIX SP | KE |
| PARAMETER | Batch Sam | ole Dup #1 | Dup #2 | RPD | Method Blank | Measured | Acceptable Limits | | Recovery | Acceptab Very Limits | | | | eptable mits |
| | Id | | | | | Value | Lower | Upper | | Lower | Upper | | Lower | Upper |
| St. Edmunds Surface Water Pa | ackage | | | | | | | | | | | | | |
| Electrical Conductivity | 6319927 | 1070 | 1070 | 0.0% | < 2 | 106% | 80% | 120% | | | | | | |
| pH | 6321167 | 7.91 | 7.98 | 0.9% | NA | 100% | 90% | 110% | | | | | | |
| Alkalinity (as CaCO3) | 6319927 | 455 | 486 | 6.6% | < 5 | 110% | 80% | 120% | | | | | | |
| Chloride | 6321392 632139 | 2 34.0 | 34.1 | 0.3% | < 0.10 | 97% | 70% | 130% | 100% | 80% | 120% | 101% | 70% | 130% |
| Nitrate as N | 6321392 632139 | 2 <0.05 | <0.05 | NA | < 0.05 | 94% | 70% | 130% | 99% | 80% | 120% | 95% | 70% | 130% |
| Nitrite as N | 6321392 632139 | 2 <0.05 | <0.05 | NA | < 0.05 | 98% | 70% | 130% | 92% | 80% | 120% | 96% | 70% | 130% |
| Sulphate | 6321392 632139 | 2 81.3 | 81.7 | 0.5% | < 0.10 | 95% | 70% | 130% | 98% | 80% | 120% | 97% | 70% | 130% |
| Total Phosphorus | 6324192 | 0.08 | 0.07 | NA | < 0.02 | 99% | 70% | 130% | 91% | 80% | 120% | 96% | 70% | 130% |
| Ammonia as N | 6340022 | < 0.02 | < 0.02 | NA | < 0.02 | 96% | 70% | 130% | 112% | 80% | 120% | 105% | 70% | 130% |
| Total Kjeldahl Nitrogen | 6320061 | <0.10 | <0.10 | NA | < 0.10 | 92% | 70% | 130% | 94% | 80% | 120% | 84% | 70% | 130% |
| Dissolved Organic Carbon | 6321392 632139 | 2 13.1 | 12.7 | 3.1% | < 0.5 | 93% | 90% | 110% | 97% | 90% | 110% | NA | 80% | 120% |
| PhenoIs | 6321392 632139 | 2 <0.001 | <0.001 | NA | < 0.001 | 102% | 90% | 110% | 101% | 90% | 110% | 93% | 80% | 120% |
| Total Calcium | 6320264 | 62.6 | 64.7 | 3.3% | < 0.20 | 106% | 70% | 130% | 101% | 80% | 120% | 102% | 70% | 130% |
| Total Magnesium | 6320264 | 47.7 | 48.1 | 0.8% | < 0.10 | 108% | 70% | 130% | 111% | 80% | 120% | 109% | 70% | 130% |
| Total Potassium | 6320264 | 1.60 | 1.69 | NA | < 0.50 | 100% | 70% | 130% | 98% | 80% | 120% | 98% | 70% | 130% |
| Total Sodium | 6320264 | 30.7 | 31.1 | 1.3% | < 0.10 | 110% | 70% | 130% | 113% | 80% | 120% | 110% | 70% | 130% |
| Total Boron | 6320264 | 0.092 | 0.094 | 2.2% | < 0.010 | 104% | 70% | 130% | 96% | 80% | 120% | 96% | 70% | 130% |
| Total Iron | 6320264 | 1.23 | 1.22 | 0.8% | < 0.050 | 107% | 70% | 130% | 114% | 80% | 120% | 106% | 70% | 130% |
| Total Zinc | 6320264 | < 0.020 | < 0.020 | NA | < 0.020 | 104% | 70% | 130% | 107% | 80% | 120% | 106% | 70% | 130% |

Comments: NA signifies Not Applicable.

Duplicate NA: results are under 5X the RDL and will not be calculated.

Matrix spike NA: Spike level < native concentration. Matrix spike acceptance limits do not apply and are not calculated.

CBOD5

Biochemical Oxygen Demand, 6324828 80 12.9% < 2 84% 70% 130% Carbonaceous

Certified By:



Method Summary

CLIENT NAME: GEI CONSULTANTS PROJECT: M1555 - St Edmunds

SAMPLING SITE:

AGAT WORK ORDER: 24T220818
ATTENTION TO: Jessica Weller
SAMPLED BY:

| 57 tilli 21115 51121 | | 9/ IIII | |
|--|---------------|--|--------------------------|
| PARAMETER | AGAT S.O.P | LITERATURE REFERENCE | ANALYTICAL TECHNIQUE |
| Water Analysis | | - | |
| Biochemical Oxygen Demand, Carbonaceous | INOR-121-6023 | SM 5210 B | INCUBATOR |
| Electrical Conductivity | INOR-93-6000 | SM 2510 B | PC TITRATE |
| рН | INOR-93-6000 | modified from SM 4500-H+ B | PC TITRATE |
| Hardness (as CaCO3) (Calculated) | MET-93-6105 | modified from EPA SW-846 6010C & 200.7 & SM 2340 B | CALCULATION |
| Alkalinity (as CaCO3) | INOR-93-6000 | Modified from SM 2320 B | PC TITRATE |
| Chloride | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Nitrate as N | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Nitrite as N | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Sulphate | INOR-93-6004 | modified from SM 4110 B | ION CHROMATOGRAPH |
| Total Phosphorus | INOR-93-6022 | modified from SM 4500-P B and SM 4500-P E | SPECTROPHOTOMETER |
| Ammonia as N | INOR-93-6059 | modified from SM 4500-NH3 H | LACHAT FIA |
| Total Kjeldahl Nitrogen | INOR-93-6048 | modified from EPA 351.2 and SM 4500-NORG D | LACHAT FIA |
| Dissolved Organic Carbon | INOR-93-6049 | modified from SM 5310 B | SHIMADZU CARBON ANALYZER |
| Phenols | INOR-93-6072 | mod from SM 510C, EPA 420.2, ISO 3696, ASTM D1193 | SEGMENTED FLOW ANALYSIS |
| Total Calcium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Magnesium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Potassium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Sodium | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP/MS |
| Total Boron | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP-MS |
| Total Iron | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP-MS |
| Total Zinc | MET-93-6103 | modified from EPA 200.8, 3005A, 3010A & 6020B | ICP-MS |
| Lab Filtration DOC | SR-78-9001 | | FILTRATION |

ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix G Historical Groundwater Quality Results (Tables and Graphs)

| | | | | | INCOMPANION IN COM | RICAL | 1 CONT. DEC. CO. | COMPANY DESCRIPTION NO. | IERW | COURSE SHE SHOULD THE | 14140132 (11201300 0000) | 0-1 | | | | | |
|-------------------------|--------------|-----------|------------|--------|--------------------|---------|----------------------|-------------------------|------|-----------------------|--------------------------|--------|------|---------|---------|--|-------|
| | Conductivity | pН | Hardness | | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| ODWS- | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | NV | NV |
| | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 592 | | 323 | | 7.0 | | | | | | | 4.1* | 2.4 | <0.001 | | | |
| Jan-89 | 578 | | 309 | , | 4.9 | | | | | | | 2.7* | 1.6 | <0.001 | | | |
| Jul-90 | 437 | | 218 | | 1.2 | | | | | | | 0.03 | 1.2 | <0.001 | | | |
| Jan-94 | 635 | | 299 | | 5.2 | | | | | | | 0.02 | 2.3 | 0.0081 | | | |
| Nov-94 | 607 | | 339 | | 0.7 | | | | | | | 0.02 | 1.6 | 0.0012 | | | |
| Oct-95 | 1008* | | 519 | ĺ, | 76.3* | | | | | | | 0.01 | 3.7 | 0.0049 | | | |
| Oct-95 Dup | 1008* | | 519 | | 76.5* | | | | | | | 0.01 | 3.7 | 0.0016 | | | |
| Dec-96 | 463 | | 240 | | 5.7 | | | | | | | < 0.01 | 2.0 | 0.0030 | | | |
| Oct-97 | 538 | | 289 | | 10.4 | | | | | | | < 0.01 | <1 | < 0.001 | | | |
| Oct-98 | 545 | | 298 | | 6.3 | | | | | | | 0.16 | 17 | 0.039 | | | |
| Nov-99 | 523 | | 287 | | 3.7 | | | | | | | < 0.01 | <1 | < 0.001 | | | |
| Oct-00 | 481 | | 267 | | 3.3 | | | | | | | < 0.01 | 10 | < 0.001 | | | |
| Nov-01 | 520 | | 243 | | 21.1 | | | | | | | <0.01 | 4.0 | <0.001 | | | |
| Nov-01 Dup | 524 | | 245 | | 21.0 | | | | | | | <0.01 | 5.0 | <0.001 | | | |
| Dec-02 | 600 | | 380 | | 4.9 | | | | | | | <0.02 | 4.7 | <0.001 | | | |
| Dec-02 Dec-02 Dup | 682 | | 381 | t | 4.8 | | | | | | | <0.02 | 4.3 | <0.001 | | | |
| Oct-03 | 547 | | 327 | | 8.0 | | | | | | | <0.005 | 13 | <0.001 | | | |
| Nov-04 | 755 | | 494 | | 6.9 | | | | | | | <0.005 | 5.7 | <0.001 | | | |
| Nov-05 | 667 | | 367 | | 10.2 | | | | | | | <0.005 | 8.3 | <0.001 | | | |
| Apr-06 | 429 | 8.05 | 225 | 215 | 1.4 | 0.90 | <0.05 | 7.82 | 4.01 | | <0.05 | 2.37* | 2.0 | ~0.001 | | | |
| Oct-06 | 402 | 8.06 | 215 | 199 | 8.96 | 0.19 | <0.05 | 15.9 | 3.66 | 1.07 | <0.05 | 0.135 | 1.9 | t | | | |
| Apr-07 | 373 | 8.41 | 207 | 186 | 1.19 | 0.19 | <0.05 | 6.34 | 2.57 | 0.37 | <0.05 | 0.133 | 1.1 | | | | |
| Nov-07 | 513 | 8.33 | 268 | 253 | 9.11 | 0.71 | <0.05 | 13.5 | 3.56 | 1.18 | <0.05 | <0.005 | 1.7 | | | | |
| Apr-08 | 357 | 7.91 | 191 | 188 | 2.81 | 0.71 | <0.05 | 5.61 | 2.62 | 0.60 | <0.05 | <0.003 | 1.0 | | | | |
| Oct-08 | 1020 | 7.85 | 602 | 504 | 4.48 | 6.96 | <0.05 | 25.6 | 3.92 | 2.06 | <0.05 | <0.010 | 9.9 | | | | |
| Apr-09 | 335 | 8.15 | 193 | 173 | 1.81 | 0.20 | <0.05 | 5.13 | 2.81 | 0.50 | <0.03 | <0.010 | 1.2 | - | | | |
| | 616 | 7.89 | 381 | 340 | 2.63 | 1.15 | <0.05 | 12.7 | 3.09 | | <0.02 | <0.010 | | | | | |
| Nov-09 | 495 | 8.21 | 281 | 282 | 1.78 | 0.25 | <0.05 | 5.36 | 2.60 | 1.35 0.88 | <0.05 | <0.01 | 5.1 | | | - | |
| Apr-10 | | 8.06 | | 406 | 3.75 | 1.80 | <0.05 | 24.8 | 3.07 | 1.41 | <0.02 | <0.01 | 1.3 | | | - | |
| Nov-10 | 682 | | 438 212 | 200 | | | | | | | | | 5.4 | | | - | |
| Apr-11 | 380 | 8.01 | | | 1.09 | 0.12 | <0.05 | 3.98 | 1.37 | 0.67 | <0.02 | <0.01 | 1.2 | | | | |
| Nov-11 | 415 | 8.12 | 267 | 269 | 3.90 | 0.96 | <0.05 | 6.45 | 2.28 | 0.82 | <0.02 | <0.01 | 2.4 | | | | |
| Apr-12 | 442 | 7.77 | 245 | 254 | 1.41 | 0.05 | < 0.05 | 3.72 | 1.58 | 0.53 | <0.02 | <0.01 | 1.2 | | | | |
| Nov-12 | 716 | 8.02 | 432 | 385 | 6.90 | 4.61 | <0.05 | 35.8 | 2.80 | 1.12 | <0.02 | <0.01 | 5.2 | | | | |
| Apr-13 | 417 | 8.08 | 218 | 219 | 0.95 | 0.07 | <0.05 | 3.16 | 1.66 | 0.70 | 0.03 | <0.01 | 1.1 | | | | |
| Nov-13 | 673 | 7.93 | 332 | 342 | 2.99 | 2.16 | <0.25 | 9.56 | 2.47 | 1.20 | <0.02 | <0.01 | 5.2 | | | | |
| May-14 | 416 | 7.90 | 218 | 224 | 1.00 | 0.26 | <0.05 | 2.84 | 1.59 | 0.57 | 0.15 | 0.02 | 1.3 | | | | |
| Oct-14 | 699 | 7.87 | 403 | 377 | 6.75 | 2.02 | <0.25 | 7.17 | 3.41 | 1.41 | <0.02 | <0.01 | 4.3 | | | | |
| Apr-15 | 465 | 7.86 | 241 | 263 | 1.7 | 0.18 | <0.05 | 2.5 | 1.65 | 0.61 | <0.02 | <0.01 | 1.0 | | | | |
| Oct-15 | 893 | 8.03 | 512 | 488 | 10.1 | 0.38 | <0.25 | 15.5 | 3.64 | 1.43 | <0.02 | 0.59 | 10.8 | | | | |
| Nov-16 | 860 | 8.20 | 438 | 479 | 11.5 | 0.33 | <0.25 | 12.8 | 5.86 | 2.72 | <0.02 | <0.01 | 11.6 | | | | |
| Apr-17 | 347 | 8.18 | 178 | 187 | 0.34 | 0.11 | <0.05 | 1.74 | 0.92 | 1.01 | <0.02 | 0.12 | 1.3 | | | ļ | |
| Nov-17 | 1180 | 7.73 | 664 | 641 | 19.2 | <0.25 | <0.25 | 21.1 | 6.31 | 4.31 | <0.02 | <0.01 | 20.5 | | | | |
| May-18 | 400 | 8.00 | 210 | 220 | 1.1 | <0.10 | <0.010 | <1.0 | 0.95 | 0.77 | <0.050 | <0.1 | 1.2 | | | | |
| Nov-18 | 696 | 7.92 | 349 | 377 | 3.99 | 1.18 | <0.05 | 6.19 | 2.79 | 3.32 | <0.02 | 0.019 | 6.4 | | | | |
| Apr-19 | 446 | 7.72 | 223 | 265 | 2.41 | 0.16 | <0.05 | 0.89 | 1.57 | 0.75 | <0.02 | <0.01 | 2.6 | | | | |
| Oct-19 | 669 | 7.62 | 359 | 355 | 20.0 | <0.10 | <0.10 | 4.16 | 2.66 | 2.45 | <0.02 | <0.01 | 8.5 | | | | |
| Apr-20 | 549 | 7.66 | 224 | 259 | 4.87 | 0.28 | <0.05 | 1.65 | 1.86 | 0.68 | <0.02 | 0.035 | 5.2 | | 63.3 | 15.9 | |
| Oct-20 | 909 | 7.78 | 613 | 527 | 14.3 | <0.25 | <0.25 | 9.99 | 5.04 | 2.33 | <0.02 | <0.010 | 10.6 | | 166 | 48.2 | |
| May-21 | 598 | 7.93 | 294 | 289 | 11.2 | 0.57 | <0.05 | 2.52 | 3.70 | 1.12 | <0.02 | <0.010 | 2.1 | | 82.6 | 21.2 | |
| Oct-21 | 1230 | 7.44 | 669 | 673 | 14.8 | <0.05 | <0.05 | 14.2 | 6.78 | <2.50 | <0.02 | <0.010 | 115 | | | | |
| Apr-22 | 574 | 7.67 | 271 | 302 | 4.45 | 0.33 | <0.05 | 1.93 | 3.79 | 0.88 | <0.02 | 0.022 | 1.9 | | 77.9 | 18.5 | |
| Apr-23 | 551 | 7.63 | 320 | 277 | 4.18 | 1.78 | < 0.05 | 3.01 | 3.15 | 1.27 | <0.02 | <0.010 | 1.8 | | 88.8 | 23.8 | 0.050 |
| Nov-23 | 755 | 7.41 | 388 | 432 | 9.93 | 2.02 | <0.05 | 9.0 | 4.30 | 2.66 | <0.02 | 0.025 | 2.7 | | 108 | 28.8 | 0.089 |
| Apr-24 | 662 | 7.69 | 327 | 373 | 4.44 | 0.86 | <0.05 | 7.2 | 4.24 | 1.11 | <0.02 | <0.020 | 2.8 | | 92.1 | 23.5 | 0.046 |
| Nov-24 | 831 | 7.58 | 532 | 513 | 6.94 | 0.57 | <0.05 | 8.1 | 5.85 | 2.76 | <0.02 | <0.020 | 8.3 | | 153 | 36.4 | 0.075 |
| | | | | | | | | | | | | | | | | | |
| Average | 598 | 7.91 | 336 | 332 | 6.30 | 0.84 | <0.05 | 9.08 | 3.17 | 1.37 | < 0.05 | 0.033 | 6.74 | 0.0034 | 104 | 27.0 | 0.065 |
| Average | | | | | 5.38 | 1.38 | NA | 7.89 | 1.47 | 0.92 | NA | 0.087 | 15.7 | 0.0088 | 36.7 | 10.6 | 0.021 |

| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|----------------------|--------------|--------------|------------|--------------|-------------|---------------|----------------|---------------|--------------------|--------------|---------------|--------------|--------------|---------|-------------|--|-------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | NV NV | NV |
| ODWS | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA. | NA | AO | AO | NA NA | NA | NA I | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 872 | 0.0 - 0.0 | 385 | 707 | 45.5 | 0.00 | 0.20 | 200 | 101 | 144 | 147 | 2.7 | 6.0 | 0.0020 | 144 | 100 | |
| Jan-89 | 1084 | | 486 | | 50.4 | | | | | | | 13.2 | 6.9 | 0.0450 | | | |
| Dec-89 | 1024 | | 100 | | 50.9 | | | | | | | 10.2 | 0.0 | 0.0 100 | | | |
| Jul-90 | 1113 | | 475 | | 7.00 | | | | | | | 23.0 | 7.1 | 0.0030 | | i i | |
| Jan-93 | 11.75 | | 568 | | 1.100 | | | | | | | 23.2 | 20.5 | 0.0045 | | | |
| Jan-94 | 984 | | 509 | | 39.7 | | | | | | | 17.3 | 20.0 | 0.0089 | | | |
| Nov-94 | 1360 | | 540 | | 50.3 | | | | | | | 14.7 | 14.6 | 0.0066 | | i i | |
| Oct-95 | 1690 | | 628 | | 98.5 | | | | | | | 28.0 | 19.5 | 0.0132 | | | |
| Dec-96 | 2110 | | 621 | | 116 | | | | | | | 31.6 | 25 | 0.0010 | | | |
| Oct-97 | 2380 | | 733 | | 146 | | | | | | | 37.7 | 35 | <0.001 | | | |
| Oct-98 | 2460 | | 794 | | 184 | | | | | | | 36.6 | 12 | 0.0010 | | | |
| Nov-99 | 2050 | | 756 | | 130 | | | | | | | 20.7 | 19 | <0.001 | | | |
| Oct-00 | 2330 | | 770 | | 139 | | | | | | | 31.4 | 47 | <0.001 | | | |
| Nov-01 | 2210 | | 712 | | 129 | | | | | | | 37.8 | 35 | <0.001 | | | |
| Dec-02 | 2090 | | 774 | | 158 | | | | | | | 32.3 | 24 | <0.001 | | | |
| Oct-03 | 2280 | | 838 | | 178 | | | | | | | 34.0 | 79 | <0.001 | | | |
| Nov-04 | 2400 | | 907 | | 181 | | | | | | | 34.0 | 28.3 | <0.001 | | | |
| Nov-05 | 2720 | | 853 | | 188 | | | | | | 0.5 | 29.8 | 79.6 | <0.001 | | ļ | |
| Apr-06 | 1620 | 7.49 | 561 | 720 | 70.4 | 0.10 | <0.05 | 5.81 | 75.5 | | 39.2 | 24.2 | 19.0 | | | | |
| Oct-06 | 1700 | 7.55 | 602 | 811 | 91.1 | 2.89 | <0.05 | 26.5 | 81.2 | 51.9 | 21.3 | 0.30 | 9.7 | | | | |
| Apr-07 | 1280 | 7.62 | 497 | 594 | 56.4 | 0.10 | < 0.05 | 13.6 | 56.7 | 30.7 | 27.0 | 0.25 | 14.4 | | | | |
| Nov-07 | 2290 | 7.48 | 719 | 1070 | 139 | 1.88 | <0.05 | 12.3 | 108 | 69.9 | 4.76 | 0.063 | 34.0 | | | | |
| Apr-08 | 2130 | 7.47 | 673 | 1050 | 140 | 0.11 | <0.05 | 29.7 | 102 | 56.3 | 78.2 | 0.83 | 18.2 | | | | |
| Oct-08 | 2450 | 7.44 | 850 | 1100 | 136 | <0.05 | <0.05 | 18.1 | 117 | 78.9 | 4.45 | 0.028 | 27.9 | | | | |
| Apr-09 | 1920 | 7.45 | 672 | 926 | 99.2 | 0.15 | <0.05 | 8.6 | 86.1 | 55.7 | 54.3 | 0.030 | 19.2 | | | - | |
| Nov-09 | 2180 | 7.40 | 802 | 1070 | 130 2.05 | < 0.05 | <0.05 <0.05 | 14.9 1020* | 110 | 70.7 | 50.4 | 1.36 | 23.8 | | | - | |
| Apr-10 | 2600 2030 | 7.55 7.33 | 950 753 | 1260 1190 | 90.7 | <0.05 0.26 | <0.05 | 4.93 | 165 95.4 | 64.3 67.9 | <0.02 58.2 | 0.14 0.01 | 38.7 31.4 | | | | |
| Nov-10 Apr-11 | 856 | 7.92 | 451 | 459 | 2.36 | 0.26 | <0.05 | 10.3 | 4.54 | 14.6 | 17.3 | 0.01 | 3.9 | | | | |
| Nov-11 | 1370 | 7.72 | 727 | 843 | 69.3 | 0.74 | <0.05 | 10.8 | 61.1 | 40.0 | 29.2 | 0.09 | 15.5 | _ | - | | |
| Apr-12 | 2140 | 7.47 | 799 | 1180 | 84.7 | < 0.05 | <0.05 | 5.28 | 78.9 | 41.6 | 32.7 | 0.13 | 15.0 | | | | |
| Nov-12 | 2750 | 7.70 | 973 | 1400 | 235 | 0.39 | <0.05 | 2.71 | 200 | 73.0 | 84.7 | 0.30 | 40.8 | | | | |
| Apr-13 | 896 | 7.78 | 324 | 414 | 29.7 | 0.29 | <0.05 | 9.34 | 27.6 | 18.3 | 5.04 | 0.07 | 8.2 | | | | |
| Nov-13 | 1900 | 7.53 | 571 | 897 | 75.5 | <1.0 | <1.0 | 7.14 | 65.2 | 34.3 | 31.2 | 0.07 | 16.3 | | | | |
| May-14 | 1560 | 7.63 | 581 | 745 | 72.3 | 0.34 | <0.05 | 4.94 | 64.2 | 40.0 | 32.4 | 0.04 | 12.3 | | | | |
| Oct-14 | 2270 | 7.57 | 713 | 1150 | 112 | <0.5 | <0.5 | 1.9 | 91.7 | 56.8 | 73.3 | 0.06 | 26.2 | | | | |
| Apr-15 | 1020 | 7.54 | 409 | 537 | 29.4 | <0.25 | <0.25 | 4.1 | 23.9 | 19.5 | 1.3 | 0.02 | 6.7 | | | † † | |
| Oct-15 | 2240 | 7.94 | 777 | 1070 | 123 | <1.0 | <1.0 | <2.0 | 101.0 | 57.6 | 62.2 | 38.1 | 25.4 | | | 1 | |
| Apr-16 | 1250 | 7.90 | 496 | 647 | 40.9 | <0.25 | < 0.25 | 8.46 | 36.9 | 22.9 | 21.3 | | 10.2 | | | | |
| Nov-16 | 2050 | 6.82 | 755 | 979 | 106 | 1.36 | <0.25 | 3.89 | 85.8 | 45.7 | 51.2 | 0.07 | 22.4 | | | | |
| Apr-17 | 1830 | 7.82 | 685 | 863 | 103 | <0.25 | <0.25 | 19.6 | 79.4 | 39.1 | 22.8 | 13.5 | 9.0 | | | | |
| Nov-17 | 2460 | 7.68 | 837 | 1190 | 150 | <0.5 | <0.5 | 13.8 | 118 | 58.5 | 46.2 | 0.06 | 20.8 | | | | |
| May-18 | 1400 | 7.45 | 470 | 650 | 58 | 0.29 | 0.015 | 6.2 | 55 | 27 | 20.0 | <0.1 | 9.2 | | | | |
| Nov-18 | 1510 | 7.76 | 581 | 703 | 54 | 20.6* | <0.25 | 4.4 | 36.6 | 17.2 | 14.3 | 0.024 | 7.0 | | | | |
| Apr-19 | 1140 | 7.68 | 368 | 610 | 43.5 | 0.22 | <0.05 | 1.75 | 42.3 | 23.3 | 25.0 | 2.98 | 15.5 | | | | |
| Oct-19 | 1910 | 7.69 | 701 | 1020 | 76.2 | <0.5 | <0.5 | <1.0 | 75.1 | 52.8 | 32.2 | <0.01 | 15.3 | | | | |
| Apr-20 | 1500 | 7.38 | 512 | 674 | 30.5 | <0.25 | <0.25 | 2.78 | 20.3 | 16.4 | 18 | 0.037 | 10.3 | | 138 | 40.7 | |
| Oct-20 | 1950 | 7.63 | 689 | 996 | 115 | <0.5 | <0.5 | <1.0 | 86.1 | 45.5 | 10 | 0.029 | 6.3 | | 161 | 69.6 | |
| May-21 | 2050 | 7.31 | 699 | 944 | 98.3 | <0.5 | <0.5 | <1.0 | 74.1 | 41.4 | 44.9 | 0.033 | 24.0 | | 168 | 67.8 | |
| Oct-21 | 2150 | 7.45 | 680 | 1030 | 122 | <0.07 | < 0.05 | <0.19 | 126 | 45.2 | 47.7 | <0.010 | 187 | | 4 | | |
| Apr-22 | 2000 | 7.26 | 582 | 958 | 111 | 0.39 | <0.05 | 1.19 | 83.1 | 33.0 | 41.0 | 0.080 | 20.6 | | 144 | 54.1 | |
| Sep-22 | 1970 | 7.27 | 643 | 911 | 65.1 | <0.07 | 1.98 | <0.2 | 30.0 | 17.8 | 33.4 | 22.5 | 24.0 | | 184 | 44.6 | 0.040 |
| Apr-23 | 903 | 7.20 | 524 | 468 | 4.73 | 0.06 | < 0.05 | 5.15 | 3.33 | 2.89 | 20.8 | <0.010 | 4.8 | | 156 | 32.6 | 0.043 |
| Nov-23 | 1610 | 7.17 | 579 | 917 | 29.7 | 1.22 | < 0.05 | 3.41 | 9.50 | 5.90 | 34.4 | 0.53 | 11.0 | | 172 | 36.4 | 0.19 |
| Apr-24 | 1370 | 7.20 | 570 | 749 808 | 30.6 | <0.05 | <0.05 <0.05 | 4.08 | 36.1 | 21.7 | 23.8 | 0.34 | 17.5 | | 152 | 46.3 | 0.39 |
| Nov-24 | 1390 | 7.12 | 520 | 808 | 39.0 | <0.05 | <0.05 | 2.33 | 57.3 | 26.7 | 26.2 | 1.47 | 23.2 | - | 131 | 46.9 | 0.64 |
| Average | 1706 | 7 5 4 | 648 | 884 | 90.1 | 0.20 | <0.2E | 0.65 | 72.9 | 40.1 | 22 E | 11.1 | 24.1 | 0.0052 | 150 | 100 | 0.24 |
| Average Std. Dev. | 1796 531 | 7.51 0.24 | 150 | 240 | 53.7 | 0.38 0.58 | <0.25 | 8.65 7.11 | | 20.2 | 33.5 20.6 | | 26.9 | 0.0052 | 156 17.0 | 48.8 12.9 | 0.31 |
| Jiu. Dev. | 551 | 0.24 | 150 | 240 | 55.7 | 0.56 | NA | 7.11 | 42.2 | 20.2 | 20.0 | 14.3 | 20.9 | 0.0109 | 17.0 | 12.9 | 0.20 |

| | Conductivity | рH | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|------------------|--------------|--------------|--------------|------------|--------------|----------------|--|------------|--------------|--------------|----------------|----------------------|-------------------|------------------|--|--------------|----------------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | NV NV | NV |
| ODWS- | NA NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA NA | NA NA | AO | AO | NA NA | NA NA | NA NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 897 | 0.0 0.0 | 456 | 101 | 36.6 | 0.00 | 0.20 | 200 | 101 | 111 | 144 | 0.88 | 5.6 | 0.0045 | 111 | 111 | - 1,1 |
| Jan-89 | 1034 | | 536 | | 40.7 | | | | | | | 0.83 | >20 | 0.0200 | | | |
| Dec-89 | 1450 | | | | 18.7 | | | | | | | | | | | | |
| Jul-90 | 1400 | | 743 | | 17.1 | | | | | | | 0.14 | 1.8 | <0.001 | | | |
| Jan-94 | 469 | | 613 | | 15.1 | | | | | | | 0.04 | 1.9 | 0.0042 | ĺ | | |
| Nov-94 | 1223 | | 696 | | 16.0 | | | | | | | 0.07 | 1.7 | <0.001 | | | |
| Oct-95 | 1228 | | 647 | | 16.4 | | | | | | | 0.11 | 1.9 | 0.0055 | | | |
| Dec-96 | 1197 | | 537 | | 15.6 | | | | | | | 0.04 | 3 | 0.0010 | | | |
| Oct-97 | 1180 | | 602 | | 16.3 | | | | | | | 0.03 | 2 | <0.001 | | | |
| Oct-98 | 1595 | | 873 | | 24.9 | | | | | | | 0.03 | 2 | <0.001 | | | |
| Nov-99 | 1767 | | 756 | | 17.2 | | | | | | | <0.01 | <1 | <0.001 | | | |
| Oct-00 | 1736 | | 931 | | 16.2 | | | | | | | 0.27 | 13.0 | <0.001 | | | |
| Nov-01 | 1676 | | 1078 | | 16.8 | ļ., | ļ | | | | | <0.01 | 7.0 | <0.001 | ļ | | |
| Dec-02 | 2100 | | 1279 | | 18.5 | | | | | | | <0.02 | 1.2 | <0.001 | - | | |
| Oct-03 | 2310 2530 | | 1450 1700 | | 17.9 20.6 | | | | | | | 0.014 | 17.0 | <0.001 <0.001 | <u> </u> | | |
| Nov-04 Nov-05 | 2530 | | 1700 | | 18.4 | | | | ļ | | | 0.025 2.63 | 1.2 5.7 | <0.001 | - | | |
| Apr-06 | 2360 | 7.50 | 1370 | 462 | 15.6 | <0.05 | <0.05 | 984 | 113 | | 0.05 | 4.93 | 2.0 | ~0.001 | | | |
| Oct-06 | 2000 | 7.77 | 1070 | 383 | 14.0 | <0.05 | <0.05 | 904 | 102 | 7.33 | <0.05 | 0.895 | 2.8 | 1 | <u> </u> | | |
| Apr-07 | 2590 | 7.68 | 1670 | 421 | 16.7 | <0.05 | <0.05 | 1370 | 88.4 | 7.54 | 0.16 | 0.093 | 1.9 | t | | | |
| Nov-07 | 2070 | 7.64 | 1030 | 408 | 15.1 | <0.05 | <0.05 | 1070 | 131 | 7.33 | 0.09 | <0.005 | 4.6 | 1 | - | | |
| Apr-08 | 2320 | 7.71 | 1430 | 448 | 16.7 | <0.05 | <0.05 | 1300 | 105 | 9.95 | 0.39 | 0.057 | 2.0 | | | | |
| Oct-08 | 2780 | 7.61 | 1760 | 440 | 17.2 | < 0.05 | <0.05 | 1240 | 96.3 | 8.98 | 0.07 | 0.143 | 1.9 | | | | |
| Apr-09 | 2650 | 7.66 | 1560 | 469 | 21.7 | < 0.05 | < 0.05 | 1330 | 107 | 7.97 | < 0.02 | 0.015 | 2.0 | ľ | | | |
| Nov-09 | 2450 | 7.83 | 1530 | 475 | 20.7 | < 0.05 | < 0.05 | 1120 | 111 | 8.10 | < 0.05 | < 0.01 | 3.2 | | | | |
| Apr-10 | 2320 | 7.94 | 1380 | 491 | 18.9 | < 0.05 | < 0.05 | 1140 | 122 | 7.93 | <0.02 | 0.17 | 1.7 | | | | |
| Nov-10 | 2010 | 7.85 | 1270 | 491 | 22.2 | <0.05 | <0.05 | 1030 | 108 | 7.98 | <0.02 | <0.01 | 2.1 | | | | |
| Apr-11 | 1360 | 7.88 | 375 | 464 | 12.4 | <0.05 | <0.05 | 315 | 149 | 6.72 | 0.03 | <0.01 | 4.9 | | | | |
| Nov-11 | 1080 | 7.84 | 468 | 447 | 10.5 | < 0.05 | <0.05 | 309 | 121 | 6.67 | <0.02 | <0.01 | 5.3 | | | | |
| Apr-12 | 1090 | 7.80 | 402 | 464 | 6.68 | <0.05 | <0.05 | 177 | 98.5 | 5.38 | <0.02 | 0.04 | 4.5 | | | | |
| Nov-12 | 729 | 8.23 | 345 | 278 | 6.97 | < 0.05 | <0.05 | 171 | 42.1 | 3.67 | <0.02 | 0.012 | 6.8 | | | | |
| Apr-13 | 1040 | 7.94 | 439 | 379 | 6.32 | <0.25 | <0.25 | 185 | 57.9 | 4.58 | 0.05 | <0.01 | 5.0 | | | | |
| Nov-13 | 873 | 7.93 | 389 | 368 | 3.65 | <0.25 | <0.25 | 110 | 33.0 | 3.67 | <0.02 | <0.01 | 5.2 | | | | |
| May-14 | 1080 1030 | 7.69 | 503 495 | 431 | 7.43 | <0.25 | <0.25 <0.25 | 181 | 42.6 | 3.91 | 0.15 0.04 | <0.01 0.03 | 4.7 | | | | |
| Oct-14 Apr-15 | 1160 | 7.69 7.80 | 559 | 477 508 | 5.92 7.05 | <0.25 <0.25 | <0.25 | 125 181 | 36.6 44.0 | 4.41 4.17 | <0.04 | <0.03 | 5.6 4.2 | - | | | |
| Oct-15 | 1670 | 7.96 | 931 | 455 | 14.5 | <0.25 | <0.25 | 547 | 49.1 | 6.23 | <0.02 | 0.64 | 3.9 | - | | | |
| Apr-16 | 1390 | 7.98 | 722 | 429 | 13.2 | <0.25 | <0.25 | 421 | 39.3 | 4.56 | <0.02 | 0.04 | 4.4 | - | | | |
| Nov-16 | 1690 | 7.19 | 851 | 461 | 17.6 | <0.25 | <0.25 | 574 | 37.9 | 5.36 | <0.02 | <0.01 | 4.4 | 1 | | | |
| Apr-17 | 1180 | 8.07 | 597 | 327 | 11.9 | <0.25 | <0.25 | 335 | 22.7 | 3.44 | <0.02 | 0.55 | 5.2 | 1 | <u> </u> | | |
| Nov-17 | 1070 | 7.73 | 547 | 440 | 6.76 | <0.25 | <0.25 | 199 | 20.9 | 3.40 | <0.02 | <0.01 | 7.7 | | | | |
| May-18 | 1300 | 7.74 | 700 | 450 | 12 | <0.10 | <0.010 | 320 | 28 | 4.1 | 0.068 | <0.1 | 5.1 | | | | |
| Nov-18 | 999 | 7.72 | 486 | 340 | 9.14 | <0.25 | <0.25 | 235 | 14.9 | 2.93 | <0.02 | <0.010 | 6.8 | | | | |
| Apr-19 | 1270 | 7.80 | 648 | 430 | 11.4 | <0.25 | <0.25 | 339 | 20.9 | 3.79 | <0.02 | <0.01 | 5.4 | | | | |
| Oct-19 | 1360 | 7.64 | 815 | 404 | 18.3 | <0.25 | <0.25 | 461 | 24.8 | 4.70 | <0.02 | <0.01 | 5.1 | | | | |
| Apr-20 | 1920 | 7.55 | 913 | 432 | 20.9 | <0.5 | <0.5 | 560 | 26.4 | 4.57 | <0.02 | 0.038 | 4.0 | | 253 | 68.4 | |
| Oct-20 | 1660 | 7.84 | 864 | 435 | 25.2 | <0.25 | <0.25 | 572 | 22.8 | 4.69 | <0.02 | 0.055 | 5.9 | | 232 | 69.1 | |
| May-21 | 1850 | 7.84 | 1020 | 427 | 29.0 | <0.5 | <0.5 | 621 | 25.1 | 4.82 | <0.02 | <0.010 | 3.7 | | 279 | 78.1 | |
| Oct-21 | 1800 | 7.51 | 1070 | 422 | 32.2 | <0.07 | <0.05 | 679 | 25.4 | 5.50 | <0.02 | <0.010 | 64.5 | | | 70.0 | |
| Apr-22 | 1780 | 7.54 | 1030 | 441 | 33.3 | <0.07 | <0.05 | 660 | 24.7 | 5.31 | <0.02 | 0.021 | 3.9 | | 283 | 78.8 | |
| Sep-22 | 2030 | 7.32 | 1120 | 422 | 35.0 | < 0.07 | <0.05 | 762 | 25.2 | 5.41 | 0.04 | 0.013 | 4.3 | - | 302 | 88.8 | 0.007 |
| Apr-23 | 1820 1720 | 7.27 | 1020 901 | 409 457 | 37.6 | <0.07 <0.07 | <0.05 <0.05 | 647 664 | 21.1 | 4.63 | <0.02 <0.02 | <0.010 | 3.4 | - | 267 234 | 86.1 76.8 | 0.027 0.056 |
| Nov-23 | 1720 | 7.33 7.43 | 901 | 457 476 | 43.8 39.0 | <0.07 | <0.05 | 589 | 19.8 18.8 | 5.55 4.20 | 0.02 | 0.027 <0.020 | 3.3 4.5 | - | 263 | 76.8 | 0.056 |
| Apr-24 Nov-24 | 1970 | 7.43 | 985 | 506 | 41.3 | <0.07 | <0.05 | 589 | 19.3 | 5.29 | 0.04 | <0.020 | 3.5 | - | 259 | 75.4 | 0.018 |
| NUV-24 | 1970 | 1.55 | 931 | 500 | 41.3 | ~0.07 | \U.U3 | 3/1 | 19.5 | 5.29 | 0.06 | \U.UZU | 3.3 | t | 259 | 75.4 | 0.044 |
| A | 1629 | 7.71 | 897 | 433 | 18.9 | <0.25 | <0.25 | 606 | 57.8 | 5.53 | 0.041 | 0.26 | 5.47 | 0.0025 | 264 | 77.9 | 0.036 |
| Average | | | | , 700 | 10.5 | -0.20 | -0.20 | 000 | 07.0 | 0.00 | 0.041 | 0.20 | 0.47 | 0.0020 | 204 | 11.0 | 0.000 |

| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|------------------|--------------|--------------|--------------------|-------------|---------------|----------------|----------------|-------------------|--------------|--------------|-----------------|----------------|--------------|------------------|--|--------------|--------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| 001110 | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | NV | NV |
| ODWS- | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 639 | | 37 | | 4.9 | | | | | | | 1.36 | 2.2 | < 0.001 | | | |
| Jan-89 | 622 | | 342 | | 2.1 | | | | | | | 2.20 | 1.5 | < 0.001 | | | |
| Dec-89 | 998 | | | | 2.6 | | | | | | | | | | | | |
| Jul-90 | 674 | | 360 | | <0.1 | | | | | | | 0.01 | 1.8 | 0.0010 | | | |
| Jan-93 | 780 | | 549 | | | | | | | | | 0.15 | 1.3 | <0.001 | | | |
| Jan-94 | 2240 | | 472 | | | | | | | | | 0.17 | 1.5 | 0.0081 | | | |
| Nov-94 | 902 | | 539 | | 0.9 | | | | | | | 0.26 | 1.1 | <0.001 | | | |
| Oct-95 | 943 | | 529 | | 0.7 | | | | | | | 1.21 | 1.6 | 0.0139 | | | |
| Dec-96 | 943 | | 468 | | 3.0 | | | | | | | 1.10 | 1.0 | 0.0010 | | | |
| Oct-97 | 796 | | 443 | | 3.0 | | , | | | | | 0.35 | <1 | <0.001 | | | |
| Oct-98 Nov-99 | 823 744 | | 452 421 | | 1.6 2.1 | | | | | | | <0.01 <0.01 | <1 1.0 | <0.001 <0.001 | | | |
| Oct-00 | 936 | | 530 | | 2.6 | | | | | | | 0.03 | 1.0 | <0.001 | | | |
| Nov-01 | 1035 | | 580 | | 2.0 | | | | | | | <0.03 | 5.0 | <0.001 | - | | |
| Dec-02 | 1050 | | 600 | | 2.3 | | - | 7 | | | | <0.01 | 1.2 | <0.001 | | | |
| Oct-03 | 1380 | | 813 | | 2.6 | | | | | | | 0.017 | 11 | <0.001 | <u> </u> | | |
| Nov-04 | 1780 | | 1070 | | 4.2 | | | | | | | 0.017 | 1.1 | <0.001 | | | |
| Nov-05 | 1350 | | 750 | | 1.7 | | | | | | | 1.45 | 5.4 | <0.001 | | | |
| Apr-06 | 975 | 7.96 | 456 | 261 | 0.24 | <0.05 | <0.05 | 281 | 40.9 | | 0.43 | 18.3 | 1.0 | | | | |
| Oct-06 | 1950 | 7.74 | 1310 | 345 | 1.4 | <0.05 | <0.05 | 1070 | 46.9 | 4.40 | <0.05 | 0.96 | 2.0 | | | | |
| Apr-07 | 1020 | 8.14 | 597 | 237 | 0.55 | <0.05 | <0.05 | 361 | 15.5 | 1.73 | 0.08 | 0.42 | 1.4 | | | | |
| Nov-07 | 939 | 7.86 | 492 | 255 | 0.70 | <0.05 | <0.05 | 312 | 17.3 | 1.46 | 0.11 | <0.005 | 1.7 | | | | |
| Apr-08 | 678 | 7.99 | 385 | 213 | 0.44 | < 0.05 | <0.05 | 187 | 4.06 | 1.00 | <0.05 | <0.010 | 1.9 | | | | |
| Oct-08 | 2010 | 7.61 | 1350 | 375 | 2.13 | < 0.05 | <0.05 | 829 | 6.91 | 3.49 | < 0.05 | 0.106 | 1.6 | | | | |
| Apr-09 | 560 | 8.03 | 326 | 201 | 0.75 | < 0.05 | < 0.05 | 118 | 2.28 | 0.66 | <0.02 | <0.01 | 1.6 | | | | |
| Nov-09 | 695 | 8.02 | 402 | 254 | 0.62 | <0.05 | < 0.05 | 133 | 3.20 | 0.67 | <0.05 | <0.01 | 3.3 | | | | |
| Apr-10 | 559 1540 | 8.22 7.93 | 315 1140 | 214 | 0.27 1.79 | <0.05 <0.05 | <0.05 | 111 821 | 1.88 | 0.61 | <0.02 | <0.01 <0.01 | 1.4 1.9 | | | | |
| Nov-10 Apr-11 | 380 | 8.08 | 208 | 351 171 | 0.60 | <0.05 | <0.05 <0.05 | 33.8 | 4.23 1.61 | 2.07 0.51 | <0.02 <0.02 | <0.01 | 1.9 | - | - | | |
| Nov-11 | 805 | 7.89 | 544 | 302 | 1.79 | <0.05 | <0.05 | 288 | 2.70 | 0.86 | <0.02 | <0.01 | 2.1 | - | | | |
| Apr-12 | 470 | 7.91 | 253 | 216 | 0.88 | <0.05 | <0.05 | 53.7 | 1.44 | 0.40 | <0.02 | <0.01 | 1.1 | | | | |
| Nov-12 | 1040 | 8.09 | 739 | 275 | 2.08 | <0.05 | <0.05 | 438 | 3.05 | 1.20 | <0.02 | 0.015 | 1.7 | | | | |
| Apr-13 | 597 | 8.00 | 311 | 189 | 0.72 | <0.05 | <0.05 | 122 | 1.60 | 0.61 | 0.04 | <0.01 | 1.3 | | | | |
| Nov-13 | 965 | 7.86 | 517 | 280 | 1.16 | <0.25 | <0.25 | 264 | 2.50 | 1.05 | <0.02 | <0.01 | 1.9 | | | | |
| May-14 | 568 | 8.07 | 307 | 186 | 0.77 | <0.10 | <0.10 | 114 | 1.57 | 1.22 | 0.15 | 0.01 | 1.4 | | | ĺ | |
| Oct-14 | 604 | 7.92 | 327 | 284 | 0.90 | <0.10 | <0.10 | 56.4 | 1.73 | 0.51 | < 0.02 | <0.01 | 1.6 | | | | |
| Apr-15 | 538 | 7.95 | 274 | 202 | 0.76 | <0.05 | <0.05 | 97 | 1.36 | 0.61 | < 0.02 | <0.01 | 1.4 | | | | |
| Oct-15 | 994 | 7.88 | 563 | 272 | 6.32 | < 0.25 | <0.25 | 305 | 4.38 | 1.62 | 0.10 | 14.9 | 1.7 | | | | |
| Apr-16 | 739 | 8.08 | 417 | 230 | 1.01 | <0.10 | <0.10 | 199 | 1.79 | 0.65 | <0.02 | 0.01 | 1.5 | | | | |
| Nov-16 | 2360 | 7.25 | 1550 | 416 | 4.40 | <1.0 | <1.0 | 1180 | 5.05 | 2.04 | <0.02 | 0.01 | 2.0 | - | | | |
| Apr-17 | 718 1010 | 8.11 | 377 587 | 231 325 | <0.50 2.21 | <0.25 <0.25 | <0.25 <0.25 | 164 279 | 2.01 3.16 | 0.52 1.22 | <0.02 | 8.0 | 1.4 2.5 | - | | | |
| Nov-17 May-18 | 690 | 7.72 7.91 | 380 | 240 | <1.0 | <0.25 | <0.25 | 140 | 1.8 | 0.71 | <0.02 <0.050 | <0.01 <0.1 | 1.3 | - | | | |
| Nov-18 | 936 | 7.76 | 491 | 333 | 1.84 | <0.10 | <0.010 | 223 | 2.38 | 0.71 | 0.10 | <0.11 | 1.9 | t | | | |
| Apr-19 | 763 | 7.73 | 401 | 285 | 0.98 | <0.25 | <0.25 | 174 | 1.74 | 0.59 | <0.02 | <0.010 | 2.1 | | | | |
| Oct-19 | 1090 | 7.75 | 656 | 338 | 9.07 | <0.25 | <0.25 | 347 | 7.46 | 1.71 | <0.02 | <0.01 | 2.2 | | | | |
| Apr-20 | 673 | 7.59 | 251 | 223 | 0.68 | <0.10 | <0.10 | 99 | 1.26 | 0.30 | <0.02 | <0.010 | 1.5 | | 70.2 | 18.4 | |
| Oct-20 | 1420 | 7.78 | 866 | 382 | 3.55 | <0.25 | <0.25 | 572 | 4.24 | 1.42 | <0.02 | <0.010 | 1.9 | | 235 | 67.8 | |
| May-21 | 716 | 7.92 | 363 | 249 | 0.81 | <0.10 | <0.10 | 125 | 1.80 | 0.62 | <0.02 | <0.010 | 1.8 | | 99.3 | 27.9 | |
| Oct-21 | 1550 | 7.53 | 921 | 358 | 3.13 | < 0.05 | < 0.05 | 747 | 3.80 | 2.52 | < 0.02 | <0.010 | 61.4 | | | | |
| Apr-22 | 504 | 7.77 | 250 | 214 | 0.47 | <0.05 | <0.05 | 60.1 | 1.42 | <0.50 | <0.02 | 0.016 | 1.9 | | 70.0 | 18.3 | |
| Apr-23 | 676 | 7.59 | 399 | 216 | 1.02 | <0.05 | <0.05 | 143 | 1.89 | 0.69 | <0.02 | <0.010 | 1.6 | | 111 | 29.7 | <0.010 |
| Nov-23 | 944 | 7.39 | 490 | 382 | 1.24 | < 0.05 | <0.05 | 194 | 2.30 | 1.52 | <0.02 | 0.030 | 2.1 | | 133 | 38.4 | 0.022 |
| Apr-24 | 765 | 7.76 | 382 | 302 | 0.42 | < 0.05 | < 0.05 | 142 | 1.64 | <0.50 | <0.02 | <0.020 | 3.0 | | 105 | 29.1 | <0.010 |
| Nov-24 | 836 | 7.83 | 387 | 385 | 15.4 | <0.05 | <0.05 | 118 | 10.1 | 1.33 | <0.02 | <0.020 | 2.4 | | 106 | 29.6 | 0.060 |
| Averege | 000 | 7.05 | F20 | 075 | 0.47 | 40.0E | 40.0E | 205 | F 00 | 4.04 | 0.007 | 0.07 | 2.05 | 0.0046 | 110 | 20.4 | 0.044 |
| Average | 962 439 | 7.85 0.21 | 536 296 | 275 66.7 | 2.17 2.53 | <0.25 | <0.25 | 295 285 | 5.92 | 1.21 0.89 | 0.037 | 0.97 | 3.25 8.32 | 0.0018 | 116 52.4 | 32.4 15.7 | 0.041 |
| Std. Dev. | 439 | 0.21 | 290 | 00.7 | 2.53 | NA | NA | 200 | 9.9 | 0.09 | 0.075 | 3.35 | 0.32 | 0.0036 | 52.4 | 15.7 | N/A |

| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|--------------|--------------|-----------|----------|------------|----------|---------|---------|----------|--------|-----------|---------|------|------|---------|---------|-----------|-------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| opws. | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | NV | NV |
| /A/E / 1/5/A | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 487 | | 248 | | 7.4 | | | | | | | 3.3 | 5.5 | 0.002 | | | |
| Jan-89 | 414 | | 233 | | 4.2 | | | | | | | 4.4 | 1.9 | 0.001 | | | |
| Dec-89 | 539 | | | | 10.3 | | | | | | | | | | | | |
| Jul-90 | 491 | | 249 | | 10.0 | | | | | | | 2.4 | 1.5 | <0.001 | | | |
| Jan-93 | 370 | | 250 | | | | | | | | | 0.03 | 1.4 | <0.001 | | | |
| Jan-94 | | | | | | | DESTR | ROYED | | | | | | | · | | · |
| Average | 460 | NA | 245 | NA | 7.98 | NA | NA | NA | NA | NA | NA | 2.53 | 2.58 | <0.001 | NA | NA | NA |
| Std. Dev. | 67.4 | NA | 8.0 | NA | 2.83 | NA | NA | NA | NA | NA | NA | 1.86 | 1.96 | NA | NA | NA | NA |

| Darameter | Conductivity | nU l | Hardness | Alkalinitu | Chloride | Nitrate | Nitrite | entrance action to | K 15 100 KM 1888 | Potassium | A. A. 1995-20 200 | U-6 | DOC | Phenols | Calaium | Magnasium | Boron |
|---------------------|--------------|--------------|------------|------------|--------------|--------------|----------------|--------------------|------------------|--------------|-------------------|---------------|-------------------|------------|--|--|-----------|
| UNITS | | pH | | Alkalinity | | | | Sulphate | | | | | | | Calcium | | |
| UNITS | uS/cm NV | Unitless | mg/L | mg/L | mg/L | mg/L 10 | mg/L 1.0 | mg/L 500 | mg/L 200 | mg/L NV | mg/L NV | mg/L 0.30 | mg/L 5.0 | mg/L NV | mg/L NV | mg/L NV | mg/L |
| ODWS | NA NA | 6.5-8.5 | 80-100 | 30-500 | 250 | MAC | MAC | 33833061 | 35-35-35-3 | 0.819183 | 505,180 | 35 (0.01.00) | AO | 2.5.5 | NA NA | NA NA | NV NA |
| RUC | NA NV | OG | OG 527 | OG 404 | AO 128 | 3.33 | 0.25 | AO 255 | AO 101 | NA NV | NA NV | AO 0.17 | 4.87 | NA NV | NV NV | NV NV | 16.000000 |
| 22 (0.00000) | 1256 | 6.5 - 8.5 | 553 | 404 | 70.5 | 3.33 | 0.25 | 255 | 101 | I NV | INV | 1.82 | 4.87 10 | 0.003 | INV | NV | NV |
| Dec-88 Jan-89 | 1240 | | 569 | | 50.5 | | | | | | | 3.0 | 8.4 | 0.003 | | | |
| Dec-89 | 1470 | | 309 | | 77.6 | | | - | | | | 3.0 | 0.4 | 0.002 | | | |
| Jul-90 | 1530 | | 582 | | 70.2 | | | | | | | 9.6 | 11 | 0.001 | - | | |
| Jan-93 | 1550 | | 506 | | 10.2 | | | | | | | 17.6 | 8.8 | 0.0035 | | | |
| Nov-94 | 1490 | | 597 | | 81.9 | | | | | | | 18.4 | 16.9 | 0.0091 | | | |
| Oct-95 | 1550 | | 716 | | 41.2 | | | · · | | | | 27.0 | 12 | 0.0063 | | | |
| Dec-96 | 1347 | | 577 | | 9.3 | | | | | | | 12.9 | 5 | 0.0010 | | | |
| Oct-97 | 1493 | | 810 | | 15.0 | | | | | | | 17.3 | 4 | <0.001 | | | |
| Oct-98 | 1467 | | 742 | | 20.9 | | | | | | | 13.6 | 29 | <0.001 | | | |
| Nov-99 | 1392 | | 766 | | 10.6 | | | 7 | | | | 9.35 | 10 | < 0.001 | | | |
| Oct-00 | 1324 | | 737 | | 5.7 | | | | | | | 3.62 | 19 | < 0.001 | | | |
| Nov-01 | 1247 | | 665 | | 6.7 | | | | | | | 2.39 | 4 | <0.001 | | | |
| Dec-02 | 1040 | | 747 | | 8.6 | | | | | | | 0.85 | 3.5 | < 0.001 | | | |
| Oct-03 | 1030 | | 732 | | 6.4 | | | | | | | 0.50 | 25 | <0.001 | | | |
| Nov-04 | 1110 | | 706 | | 10.7 | | | | | | | 0.137 | 2.8 | <0.001 | | | |
| Nov-05 | 1140 | | 682 | | 9.9 | | | | | | | 0.26 | 11.3 | <0.001 | | | |
| Apr-06 | 854 | 7.76 | 465 | 429 | 1.96 | 1.07 | <0.05 | 28.6 | 3.3 | | < 0.05 | 3.45 | 2.0 | | | | |
| Oct-06 | 1130 | 7.61 | 653 | 625 | 17.0 | 0.42 | <0.05 | 83.0 | 12.3 | 6.61 | 0.44 | 0.47 | 4.5 | | | | |
| Apr-07 | 845 | 7.84 | 484 | 432 | 2.27 | 2.20 | <0.05 | 35.2 | 3.07 | 4.35 | 0.13 | 0.26 | 1.8 | | | | |
| Nov-07 | 1050 | 7.90 | 561 | 550 | 11.4 | 0.36 | <0.05 | 56.2 | 8.09 | 6.15 | <0.05 | <0.005 | 3.4 | | | | |
| Apr-08 | 905 | 7.98 | 523 | 503 | 4.56 | 1.71 | <0.05 | 53.2 | 5.13 | 5.69 | <0.05 | <0.010 | 1.9 | | | | |
| Oct-08 | 1090 | 7.72 | 622 | 551 | 8.18 | 0.12 | <0.05 | 41.1 | 8.61 | 6.22 | 0.20 | <0.01 | 2.6 | | | | |
| Apr-09 | 910 | 7.99 | 553 | 467 | 4.80 | 1.95 | <0.05 | 37.4 | 6.09 | 4.39 | 0.05 | 0.048 | 2.0 | | | | |
| Nov-09 | 924 | 7.86 | 555 | 505 | 6.53 | 0.39 | <0.05 | 26.9 | 6.30 | 5.42 | <0.05 | <0.01 | 1.7 | | | | |
| Apr-10 | 845 | 8.00 | 533 | 470 | 6.94 | 0.80 | 0.07 | 31.5 | 7.84 | 5.04 | 0.02 | <0.01 | 1.8 | | | | |
| Nov-10 | 905 | 7.90 | 545 | 539 | 14.9 | < 0.05 | <0.05 | 37.4 | 9.98 | 5.79 | 0.38 | 0.02 | 2.7 | | | | |
| Apr-11 | 905 | 7.96 | 541 | 432 | 9.62 | 1.19 | < 0.05 | 74.6 | 7.91 | 4.47 | 0.12 | < 0.01 | 2.1 | | | | |
| Nov-11 | 832 944 | 7.88 7.77 | 535 531 | 511 506 | 5.75 3.53 | 0.21 0.96 | <0.05 <0.05 | 65.7 51.8 | 7.02 4.24 | 4.99 3.99 | 0.17 <0.02 | <0.01 0.01 | 2.7 1.4 | | | | |
| Apr-12 Nov-12 | 912 | 8.00 | 592 | 525 | 6.58 | 0.96 | <0.05 | 53.6 | 5.71 | 5.19 | 0.05 | <0.01 | 2.7 | | , | | |
| Apr-13 | 1100 | 7.91 | 605 | 545 | 4.14 | 1.68 | <0.05 | 68.4 | 3.56 | 4.17 | 0.03 | <0.01 | 1.8 | † | - | | |
| Nov-13 | 1250 | 7.64 | 686 | 629 | 21.0 | <0.5 | <0.25 | 39.6 | 15.2 | 6.21 | 0.03 | <0.01 | 3.5 | - | | | |
| May-14 | 1150 | 7.43 | 708 | 583 | 14.2 | 2.84 | <0.25 | 45.6 | 11.1 | 4.87 | 0.14 | 0.02 | 2.6 | - | | | |
| Oct-14 | 1040 | 7.68 | 552 | 559 | 12.6 | 0.30 | <0.25 | 35.4 | 9.6 | 4.10 | <0.02 | 0.02 | 2.5 | | | | |
| Apr-15 | 1020 | 7.58 | 551 | 569 | 7.8 | 0.71 | <0.25 | 25.3 | 6.9 | 3.65 | <0.02 | <0.01 | 1.9 | † | | | |
| Oct-15 | 1100 | 7.81 | 586 | 580 | 16.1 | <0.25 | <0.25 | 24.6 | 11.7 | 5.82 | 0.96 | 0.27 | 3.5 | 1 | - | | |
| Apr-16 | 940 | 7.97 | 491 | 503 | 6.2 | 1.10 | <0.25 | 40.0 | 6.6 | 3.76 | <0.02 | 0.21 | 2.0 | | | | |
| Nov-16 | 1450 | 6.88 | 699 | 797 | 33.9 | 0.29 | <0.25 | 24.3 | 29.1 | 9.43 | 5.06 | <0.01 | 4.8 | | | | |
| Apr-17 | 1040 | 7.78 | 541 | 507 | 10.3 | 1.22 | 0.41 | 49.0 | 11.6 | 4.74 | 1.06 | 0.69 | 2.1 | | | | |
| Nov-17 | 1210 | 7.52 | 609 | 640 | 21.4 | 0.29 | <0.25 | 36.3 | 17.1 | 6.68 | 2.93 | <0.01 | 5.6 | | | | |
| May-18 | 960 | 7.36 | 510 | 510 | 7.5 | 1.33 | 0.14 | 29.0 | 7.9 | 4.7 | 1.7 | <0.1 | 1.9 | | | | |
| Nov-18 | 1290 | 7.70 | 600 | 669 | 24.6 | <0.05 | <0.05 | 34.2 | 18.4 | 8.36 | 3.24 | <0.010 | 3.2 | | | | |
| Oct-19 | 1190 | 7.75 | 585 | 672 | 21.3 | 0.30 | <0.25 | 14.1 | 21.6 | 12.9 | 11.0 | <0.01 | <0.5 | | | | |
| Apr-20 | 1500 | 7.41 | 543 | 693 | 20.0 | 0.88 | 0.44 | 13.4 | 20.9 | 15.5 | 16.3 | 0.040 | 9.7 | | 151 | 40.3 | |
| Oct-20 | 1380 | 7.73 | 626 | 777 | 30.2 | 0.44 | <0.25 | 8.81 | 30.9 | 19.2 | 27.9 | <0.010 | 12.8 | | 165 | 51.9 | |
| May-21 | 1440 | 7.36 | 559 | 717 | 20.7 | 1.06 | <0.25 | 9.71 | 22.7 | 21.7 | 32.4 | <0.010 | 9.3 | | 149 | 45.4 | |
| Oct-21 | 1400 | 7.42 | 577 | 742 | 18.7 | 0.81 | <0.05 | 8.18 | 24.4 | 21.5 | 22.7 | <0.010 | 165 | | | | |
| Apr-22 | 1190 | 7.31 | 485 | 644 | 9.7 | 0.46 | <0.05 | 13.3 | 13.0 | 16.1 | 18.9 | 0.038 | 6.5 | | 135 | 36.0 | |
| Sep-22 | 1560 | 7.02 | 654 | 774 | 28.3 | 1.08 | 0.93 | 6.56 | 27.1 | 23.6 | 24.2 | 0.036 | 18.3 | | 178 | 51.0 | |
| Apr-23 | 1400 | 7.00 | 658 | 692 | 22.3 | < 0.05 | <0.05 | 11.6 | 26.1 | 22.1 | 20.0 | 0.03 | 12.7 | | 179 | 51.2 | 0.256 |
| Nov-23 | 1400 | 6.94 | 733 | 839 | 23.5 | 1.49 | <0.05 | 8.78 | 35.2 | 26.3 | 23.4 | 2.68 | 16.9 | | 190 | 62.7 | 0.448 |
| Apr-24 | 1430 | 7.05 | 600 | 836 | 16.9 | < 0.05 | <0.05 | 7.04 | 24.0 | 21.0 | 24.9 | <0.020 | 14.6 | | 160 | 48.7 | 0.282 |
| Nov-24 | 1400 | 7.17 | 535 | 838 | 23.8 | 0.81 | <0.05 | 10.2 | 20.3 | 20.6 | 24.2 | 0.03 | 19.5 | - | 150 | 38.9 | 0.278 |
| Augraga | 4400 | 7.04 | COF | 604 | 40.4 | 0.00 | 40.0E | 22.5 | 40.00 | 0.07 | 7.40 | 2.02 | 40.00 | 0.0040 | 100 | 47.0 | 0.00 |
| Average Std. Dov | 1189 225 | 7.61 | 605 | 604 | 19.1 | 0.80 | <0.25 | 33.5 | 13.80 | 9.87 | 7.10 | 2.82 | 10.28 | 0.0019 | 162 | 47.3 | 0.32 |
| Std. Dev. | 225 | 0.33 | 84.2 | 122.2 | 18.9 | 0.69 | NA | 20.4 | 8.88 | 7.24 | 10.55 | 6.02 | 22.8 | 0.0025 | 17.7 | 8.22 | 0.09 |

| Darameter | Canduativity | nH. | Hardness | Alkalinitu | CONTRACTOR IN 1811 | Nitroto | 5 IN S CO. 100 CO | pomorphism morphism to | W C | Detection | ABS A 1990-0-100 | U-1 | DOC | Dhanala | Coloium | Magnacium | Baran |
|------------------|--------------|-----------|--------------|------------|--------------------|------------|---------------------------------------|------------------------|---|-----------|------------------|--------------|------------|------------------|---------|------------|--|
| UNITS | Conductivity | pH | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | 1 0000000000000000000000000000000000000 | Potassium | | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
| UNITS | uS/cm NV | Unitless | mg/L | mg/L | mg/L | mg/L 10 | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L NV | mg/L NV |
| ODWS | 30.818 | 6.5-8.5 | 80-100 | 30-500 | 250 | | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | 100.00 | |
| DUO | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Jan-89 | 2030 | | 1165 | | 14.1 | | | | | | | 0.10 | 13.3 | 0.0020 | | | —— |
| Dec-89 | 1900 | | 4407 | | 6.70 | | | - | | | | 0.00 | 4.0 | 10.004 | | | |
| Jul-90 | 2210 2360 | | 1197 1338 | | 5.50 0.50 | | | | | | | 0.02 0.04 | 4.0 3.6 | <0.001 0.0138 | | | |
| Nov-94 Oct-95 | 2190 | | 1114 | | 0.50 | | | | | | | 0.04 | 4.3 | 0.0138 | | - | |
| Dec-96 | 1859 | | 596 | | 2.80 | | | _ | | | | 0.03 | 6 | <0.0021 | - | | |
| Oct-97 | 518 | - | 528 | | 3.00 | | - | - | | | | 0.20 | 6 | <0.001 | | | |
| Nov-99 | 1281 | | 470 | | 1.70 | | | | | | | 0.23 | 3 | <0.001 | _ | | |
| Nov-01 | 1042 | | 463 | | <1.0 | | | | | | | <0.01 | 6 | <0.001 | | | |
| Dec-02 | 1420 | | 678 | | 1.00 | | - | | | | | <0.01 | 6.7 | <0.001 | | | |
| Oct-03 | 1970 | - | 1270 | | 1.10 | | · · · · · · · · · · · · · · · · · · · | | | | | <0.02 | 13 | <0.001 | | | |
| Nov-05 | 869 | | 465 | | 8.00 | | | | | | | 0.012 | 14.5 | <0.001 | | | |
| Apr-06 | 978 | 7.79 | 527 | 373 | 0.38 | <0.05 | <0.05 | 188 | 14.2 | | <0.05 | 1.67 | 7 | 30.001 | | | |
| Oct-06 | 690 | 8.10 | 396 | 216 | 0.57 | <0.05 | <0.05 | 216 | 7.58 | 1.36 | <0.05 | 0.39 | 48 | | | | |
| Apr-07 | 913 | 8.08 | 531 | 290 | 0.20 | <0.05 | <0.05 | 236 | 10.9 | 1.51 | 2.00 | 0.45 | 7.1 | 1 | | | i |
| Nov-07 | 869 | 8.11 | 483 | 227 | 0.36 | <0.05 | <0.05 | 298 | 10.1 | 1.70 | <0.05 | <0.005 | 9.6 | | | | |
| Apr-08 | 491 | 8.19 | 268 | 195 | 1.07 | 0.17 | <0.05 | 83 | 3.67 | 0.89 | <0.05 | <0.010 | 4.2 | | | | |
| Apr-09 | 1370 | 8.05 | 876 | 274 | 1.61 | < 0.05 | < 0.05 | 594 | 11.6 | 1.82 | <0.02 | <0.010 | 4.4 | | | | |
| Nov-09 | 1530 | 8.05 | 997 | 264 | 0.65 | < 0.05 | <0.05 | 711 | 14.4 | 2.23 | < 0.05 | <0.01 | 7.1 | | | | |
| Apr-10 | 1330 | 8.13 | 834 | 265 | 0.70 | 0.42 | < 0.05 | 615 | 12.0 | 1.78 | <0.02 | < 0.01 | 4.1 | | | | |
| Nov-10 | 2170 | 7.88 | 1790 | 291 | 0.41 | < 0.05 | < 0.05 | 1520 | 12.2 | 2.49 | < 0.02 | < 0.01 | 3.3 | | | | |
| Apr-11 | 1340 | 8.01 | 809 | 240 | 1.83 | 0.19 | < 0.05 | 618 | 9.95 | 1.42 | < 0.02 | < 0.01 | 4.5 | | | | |
| Nov-11 | 971 | 8.05 | 650 | 235 | 1.14 | < 0.05 | < 0.05 | 473 | 8.57 | 1.49 | < 0.02 | <0.01 | 7.1 | | | | |
| Apr-12 | 1030 | 7.93 | 572 | 247 | 1.13 | < 0.05 | <0.05 | 373 | 7.17 | 1.09 | <0.02 | 0.010 | 3.0 | | | | |
| Nov-12 | 792 | 8.14 | 485 | 215 | 1.09 | < 0.05 | <0.05 | 310 | 7.69 | 1.22 | <0.02 | 0.012 | 5.4 | | | | |
| Apr-13 | 695 | 8.04 | 368 | 218 | 0.83 | 0.07 | < 0.05 | 155 | 4.98 | 0.82 | 0.03 | <0.01 | 4.0 | | | | |
| Nov-13 | 1120 | 8.00 | 594 | 258 | 0.54 | <0.25 | <0.25 | 399 | 7.43 | 1.46 | < 0.02 | <0.01 | 6.5 | | | | |
| May-14 | 1330 | 7.90 | 875 | 282 | 1.30 | <0.25 | <0.25 | 517 | 8.40 | 1.26 | 0.09 | 0.02 | 4.7 | | | | |
| Oct-14 | 1560 | 7.98 | 919 | 361 | 0.78 | <0.25 | <0.25 | 667 | 8.73 | 1.63 | 0.14 | 0.03 | 4.6 | | | | ĺ |
| Apr-15 | 1590 | 7.93 | 936 | 442 | 1.46 | < 0.25 | < 0.25 | 547 | 8.07 | 0.95 | <0.02 | <0.01 | 4.3 | | | | <u> </u> |
| Oct-15 | 2530 | 8.10 | 1880 | 311 | 3.2 | <1.0 | <1.0 | 1500 | 8.66 | 3.01 | <0.02 | 1.17 | 3.3 | | | | |
| Apr-16 | 381 | 7.94 | 196 | 139 | 0.73 | 0.80 | <0.05 | 65.2 | 2.57 | 0.36 | <0.02 | | 3.5 | | | | |
| Nov-16 | 1420 | 7.10 | 897 | 291 | 1.2 | <0.5 | <0.5 | 593 | 6.87 | 1.66 | <0.02 | <0.01 | 4.3 | | | | |
| Apr-17 | 651 | 8.21 | 339 | 210 | 0.92 | <0.25 | <0.25 | 149 | 3.52 | 0.55 | <0.02 | 1.08 | 4.6 | | | | |
| Nov-17 | 1110 | 7.94 | 656 | 268 | 1.46 | < 0.25 | <0.25 | 408 | 6.03 | 1.17 | 0.03 | <0.01 | 4.5 | | | | |
| May-18 | 500 | 7.94 | 250 | 210 | 1.4 | <0.10 | <0.010 | 49 | 2.8 | 0.40 | <0.050 | <0.1 | 4.3 | | | | |
| Nov-18 | 674 | 7.96 | 337 | 311 | 0.98 | <0.10 | <0.10 | 74.9 | 4.48 | 0.63 | <0.02 | 0.04 | 7.5 | | | | |
| Apr-19 | 526 | 7.82 | 268 | 286 | 2.57 | 0.07 | < 0.05 | 29.0 | 3.24 | 0.44 | <0.02 | <0.01 | 6.0 | | - | | |
| Oct-19 | 552 | 7.69 | 303 | 262 | 0.79 | 0.19 | < 0.05 | 58.9 | 3.99 | 0.72 | <0.02 | <0.01 | <0.5 | | 70.7 | 110 | |
| Apr-20 | 552 | 7.75 | 242 | 247 | 0.55 | <0.05 | < 0.05 | 16.3 | 2.96 | 0.46 | <0.02 | 0.084 | 4.8 | | 72.7 | 14.8 | |
| Oct-20 | 504 | 8.09 | 274 | 264 | 0.28 | 0.15 | < 0.05 | 30.5 | 4.06 | 0.73 | 0.03 | 0.103 | 6.0 | - | 81.2 | 17.2 | |
| May-21 | 447 | 8.06 | 218 | 220 | 0.32 | 0.11 | <0.05 | 11.3 | 2.46 | 0.56 | <0.02 | <0.010 | 5.5 | | 65.4 | 13.4 | |
| Apr-22 | 403 | 7.77 | 169 | 206 | 0.43 | 0.17 | <0.05 | 8.39 | 1.91 | <0.50 | <0.02 | 0.034 | 5.0 | - | 49.7 | 10.8 | 40.010 |
| Apr-23 | 445 | 7.86 | 236 | 192 | 0.66 | 0.16 | <0.05 | 23.6 | 2.50 | 0.68 | <0.02 | 0.016 | 4.9 | | 71.6 | 14.0 | <0.010 |
| Apr-24 | 396 | 7.76 | 221 | 228 | 0.53 | 0.91 | <0.05 | 14.8 | 2.55 | 0.90 | 0.55 | <0.020 | 7.4 | - | 67.0 | 13.0 | <0.010 |
| Ανοτασο | 1115 | 7.05 | CEO | 250 | 1.751 | 0.16 | <0.0E | 350 | 6.06 | 1.01 | 0.10 | 0.14 | 6 77 | 0.0000 | 67.0 | 12.0 | <0.010 |
| Average | 1145 | 7.95 | 652 | 259 | 1.754 | 0.16 | <0.25 | 350 | 6.86 | 1.21 | 0.10 | 0.14 | 6.77 | 0.0020 | 67.9 | 13.9 | <0.010 |
| Std. Dev. | 617 | 0.20 | 414 | 58.0 | 2.506 | 0.21 | NA | 378 | 3.67 | 0.64 | 0.35 | 0.34 | 6.94 | 0.0040 | 10.5 | 2.12 | N/A |

| WINTS | | | | | | | K 425 1002 (W) | 0 10 1 2 2 20 0 | NOVA | ((SINIST) 1977 (1980) | ANTEN MODERATE AS | ASSET A LIMBOUR DAY | | | | | | |
|---|---------------|------|-----------|------|------|------|----------------|-----------------|------|------------------------|-------------------|---------------------|--------|-------|--------|------|-------|--------|
| ODWS NV 68-86 80-100 30-500 220 10 1 0 500 200 NV NV O.3 5.0 NV NV NV NV RUC NV 6.5 6.5 527 404 428 3.33 0.25 255 101 NV NV NV NV NV NV NV N | | | | | | | | | | | | | | | | | | Boron |
| Nov-99 | UNITS | | | | | | | | | | | | | | | | | mg/L |
| RUC NV S5-35 527 404 128 3.33 0.25 255 101 NV NV 0.17 4.87 NV NV NV NV 0.17 4.87 NV | ODWS | | | | | | | | | | | | | | | | | |
| Jan-88 | | | | | | | | | | | | 1,000,000 | | | | | | |
| Jul-90 | | | 6.5 - 8.5 | | 404 | | 3.33 | 0.25 | 255 | 101 | NV | NV | | | | NV | NV | NV |
| Nov-94 | | 1920 | | 1186 | | 6.8 | | | | | | | 0.19 | | | | | |
| Dec-96 1330 696 0.8 | | | | | | | | | | | | | | | | | | |
| Dec-96 | | | | | | | | | | | | | | | | | | |
| Coct-97 Nov-99 | | | | | | | | | | | | | | | | | | |
| Nov-99 | | 1001 | | 240 | | 2.4 | | | | | | | 0.04 | 6.0 | | | | |
| Nov-01 790 | | | | | | | l | | | | | | | | | | | |
| Dec-02 | | | | | | | | | | | | | | | | | | |
| Nov-05 | | | | | | | | | | | | | | | | | | |
| Apr-06 567 7.55 295 301 0.71 <0.05 <0.05 1.14 6.01 <0.05 <0.05 7.53 8.0 | | | | | | | | | | | | | | | | | | |
| Apr-07 798 | | | | | | | | | | | | | | | <0.001 | | | |
| Nov-07 | | | | | | | | | | | | | | | | | | |
| Apr-109 | Apr-07 | 798 | 8.32 | | | | < 0.05 | < 0.05 | | 8.93 | 0.63 | 0.09 | 0.27 | 7.5 | | | | |
| Apr-10 529 8.23 301 274 1.72 0.09 <0.05 30.0 3.16 0.25 <0.02 <0.01 5.1 | Nov-07 | 1010 | 7.57 | | | | < 0.05 | <0.05 | 274 | 7.64 | 0.87 | <0.05 | <0.005 | 9.3 | | | | |
| Nov-10 | Apr-09 | | 7.71 | | | 2.46 | 0.06 | <0.05 | 8.06 | 3.06 | 0.27 | <0.02 | 0.043 | 5.6 | | | | |
| Nov-12 | Apr-10 | 529 | 8.23 | 301 | 274 | 1.72 | 0.09 | <0.05 | 30.0 | 3.16 | 0.25 | <0.02 | <0.01 | 5.1 | | | | |
| Apr-13 | Nov-10 | 948 | 8.22 | 638 | 388 | 2.87 | < 0.05 | <0.05 | 261 | 5.11 | 0.71 | <0.02 | <0.01 | 5.6 | | | | |
| Nov-13 | Nov-12 | 477 | 8.12 | 266 | 229 | 2.32 | 0.42 | <0.05 | 49.4 | 6.20 | 0.67 | <0.02 | <0.01 | 11.3 | | | | |
| May-14 | Apr-13 | 463 | 8.06 | 244 | 233 | 1.92 | < 0.05 | < 0.05 | 9.55 | 3.12 | 0.20 | 0.07 | <0.01 | 5.4 | | | | |
| Oct-14 695 7.73 384 404 2.58 <0.25 <0.25 1.78 4.20 0.38 <0.02 0.02 7.3 Apr-15 817 7.64 421 472 1.80 <0.25 | Nov-13 | 458 | 8.08 | 225 | 232 | 1.02 | <0.10 | <0.10 | 10.6 | 3.55 | 0.21 | <0.02 | <0.01 | 11.4 | | | | |
| Apr-15 817 7.64 421 472 1.80 <0.25 <0.25 0.3 5.37 0.28 <0.02 <0.01 6.3 Oct-15 819 8.11 475 450 6.51 <0.25 | May-14 | 454 | 7.85 | 240 | 233 | 0.82 | 0.20 | < 0.05 | 7.61 | 3.20 | 0.24 | 0.10 | 0.02 | 6.4 | | | | |
| Oct-15 819 8.11 475 450 6.51 <0.25 <0.25 15.3 4.24 0.40 <0.02 6.03 5.4 Apr-16 625 8.04 350 338 2.00 <0.10 | Oct-14 | 695 | 7.73 | 384 | 404 | 2.58 | < 0.25 | < 0.25 | 1.78 | 4.20 | 0.38 | <0.02 | 0.02 | 7.3 | | | | |
| Apr-16 625 8.04 350 338 2.00 <0.10 <0.10 29.0 4.47 0.22 <0.02 7.6 Apr-17 366 8.13 188 192 0.60 <0.05 | Apr-15 | 817 | 7.64 | 421 | 472 | 1.80 | < 0.25 | < 0.25 | 0.3 | 5.37 | 0.28 | < 0.02 | < 0.01 | 6.3 | | | ĺ | |
| Apr-17 366 8.13 188 192 0.60 <0.05 <0.05 6.43 2.66 0.21 <0.02 2.42 5.9 Nov-17 520 7.87 281 278 2.77 <0.10 | Oct-15 | 819 | 8.11 | 475 | 450 | 6.51 | <0.25 | <0.25 | 15.3 | 4.24 | 0.40 | <0.02 | 6.03 | 5.4 | | | | |
| Nov-17 520 7.87 281 278 2.77 <0.10 <0.10 12.4 4.41 0.29 <0.02 <0.01 6.1 May-18 310 7.91 160 170 <1.0 | Apr-16 | 625 | 8.04 | 350 | 338 | 2.00 | <0.10 | <0.10 | 29.0 | 4.47 | 0.22 | <0.02 | | 7.6 | | | | |
| May-18 310 7.91 160 170 <1.0 <0.010 <0.010 1.3 2.6 <0.2 <0.050 <0.1 5.0 Nov-18 509 7.80 252 276 1.19 <0.05 | Apr-17 | 366 | 8.13 | 188 | 192 | 0.60 | < 0.05 | < 0.05 | 6.43 | 2.66 | 0.21 | <0.02 | 2.42 | 5.9 | | | | |
| Nov-18 509 7.80 252 276 1.19 <0.05 <0.05 5.29 3.63 0.20 <0.02 0.033 10 Apr-19 391 7.80 195 232 0.55 <0.05 | Nov-17 | 520 | 7.87 | 281 | 278 | 2.77 | < 0.10 | <0.10 | 12.4 | 4.41 | 0.29 | < 0.02 | <0.01 | 6.1 | | | | |
| Apr-19 391 7.80 195 232 0.55 <0.05 1.90 1.99 0.07 0.03 <0.01 4.1 Oct-19 451 7.81 249 257 0.71 <0.05 | May-18 | 310 | 7.91 | 160 | 170 | <1.0 | < 0.10 | <0.010 | 1.3 | 2.6 | <0.2 | < 0.050 | <0.1 | 5.0 | | | | |
| Apr-19 391 7.80 195 232 0.55 <0.05 1.90 1.99 0.07 0.03 <0.01 4.1 Oct-19 451 7.81 249 257 0.71 <0.05 | | | | 252 | | | < 0.05 | | | | | | | | | | | |
| Oct-19 451 7.81 249 257 0.71 <0.05 <0.05 2.93 3.42 0.39 <0.02 <0.01 13 Apr-20 456 7.68 200 213 0.42 <0.05 | | | | | | | | | | | | | | | | | | |
| Apr-20 456 7.68 200 213 0.42 <0.05 <0.05 2.31 2.00 0.09 <0.02 0.027 6.0 65.6 8.72 Oct-20 498 8.02 268 228 0.67 <0.05 | | | | | | | | | | | | | | | | | | |
| Oct-20 498 8.02 268 288 0.67 <0.05 <0.05 1.73 3.38 0.39 <0.02 0.068 11 87.5 12.0 May-21 396 7.98 190 202 0.35 <0.05 | | | | | | | | | | | | | | | | 65.6 | 8.72 | |
| May-21 396 7.98 190 202 0.35 <0.05 <0.05 2.35 2.74 <0.50 <0.02 0.146 5.8 62.5 8.27 Apr-22 407 7.62 186 218 0.59 <0.05 | | | | | | | | | | | | | | | | | | |
| Apr-22 407 7.62 186 218 0.59 <0.05 <0.05 1.76 2.53 <0.50 <0.02 0.034 6.3 60.8 8.29 Nov-23 785 7.33 446 489 4.84 <0.05 | | | | | | | | | | | | | | | | | | |
| Nov-23 785 7.33 446 489 4.84 <0.05 <0.05 0.54 3.90 0.74 <0.02 <0.010 6.8 140 23.4 0.02 Apr-24 764 7.53 431 475 3.96 <0.05 | | | | | | | | | | | | | | | | | | |
| Apr-24 764 7.53 431 475 3.96 <0.05 <0.05 0.55 3.86 <0.50 0.02 <0.020 9.2 132 24.7 <0.00 Average 716 7.87 366 304 2.08 0.066 <0.10 | | | | | | | | | | | | | | | | | | 0.027 |
| Average 716 7.87 366 304 2.08 0.066 <0.10 30.1 4.05 0.37 0.022 0.64 8.05 0.0019 91.4 14.23 0.03 | | | | | | | | | | | | | | | | | | <0.010 |
| | New Committee | | | | | 0.00 | .0.00 | .0.00 | 0.00 | 0.00 | .0.00 | 0.02 | 0.020 | - U.Z | | | | 0.0.0 |
| | Average | 716 | 7.87 | 366 | 304 | 2.08 | 0.066 | <0.10 | 30.1 | 4.05 | 0.37 | 0.022 | 0.64 | 8.05 | 0.0019 | 91.4 | 14.23 | 0.03 |
| IStd. Dev. 410 0.25 247 98.7 1.61 0.085 NA 71.2 1.67 0.23 0.025 1.69 4.06 0.0036 36.0 7.74 N/A | Std. Dev. | 410 | 0.25 | 247 | 98.7 | 1.61 | 0.085 | NA | 71.2 | 1.67 | 0.23 | 0.025 | 1.69 | 4.06 | 0.0036 | 36.0 | 7.74 | N/A |

| Parameter | Conductivity | рΗ | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|------------------|--------------|--------------|------------|--|--------------|----------------|----------------|--------------|--------------|--------------|---------------|----------------------|--------------|------------------|---------|--|-------|
| UNITS | uS/cm | Unitless | ma/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | ma/L |
| | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| ODWS- | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA. | AO | AO | NA | NA | NA NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 554 | | 281 | | 20.3 | | | | | | | 2.95 | 8.8 | 0.0020 | | | |
| Jan-89 | 587 | | 317 | | 21.5 | | | | | | | 4.90 | 7.3 | 0.0010 | | | 1 |
| Dec-89 | 585 | | | | 17.8 | | | | | | | | | | | | |
| Jul-90 | 629 | | 321 | | 13.6 | | | | | | | 0.54 | 9.1 | 0.0074 | | | |
| Jan-94 | 618 | | 335 | | 9.4 | | | | | | | 0.30 | 13.4 | 0.0064 | | | |
| Nov-94 | 671 | | 379 | | 9.0 | | | | | | | 0.26 | 10 | 0.0037 | | i e | |
| Oct-95 | 637 | | 361 | | 8.2 | | | | | | | 0.53 | 19 | 0.0049 | | | |
| Dec-96 | 559 | | 308 | | 7.7 | | | | | | | 0.26 | 11 | 0.0010 | | | |
| Oct-97 | 614 | | 324 | | 6.9 | | | | | | | 0.25 | 12 | <0.001 | | | |
| Oct-98 | 777 | | 431 | | 6.7 | | | | | | | 0.42 | 10 | <0.001 | | | |
| Nov-99 | 618 | | 342 | | 6.2 | | | | | | | 0.46 | 15 | <0.001 | | | |
| Oct-00 | 679 | | 403 | | 4.5 | | | | | | | 2.39 | 18 | <0.001 | | | |
| Nov-01 Dec-02 | 593 582 | | 319 321 | | 5.5 4.6 | | | - | | | | 0.18 0.14 | 21 15.2 | <0.001 <0.001 | | | |
| Oct-03 | 582 650 | | 418 | \vdash | 4.6 | | | | | | | 0.14 | 28 | <0.001 | | | |
| Nov-04 | 601 | | 376 | | 5.8 | | | | | | | 0.71 | 13.4 | <0.001 | | | |
| Nov-05 | 647 | | 388 | | 4.9 | | | | | | | 0.50 | 25.2 | <0.001 | | | |
| Apr-06 | 496 | 7.99 | 271 | 236 | 4.45 | <0.05 | <0.05 | 20.6 | 3.35 | | 0.08 | 10.60 | 15.0 | 30.001 | | | |
| Oct-06 | 566 | 7.90 | 314 | 201 | 6.34 | < 0.05 | <0.05 | 112 | 3.55 | 1.71 | <0.05 | 0.26 | 21.8 | | | | |
| Apr-07 | 504 | 8.24 | 286 | 211 | 4.41 | <0.05 | <0.05 | 47.5 | 3.74 | 0.95 | 6.60 | 0.15 | 11.0 | | | | |
| Nov-07 | 608 | 8.21 | 331 | 230 | 5.72 | < 0.05 | <0.05 | 119 | 2.77 | 1.20 | <0.05 | 0.01 | 22.1 | | | | |
| Apr-08 | 502 | 8.04 | 283 | 243 | 4.98 | < 0.05 | < 0.05 | 40.5 | 3.59 | 1.13 | < 0.05 | 0.05 | 10.9 | | | İ | |
| Oct-08 | 724 | 7.88 | 418 | 313 | 5.80 | <0.05 | <0.05 | 64.9 | 4.80 | 1.44 | 0.08 | 1.19 | 14.4 | | | | |
| Apr-09 | 499 | 8.08 | 299 | 234 | 4.10 | <0.05 | <0.05 | 34.5 | 3.39 | 1.01 | <0.02 | 0.10 | 11.7 | | | | |
| Nov-09 | 553 | 7.76 | 346 | 267 | 3.69 | < 0.05 | <0.05 | 44.3 | 3.33 | 1.65 | <0.05 | 0.01 | 19.4 | | | | |
| Apr-10 | 577 | 8.06 | 332 | 304 | 4.08 | <0.05 | <0.05 | 35.6 | 3.29 | 1.26 | <0.02 | 0.09 | 12.6 | | | | |
| Nov-10 | 611 | 7.89 | 373 | 298 | 4.09 | <0.05 | <0.05 | 92.3 | 3.62 | 1.83 | <0.02 | 0.07 | 16.9 | | | | |
| Apr-11 | 546 | 7.89 | 310 | 235 | 4.95 | <0.05 | <0.05 | 57.2 | 2.97 | 1.19 | 0.02 | 0.04 | 16.3 | | | | |
| Nov-11 | 529 | 7.94 | 340 | 249 | 4.04 | < 0.05 | < 0.05 | 87.2 | 3.02 | 1.39 | 0.04 | <0.01 | 19.8 | | | | |
| Apr-12 | 497 | 7.89 | 269 | 253 | 3.55 | < 0.05 | < 0.05 | 25.7 | 2.54 | 1.00 | <0.02 | 0.13 | 12.6 | | | | |
| Nov-12 | 636 | 8.12 | 380 | 207 | 5.99 | < 0.05 | <0.05 | 190 | 3.35 | 1.61 | <0.02 | 0.04 | 13.9 | | | | |
| Apr-13 Nov-13 | 509 559 | 8.00 | 270 273 | 222 209 | 5.66 | <0.05 <0.10 | <0.05 <0.10 | 40.7 75.3 | 2.78 2.76 | 0.99 1.19 | 0.03 <0.02 | 0.02 0.04 | 11.4 19.8 | | | | |
| May-14 | 540 | 7.98 7.89 | 292 | 263 | 5.73 5.38 | <0.10 | <0.10 | 26.3 | 3.07 | 1.19 | 0.18 | 0.04 | 12.7 | | | | |
| Oct-14 | 678 | 7.81 | 397 | 371 | 6.54 | <0.05 | <0.05 | 11.0 | 3.58 | 1.42 | 0.18 | 0.03 | 22.3 | | | | |
| Apr-15 | 618 | 7.75 | 328 | 341 | 6.70 | <0.25 | <0.25 | 3.0 | 3.22 | 1.03 | <0.02 | 0.13 | 16.4 | | | | |
| Oct-15 | 716 | 7.88 | 411 | 324 | 7.52 | <0.25 | <0.25 | 71.9 | 3.87 | 1.65 | 0.05 | 4.06 | 15.2 | | | | |
| Apr-16 | 530 | 7.97 | 295 | 259 | 5.58 | < 0.05 | <0.05 | 36.6 | 3.27 | 1.44 | <0.02 | 4.00 | 13.4 | | | | |
| Nov-16 | 690 | 7.31 | 345 | 277 | 8.68 | <0.25 | <0.25 | 102 | 3.89 | 1.79 | <0.02 | 0.05 | 16.6 | | | | |
| Apr-17 | 513 | 8.13 | 266 | 247 | 5.81 | <0.05 | < 0.05 | 17.5 | 3.54 | 1.34 | <0.02 | 1.70 | 11.5 | | | | |
| Nov-17 | 702 | 7.78 | 384 | 331 | 11.5 | <0.10 | <0.10 | 52.8 | 5.03 | 2.07 | <0.02 | 0.09 | 19.6 | | | | |
| May-18 | 620 | 7.76 | 320 | 320 | 10.0 | <0.10 | <0.010 | <1.0 | 4.7 | 1.8 | <0.050 | <0.1 | 13.0 | | | | |
| Nov-18 | 663 | 7.77 | 328 | 321 | 10.3 | <0.05 | <0.05 | 43.2 | 5.04 | 2.77 | <0.02 | 0.058 | 19.5 | | | | |
| Apr-19 | 589 | 7.81 | 299 | 341 | 6.87 | <0.05 | <0.05 | 6.97 | 4.35 | 2.40 | <0.02 | 0.040 | 12.3 | | | | |
| Oct-19 | 680 | 7.80 | 376 | 352 | 8.21 | <0.10 | <0.10 | 41.1 | 5.05 | 3.88 | 0.02 | 0.19 | 25.4 | | | | |
| Apr-20 | 747 | 7.64 | 348 | 347 | 9.06 | <0.10 | <0.10 | 2.56 | 4.07 | 3.12 | <0.02 | 0.15 | 21.8 | | 92.4 | 28.5 | |
| Oct-20 | 671 | 7.83 | 365 | 364 | 10.3 | <0.10 | <0.10 | 21.8 | 4.99 | 3.70 | 0.05 | 0.31 | 27.8 | | 97.0 | 29.8 | |
| May-21 | 668 | 7.91 | 322 | 334 | 9.06 | <0.10 | <0.10 | 2.16 | 3.92 | 3.40 | 0.03 | 0.48 | 17.7 | | 85.9 | 26.1 | |
| Oct-21 | 819 662 | 7.62 7.29 | 438 314 | 441 329 | 8.44 8.74 | <0.05 0.09 | <0.05 <0.05 | 2.60 4.36 | 5.42 4.23 | 4.59 3.43 | 0.06 0.07 | 0.042 0.51 | 82.8 17.4 | - | 84.4 | 25.0 | |
| Apr-22 Sep-22 | 866 | 7.29 | 361 | 329 414 | 7.06 | <0.09 | 0.05 | 13.6 | 4.23 | 4.49 | 0.07 | 0.51 | 27.0 | - | 97.5 | 25.0 | |
| Apr-23 | 550 | 7.60 | 307 | 259 | 5.85 | 0.06 | <0.05 | 5.0 | 3.63 | 4.49 | 0.10 | 0.40 | 25.6 | | 83.2 | 24.1 | 0.023 |
| Nov-23 | 690 | 7.47 | 349 | 420 | 6.54 | < 0.05 | <0.05 | 6.57 | 3.90 | 6.05 | <0.02 | 0.37 | 20.8 | | 92.0 | 28.9 | 0.023 |
| Apr-24 | 548 | 7.66 | 292 | 330 | 6.42 | <0.05 | <0.05 | 2.67 | 3.98 | 3.89 | 0.06 | 0.47 | 26.2 | 1 | 76.7 | 24.4 | 0.075 |
| Nov-24 | 742 | 7.77 | 402 | 433 | 8.16 | 0.12 | <0.05 | 8.35 | 3.89 | 5.90 | 0.07 | 0.15 | 27.2 | | 114 | 28.4 | 0.052 |
| | | | | | 0.10 | U. 12 | 2.00 | 2.00 | 0.00 | 2.00 | 0.01 | 0.10 | -/ | | | | 0.302 |
| Average | 619 | 7.84 | 338 | 298 | 7.41 | <0.10 | <0.10 | 42.4 | 3.80 | 2.29 | 0.21 | 0.74 | 18.1 | 0.0019 | 91.5 | 27.1 | 0.04 |
| | 83.6 | 0.21 | 45.7 | 66.4 | 3.70 | NA | NA | 41.5 | 0.74 | 1.43 | 1.07 | 1.72 | 10.54 | 0.0023 | 10.86 | 2.17 | 0.03 |

| | | | | | 111010 | NOAL | GIVOC | INDVVA | C ALBERTO 1250 | UALITY | DESCRIPTION NOT | V V = 1 | | | | | |
|-----------|--------------|-----------|----------|------------|----------|---------|---------|----------|----------------|-----------|-----------------|---------|------|---------|---------|-----------|--------|
| | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| opws | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.30 | 5.0 | NV | NV | NV | NV |
| ODWS | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 901 | | 466 | | 57.9 | | | | | | | 0.74 | 12.6 | <0.001 | | | |
| Jan-89 | 629 | | 331 | | 21.2 | | | | | | | 1.20 | 9.0 | 0.0215 | | | |
| Dec-89 | 900 | | | î. | 54.1 | | | | | | | | | | | | |
| Nov-94 | 600 | | 349 | | 6.9 | | | | | | | 0.19 | 12.8 | <0.001 | | | |
| Oct-95 | 551 | | 312 | | 6.6 | | | | | | | 1.04 | 18.1 | 0.0085 | | | |
| Dec-96 | 366 | | 188 | | 5.4 | | | | | | | 0.08 | 13 | <0.001 | | | |
| Oct-97 | 603 | | 306 | | 3.7 | | | | | | | 1.62 | 21 | <0.001 | | | |
| Oct-98 | 538 | | 314 | | 2.5 | | | | | | | 0.99 | 21 | <0.001 | | | |
| Nov-99 | 682 | | 403 | | 7.9 | | | | | | | 1.29 | 29 | <0.001 | | | |
| Oct-00 | 626 | | 365 | | 4.3 | | | | | | | 0.66 | 17 | <0.001 | | | |
| Nov-01 | 541 | | 302 | | 5.0 | | | | | | | 0.42 | 15 | <0.001 | | | |
| Dec-02 | 650 | | 375 | | 4.4 | | | | | | | 0.43 | 13.2 | <0.001 | | | |
| Nov-04 | 861 | | 529 | | 4.9 | | | | | | | 0.17 | 11.0 | <0.001 | | | |
| Nov-12 | 535 | 8.13 | 305 | 221 | 7.45 | < 0.05 | <0.05 | 91.6 | 5.45 | 0.74 | 0.04 | 0.19 | 12.2 | | | | |
| Apr-13 | 475 | 7.85 | 246 | 225 | 5.73 | < 0.05 | <0.05 | 17.2 | 4.62 | 0.49 | 0.06 | 0.28 | 9.3 | | | | |
| Nov-13 | 575 | 8.04 | 283 | 268 | 8.99 | <0.10 | <0.10 | 25.5 | 6.98 | 0.69 | 0.05 | 0.32 | 14.5 | | | | |
| May-14 | 522 | 7.85 | 270 | 270 | 8.13 | 0.17 | <0.05 | 5.4 | 6.15 | 0.58 | 0.17 | 0.77 | 11.9 | | | | |
| Oct-14 | 505 | 8.01 | 272 | 275 | 5.96 | <0.10 | <0.10 | 6.0 | 4.90 | 0.61 | 0.08 | 0.13 | 4.7 | | | | |
| Apr-15 | 525 | 7.93 | 266 | 281 | 6.03 | < 0.05 | <0.05 | 4.9 | 5.51 | 0.50 | 0.05 | 0.35 | 6.1 | | | | |
| Oct-15 | 561 | 7.87 | 301 | 281 | 5.17 | <0.10 | <0.10 | 23.0 | 6.24 | 0.59 | 0.04 | 9.32 | 6.7 | | | | |
| Apr-16 | 468 | 7.92 | 250 | 252 | 4.63 | 0.21 | <0.05 | 8.9 | 4.62 | 0.45 | <0.02 | | 9.3 | | | | |
| Nov-16 | 608 | 7.80 | 307 | 249 | 6.15 | 0.13 | <0.05 | 67.8 | 5.01 | 0.78 | <0.02 | 0.20 | 11.8 | | | | |
| Apr-17 | 448 | 7.87 | 230 | 222 | 4.11 | 0.08 | <0.05 | 8.6 | 4.3 | 0.46 | 0.05 | 8.65 | 9.2 | | | | |
| Nov-17 | 522 | 7.91 | 277 | 279 | 4.47 | <0.10 | <0.10 | 7.1 | 4.66 | 0.78 | 0.06 | 0.13 | 6.4 | | | | |
| May-18 | 490 | 7.61 | 260 | 260 | 4.1 | <0.10 | <0.010 | 6.2 | 3.9 | 0.57 | 0.14 | 0.13 | 4.8 | | | | |
| Nov-18 | 562 | 7.86 | 270 | 284 | 6.46 | 0.10 | <0.05 | 13.8 | 5.16 | 0.73 | <0.02 | 0.017 | 11.6 | | | | |
| Apr-19 | 444 | 7.76 | 221 | 248 | 5.89 | <0.05 | <0.05 | 7.10 | 3.87 | 0.54 | 0.03 | 0.020 | 7.1 | | | | |
| Oct-19 | 525 | 7.80 | 278 | 295 | 4.21 | <0.05 | <0.05 | 7.77 | 4.70 | 0.83 | 0.03 | 0.070 | 16.5 | | | | |
| Apr-20 | 565 | 7.58 | 246 | 259 | 3.60 | 0.11 | <0.05 | 8.70 | 3.75 | 0.53 | 0.03 | 0.093 | 10.1 | | 69.9 | 17.3 | |
| Oct-20 | 546 | 7.97 | 296 | 310 | 4.93 | 0.13 | <0.05 | 3.74 | 4.60 | 0.80 | 0.24 | <0.010 | 14.8 | | 83.2 | 21.5 | |
| May-21 | 519 | 7.87 | 256 | 268 | 3.72 | 0.12 | <0.05 | 1.68 | 4.01 | 0.55 | 0.03 | 0.64 | 11.3 | | 74.1 | 17.2 | |
| Apr-22 | 623 | 7.72 | 315 | 331 | 4.75 | 0.12 | < 0.05 | 5.36 | 4.45 | 0.61 | 0.03 | 0.37 | 14.2 | | 91.8 | 20.9 | -0.040 |
| Apr-23 | 456 | 7.72 | 220 | 197 | 3.00 | 0.17 | < 0.05 | 23.9 | 3.06 | 0.82 | <0.02 | 0.52 | 18.8 | | 63.1 | 15.2 | <0.010 |
| Nov-23 | 608 | 7.46 | 305 | 337 | 4.56 | 0.12 | <0.05 | 26.0 | 3.80 | 2.05 | 0.04 | 0.23 | 28.3 | | 87.9 | 20.7 | 0.030 |
| Apr-24 | 507 | 7.85 | 288 | 306 | 3.12 | 0.06 | < 0.05 | 10.7 | 3.45 | 0.65 | 0.08 | 0.34 | 33.9 | | 84.7 | 18.5 | <0.010 |
| Nov-24 | 616 | 7.90 | 292 | 392 | 4.07 | 0.10 | <0.05 | 24.6 | 3.42 | 0.76 | 0.11 | 0.045 | 28.5 | | 92.8 | 14.6 | 0.015 |
| Δυστασο | E74 | 7.04 | 200 | 274 | 0.4 | 0.00 | <0.10 | 17.0 | 4.64 | 0.70 | 0.06 | 0.00 | 44.4 | 0.0000 | 90.0 | 18.2 | 0.00 |
| Average | 574 | 7.84 | 300 | 274 | 8.4 | 0.09 | <0.10 | 17.6 | 4.64 | 0.70 | 0.06 | 0.96 | 14.1 | 0.0029 | 80.9 | | 0.02 |
| Std. Dev. | 116 | 0.15 | 67 | 43 | 12.1 | 0.05 | NA | 21.4 | 0.97 | 0.32 | 0.06 | 2.11 | 7.1 | 0.0063 | 10.78 | 2.63 | N/A |

| | | | | | HISTO | at the trust tiers | C00125 10025 16 | | C 60000000 00000 | int is the court of the | DATA: | VV-Z | | | | | |
|------------------|--------------|--------------|-------------|-------------------|--------------|--------------------|-----------------|------------|------------------|-------------------------|----------------|----------------|------------|----------|---------|------|--------|
| | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | | Iron | DOC | Phenols | Calcium | | Boron |
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| odws | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| ODWS | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 1530 | | 911 | | 1.7 | | | | | | | 1.16 | 8.0 | <0.001 | ĺ | | |
| Jan-89 | 1940 | | 1232 | | 1.7 | l i | | | | | | 2.50 | 5.9 | 0.0010 | | | |
| Jul-90 | 2130 | | 1942 | | 6.7 | | | | | | | 94* | 7.2 | 0.0015 | | | |
| Nov-94 | 2040 | | 1375 | | 0.9 | | | | | | | 2.73 | 5.4 | <0.001 | | | |
| Oct-95 | 1630 | | 1055 | | 0.7 | | | | | | | 1.83 | 7 | 0.0057 | | | |
| Oct-95 Dup | 1630 | | 1049 | | 0.7 | | | | | | | 1.85 | 7 | 0.0020 | | | |
| Dec-96 | 1608 | | 765 | | 2.8 | | | | | | | 2.00 | 5 | <0.001 | | | |
| Oct-97 | 1440 | | 878 | | 2.9 | | | | | | | 1.94 | 10 | <0.001 | | | |
| Nov-99 | 988 | | 548 | | 2.3 | | | | | | | 0.01 | 13 | <0.001 | | | |
| Oct-00 | 2732 | | 2080 | | 3.0 | | | | | | | 9.38 | 18 | <0.001 | | | |
| Nov-01 | 1605 | | 1143 | | 2.1 | | | | | | | 0.54 | 3 | <0.001 | | | |
| Dec-02 | 1700 | | 1088 | | 1.5 | | | | | | | 0.130 | 4.8 | <0.001 | | | |
| Oct-03 | 3170 | | 2730 | | 2.7 | | | | | | | 0.022 | 22 | <0.001 | | | |
| Nov-04 | 3200 | | 2710 | | 2.6 | | | | | | | 0.008 | 3.8 | <0.001 | | | |
| Nov-05 | 2430 | | 1800 | 0.00 | 2.7 | | | | | | | 0.56 | 16.1 | <0.001 | | | |
| Apr-06 | 2290 | 7.64 | 1650 | 464 | 1.18 | 0.94 | <0.05 | 1100 | 7.12 | | <0.05 | 6.13 | 3.0 | | | | |
| Oct-06 | 1930 | 7.65 | 1340 | 395 | 2.16 | <0.05 | <0.05 | 1030 | 5.81 | 3.69 | 0.08 | 0.72 | 3.7 | ļ | | | |
| Apr-07 | 2470 | 7.89 | 1780 | 420 | 1.45 | < 0.05 | <0.05 | 1360 | 6.81 | 4.10 | 0.17 | 0.81 | 2.9 | | | | |
| Nov-07 | 2100 | 7.87 | 1500 | 382 | 0.8 | < 0.05 | < 0.05 | 1400 | 4.51 | 2.58 | 0.07 | <0.005 | 5.0 | | | | |
| Apr-08 | 1750 | 7.82 | 1260 | 400 | 1.4 | <0.05 | <0.05 | 933 | 5.24 | 3.51 | <0.05 | <0.010 | 2.8 | | | | |
| Oct-08 | 3290 | 7.71 | 2740 | 469 | 1.67 | 0.11 | <0.05 | 1760 | 9.99 | 7.19 | 0.35 | <0.01 | 3.8 | | | | |
| Apr-09 | 1410 | 7.85 | 905 | 374 | 1.74 | < 0.05 | < 0.05 | 507 | 3.88 | 1.76 | <0.02 | <0.010 | 3.1 | | | | |
| Nov-09 | 1420 | 7.95 | 935 | 429 | 1.30 | <0.01 | < 0.05 | 471 538 | 4.17 | 2.46 2.34 | <0.05 | <0.01 | 4.7 2.5 | - | | | |
| Apr-10 | 1360 | 8.06 | 866 | 376 | 0.79 | <0.05 | <0.05 | | 3.19 | | 0.02 | <0.01 | | ļ | - | | |
| Nov-10 | 1510 902 | 7.81 7.97 | 1110 533 | 412 351 | 4.47 2.13 | <0.05 <0.05 | <0.05 <0.05 | 729 | 4.59 2.29 | 3.30 | <0.02 <0.02 | <0.01 <0.01 | 2.8 | 1 | | | |
| Apr-11 Nov-11 | 731 | 8.05 | 482 | 360 | 3.21 | <0.05 | <0.05 | 180 154 | 2.29 | 1.26 1.52 | 0.02 | <0.01 | 2.3 3.0 | | , | | - |
| Apr-12 | 694 | 7.94 | 376 | 302 | 1.77 | <0.05 | <0.05 | 96.1 | 1.54 | 1.23 | <0.02 | 0.04 | 2.1 | ł | | | |
| Nov-12 | 780 | 8.23 | 490 | 273 | 5.04 | <0.05 | <0.05 | 227 | 2.45 | 1.80 | 0.04 | <0.04 | 4.1 | 1 | | | |
| Apr-13 | 607 | 8.00 | 321 | 247 | 1.82 | 0.06 | <0.05 | 78.9 | 1.30 | 1.85 | 0.04 | <0.01 | 2.7 | ł | - | | |
| Nov-13 | 703 | 8.04 | 361 | 273 | 2.43 | <0.25 | <0.05 | 108 | 1.46 | 2.12 | <0.02 | <0.01 | 4.0 | | | | |
| May-14 | 602 | 7.88 | 317 | 250 | 1.37 | <0.10 | <0.10 | 74.0 | 1.13 | 1.80 | 0.17 | 0.02 | 2.8 | † | | | |
| Oct-14 | 860 | 8.00 | 487 | 359 | 5.38 | <0.25 | <0.25 | 135 | 1.91 | 1.75 | 0.06 | <0.01 | 2.7 | 1 | | | |
| Apr-15 | 844 | 7.88 | 436 | 404 | 4.07 | <0.25 | <0.25 | 79.3 | 1.76 | 1.22 | <0.02 | <0.01 | 2.5 | ł | | | |
| Oct-15 | 961 | 8.02 | 541 | 300 | 8.18 | <0.25 | <0.25 | 248 | 2.94 | 2.04 | 0.03 | 2.11 | 2.9 | | | | 1 |
| Apr-16 | 622 | 8.02 | 351 | 319 | 2.44 | <0.10 | <0.10 | 35.9 | 1.96 | 0.88 | 0.31 | | 2.9 | Ì | | | |
| Nov-16 | 891 | 8.19 | 493 | 299 | 4.88 | <0.25 | <0.25 | 194 | 2.95 | 1.77 | <0.02 | <0.01 | 4.0 | Ì | | | |
| Apr-17 | 347 | 8.14 | 178 | 178 | 0.41 | <0.05 | <0.05 | 6.1 | 0.64 | 1.83 | <0.02 | 12.1 | 3.4 | Ī | İ | | |
| Nov-17 | 794 | 8.01 | 441 | 379 | 2.03 | <0.25 | <0.25 | 98.4 | 2.11 | 1.37 | <0.02 | <0.01 | 3.5 | | | | |
| May-18 | 450 | 8.05 | 240 | 240 | <1.0 | <0.10 | <0.010 | 13 | 0.93 | 0.63 | < 0.050 | <0.1 | 1.6 | | | | |
| Nov-18 | 741 | 7.96 | 377 | 378 | 1.62 | <0.05 | <0.05 | 40.9 | 1.69 | 1.25 | <0.02 | <0.010 | 2.3 | | | | |
| Apr-19 | 456 | 7.77 | 230 | 271 | 0.71 | <0.05 | <0.05 | 5.16 | 0.85 | 0.49 | <0.02 | <0.01 | 2.0 | | | | |
| Oct-19 | 620 | 7.87 | 336 | 341 | 1.08 | <0.10 | <0.10 | 26.1 | 1.32 | 1.25 | <0.02 | <0.01 | 3.9 | | | | |
| Apr-20 | 515 | 7.70 | 237 | 239 | 0.66 | <0.05 | <0.05 | 7.08 | 0.83 | 1.15 | <0.02 | 0.032 | 3.0 | | 73.5 | 13.0 | |
| Oct-20 | 626 | 8.05 | 456 | 347 | 1.68 | <0.10 | <0.10 | 22.8 | 1.74 | 1.29 | <0.02 | 0.075 | 5.2 | | 142 | 24.7 | |
| May-21 | 381 | 8.03 | 185 | 193 | 0.34 | <0.05 | <0.05 | 3.19 | 0.82 | 2.71 | <0.02 | 0.057 | 5.5 | | 59.6 | 8.87 | |
| Oct-21 | 649 | 7.72 | 337 | 332 | 0.52 | <0.05 | <0.05 | 10.7 | 1.30 | 1.57 | <0.02 | <0.010 | 72.6 | | | | |
| Apr-22 | 603 | 7.75 | 312 | 330 | 0.31 | <0.05 | <0.05 | 7.00 | 1.01 | 0.70 | <0.02 | 0.051 | 2.9 | | 94.7 | 18.4 | |
| Sep-22 | 739 | 7.50 | 347 | 323 | 2.27 | 0.34 | 0.10 | 51.7 | 0.93 | 1.84 | 0.04 | 0.021 | 3.6 | | 106 | 20.0 | |
| Apr-23 | 641 | 7.63 | 361 | 326 | 1.62 | < 0.05 | <0.05 | 7.6 | 0.88 | 0.61 | <0.02 | <0.010 | 3.1 | | 112 | 19.8 | <0.010 |
| Nov-23 | 726 | 7.75 | 408 | 448 | 7.20 | <0.05 | <0.05 | 8.88 | 1.80 | 1.79 | <0.02 | 0.011 | 3.7 | | 128 | 21.4 | 0.032 |
| Apr-24 | 672 | 7.80 | 374 | 411 | 1.72 | <0.05 | <0.05 | 4.0 | 1.24 | 0.71 | 0.02 | <0.020 | 4.8 | _ | 116 | 20.4 | <0.010 |
| Nov-24 | 790 | 7.95 | 374 | 421 | 7.52 | 0.13 | <0.05 | 48.7 | 2.68 | 1.29 | <0.02 | <0.020 | 4.6 | ļ | 115 | 21.0 | 0.022 |
| Augus | 4000 | 7.00 | 001 | 0.10 | 0.00 | 0.00 | -0.05 | 0.11 | 0.04 | 4.04 | 0.05 | 0.00 | | 0.0010 | 405.0 | 10.0 | 0.00 |
| Average | 1288 | 7.90 | 864 | 343 | 2.39 | 0.08 | <0.25 | 311 | 2.64 | 1.91 | 0.05 | 0.92 | 6.3 | 0.0010 | 105.2 | 18.6 | 0.03 |
| Std. Dev. | 784 | 0.17 | 680 | 73.1 | 1.88 | 0.16 | NA | 464 | 2.09 | 1.24 | 0.08 | 2.30 | 10.1 | 0.0014 | 25.8 | 4.79 | N/A |

| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|-----------|--------------|-----------|----------|------------|----------|---------|---------|----------|----------|-----------|---------|------|------|---------|---------|-----------|-------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| ODWS | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| ODWS | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Dec-88 | 935 | | 476 | | 47.2 | | | | | | | 0.33 | 1.5 | 0.0010 | | | |
| Jan-89 | 918 | | 477 | | 34.1 | | | Î | | | | 0.20 | 5.9 | 0.0015 | | | |
| Dec-89 | 1064 | | | | 58.1 | | | | | | | | | | | | |
| Jul-90 | 883 | | 440 | | 31.4 | | | | | | | 0.48 | 5.8 | 0.0010 | | | |
| Jan-93 | 750 | | 639 | | | | | | | | | 0.66 | 5.1 | 0.0095 | | | |
| Jan-94 | 1255 | | 676 | | 50.7 | | | Î | | | | 0.55 | 6.5 | 0.0139 | | | |
| Nov-94 | 1147 | | 672 | | 34.7 | | | | | | | 0.39 | 4.0 | 0.0034 | | | |
| Oct-95 | 1177 | | 676 | | 25.8 | | | | | | | 0.41 | 6.6 | 0.0055 | | | |
| Dec-96 | 1183 | | 606 | | 19.3 | | | | | | | 0.42 | 6.0 | <0.001 | | | |
| Oct-97 | 1241 | | 672 | | 21.7 | | | Î | | | | 0.29 | <1 | 0.003 | | | |
| Oct-98 | 1120 | | 624 | | 28.0 | | | | | | | 0.10 | 20 | 0.004 | · | | |
| Nov-99 | 1533 | | 678 | | 30.6 | | | | | | | 0.31 | 20 | 0.127 | | | |
| Oct-00 | | , | • | | | | | Replaced | by W3/03 | | | | | • | · | | |
| Average | 1101 | NA | 603 | NA | 34.7 | NA | NA | NA | NA | NA | NA | 0.38 | 8.14 | 0.017 | NA | NA | NA |
| Std. Dev. | 208 | NA | 92.8 | NA | 12.3 | NA | NA | NA | NA | NA | NA | 0.16 | 6.43 | 0.039 | NA | NA | NA |

| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|---------------------|--------------|-----------|------------|------------|----------|--------------|---------|----------|--------|-----------|---------|---------|-------------|---------|------------|-----------|-------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| ODWO | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| ODWS | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | 6.5 - 8.5 | 527 | 404 | 128 | 3.33 | 0.25 | 255 | 101 | NV | NV | 0.17 | 4.87 | NV | NV | NV | NV |
| Oct-03 | 1230 | 0.0 | 685 | | 48.6 | | 3.23 | | | | | 10.3 | 33 | <0.001 | | | |
| Nov-04 | 1120 | | 661 | | 30.8 | | | | | | | 16.4 | 7.0 | <0.001 | | | |
| Nov-05 | 1200 | | 638 | | 41.0 | | | | | | | 20.6 | 13.5 | <0.001 | | | |
| Apr-06 | 1440 | 7.81 | 789 | 489 | 47.7 | < 0.05 | < 0.05 | 238 | 16.4 | | 4.96 | 34.6 | 8 | | | | |
| Oct-06 | 1220 | 7.64 | 619 | 530 | 49.1 | < 0.05 | < 0.05 | 167 | 27.6 | 13.9 | 2.17 | 0.33 | 13.1 | | | | |
| Apr-07 | 1240 | 7.94 | 690 | 514 | 31.0 | < 0.05 | < 0.05 | 167 | 23.9 | 14.6 | 4.95 | 0.35 | 7.4 | | | | |
| Nov-07 | 1130 | 7.73 | 563 | 468 | 38.0 | < 0.05 | <0.05 | 141 | 21.9 | 14.5 | 0.47 | < 0.005 | 12.8 | | | | |
| Apr-08 | 1070 | 7.78 | 575 | 415 | 35.1 | <0.05 | < 0.05 | 195 | 16.4 | 12.3 | 7.18 | 0.59 | 7.4 | | | | |
| Oct-08 | 1310 | 7.64 | 309 | 532 | 33.9 | < 0.05 | <0.05 | 133 | 8.43 | 4.77 | 6.37 | 0.20 | 6.8 | | | | |
| Apr-09 | 1080 | 7.82 | 597 | 431 | 17.1 | < 0.05 | <0.05 | 178 | 16.4 | 7.61 | 0.84 | <0.010 | 5.0 | | | | |
| Nov-09 | 1110 | 7.69 | 630 | 571 | 19.9 | < 0.05 | <0.05 | 76.9 | 19.8 | 10.6 | 1.27 | 0.01 | 6.6 | | | | |
| Apr-10 | 992 | 8.01 | 523 | 483 | 20.9 | <0.05 | < 0.05 | 91.2 | 18.8 | 11.3 | 2.25 | <0.01 | 7.2 | | | | |
| Nov-10 | 816 | 7.73 | 417 | 411 | 21.0 | <0.05 | <0.05 | 85.0 | 10.9 | 12.7 | 5.53 | <0.01 | 6.4 | | | | |
| Apr-11 | 856 | 7.77 | 431 | 393 | 19.8 | < 0.05 | < 0.05 | 66.7 | 13.3 | 13.3 | 0.06 | < 0.01 | 7.9 | | | | |
| Nov-11 | 741 | 7.86 | 422 | 399 | 16.1 | < 0.05 | <0.05 | 63.9 | 8.14 | 12.1 | 1.73 | 0.11 | 5.1 | | | | |
| Apr-12 | 1200 | 7.74 | 651 | 673 | 14.0 | < 0.05 | < 0.05 | 36.9 | 9.28 | 10.2 | 1.16 | 0.030 | 4.6 | | | | |
| Nov-12 | 850 | 7.85 | 470 | 410 | 24.6 | <0.05 | <0.05 | 84.0 | 12.9 | 10.9 | 0.34 | 1.06 | 8.2 | | | | |
| Apr-13 | 924 | 7.97 | 462 | 409 | 18.8 | <0.25 | <0.25 | 66.6 | 14.5 | 11.7 | 0.49 | 1.50 | 4.4 | | | | |
| Nov-13 | 1330 | 7.61 | 617 | 658 | 34.1 | < 0.5 | <0.5 | 32.6 | 25.7 | 15.5 | 1.60 | 0.76 | 7.9 | | | | |
| May-14 | 1070 | 7.55 | 506 | 520 | 23.5 | <0.25 | <0.25 | 44.9 | 24.4 | 14.9 | 3.26 | 0.030 | 6.0 | | | | |
| Oct-14 | 1180 | 7.72 | 534 | 610 | 32.4 | <0.25 | <0.25 | 22.9 | 25.7 | 16.9 | 7.6 | 0.010 | 7.2 | | | | |
| Apr-15 | 1270 | 7.59 | 575 | 678 | 34.8 | < 0.25 | <0.25 | 18.1 | 23.7 | 18.3 | 10.2 | <0.01 | 7.4 | | | | |
| Oct-15 | 1060 | 7.87 | 475 | 523 | 25.5 | 0.57 | <0.25 | 27.7 | 20.2 | 16.8 | 9.2 | 47.5 | 7.4 | | | | |
| Apr-16 | 877 | 7.86 | 389 | 416 | 21.7 | <0.25 | <0.25 | 47.0 | 15.4 | 14.6 | <0.02 | | 10.0 | | | | |
| Nov-16 | 1350 | 7.90 | 622 | 669 | 37.2 | <0.25 | <0.25 | 20.0 | 31.3 | 14.5 | 6.1 | 0.020 | 8.2 | | | | |
| Apr-17 | 956 | 7.97 | 421 | 401 | 28.6 | <0.25 | <0.25 | 83.3 | 19.8 | 12.7 | 6.8 | 39.9 | 5.0 | | | | |
| Nov-17 | 1280 | 7.65 | 626 | 663 | 38.6 | <0.25 | <0.25 | 25.9 | 34.8 | 13.0 | 5.38 | 0.03 | 9.4 | | | | |
| May-18 | 960 | 7.49 | 430 | 420 | 35.0 | <0.10 | <0.010 | 40 | 16 | 14 | 7.9 | <0.1 | 5.3 | | | | |
| Nov-18 | 1410 | 7.73 | 644 | 734 | 44.6 | <0.05 | <0.05 | 11.8 | 34.9 | 14.5 | 5.32 | <0.010 | 9.1 | | | | |
| Apr-19 | 968 | 7.69 | 393 | 526 | 20.5 | < 0.05 | <0.05 | 25.1 | 22.3 | 14.4 | 7.60 | 0.20 | 7.7 | | | | |
| Oct-19 | 1020 | 7.84 | 496 | 568 | 20.2 | 0.28 | <0.25 | 9.67 | 24.4 | 14.8 | 8.45 | <0.01 | 9.9 | | 100 | | |
| Apr-20 | 1090 | 7.56 | 386 | 483 | 19.4 | <0.25 | <0.25 | 17.8 | 20.2 | 15.0 | 10.6 | 0.013 | 9.3 | | 100 | 33.0 | |
| Oct-20 | 1080 | 7.82 | 498 | 582 | 29.5 | < 0.25 | < 0.25 | 9.62 | 27.0 | 17.9 | 12.3 | <0.010 | 10.4 | | 129 | 42.7 | |
| May-21 | 1060 | 7.53 | 442 | 511 | 22.6 | < 0.25 | < 0.25 | 18.4 | 27.9 | 13.8 | 6.72 | 0.015 | 8.4 | - | 116 | 36.9 | |
| Oct-21 | 913 | 7.50 | 402 | 461 | 17.9 | < 0.05 | < 0.05 | 11.7 | 20.8 | 13.6 | 7.35 | <0.010 | 65.6 | | 110 | 20.0 | |
| Apr-22 | 1000 | 7.58 | 421 482 | 521 | 17.1 | 0.17 0.52 | <0.05 | 12.0 | 22.5 | 13.8 | 8.67 | 0.034 | 6.3 12.0 | | 119 135 | 30.0 | |
| Sep-22 | 1280 | 7.19 | | 605 | 23.8 | | 0.63 | 6.55 | 28.3 | 14.9 | 12.5 | 0.016 | | | | 35.3 | 0.070 |
| Apr-23 | 869 | 7.26 | 396 | 411 | 19.7 | <0.05 | < 0.05 | 21.6 | 20.3 | 12.6 | 8.30 | 0.016 | 14.2 | | 108 | 30.6 | 0.273 |
| Nov-23 | 956 | 7.17 | 308 | 522 | 21.6 | <0.05 | <0.05 | 19.9 | 19.4 | 18.9 | 11.4 | <0.010 | 8.0 | - | 82.1 | 25.1 | 0.349 |
| Apr-24 | 1040 | 7.52 | 416 | 529 | 19.1 | < 0.05 | <0.05 | 12.8 | 21.7 | 14.0 | 8.08 | <0.020 | 11.3 | | 113 | 32.4 | 0.363 |
| Nov-24 | 975 | 7.75 | 382 | 590 | 17.6 | 0.27 | <0.05 | 4.49 | 18.3 | 13.2 | 9.12 | <0.020 | 12.7 | | 109 | 26.6 | 0.362 |
| Augraga | 1000 | 7.00 | F40 | F40 | 07.6 | <0.0E | <0.0E | 61.4 | 20.6 | 12.6 | F 70 | 4.07 | 40.22 | <0.0005 | 110 | 20.5 | 0.2 |
| Average Std. Dov | 1086 171 | 7.69 | 512 | 519 | 27.6 | <0.25 | <0.25 | 61.4 | 20.6 | 13.6 | 5.79 | 4.37 | 10.32 | <0.0005 | 112 | 32.5 | 0.3 |
| Std. Dev. | 171 | 0.20 | 115 | 94 | 9.8 | NA | NA | 61.2 | 6.62 | 2.71 | 3.66 | 11.4 | 9.98 | NA | 15.6 | 5.37 | 0.04 |

| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Sodium | Potassium | Ammonia | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|-----------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|-----------|---------|--------|------|---------|---------|-----------|-------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| odws. | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| ODWS | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | NA | 543 | 375 | 130 | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV | NV | NV | NV |
| Dec-88 | 446 | | 241 | | 5.1 | | | | | | | 0.94 | 2.2 | <0.001 | | | |
| Jan-89 | 456 | | 234 | | 4.8 | | | | | | | 0.05 | 2.1 | <0.001 | | | |
| Dec-89 | 438 | | | | 4.5 | | | | | | | | | | | | |
| Jul-90 | 439 | | 229 | | 2.2 | | | | | | | 0.25 | 0.5 | <0.001 | | | |
| Jan-93 | 420 | | 261 | | | | | | | | | 0.04 | 1.8 | <0.001 | | | |
| Jan-94 | 430 | | 223 | | 2.8 | | | | | | | 0.02 | 0.9 | 0.0010 | | | |
| Oct-95 | 445 | | 230 | | 3.4 | | | | | | | 0.06 | 1.2 | <0.001 | | | |
| Dec-96 | 506 | | 277 | | 7.7 | | | | | | | <0.01 | <1 | 0.0010 | | | |
| Oct-97 | 529 | | 297 | | 4.9 | | | | | | | <0.01 | <1 | <0.001 | | | |
| Oct-98 | 554 | | 315 | | 3.7 | | | | | | | < 0.01 | 4.0 | <0.001 | | | |
| Nov-99 | | | | | | | | | DESTROY | ED | | • | • | - | • | | |
| Average | 466 | NA | 256 | NA | 4.34 | NA | NA | NA | NA | NA | NA | 0.15 | 1.52 | <0.001 | NA | NA | NA |
| Std. Dev. | 46.2 | NA | 33.2 | NA | 1.61 | NA | NA | NA | NA | NA | NA | 0.31 | 1.15 | NA | NA | NA | NA |

| Dave | | 01 | 14.11 | [[] | Allerites | AG PICTOR N. 701 | DATES TO THE CONTRACT OF THE C | 2 00 0000 101 10 | 200 Halla (2) HE, (2) | over the role. | UALITY | TODA SET SE SCHOOL COST | B-Z | D00 | Discourte | 0-1-1 | T 64 1 | D |
|------------------|-------|--------------|---------------|------------|--------------|------------------|--|------------------|-----------------------|----------------|--------------|-------------------------|------------------|--------------------|-----------|--------------|--|----------|
| | UNITS | Conductivity | pH | Hardness | | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
| - | UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| (| ODWS- | NV NA | 6.5-8.5 OG | 80-100 | 30-500 OG | 250 AO | 10 MAC | 1.0 MAC | 500 AO | 200 | NV | NV | 0.3 AO | 5.0 AO | NV | NV | NV NA | NV |
| | RUC | NV | NA NA | OG 543 | | 130 | 2.50 | | | AO 102 | NA NV | NA NV | 0.24 | 4.3 | NA NV | NA NV | NV NV | NA NV |
| D 00 | KUC | 681 | NA | 353 | 375 | 24.6 | 2.50 | 0.25 | 324 | 102 | NV | INV | | 2.6 | <0.001 | INV | NV | INV |
| Dec-88 | | 695 | | 382 | | 24.6 | | | | | | | 0.92 2.10 | 1.8 | <0.001 | | | |
| Jan-89 Dec-89 | | 660 | | 302 | | 23.9 | | | | | | | 2.10 | 1.0 | <0.001 | | | |
| Jul-90 | | 647 | - | 335 | | 22.2 | | | | 102 | | | 0.72 | 1.6 | <0.001 | | | |
| Jan-93 | - | 250 | | 384 | | 22.2 | | | | 102 | | | 0.72 | 2.3 | <0.001 | | | |
| Jan-94 | - | 700 | | 332 | | 34.6 | | _ | | | | | 0.84 | 2.7 | 0.0009 | | | |
| Jan-94 | Dup | 700 | | 331 | | 01.0 | | | | | | | 0.83 | 2.9 | 0.0094 | | | |
| Nov-94 | Вар | 539 | | 308 | | 10.4 | | | | | | | 0.62 | 3.1 | 0.0015 | | | |
| Nov-94 | Dup | 535 | | 306 | | 9.9 | | i i | | | | | 0.64 | 3.3 | <0.001 | | | |
| Oct-95 | | 499 | | 286 | | 2.9 | | | | | | | 0.61 | 3.9 | 0.0101 | | | |
| Dec-96 | | 488 | | 250 | | 4.9 | | | | | | | 0.46 | 2 | 0.0010 | | | |
| Oct-97 | | 496 | | 281 | | 4.4 | | | | | | | 0.49 | 2 | < 0.001 | | | |
| Oct-98 | | 547 | | 295 | | 11.6 | | | | | | | 0.48 | 6 | < 0.001 | | | |
| Nov-99 | | 492 | | 268 | | 3.7 | | | | | | | 0.52 | <1 | < 0.001 | | | |
| Oct-00 | | 497 | | 284 | | 3.8 | | | | | | | 0.44 | 6 | <0.001 | | | |
| Nov-01 | | 486 | | 247 | | 4.0 | | | | | | | 0.36 | 5 | <0.001 | | | |
| Dec-02 | | 506 | | 277 | | 4.1 | | | | | | | 0.42 | 3.1 | <0.001 | | | |
| Oct-03 | | 485 | | 284 | | 4.1 | | | | | | | 0.46 | 15 | <0.001 | | | |
| Nov-04 |] | 498 | | 298 | | 7.0 | | | | | | | 0.51 | 3.6 | <0.001 | | | |
| Nov-05 | | 529 | | 297 | | 4.2 | | | | | | | 0.50 | 7.9 | <0.001 | | | |
| Apr-06 | | 546 | 8.15 | 289 | 234 | 3.26 | <0.05 | <0.05 | 46.1 | 3.67 | | <0.05 | 1.55 | 4.0 | | | | |
| Oct-06 | | 541 | 8.07 | 285 | 243 | 17.9 | <0.05 | <0.05 | 45.4 | 5.77 | 1.19 | 0.12 | 0.16 | 2.4 | | | | |
| Apr-07 | | 662 | 8.25 | 349 | 283 | 26.9 | < 0.05 | <0.05 | 31.4 | 10.5 | 2.07 | 0.72 | 0.14 | 2.9 | | | | |
| Nov-07 | - | 588 | 8.19 | 304 | 250 | 17.7 | < 0.05 | < 0.05 | 43.7 | 5.38 | 1.27 | 0.09 | < 0.005 | 2.6 | ļ- | | | |
| Apr-08 | | 489 | 8.21 | 270 | 249 | 4.6 | < 0.05 | < 0.05 | 28.1 | 3.26 | 1.49 | 0.13 | <0.010 | 3.5 | | | | - |
| Oct-08 | | 752 | 7.96 | 388 | 300 | 34.7 | < 0.05 | <0.05 <0.05 | 35.4 | 14.2 | 2.03 | 0.31 | 0.064 0.024 | 3.6 | - | | | |
| Apr-09 | - | 496 569 | 8.10 8.01 | 290 332 | 244 263 | 3.54 16.3 | <0.05 <0.05 | <0.05 | 28.4 26.6 | 3.09 6.61 | 0.91 1.41 | <0.02 0.07 | < 0.024 | 4.0 4.9 | - | | | |
| Nov-09 Apr-10 | | 485 | 8.19 | 283 | 203 | 3.44 | <0.05 | <0.05 | 30.3 | 3.44 | 0.96 | 0.07 | <0.01 | 3.7 | | | | |
| Nov-10 | - | 447 | 8.03 | 261 | 254 | 3.95 | <0.05 | <0.05 | 30.0 | 3.06 | 0.86 | <0.02 | <0.01 | 4.8 | † | | | |
| Apr-11 | | 664 | 7.97 | 345 | 252 | 4.72 | <0.05 | <0.05 | 114.0 | 3.54 | 1.04 | 0.02 | <0.01 | 4.2 | ł — — — | | | |
| Nov-11 | - | 659 | 8.02 | 386 | 314 | 33.7 | <0.05 | <0.05 | 61.9 | 13.7 | 1.58 | 0.02 | <0.01 | 3.3 | | | | |
| Apr-12 | - | 532 | 8.02 | 279 | 255 | 6.80 | <0.05 | <0.05 | 32.5 | 4.27 | 0.90 | 0.03 | <0.01 | 3.7 | | | | |
| Nov-12 | - | 596 | 8.13 | 341 | 286 | 21.9 | <0.05 | <0.05 | 42.8 | 11.4 | 1.54 | 0.09 | <0.01 | 4.0 | | | | |
| Apr-13 | - 1 | 539 | 8.03 | 281 | 249 | 4.02 | <0.05 | <0.05 | 30.3 | 3.34 | 1.06 | 0.07 | <0.01 | 3.9 | | | | |
| Nov-13 | | 823 | 7.97 | 367 | 324 | 37.3 | <0.25 | <0.25 | 56.7 | 15.8 | 1.65 | 0.18 | <0.01 | 3.2 | ľ | | | |
| May-14 | | 514 | 7.88 | 273 | 245 | 4.5 | < 0.05 | < 0.05 | 28.9 | 3.14 | 1.01 | 0.21 | <0.01 | 4.3 | | | | |
| Oct-14 | 1 | 498 | 8.19 | 263 | 240 | 3.1 | <0.10 | <0.10 | 30.4 | 2.79 | 0.78 | 0.10 | 0.010 | 3.9 | | | | |
| Apr-15 | | 578 | 7.93 | 298 | 258 | 5.6 | < 0.05 | < 0.05 | 61.0 | 3.34 | 0.88 | 0.05 | <0.01 | 3.9 | | | | |
| Oct-15 | | 587 | 7.94 | 317 | 279 | 15.1 | <0.10 | <0.10 | 32.2 | 5.56 | 1.06 | 0.12 | 0.85 | 5.4 | | | | |
| Apr-16 | | 559 | 8.11 | 302 | 257 | 4.8 | <0.10 | <0.10 | 54.1 | 4.29 | 0.88 | 0.04 | | 4.4 | | | | |
| Nov-16 | | 881 | 8.14 | 413 | 380 | 56.0 | <0.25 | <0.25 | 38.9 | 21.4 | 1.86 | 0.22 | <0.01 | 4.4 | | | | |
| Apr-17 |] | 853 | 8.05 | 408 | 332 | 37.6 | <0.25 | <0.25 | 65.3 | 17.0 | 1.70 | 0.15 | 1.10 | 2.9 | | | | |
| Nov-17 | | 635 | 7.88 | 324 | 284 | 18.6 | <0.10 | <0.10 | 40.5 | 8.51 | 1.05 | 0.08 | <0.01 | 5.4 | | | | |
| May-18 | | 540 | 7.95 | 290 | 260 | 3.9 | <0.10 | <0.010 | 32.0 | 3.3 | 0.90 | 0.12 | <0.1 | 4.2 | | | ļ | |
| Nov-18 | | 653 | 7.64 | 301 | 296 | 23.8 | < 0.05 | <0.05 | 29.3 | 8.88 | 1.37 | 0.22 | 0.042 | 5.0 | ļ | | | |
| Apr-19 | | 548 | 7.86 | 270 | 283 | 4.79 | <0.05 | <0.05 | 34.7 | 3.99 | 0.91 | 0.07 | 0.010 | 4.4 | | | | |
| Oct-19 | | 543 | 7.72 | 296 | 266 | 8.10 | < 0.05 | < 0.05 | 36.3 | 4.06 | 0.87 | 0.08 | <0.01 | 5.1 | | 00.0 | 07.0 | |
| Apr-20 | - | 721 | 7.72 | 321 297 | 262 | 4.74 | <0.10 | <0.10 | 78.2 | 4.25 | 0.97 | 0.06 | 0.031 | 5.6 | - | 83.6 | 27.2 | |
| Oct-20 | | 550 623 | 8.00 7.98 | 297 | 275 267 | 7.15 7.12 | <0.05 <0.10 | <0.05 <0.10 | 39.4 44.6 | 4.76 | 0.93 0.99 | 0.07 0.03 | <0.010 <0.010 | 4.8 4.3 | - | 75.7 76.9 | 26.2 25.9 | |
| May-21 Oct-21 | - | 559 | 7.98 | 299 | 267 | 3.42 | <0.10 | <0.10 | 51.0 | 5.18 3.29 | 0.99 | 0.03 | <0.010 | 4.3 42.1 | - | 70.9 | ∠5.9 | |
| Apr-22 | + | 631 | 7.67 | 282 | 270 | 7.58 | <0.05 | <0.05 | 61.5 | 5.94 | 1.05 | 0.03 | 0.034 | 42.1 | - | 73.4 | 24.6 | |
| Sep-22 | - 1 | 658 | 7.74 | 337 | 248 | 4.51 | <0.05 | <0.05 | 75.1 | 4.13 | 1.05 | 0.03 | 0.034 | 5.1 | | 84.2 | 30.8 | |
| Apr-23 | | 616 | 7.69 | 317 | 255 | 9.19 | <0.05 | <0.05 | 44.4 | 6.58 | 1.16 | 0.05 | 0.014 | 4.9 | 1 | 80.3 | 28.4 | 0.036 |
| Nov-23 | | 628 | 7.48 | 291 | 296 | 6.53 | <0.05 | <0.05 | 64.1 | 5.00 | 0.92 | 0.00 | <0.039 | 3.9 | † | 73.8 | 26.0 | 0.055 |
| Apr-24 | * | 688 | 7.81 | 333 | 309 | 10.3 | <0.05 | <0.05 | 50.2 | 10.6 | 1.45 | 0.20 | <0.020 | 6.2 | | 84.1 | 29.9 | 0.033 |
| Nov-24 | 1 | 653 | 7.93 | 288 | 326 | 15.0 | <0.05 | <0.05 | 39.1 | 12.1 | 1.30 | 0.29 | <0.020 | 5.7 | | 72.0 | 26.2 | 0.054 |
| | 1 | 550 | | | | | 2.00 | 0,00 | 55.1 | | | J.20 | J.OLO | | | . 2.0 | | 0.001 |
| Average | , † | 585 | 7.96 | 310 | 273 | 12.6 | <0.10 | <0.10 | 45.1 | 9.2 | 1.20 | 0.12 | 0.30 | 4.9 | 0.0015 | 78.2 | 27.2 | 0.05 |
| Std. Dev | | 106 | 0.18 | 39.1 | 31.7 | 11.8 | NA | NA | 18.0 | 15.8 | 0.35 | 0.13 | 0.43 | 5.4 | 0.0028 | 4.91 | 2.05 | 0.01 |

| | | | | | 44 Harrion A. 199 | | 0.000 | INDWA | 10.04 200 020 500000 | CONTRACTOR OF THE PERSON OF TH | CONTRACTOR OF STREET | B-3 | | | | | |
|------------------|--------------|--------------|--------------|------------|-------------------|---------------|---------------------------------------|------------|----------------------|--|----------------------|---------------------|------------|--|---------|--|-------|
| | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | | Iron | DOC | Phenols | Calcium | | Boron |
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| odws | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| RUC | NV | NA | 543 | 375 | 130 | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV | NV | NV | NV |
| Dec-88 | 2020 | | 1307 | | 7.7 | | | | | | | 1.92 | 4.8 | <0.001 | | | |
| Jan-89 | 2160 | | 1383 | | 5.3 | | | | | | | 5.50 | 4.0 | <0.001 | | | |
| Dec-89 | 1960 | | 4445 | | 7.6 | | | | | | | 0.00 | 0.0 | 10.004 | | | |
| Jul-90 | 2260 | | 1415 | | 5.2 | | | | | | | 9.20 | 3.3 | <0.001 | | | |
| Jan-93 Jan-94 | 2110 1241 | | 1738 1446 | | | | | | | | | 10.30 8.38 | 3.8 | <0.001 <0.001 | | | |
| Nov-94 | 2170 | - | 1462 | | 6.9 | | - | - | | | | 8.41 | 3.7 | <0.001 | | | |
| Oct-95 | 2110 | | 1402 | | 8.0 | | | | | | | 8.45 | 4.2 | 0.011 | | | |
| Dec-96 | 2140 | | 1330 | | 8.2 | | | | | | | 8.50 | 3 | <0.001 | | <u> </u> | |
| Dec-96 Dup | 2140 | | 1434 | | 8.1 | | - | | | | | 8.70 | 3 | 0.001 | | | |
| Oct-97 | 2140 | | 1354 | | 8.8 | | · · · · · · · · · · · · · · · · · · · | · | | | | 8.53 | 3 | <0.001 | | | |
| Oct-97 Dup | 2130 | - | 1372 | | 8.9 | | | | | | | 8.45 | 4 | <0.001 | | | |
| Oct-98 | 1812 | | 1078 | | 29 | | | | | | | 6.45 | 3 | <0.001 | | | |
| Oct-98 Dup | 1812 | | 1122 | | 24 | | | | | | | 6.15 | 2 | <0.001 | | | |
| Nov-99 | 2160 | | 1381 | | 12.2 | | | - | | | | 8.95 | 17 | <0.001 | | | |
| Oct-00 | 2310 | | 1654 | | 12.0 | | | | | | | 9.17 | 10 | <0.001 | | | |
| Nov-01 | 2130 | | 1656 | | 17.0 | | | | | | | 10.00 | <1 | <0.001 | | | |
| Nov-01 Dup | 2140 | | 1583 | | 17.1 | | | | | | | 10.20 | 10 | <0.001 | | | |
| Dec-02 | 2270 | | 1504 | | 20.0 | | | İ | | | | 8.42 | 3.9 | <0.001 | | | |
| Dec-02 Dup | 2190 | | 1504 | | 17.6 | | | | | | | 8.55 | 4.0 | <0.001 | | | |
| Oct-03 | 2080 | | 1550 | | 18.6 | | | | | | | 8.84 | 17 | <0.001 | | 1 | |
| Nov-04 | 2110 | | 1510 | | 26.2 | | | | | | | 8.22 | 3.5 | <0.001 | | | |
| Nov-05 | 2220 | | 1570 | | 30.6 | | | | | | | 8.99 | 10.5 | < 0.001 | | | |
| Apr-06 | 2280 | 7.70 | 1530 | 384 | 22.2 | 0.75 | <0.05 | 1060 | 12.5 | | 0.18 | 13.10 | 4.0 | | | i i | |
| Oct-06 | 1920 | 7.69 | 1290 | 376 | 35.7 | <0.05 | <0.05 | 904 | 16.7 | 3.29 | 0.23 | 0.76 | 4.2 | | | | |
| Apr-07 | 1800 | 7.84 | 1160 | 334 | 23.9 | < 0.05 | <0.05 | 786 | 11.8 | 2.69 | 0.22 | 1.44 | 3.5 | | | | |
| Nov-07 | 1930 | 7.61 | 1240 | 378 | 37.6 | < 0.05 | <0.05 | 1020 | 13.6 | 3.29 | 0.13 | < 0.005 | 5.5 | | | , | |
| Apr-08 | 1670 | 7.82 | 1170 | 376 | 25.3 | < 0.05 | < 0.05 | 813 | 12.0 | 3.68 | 0.13 | 1.10 | 3.9 | | | | |
| Oct-08 | 2400 | 7.52 | 1710 | 393 | 35.5 | < 0.05 | <0.05 | 1000 | 18.2 | 3.94 | 0.54 | 5.43 | 4.1 | | | | |
| Apr-09 | 2040 | 7.46 | 1440 | 375 | 23.8 | < 0.05 | < 0.05 | 957 | 14.1 | 3.36 | 0.06 | 1.64 | 4.0 | | | | |
| Nov-09 | 2310 | 7.78 | 1660 | 420 | 35.5 | < 0.05 | <0.05 | 1110 | 18.6 | 3.80 | 0.15 | 2.00 | 5.1 | | | | |
| Apr-10 | 2260 | 7.93 | 1570 | 417 | 29.0 | <0.05 | <0.05 | 1220 | 16.0 | 3.70 | 0.20 | 1.06 | 3.6 | | | | |
| Nov-10 | 1940 | 7.66 | 1450 | 401 | 35.5 | <0.05 | <0.05 | 1056 | 19.4 | 3.68 | 0.08 | 0.95 | 4.2 | | | | |
| Apr-11 | 2310 | 7.70 | 1560 | 398 | 37.0 | < 0.05 | <0.05 | 1190 | 16.2 | 3.53 | 0.11 | 0.19 | 3.5 | | | | |
| Nov-11 | 1860 | 7.74 | 1490 | 398 | 75.3 | <0.05 | <0.05 | 1090 | 19.1 | 3.83 | 0.18 | 1.89 | 3.9 | | | | |
| Apr-12 | 2320 | 7.82 | 1520 | 404 | 31.5 | <0.05 | <0.05 | 1210 | 16.5 | 3.38 | 0.10 | 0.18 | 3.2 | | | | |
| Nov-12 | 1920 | 7.97 | 1490 | 382 | 43.7 | <0.10 | <0.10 | 1060 | 23.4 | 4.24 | 0.14 | 3.20 | 3.7 | | | | |
| Apr-13 | 2380 | 7.87 | 1490 | 409 | 35.2 | <0.5 | <0.5 | 1110 | 19.6 | 3.68 | 0.10 | 0.39 | 3.6 | | | | |
| Nov-13 | 2320 | 7.76 | 1490 | 386 | 34.6 | <1.0 | <1.0 | 1090 | 22.4 | 4.55 | 0.15 | 2.22 | 3.5 | | | | |
| May-14 | 1830 | 7.57 | 1100 | 350 | 18.5 | <0.5 | <0.5 | 783 | 12.5 | 2.96 | 0.60 | <0.01 | 3.6 | | | | |
| Oct-14 | 2230 | 7.76 | 1550 | 409 | 32.0 | <0.5 | <0.5 | 1090 | 21.2 | 4.26 | 0.18 | 1.10 | 3.3 | | | | |
| Apr-15 | 2220 | 7.77 | 1400 | 408 | 24.9 | <0.25 | <0.25 | 1070 | 17.9 | 3.35 | 0.14 | 1.07 | 3.2 | | | | |
| Oct-15 | 2380 | 7.90 | 1620 | 400 | 42.0 | <1.0 | <1.0 | 1180 | 22.7 | 3.58 | 0.15 | 3.45 | 4.5 | <u> </u> | | | |
| Apr-16 | 2130 | 7.88 | 1410 | 405 | 23.0 | <0.5 | <0.5 | 1042 | 17.6 | 3.35 | 0.12 | 0.44 | 4.1 | | | | |
| Nov-16 | 2120 1710 | 7.20 7.97 | 1220 1070 | 445 378 | 30.2 27.0 | <0.5 <0.25 | <0.5 <0.25 | 854 609 | 22.1 17.4 | 3.47 3.28 | 0.13 0.10 | 0.14 4.70 | 3.5 | | | | |
| Apr-17 | 2270 | 7.57 | 1540 | 419 | 27.0 | <0.25 | <0.25 | 1070 | | 4.06 | | 0.42 | | | | | - |
| Nov-17 May-18 | 2400 | 7.54 | 1500 | 430 | 24.0 | <0.10 | <0.010 | 1070 | 23.0 19.0 | 3.5 | 0.14 0.16 | 1.70 | 4.2 3.5 | | | | |
| Nov-18 | 2260 | 7.70 | 1280 | 417 | 33.1 | <0.10 | <0.010 | 1080 | 22.7 | 3.5 | 0.16 | 1.70 | 4.0 | | | | |
| Apr-19 | 2260 | 7.70 | 1360 | 450 | 16.2 | <0.5 | <0.5 | 975 | 19.8 | 3.5 | 0.07 | 2.34 | 3.5 | | | | |
| Oct-19 | 2100 | 7.72 | 1350 | 419 | 25.6 | <0.5 | <0.5 | 1100 | 24.1 | 3.9 | 0.10 | 0.020 | 4.4 | | | | |
| Apr-20 | 2670 | 7.38 | 1420 | 422 | 19.4 | <1.0 | <1.0 | 1120 | 18.7 | 3.47 | 0.13 | 0.020 | 4.0 | | 394 | 106 | |
| Oct-20 | 2110 | 8.00 | 1370 | 423 | 23.7 | <0.5 | <0.5 | 1070 | 23.8 | 4.10 | 0.14 | 0.013 | 3.9 | | 372 | 106 | |
| May-21 | 2340 | 7.66 | 1410 | 418 | 19.6 | <1.0 | <1.0 | 1030 | 19.9 | 4.04 | 0.13 | 1.63 | 3.8 | | 387 | 107 | |
| Oct-21 | 2140 | 7.40 | 1380 | 410 | 20.0 | <0.07 | <0.05 | 995 | 22.0 | 4.36 | 0.07 | <0.010 | 91.2 | | 557 | .5, | |
| Apr-22 | 2110 | 7.44 | 1320 | 425 | 17.0 | <0.07 | <0.05 | 997 | 20.6 | 3.97 | 0.04 | 0.074 | 4.2 | | 366 | 97.9 | |
| Sep-22 | 2390 | 7.17 | 1370 | 433 | 18.9 | <0.14 | 1.05 | 1110 | 21.1 | 3.16 | 0.12 | 0.044 | 4.5 | | 379 | 102 | |
| Apr-23 | 2210 | 7.15 | 1380 | 392 | 17.4 | <0.07 | <0.05 | 1060 | 18.3 | 3.92 | 0.07 | 0.53 | 4.0 | | 371 | 111 | 0.058 |
| Nov-23 | 2150 | 7.15 | 1050 | 470 | 17.4 | < 0.07 | <0.05 | 946 | 20.1 | 3.74 | 0.10 | 0.077 | 2.8 | | 286 | 80.6 | 0.077 |
| Apr-24 | 2690 | 7.40 | 1310 | 463 | 16.0 | <0.14 | <0.11 | 983 | 16.0 | 3.17 | 0.12 | 0.53 | 5.3 | | 359 | 100 | 0.047 |
| Nov-24 | 2460 | 7.59 | 1230 | 502 | 16.0 | <0.14 | <0.11 | 888 | 19.7 | 3.35 | 0.16 | 0.65 | 4.2 | i | 329 | 99.2 | 0.069 |
| | | | | | . 3,0 | | | | | | 2.10 | | | | | -2.2 | 000 |
| Average | 2142 | 7.64 | 1411 | 408 | 23.2 | < 0.25 | <0.25 | 1019 | 18.7 | 3.64 | 0.15 | 4.21 | 6.07 | <0.001 | 360.33 | 101.08 | 0.06 |
| Average | | | | | | NA | NA | | | | 0.11 | | | | | | 0.01 |

| D | -4T | ~ · · · · · | | | | пото | | | | | UALIT | DATA. | D-4 | | T 50 V | | 1 | |
|-----------|------|--------------------|----------|----------|------------|----------|---------|---------|----------|------|-----------|--------|--------|------|---------|---------|-------------|-------|
| | | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
| UN | VITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| OE | ows- | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV | NV |
| | | NA | OG | OG | OG | AO | MAC | MAC | AO | AO | NA | NA | AO | AO | NA | NA | NA | NA |
| | RUC | NV | NA | 543 | 375 | 130 | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV | NV | NV | NV |
| Dec-88 | | 386 | | 179 | | 2.5 | | | | | | | 0.77 | 2.8 | 0.0010 | | | |
| Jan-89 | | 489 | | 253 | | 2.8 | | | | | | | 0.26 | 8.5 | 0.0010 | | | |
| Dec-89 | | 511 | | | | 10.0 | | | | | | | | | | | | |
| Jul-90 | | 479 | | 315 | | 6.0 | | | | , | | | 36* | 1.5 | 0.0055 | | | |
| Jan-93 | | 440 | | 263 | | | | | | | | | 68.8* | 1.5 | 0.0120 | | | |
| Jan-94 | | 474 | | 233 | | 4.3 | | | | | | | 1.04 | 1.6 | <0.001 | | | |
| Nov-94 | | 445 | | 247 | | 3.8 | | | | | | | 0.37 | 1.3 | 0.0027 | | | |
| Oct-95 | | 496 | | 275 | | 4.2 | | | | , | | | 0.78 | 1.4 | 0.0210 | | | |
| Dec-96 | | 488 | | 242 | | 4.7 | | | | | | | 17.9* | 1.0 | <0.001 | | | |
| Oct-97 | | 477 | | 346 | | 5.3 | | | | | | | 17.8* | 1.0 | <0.001 | | | |
| Oct-98 | | 482 | | 355 | | 3.3 | | | | | | | 2.06 | <1 | <0.001 | | | |
| Nov-99 | | 492 | | 495 | | 3.7 | | | | | | | <0.01 | 3.0 | <0.001 | | | |
| Oct-00 | | 481 | | 265 | | 6.7 | | | | | | | 8.70 | 12 | <0.001 | | | |
| | Dup | 484 | | 263 | | 6.9 | | | | | | | 10.10 | 4.0 | <0.001 | | | |
| Nov-01 | | 509 | | 273 | | 6.9 | | | | | | | 0.50 | 4.0 | <0.001 | | | |
| Dec-02 | | 485 | | 254 | | 4.5 | | | | | | | 0.09 | 2.8 | <0.001 | | | |
| Oct-03 | | 501 | | 267 | | 11.6 | | | | | | | 1.02 | 11 | <0.001 | | | |
| Nov-04 | | 504 | | 284 | | 4.4 | | | | | | | 0.60 | 3.6 | <0.001 | | | |
| Nov-05 | | 536 | | 294 | | 11.2 | | | | | | | 0.03 | 6.3 | <0.001 | | | |
| Apr-06 | | 561 | 8.23 | 287 | 238 | 12.2 | <0.05 | <0.05 | 34.3 | 6.37 | | < 0.05 | 3.16 | 2.0 | | | | |
| Oct-06 | | 530 | 8.22 | 281 | 247 | 16.0 | < 0.05 | <0.05 | 39.8 | 6.77 | 1.45 | 0.10 | 0.26 | 1.9 | | | | |
| Apr-07 | | 622 | 8.33 | 343 | 261 | 16.4 | < 0.05 | <0.05 | 42.7 | 9.06 | 1.57 | 0.29 | 0.15 | 2.2 | | | | |
| Nov-07 | | 554 | 8.32 | 286 | 253 | 9.1 | <0.05 | <0.05 | 35.7 | 4.52 | 1.37 | < 0.05 | <0.005 | 5.1 | | | | |
| Apr-08 | | 589 | 8.28 | 315 | 271 | 17.8 | < 0.05 | <0.05 | 46.2 | 8.04 | 1.97 | 0.05 | 0.034 | 2.8 | | | | |
| Oct-08 | | 594 | 8.02 | 333 | 252 | 10.7 | < 0.05 | <0.05 | 37.4 | 6.38 | 1.42 | 0.16 | 0.15 | 4.1 | | | | |
| Apr-09 | | 817 | 8.05 | 434 | 297 | 49.3 | < 0.05 | <0.05 | 75.5 | 18.1 | 1.86 | 0.03 | 0.015 | 4.2 | | | | |
| Nov-09 | | 701 | 8.13 | 374 | 289 | 33.5 | < 0.05 | < 0.05 | 54.7 | 14.8 | 1.74 | 0.06 | <0.01 | 5.5 | | | | |
| Apr-10 | | 565 | 8.23 | 312 | 259 | 12.9 | < 0.05 | < 0.05 | 46.2 | 7.67 | 1.39 | 0.08 | 0.030 | 4.2 | | | | |
| Nov-10 | | 749 | 8.03 | 396 | 310 | 53.9 | < 0.05 | < 0.05 | 71.2 | 21.9 | 2.09 | 0.09 | <0.01 | 5.4 | | | | |
| Apr-11 | | 709 | 7.92 | 364 | 284 | 45.5 | < 0.05 | <0.05 | 60.5 | 18.3 | 1.80 | 0.11 | 0.15 | 3.7 | | | | |
| Nov-11 | | 600 | 8.06 | 350 | 286 | 32.0 | < 0.05 | <0.05 | 50.8 | 15.4 | 1.71 | 0.13 | <0.01 | 4.9 | | | | |
| Apr-12 | | 792 | 8.10 | 389 | 313 | 45.6 | < 0.05 | <0.05 | 57.2 | 22.8 | 2.05 | 0.08 | <0.01 | 3.8 | | | | |
| Nov-12 | | 560 | 8.24 | 324 | 260 | 16.7 | < 0.05 | < 0.05 | 51.0 | 9.85 | 1.44 | 0.09 | 0.010 | 4.5 | | | | |
| Apr-13 | | 750 | 8.17 | 360 | 292 | 36.3 | <0.25 | <0.25 | 53.5 | 18.4 | 1.97 | 0.10 | <0.01 | 3.7 | | | | |
| Nov-13 | | 625 | 8.10 | 296 | 265 | 15.5 | <0.10 | <0.10 | 45.5 | 9.83 | 1.58 | 0.14 | 0.010 | 4.2 | | | | |
| May-14 | | 770 | 7.99 | 371 | 300 | 40.2 | < 0.25 | < 0.25 | 55.9 | 20.1 | 1.97 | 0.25 | 0.020 | 4.0 | | | | |
| Oct-14 | | 751 | 8.10 | 371 | 307 | 41.0 | < 0.25 | <0.25 | 58.1 | 19.6 | 2.11 | 0.16 | <0.01 | 4.3 | | | | |
| Apr-15 | | 783 | 7.97 | 350 | 313 | 43.2 | < 0.25 | <0.25 | 58.0 | 21.4 | 1.69 | 0.16 | <0.01 | 5.7 | | | | |
| Oct-15 | | 783 | 8.00 | 366 | 303 | 43.4 | <0.25 | <0.25 | 59.7 | 22.7 | 1.84 | 0.23 | 1.70 | 6.7 | | | | |
| Apr-16 | | 753 | 8.05 | 350 | 306 | 40.6 | <0.10 | <0.10 | 57.7 | 22.3 | 1.81 | 0.35 | | 6.2 | | | | |
| Nov-16 | | 926 | 7.05 | 389 | 391 | 58.2 | <0.25 | <0.25 | 59.9 | 34.0 | 2.59 | 0.45 | <0.01 | 6.6 | | | | |
| Apr-17 | | 777 | 8.11 | 356 | 308 | 35.9 | <0.05 | <0.05 | 50.2 | 21.7 | 2.01 | 0.29 | 1.21 | 4.7 | | | | |
| Nov-17 | | 999 | 7.85 | 418 | 365 | 79.1 | <0.25 | <0.25 | 73.4 | 42.6 | 3.24 | 0.65 | <0.01 | 7.4 | | | | |
| May-18 | | 1000 | 7.84 | 450 | 430 | 60.0 | <0.10 | <0.010 | 43.0 | 38.0 | 4.4 | 1.4 | <0.1 | 6.1 | | | | |
| Nov-18 | | 928 | 7.92 | 384 | 379 | 59.4 | <0.25 | <0.25 | 54.1 | 33.2 | 3.55 | 0.60 | 0.022 | 5.9 | | | | |
| Apr-19 | | 914 | 7.80 | 389 | 428 | 45.2 | <0.25 | <0.25 | 41.5 | 30.6 | 4.00 | 0.89 | <0.01 | 6.1 | | | | |
| Oct-19 | | 809 | 7.82 | 376 | 357 | 42.6 | <0.25 | <0.25 | 46.3 | 27.5 | 3.84 | 0.80 | <0.01 | 5.9 | | | | |
| Apr-20 | | 1100 | 7.56 | 417 | 451 | 34.5 | <0.25 | <0.25 | 35.0 | 24.0 | 6.56 | 4.65 | <0.010 | 6.5 | | 99.8 | 40.8 | |
| Oct-20 | | 846 | 8.01 | 396 | 395 | 37.4 | <0.25 | <0.25 | 46.5 | 25.7 | 4.61 | 0.68 | 0.086 | 5.7 | | 93.9 | 39.3 | |
| May-21 | | 985 | 7.88 | 432 | 444 | 33.5 | <0.25 | <0.25 | 30.7 | 24.5 | 6.40 | 1.86 | 0.024 | 5.7 | | 105 | 41.2 | |
| Oct-21 | | 928 | 7.58 | 303 | 430 | 31.6 | < 0.05 | < 0.05 | 31.7 | 5.0 | 1.15 | 1.37 | <0.010 | 108 | | | | |
| Apr-22 | | 859 | 7.64 | 389 | 398 | 30.8 | 0.19 | < 0.05 | 33.3 | 22.8 | 5.22 | 1.57 | 0.027 | 5.2 | | 92.8 | 38.2 | |
| Sep-22 | | 996 | 7.69 | 432 | 402 | 44.0 | < 0.05 | < 0.05 | 43.8 | 27.8 | 5.29 | 1.32 | 0.024 | 7.8 | | 101 | 43.7 | |
| Apr-23 | | 1020 | 7.52 | 448 | 402 | 58.4 | <0.05 | < 0.05 | 43.3 | 31.0 | 5.14 | 1.06 | 0.013 | 8.9 | | 105 | 45.1 | 0.123 |
| Nov-23 | | 1260 | 7.42 | 489 | 550 | 99.4 | <0.05 | <0.05 | 53.6 | 61.4 | 6.61 | 1.48 | 0.033 | 9.3 | | 110 | 52.0 | 0.252 |
| Apr-24 | | 1560 | 7.55 | 542 | 578 | 115 | <0.05 | <0.05 | 53.9 | 72.1 | 5.63 | 2.92 | <0.020 | 18.0 | | 119 | 59.5 | 0.218 |
| Nov-24 | | 1450 | 7.63 | 532 | 631 | 129 | <0.05 | <0.05 | 58.5 | 69.0 | 7.13 | 4.16 | <0.020 | 17.2 | | 128 | 51.6 | 0.268 |
| | | | | | | | | | | | | | | | | | | |
| Average | | 714 | 7.93 | 348 | 349 | 30.9 | < 0.25 | <0.25 | 49.7 | 23.6 | 3.03 | 0.76 | 0.71 | 7.12 | 0.0027 | 106 | 45.7 | 0.22 |
| Std. Dev. | | 254 | 0.28 | 77.3 | 95.0 | 28.1 | NA | NA | 11.2 | 16.2 | 1.83 | 1.09 | 1.89 | 14.3 | 0.0054 | 11.48 | 7.17 | 0.06 |
| | | - Charles | | | | | | | | | | | | | | | - Autototic | |

| Do | ameter | Camalizativita | | Handrasa | Allealinites | Chlorida | DAVID DOOR CO. | D 001 0000 101 10 | Sulabata | promise to the | topa dellinoto d | DATA. | D-0 | DOC | Dhanala | Calairea | Manualium | Davas |
|------------------|--------|----------------|---------------|------------|--------------|--------------|----------------|-------------------|--------------|----------------|------------------|----------------|---------------------|-------------------|------------------|------------|--|----------|
| Pai | UNITS | Conductivity | pH | Hardness | | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
| | UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| | ODWS- | NV NA | 6.5-8.5 OG | 80-100 | 30-500 | 250 AO | 10 MAC | 1.0 MAC | 500 AO | 200 AO | NV NA | NV NA | 0.3 AO | 5.0 AO | NV | NV NA | NV NA | NV NA |
| | RUC | | | OG 543 | OG | 130 | 2.50 | | | 102 | | | | | NA NV | | NV NV | |
| 1 00 | RUC | NV 047 | NA | 543 | 375 | | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV 0.0040 | NV | INV | NV |
| Jan-89 | | 847 857 | | 464 478 | | 1.6 0.3 | | | | | | | 0.45 1.14 | 4.4 5.2 | 0.0010 <0.001 | | | |
| Jul-90 | - | 676 | | 385 | | 3.4 | | | | | | | 0.19 | 1.1 | | | | |
| Nov-94 | Dive | 666 | | 377 | | | | | | | | | | | <0.001 <0.001 | | - | |
| Nov-94 | Dup | 469 | | 261 | | 3.3 4.0 | | | | | | | 0.15 0.02 | 1.1 | 0.0116 | | | |
| Oct-95 | | 573 | | 279 | | 7.7 | | | | | | | 0.02 | 3.0 | <0.001 | | | |
| Dec-96 | - | 504 | | 289 | | 7.4 | | | | | | | | <1 | <0.001 | | | |
| Oct-97 | | 472 | | 268 | | 3.4 | | | | | | | 0.23 0.11 | <1 | <0.001 | | | |
| Oct-98 | | 515 | | 288 | | 10.3 | | | | | | | 0.11 | 5.0 | <0.001 | | | |
| Nov-99 Oct-00 | | 482 | | 277 | | 5.1 | | | | | | | 0.03 | 11.0 | <0.001 | | | |
| | - | 565 | | 280 | | 20.8 | | | | | | | 0.18 | 3.0 | <0.001 | | | |
| Nov-01 | | 623 | | 333 | | 40.8 | | | | | | | | 2.6 | | | - | |
| Dec-02 | | 462 | | 255 | | | | | | | | | 0.23 0.14 | 9.0 | <0.001 <0.001 | | | |
| Oct-03 | Dun | | | 255 | | 6.1 | | | | | | | | | | | | |
| Oct-03 | Dup | 465 461 | - | | | 6.1 | | | | | | | 0.14 | 8.0 0.7 | <0.001 | | | |
| Nov-04 | Dur | | | 249 | | 5.8 | | | | | | | 0.12 | 34.5.5 | <0.001 | | | |
| Nov-04 | | 466 | | 252 | | 6.1 | | | | | | | 0.12 | 0.6 | <0.001 | | | |
| Nov-05 | | 558 | | 312 | | 25.7 25.6 | | | | | | | 0.17 | 4.4 | <0.001 | | | |
| Nov-05 | Dup | 552 | 0 45 | 314 | 207 | | <0.0E | <0.0E | 10.4 | 274 | | <0.0E | 0.17 | 4.4 | <0.001 | | | |
| Apr-06 | | 625 | 8.15 8.17 | 311 | 227 | 42.8 10.5 | <0.05 | <0.05 <0.05 | 19.1 | 2.74 | 1.04 | <0.05 | 1.97 | 2.0 | | | | |
| Oct-06 | | 390 | | 244 | 229 | | < 0.05 | | 21.4 | 1.60 | 1.01 | <0.05 | 0.16 | 1.7 | | | | |
| Apr-07 | | 537 556 | 8.30 | 298 286 | 228 244 | 22.3 24.8 | <0.05 | <0.05 <0.05 | 19.5 18.2 | 1.95 1.52 | 0.96 1.20 | <0.05 | 0.16 | 1.4 2.0 | | | | |
| Nov-07 | | | 8.13 | | | | <0.05 | | | | | <0.05 | <0.005 | | | | | |
| Apr-08 | | 563 | 8.18 | 312 | 283 | 2.86 | < 0.05 | <0.05 | 85.3 | 2.82 | 1.54 | 0.05 | <0.010 | 3.1 | | | | |
| Oct-08 | | 535 | 8.04 | 303 | 229 | 11.9 | < 0.05 | <0.05 | 30.0 | 2.45 | 1.30 | 0.07 | 0.011 | 1.6 | | | | |
| Apr-09 | | 679 | 7.98 | 394 | 257 | 2.43 | <0.05 | 0.26 | 126 | 2.94 | 1.24 | <0.02 | <0.010 | 3.7 | | | | |
| Nov-09 | | 519 | 8.12 | 295 | 224 | 3.20 | <0.05 | < 0.05 | 50.6 | 2.80 | 1.14 | <0.05 | 0.011 | 5.0 | | | <u> </u> | |
| Apr-10 | | 742 | 8.11 | 433 | 243 | 1.68 | < 0.05 | < 0.05 | 201 | 3.06 | 1.32 | 0.02 | <0.01 | 4.2 | | | <u> </u> | |
| Nov-10 | | 598 | 8.09 | 362 | 250 | 4.06 | < 0.05 | <0.05 | 127 | 2.70 | 1.29 | <0.02 | <0.01 | 2.2 | | | | |
| Apr-11 | | 937 | 7.92 | 543 | 284 | 3.04 | < 0.05 | <0.05 | 267 | 2.89 | 1.15 | 0.05 | <0.01 | 4.2 | | | | |
| Nov-11 | | 646 | 8.01 | 402 | 263 | 6.66 | <0.05 | < 0.05 | 157 | 3.60 | 1.28 | 0.08 | <0.01 | 3.7 | | | - | |
| Apr-12 | | 980 | 7.96 | 544 | 281 | 2.42 | < 0.05 | <0.05 | 302 | 3.08 | 1.26 | <0.02 | 0.020 | 3.7 | | | | |
| Nov-12 | | 573 | 8.11 | 333 | 230 | 12.7 | <0.05 | <0.05 | 89.0 | 5.10 | 1.34 | <0.02 | <0.01 | 2.7 | | | | |
| Apr-13 | | 876 | 8.00 | 477 | 277 | 4.82 | < 0.25 | <0.25 | 199 | 3.25 | 1.30 | <0.02 | <0.01 | 3.6 | | | <u> </u> | |
| Nov-13 | | 822 | 7.90 | 404 | 261 | 11.2 | <0.25 | <0.25 | 182 | 5.72 | 1.62 | 0.08 | <0.01 | 3.7 | | | | |
| May-14 | | 941 | 7.81 | 517 | 262 | 3.3 | <0.25 | <0.25 | 273 | 3.45 | 1.24 | 0.21 | 0.010 | 3.7 | | | <u> </u> | |
| Oct-14 | - | 855 | 7.92 7.88 | 484 | 274 300 | 5.5 9.0 | <0.25 | <0.25 | 236 | 4.54 5.57 | 1.45 | 0.13 | <0.01 | 3.6 | | | | |
| Apr-15 | | 1110 | | 598 | | | <0.25 | <0.25 | 338 | | 1.31 | 0.09 | <0.01 | 3.5 | | | | |
| Oct-15 | | 354 909 | 7.78 | | 130 257 | 8.2 | < 0.05 | < 0.05 | 45.1 | 4.43 | 0.66 | 0.10 | 0.11 | 6.7 | | | | |
| Apr-16 | | | 8.01 | 513 | | 11.1 | <0.25 | <0.25 | 264 | 6.82 | 1.42 | 0.06 | 40.04 | 3.3 | | | - | |
| Nov-16 | | 641 853 | 8.13 8.03 | 291 444 | 241 265 | 31.3 | <0.05 <0.25 | <0.05 <0.25 | 53.2 | 15.8 | 1.27 1.32 | 0.13 | <0.01 | 2.7 3.2 | | | | |
| Apr-17 | | 853 885 | 7.81 | 444 | 265 | 8.5 12.0 | | <0.25 | 195 | 6.59 | | 0.06 | 0.47 | | | | | |
| Nov-17 | | 990 | 7.81 | 530 | 270 | | <0.25 <0.10 | <0.25 | 226 250 | 6.79 4.7 | 1.55 1.2 | 0.12 <0.050 | 0.020 <0.1 | 3.8 | | | | |
| May-18 | | 728 | 7.81 | 358 | 250 | 6.2 11.4 | <0.10 | <0.010 | 147 | 4.7 | 1.24 | 0.050 | <0.1 | 3.4 4.0 | - | | | |
| Nov-18 | | 728 840 | 7.81 | 435 | 250 | 5.69 | <0.10 | <0.10 | 193 | 5.05 | 1.24 | 0.07 | 0.090 | 3.6 | | | | |
| Apr-19 | | 775 | 7.80 | 435 | 294 | 12.9 | | <0.25 | 176 | | | | <0.090 | | | | + | |
| Oct-19 | | 1020 | | 447 | | | <0.10 | <0.10 | 234 | 8.03 | 1.42 | 0.09 | 0.044 | 2.6 | | 110 | 26.2 | |
| Apr-20 | | 886 | 7.69 7.95 | 447 | 264 271 | 3.42 11.9 | <0.25 <0.25 | <0.25 | | 3.82 7.04 | 1.35 1.43 | 0.06 0.12 | 0.044 | 4.5 3.9 | | 119 | 36.3 39.4 | |
| Oct-20 May-21 | | 1080 | 7.95 | 562 | 319 | 4.52 | <0.25 | <0.25 | 250 270 | 3.93 | <2.50 | <0.02 | <0.010 | 3.9 4.4 | | 126 155 | 39.4 42.5 | |
| Oct-21 | | 993 | 7.75 | 242 | 274 | 22.4 | <0.25 | <0.25 | 253 | 0.79 | <1.00 | 0.02 | <0.010 | 58.3 | | 100 | 42.5 | |
| Apr-22 | - | 1100 | 7.75 | 573 | 335 | 2.01 | <0.05 | <0.05 | 324 | 3.73 | <2.50 | <0.04 | 0.038 | 4.9 | | 157 | 44.0 | |
| Apr-22 Sep-22 | | 1180 | 7.82 | 386 | 282 | 170 | <0.05 | <0.05 | 61.4 | 89.7 | 2.41 | 0.02 | 0.038 | 4.9 | _ | 113 | 25.3 | |
| | | | 7.50 | 657 | 282 | 13.8 | <0.05 | <0.05 | 356 | 9.98 | 1.53 | 0.06 | 0.034 | 4.3 | | 177 | 25.3 52.2 | 0.03 |
| Apr-23 | - | 1130 | | | | | | | | | | | | | | | | 0.03 |
| Nov-23 | 1 | 1020 | 7.39 | 494 | 324 | 34.0 | <0.05 | <0.05 <0.05 | 224 | 22.1 | 1.54 | 0.08 | 0.012 | 2.6 | | 131 | 40.5 50.9 | 0.08 |
| Apr-24 | | 1260 | 7.73 | 642 | 345 | 15.1 | <0.05 | | 318 | 10.7 | 1.39 1.44 | 0.09 | 0.026 | 5.3 | | 173 | | 0.03 |
| Nov-24 | | 1870 | 7.84 | 375 | 414 | 306 | <0.07 | <0.05 | 71.3 | 173 | 1.44 | <0.02 | <0.020 | 3.4 | | 106 | 26.8 | 0.18 |
| Avera | | 751 | 7.92 | 207 | 260 | 10.0 | <0.0E | <0.0E | 175 | 11.00 | 1.04 | 0.057 | 0.42 | 4.00 | 0.0044 | 140 | 20.0 | 0.08 |
| Averag | | 754 | | 387 | 269 | 18.9 | <0.25 | <0.25 | 175 | 11.83 | 1.34 | 0.057 | 0.13 | 4.69 | 0.0011 | 140 | 39.8 | |
| Std. De | v. | 275 | 0.20 | 116 | 44.3 | 45.5 | NA | NA | 103 | 30.41 | 0.26 | 0.045 | 0.31 | 7.67 | 0.0026 | 26.4 | 9.31 | 0.07 |


| Darameter | Conductivity | На | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Continue to the | Potassium | Ammonio | Iron | DOC | Phenols | Calcium | Magnesium | Boron |
|------------------|--------------|---------------|------------|------------|--------------|----------------|----------------|--------------|-----------------|--------------|----------------|-------------------|------------|--|--|-----------|----------|
| UNITS | uS/cm | Unitless | mg/l | mg/L | ma/L | mg/l | ma/L | mg/L | ma/L | mg/L | mg/L | ma/L | ma/L | ma/L | mg/L | mg/L | ma/l |
| | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV NV | NV | 0.3 | 5.0 | NV | NV | NV IIIg/L | NV |
| ODWS- | NA NA | 0.5-6.5 OG | 0G OG | OG | AO | MAC | MAC | AO | AO | NA NA | NA NA | AO | AO | NA NA | NA NA | NA NA | NA NA |
| RUC | NV | NA NA | 543 | 375 | 130 | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV NV | NV | NV | NV |
| Dec-89 | 410 | 100 | 0.10 | 0,0 | 2.1 | 2.00 | 0.20 | 021 | 102 | 111 | 144 | 0.21 | 1.0 | | 111 | 111 | 1,1,1 |
| Jul-90 | 407 | | 515 | | 0.2 | | | | | | | 0.76 | 0.6 | 0.0079 | | | |
| Jan-93 | 390 | | 242 | | | | | | | | | 4.98* | 0.6 | < 0.001 | | | |
| Jan-94 | 418 | | 208 | , | 5.7 | | | | | | | 0.01 | 0.9 | 0.0010 | | | |
| Nov-94 | 413 | | 216 | | 5.1 | | | | | | | <0.01 | 0.6 | <0.001 | | | |
| Oct-95 | 447 | | 250 | | 6.4 | | | | | | | <0.01 | 1.0 | 0.0085 | | | |
| Dec-96 | 500 | | 278 | | 7.2 | | | | | | | 0.08 | <1 | 0.0010 | | | |
| Oct-97 | 557 | | 314 | | 16.1 | | | | | | | <0.01 | 10 | <0.001 | | | - |
| Oct-98 | 575 | | 329 | | 23.6 | | | | | | | <0.01 | <1 | <0.001 | | | |
| Nov-99 Oct-00 | 617 680 | | 316 408 | | 36.4 49.8 | | | | | | | <0.01 0.05 | <1 6 | <0.001 <0.001 | | | |
| Nov-01 | 666 | | 361 | | 49.8 | | | | | | | <0.05 | 3 | <0.001 | | | |
| Dec-02 | 669 | | 345 | | 50.3 | | | | | | | <0.01 | 1 | <0.001 | | | |
| Oct-03 | 646 | | 368 | | 56.1 | | | | | | | <0.02 | 10 | <0.001 | | | |
| Nov-04 | 626 | | 371 | | 56.4 | | | | | | | <0.005 | 1.0 | <0.001 | | | |
| Nov-05 | 644 | | 355 | | 43.5 | | | | | | | <0.005 | 5.3 | <0.001 | | | |
| Apr-06 | 604 | 8.28 | 215 | 224 | 32.0 | 0.70 | <0.05 | 15.3 | 2.53 | | < 0.05 | 1.66 | 2.0 | | | | |
| Oct-06 | 555 | 8.01 | 289 | 248 | 29.6 | 0.70 | <0.05 | 16.4 | 2.22 | 0.82 | < 0.05 | 0.20 | 2.5 | | | | |
| Apr-07 | 592 | 8.17 | 322 | 232 | 33.2 | 0.64 | <0.05 | 15.3 | 2.46 | 0.78 | < 0.05 | 0.15 | 1.1 | | | | |
| Nov-07 | 630 | 8.16 | 312 | 239 | 47.8 | 0.86 | <0.05 | 14.9 | 2.67 | 0.98 | <0.05 | <0.005 | 2.0 | | | | |
| Apr-08 | 577 | 8.19 | 308 | 253 | 36.4 | 0.67 | <0.05 | 15.6 | 4.15 | 1.21 | <0.05 | <0.010 | 1.9 | | | | |
| Oct-08 | 731 | 7.94 | 375 | 249 | 62.5 | 0.81 | <0.05 | 16.0 | 7.68 | 1.45 | <0.05 | <0.01 | 1.7 | | | | |
| Apr-09 | 584 | 8.04 | 328 | 244 | 35.6 | 0.62 | <0.05 | 15.3 | 5.01 | 0.86 | <0.02 | <0.010 | 2.1 | | | | |
| Nov-09 | 587 | 8.07 | 326 | 256 | 29.4 | 0.05 | < 0.05 | 15.3 | 3.70 | 0.82 | <0.05 | <0.01 | 3.0 | | | | |
| Apr-10 | 504 | 8.03 | 285 | 237 271 | 15.1 | 0.30 | < 0.05 | 21.5 18.3 | 2.22 | 0.83 | <0.02 | <0.01 | 1.3 | | | | |
| Nov-10 Apr-11 | 565 539 | 7.94 7.74 | 315 289 | 238 | 33.1 16.1 | 0.79 | <0.05 <0.05 | 22.3 | 4.15 2.39 | 0.83 0.69 | <0.02 0.02 | <0.01 <0.01 | 1.8 2.3 | - | | | |
| Nov-11 | 457 | 8.03 | 281 | 252 | 18.9 | 0.25 | <0.05 | 20.1 | 2.78 | 0.09 | <0.02 | <0.01 | 1.7 | | | | |
| Apr-12 | 525 | 7.94 | 276 | 251 | 13.5 | 0.33 | <0.05 | 19.9 | 2.09 | 0.62 | <0.02 | <0.01 | 1.0 | | | | |
| Nov-12 | 536 | 8.12 | 296 | 251 | 27.0 | 0.53 | <0.05 | 21.7 | 4.90 | 0.89 | <0.02 | <0.01 | 1.6 | | | | |
| Apr-13 | 534 | 8.05 | 277 | 245 | 13.0 | 0.21 | <0.05 | 20.6 | 2.22 | 0.75 | 0.04 | <0.01 | 1.2 | | | | |
| Nov-13 | 537 | 7.99 | 252 | 240 | 16.2 | 0.30 | <0.10 | 21.4 | 3.06 | 0.73 | 0.06 | 0.07 | 1.1 | | | | |
| May-14 | 512 | 7.87 | 266 | 231 | 13.3 | 0.16 | < 0.05 | 20.9 | 1.92 | 0.54 | 0.19 | <0.01 | 1.3 | | | | |
| Oct-14 | 512 | 8.16 | 264 | 239 | 14.7 | <0.10 | <0.10 | 21.2 | 2.33 | 0.57 | 0.06 | <0.01 | 0.9 | | | | |
| Apr-15 | 493 | 7.95 | 254 | 232 | 16.2 | <0.05 | <0.05 | 22.9 | 2.34 | 0.77 | <0.02 | <0.01 | 0.9 | | | | |
| Oct-15 | 523 | 7.86 | 277 | 233 | 17.6 | <0.10 | <0.10 | 23.3 | 2.49 | 0.52 | <0.02 | 6.18 | 1.4 | | | | |
| Apr-16 | 519 | 7.87 | 285 | 240 | 18.6 | < 0.05 | < 0.05 | 23.2 | 3.16 | 0.55 | <0.02 | 10.04 | 1.3 | | | | |
| Nov-16 | 519 542 | 8.23 | 263 270 | 220 275 | 20.5 21.4 | <0.05 <0.05 | <0.05 <0.05 | 20.8 20.7 | 3.93 | 0.58 | <0.02 | <0.01 | 1.3 | - | | | |
| Apr-17 Nov-17 | 542 552 | 8.10 7.91 | 268 | 242 | 23.7 | <0.05 | <0.05 | 20.7 | 4.98 7.54 | 0.72 0.68 | <0.02 <0.02 | 2.72 <0.01 | 0.8 1.8 | + | | | |
| May-18 | 520 | 7.91 | 260 | 242 | 18.0 | <0.10 | <0.10 | 17.0 | 5.3 | 0.68 | <0.02 | <0.01 | 1.8 | 1 | | | |
| Nov-18 | 584 | 7.85 | 256 | 242 | 34.1 | <0.10 | <0.010 | 23.8 | 10.1 | 0.65 | <0.030 | <0.010 | 1.5 | | | | |
| Apr-19 | 592 | 7.85 | 267 | 267 | 34.9 | <0.05 | <0.05 | 20.7 | 12.1 | 0.60 | <0.02 | <0.010 | 1.6 | 1 | | | |
| Oct-19 | 563 | 7.83 | 274 | 235 | 38.8 | <0.05 | <0.05 | 21.7 | 13.7 | 0.72 | <0.02 | <0.01 | <0.5 | | i | | |
| Apr-20 | 639 | 7.69 | 256 | 236 | 27.8 | <0.10 | <0.10 | 19.2 | 11.5 | 0.71 | 0.03 | 0.061 | 3.7 | | 67.9 | 21.0 | |
| Oct-20 | 541 | 7.98 | 259 | 239 | 39.8 | 0.12 | <0.05 | 21.5 | 12.0 | 0.77 | 0.04 | <0.010 | 1.6 | | 67.0 | 22.2 | |
| May-21 | 659 | 8.02 | 270 | 237 | 50.0 | <0.10 | <0.10 | 27.3 | 18.6 | 0.72 | <0.02 | <0.010 | 4.1 | | 70.5 | 22.7 | |
| Oct-21 | 524 | 8.00 | 243 | 226 | 17.9 | 0.08 | <0.05 | 18.9 | 6.4 | 0.66 | <0.02 | <0.010 | 25.2 | | | | |
| Apr-22 | 545 | 7.75 | 240 | 238 | 24.6 | 0.10 | <0.05 | 19.0 | 12.4 | 0.67 | <0.02 | 0.017 | 1.7 | | 63.1 | 19.9 | |
| Sep-22 | 585 | 7.98 | 250 | 224 | 25.7 | 0.09 | <0.05 | 20.4 | 10.0 | 0.74 | <0.02 | 0.021 | 1.8 | | 66.3 | 20.5 | |
| A | 550 | 7.00 | 000 | 0.40 | 00.0 | 0.07 | -0.46 | 40.0 | 5.70 | 0.75 | 0.00 | 0.00 | 0.40 | 0.0046 | 07.0 | 04.0 | N174 |
| Average | 553 | 7.99 | 293 | 242 | 26.9 | 0.27 | <0.10 | 19.8 | 5.73 | 0.75 | 0.02 | 0.26 | 2.49 | 0.0016 | 67.0 | 21.3 | N/A |
| Std. Dev. | 75.9 | 0.14 | 54.8 | 12.6 | 15.3 | 0.28 | NA | 3.00 | 4.29 | 0.19 | 0.03 | 1.00 | 3.88 | 0.0027 | 2.68 | 1.17 | N/A |


| Dawawa ta w | 0 1 11 11 | - 11 | I Hamilton | A How Profess | IN PERMIT IN M | 25 90 30 2 39 | | | The second | UALITY | DATA: | P-2 | 200 | I Bloom I | | I 84I | |
|----------------------|-----------------------|-----------------------|------------------|--------------------|----------------|-----------------|-----------------|--------------|-------------|--------------|-----------------|----------------|-------------------|------------------|------------|--|---------------|
| UNITS | Conductivity uS/cm | pH Unitless | Hardness mg/L | Alkalinity mg/L | Chloride | Nitrate mg/L | Nitrite ma/L | Sulphate | ma/L | Potassium | | Iron | DOC | Phenois | Calcium | And the second second | Boron ma/L |
| | NV | 6.5-8.5 | 80-100 | 30-500 | mg/L 250 | 10 | 1.0 | mg/L 500 | 200 | mg/L NV | mg/L NV | mg/L 0.3 | mg/L 5.0 | mg/L NV | mg/L NV | mg/L NV | NV |
| ODWS | NA NA | 0.5-6.5 OG | 0G | OG | AO | MAC | MAC | AO | AO | NA NA | NA | AO | AO | NA NA | NA NA | NA NA | NA |
| RUC | NV | NA NA | 543 | 375 | 130 | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV | NV | NV | NV |
| Dec-89 | 385 | 13/5 | 040 | 3/3 | 4.3 | 2.00 | 0.20 | 02T | 102 | 140 | 14.0 | 0.24 | 7.0 | 111 | 111 | 100 | 140 |
| Jul-90 | 383 | + | 199 | | 1.6 | | + | - | | | | 0.01 | <0.01 | 0.0078 | | | |
| Jan-93 | 390 | | 244 | | 1.0 | | | | | | | 0.05 | 0.6 | <0.001 | | | |
| Jan-94 | 424 | | 224 | | 2.0 | | | | | | | 0.02 | 0.7 | 0.0010 | | | |
| Nov-94 | 416 | | 230 | | 4.1 | | | | | | | 0.01 | 0.7 | 0.0027 | | | |
| Oct-95 | 432 | | 244 | | 1.7 | | | | | | | <0.01 | 0.8 | < 0.001 | | | |
| Dec-96 | 437 | | 245 | | 3.7 | | | | | | | <0.01 | <1 | 0.0020 | | | |
| Oct-97 | 456 | | 260 | | 6.0 | | | | | | | <0.01 | 1.0 | <0.001 | | | |
| Oct-97 Dup | 456 | | 265 | | 6.1 | | | | | | | 0.01 | 2.0 | <0.001 | | | |
| Oct-98 | 451 | | 261 | | 4.8 | | | | | | | 0.01 | <1 | <0.001 | | | |
| Oct-98 Dup | 451 | | 251 | | 4.7 | | | | | | | 0.01 | <1 | < 0.001 | | | |
| Nov-99 | 482 | | 269 | | 11.9 | | | | | | | <0.01 | <1 | <0.001 | | | |
| Nov-99 Dup | 484 | | 272 | | 11.9 | | | | | | | 0.04 | <1 | <0.001 | | | |
| Oct-00 | 527 | | 294 | | 18.8 | | | | | | | <0.01 | 5.0 | <0.001 | | | |
| Oct-00 Dup | 526 | | 295 | | 18.9 | ļ. | | | | | | <0.01 | 3.0 | <0.001 | | | |
| Nov-01 | 591 | | 315 | | 32.1 | ļ., | | | | | | <0.01 | 5.0 | <0.001 | | - | |
| Dec-02 | 520 | | 272 | | 17.4 | | , | - | | | | <0.02 | 0.7 | <0.001 | | | |
| Oct-03 | 477 | | 278 | | 16.0 | | | | | | | 0.008 | 8.0 | <0.001 | | | |
| Nov-04 | 472 470 | | 279 | | 16.0 16.4 | | | | | | | 0.005 | 0.6 | <0.001 <0.001 | | | |
| Nov-04 Dup Nov-05 | 508 | | 281 285 | | 15.9 | | | | | | | 0.005 0.012 | 0.6 5.1 | <0.001 | | | |
| Nov-05 Dup | 506 | | 286 | | 15.9 | | | | | | | 0.012 | 3.4 | <0.001 | | | |
| Apr-06 | 479 | 8.25 | 253 | 212 | 12.6 | 0.24 | <0.05 | 12.9 | 1.57 | | <0.05 | 0.013 | 1.0 | <0.001 | - | | |
| Oct-06 | 449 | 7.99 | 235 | 222 | 12.0 | 0.22 | <0.05 | 12.7 | 1.27 | 0.58 | <0.05 | 0.14 | 0.9 | | | | |
| Apr-07 | 479 | 8.16 | 269 | 216 | 15.3 | 0.25 | <0.05 | 12.4 | 1.43 | 0.58 | <0.05 | 0.14 | 0.8 | <u> </u> | | | |
| Nov-07 | 501 | 8.25 | 252 | 223 | 19.0 | 0.32 | <0.05 | 12.8 | 1.12 | 0.71 | <0.05 | < 0.005 | 2.7 | 1 | | | |
| Apr-08 | 459 | 8.29 | 250 | 226 | 13.3 | 0.20 | <0.05 | 12.5 | 1.88 | 0.74 | <0.05 | <0.010 | 0.9 | t | | | |
| Oct-08 | 522 | 8.05 | 279 | 219 | 19.3 | 0.23 | <0.05 | 11.9 | 2.93 | 0.79 | 0.08 | <0.01 | 1.0 | | | | |
| Apr-09 | 521 | 8.11 | 295 | 231 | 22.5 | 0.40 | <0.05 | 13.4 | 3.33 | 0.71 | <0.02 | <0.010 | 1.4 | <u> </u> | | | |
| Nov-09 | 476 | 8.15 | 279 | 228 | 11.8 | 0.17 | <0.05 | 11.2 | 2.01 | 0.65 | <0.05 | <0.01 | 2.5 | | | | |
| Apr-10 | 443 | 8.28 | 244 | 233 | 7.37 | 0.14 | < 0.05 | 14.3 | 1.52 | 0.59 | <0.02 | < 0.01 | 0.8 | 1 | | | |
| Nov-10 | 427 | 8.09 | 254 | 231 | 13.1 | 0.24 | < 0.05 | 13.7 | 1.94 | 0.62 | < 0.02 | < 0.01 | 0.9 | 1 | | | |
| Apr-11 | 453 | 8.05 | 254 | 220 | 6.44 | 0.05 | < 0.05 | 15.4 | 1.41 | 0.60 | <0.02 | <0.01 | 0.9 | | | | |
| Nov-11 | 407 | 8.05 | 238 | 230 | 6.84 | <0.05 | < 0.05 | 14.6 | 1.34 | 0.52 | < 0.02 | <0.01 | 1.2 | | | | |
| Apr-12 | 465 | 7.96 | 249 | 232 | 7.73 | 0.11 | <0.05 | 14.5 | 1.49 | 0.54 | < 0.02 | <0.01 | 8.0 | | | | |
| Nov-12 | 461 | 8.14 | 260 | 233 | 16.8 | 0.30 | < 0.05 | 16.1 | 3.35 | 0.60 | < 0.02 | <0.01 | 1.2 | | | | |
| Apr-13 | 488 | 8.08 | 256 | 231 | 7.95 | 0.10 | <0.05 | 13.5 | 1.94 | 0.75 | 0.04 | <0.01 | 1.0 | | | | |
| Nov-13 | 583 | 8.05 | 269 | 255 | 18.2 | 0.48 | <0.10 | 18.5 | 4.04 | 0.75 | <0.02 | <0.01 | 1.6 | | | | |
| May-14 | 459 | 7.94 | 239 | 219 | 8.2 | <0.05 | <0.05 | 15.8 | 1.36 | 0.49 | 0.11 | <0.01 | 1.1 | ļ | | | |
| Oct-14 | 479 | 8.12 | 249 | 227 | 10.3 | <0.10 | <0.10 | 19.4 | 1.96 | 0.57 | 0.02 | <0.01 | 0.9 | | | | |
| Apr-15 | 445 | 7.89 | 232 | 224 | 7.7 | < 0.05 | <0.05 | 14.6 | 1.73 | 0.54 | <0.02 | <0.01 | 1.8 | | | | |
| Oct-15 | 460 | 7.99 | 249 | 222 | 8.2 | <0.10 | <0.10 | 15.3 | 1.70 | 0.49 | <0.02 | 0.080 | 1.2 | - | | | |
| Apr-16 | 468 | 8.05 | 252 | 229 | 10.5 | < 0.05 | < 0.05 | 16.6 | 2.17 | 0.50 | <0.02 | -0.04 | 0.7 | ļ | | 1 | |
| Nov-16 | 471 | 8.13 | 237 | 218 | 9.8 | <0.05 | < 0.05 | 14.2 | 2.43 | 0.49 | <0.02 | <0.01 | 1.5 | - | | | |
| Apr-17 | 553 | 8.14 | 283 | 266 | 11.9 | 0.31 | <0.05 | 14.2 | 3.63 | 0.87 | <0.02 | 0.47 | 1.5 | | - | | |
| Nov-17 | 530 540 | 7.90 7.91 | 261 270 | 237 240 | 19.4 21.0 | <0.10 <0.10 | <0.10 <0.010 | 18.8 19.0 | 5.32 | 0.53 0.53 | <0.02 <0.050 | <0.01 <0.1 | 1.4 0.8 | 1 | | - | |
| May-18 Nov-18 | 540 536 | 7.91 | 247 | 237 | 23.9 | <0.10 | <0.010 | 19.0 | 6.1 6.91 | 0.53 | <0.050 | <0.11 | 1.1 | - | | - | |
| Apr-19 | 580 | 7.85 | 265 | 265 | 32.1 | <0.05 | <0.05 | 19.1 | 10.9 | 0.57 | <0.02 | <0.010 | 1.7 | - | - | | |
| Oct-19 | 559 | 7.85 | 294 | 248 | 33.7 | 0.20 | <0.05 | 15.9 | 13.3 | 0.59 | <0.02 | <0.01 | 1.6 | | - | | |
| Apr-20 | 681 | 7.71 | 270 | 240 | 37.1 | <0.10 | <0.05 | 19.7 | 13.1 | 0.76 | <0.02 | <0.010 | 2.9 | 1 | 71.5 | 22.1 | |
| Oct-20 | 537 | 8.07 | 257 | 236 | 34.2 | 0.06 | <0.10 | 18.7 | 10.4 | 0.61 | <0.02 | 0.016 | 1.0 | 1 | 66.1 | 22.1 | |
| May-21 | 598 | 8.07 | 258 | 233 | 37.5 | < 0.05 | <0.05 | 17.5 | 13.4 | 0.61 | <0.02 | <0.016 | 1.4 | † | 66.9 | 22.4 | |
| Average | 486 | 8.05 | 261 | 232 | 14.3 | 0.14 | <0.03 | 15.4 | 4.10 | 0.73 | 0.020 | 0.041 | 1.54 | 0.0010 | 68.2 | 22.2 | N/A |
| Std. Dev. | 58.2 | 0.13 | 21.2 | 12.9 | 9.27 | 0.14 | NA | 2.57 | 3.92 | 0.02 | 0.020 | 0.041 | 1.46 | 0.0016 | 2.91 | 0.21 | N/A |
| Old. DOV. | JU.Z | 0.10 | 21.2 | 12.3 | 3.21 | 0.15 | IN/A | 2.01 | 3.32 | 0.10 | U.UZZ | 0.13 | 1.40 | 0.0010 | 2.31 | 0.21 | IN//N |


| Parameter | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | | Potassium | DATA: | P-3 | DOC | Phenols | Calcium | Magnesium | Boron |
|------------------|--------------|---------------|------------|------------|--------------|--------------|----------------|--------------|--------------|--------------|---------------|----------------|------------|---------|---------|--|----------|
| UNITS | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | ma/L |
| | NV | 6.5-8.5 | 80-100 | 30-500 | 250 | 10 | 1.0 | 500 | 200 | NV | NV | 0.3 | 5.0 | NV | NV | NV NV | NV |
| ODWS | NA NA | 0.5-6.5 OG | OG | OG | AO | MAC | MAC | AO | AO | NA NA | NA NA | AO | AO | NA NA | NA NA | NA NA | NA NA |
| RUC | NV | NA NA | 543 | 375 | 130 | 2.50 | 0.25 | 324 | 102 | NV | NV | 0.24 | 4.3 | NV | NV | NV | NV |
| Dec-89 | 384 | INA | 543 | 3/3 | 3.8 | 2.50 | 0.25 | 324 | 102 | INV | INV | 0.24 | 4.3 | INV | INV | INV | INV |
| Jan-93 | 390 | | 241 | | 3.0 | | | | | | | 0.04 | 0.6 | 0.0015 | | | |
| Jan-94 | 425 | | 218 | | 5.7 | | | | | | | <0.01 | 0.7 | <0.0013 | | | |
| Nov-94 | 407 | | 223 | | 4.6 | | | | | | | 0.01 | 0.7 | 0.0027 | | | |
| Oct-95 | 445 | | 244 | | 6.4 | | | | | | | 0.01 | 1.0 | <0.001 | | | |
| Dec-96 | 497 | | 269 | | 7.3 | | | | | | | <0.01 | <1 | <0.001 | | | |
| Dec-96 Dup | 499 | | 276 | | 5.3 | | | | | | | <0.01 | 1.0 | <0.001 | | | |
| Oct-97 | 548 | | 304 | | 15.2 | | | | | | | <0.01 | <1 | <0.001 | | | |
| Oct-98 | 566 | | 302 | | 21.5 | | | | | | | < 0.01 | <1 | < 0.001 | | | |
| Nov-99 | 587 | | 317 | | 30.3 | | | | | | | < 0.01 | <1 | < 0.001 | ĺ | | |
| Oct-00 | 679 | | 378 | | 48.8 | | | | | | | <0.01 | 1.0 | < 0.001 | | | |
| Nov-01 | 647 | | 341 | | 39.5 | | | | | | | <0.01 | 5.0 | <0.001 | | | |
| Dec-02 | 533 | | 336 | | 45.4 | | | | | | | < 0.02 | 1.1 | <0.001 | | | |
| Oct-03 | 636 | | 357 | | 53.9 | | | | | | | <0.005 | 9.0 | <0.001 | | | |
| Oct-03 Dup | 636 | | 360 | | 53.9 | | | | | | | <0.005 | 11 | <0.001 | | | |
| Nov-04 | 616 | | 368 | | 51.4 | | | | | | | <0.005 | 1.0 | <0.001 | | | |
| Nov-05 | 631 | | 350 | | 39.3 | | | | | | | <0.005 | 6.5 | <0.001 | | | |
| Apr-06 | 583 | 8.23 | 295 | 231 | 28.5 | 0.70 | <0.05 | 15.3 | 3.53 | | < 0.05 | 1.88 | 1.0 | | | | |
| Oct-06 | 536 | 7.97 | 287 | 245 | 30.4 | 0.70 | <0.05 | 16.9 | 2.24 | 0.82 | < 0.05 | 0.18 | 1.4 | | | | |
| Apr-07 | 588 | 8.31 | 316 | 236 | 35.2 | 0.68 | <0.05 | 15.6 | 2.54 | 0.74 | <0.05 | 0.16 | 1.1 | | | | |
| Nov-07 | 617 | 8.27 | 321 | 245 | 43.0 | 0.81 | <0.05 | 15.8 | 2.61 | 0.98 | <0.05 | <0.005 | 1.3 | | | | |
| Apr-08 | 577 | 8.32 | 304 | 255 | 38.4 | 0.72 | <0.05 | 16.2 | 4.06 | 1.12 | < 0.05 | <0.010 | 1.4 | | | | |
| Oct-08 | 709 | 7.98 | 371 | 248 | 55.7 | 0.72 | <0.05 | 15.6 | 6.87 | 1.26 | 0.09 | <0.01 | 1.4 | | | | |
| Apr-09 | 582 | 8.10 | 310 | 246 | 32.2 | 0.56 | <0.05 | 16.3 | 4.23 | 0.80 | <0.02 | 0.017 | 1.7 | | | | |
| Nov-09 | 568 | 8.09 | 329 | 258 | 24.9 | 0.50 | <0.05 | 13.9 | 3.54 | 0.76 | <0.05 | <0.01 | 3.1 | | | | |
| Apr-10 | 540 | 8.20 | 302 | 255 | 19.7 | 0.48 | <0.05 | 19.1 | 2.83 | 0.76 | <0.02 | <0.01 | 1.3 | | | | |
| Nov-10 | 544 | 8.04 | 313 | 265 | 30.1 | 0.79 | <0.05 | 18.9 | 3.83 | 0.69 | <0.02 0.02 | <0.01 | 1.4 1.4 | | | | |
| Apr-11 | 546 485 | 7.99 8.11 | 302 300 | 265 | 17.7 19.7 | 0.37 0.48 | <0.05 <0.05 | 16.9 19.8 | 2.82 | 0.69 0.69 | 0.02 | <0.01 <0.01 | | | | | |
| Nov-11 | 543 | 7.99 | 291 | 266 269 | 13.7 | 0.48 | <0.05 | 16.9 | 3.21 2.38 | 0.65 | <0.02 | <0.01 | 2.6 1.2 | | | | |
| Apr-12 Nov-12 | 544 | 8.17 | 313 | 259 | 26.6 | 0.65 | <0.05 | 20.7 | 5.32 | 0.65 | 0.02 | <0.01 | 2.0 | | | | |
| Apr-13 | 547 | 8.10 | 280 | 259 | 13.6 | 0.00 | <0.05 | 15.3 | 3.16 | 0.74 | <0.02 | <0.01 | 1.4 | | | _ | |
| Nov-13 | 481 | 8.05 | 227 | 221 | 8.94 | 0.30 | <0.03 | 14.0 | 2.05 | 0.62 | <0.02 | <0.01 | 1.0 | | | | |
| May-14 | 524 | 7.97 | 277 | 251 | 12.4 | 0.11 | <0.10 | 14.8 | 2.96 | 0.61 | 0.22 | 0.010 | 1.7 | | | | |
| Oct-14 | 591 | 8.11 | 307 | 281 | 16.0 | 0.20 | <0.10 | 19.1 | 3.94 | 0.72 | 0.02 | <0.010 | 1.6 | | | | |
| Apr-15 | 554 | 7.88 | 288 | 278 | 12.6 | 0.36 | <0.05 | 18.3 | 2.75 | 0.72 | <0.02 | <0.01 | 1.3 | | | | |
| Oct-15 | 724 | 8.02 | 350 | 291 | 51.5 | 0.42 | <0.10 | 25.1 | 18.9 | 0.88 | <0.02 | 0.94 | 1.7 | | | | |
| Apr-16 | 529 | 8.08 | 288 | 263 | 12.4 | 0.36 | <0.05 | 15.6 | 3.41 | 0.59 | <0.02 | 0.01 | 1.7 | | | | |
| Nov-16 | 699 | 8.12 | 305 | 268 | 62.4 | 0.68 | <0.25 | 16.7 | 18.2 | 0.79 | <0.02 | <0.01 | 2.3 | | | | |
| Apr-17 | 495 | 8.12 | 246 | 227 | 12.4 | <0.05 | <0.05 | 15.2 | 3.28 | 0.59 | <0.02 | 0.090 | 0.8 | | | | |
| Nov-17 | 669 | 7.89 | 315 | 297 | 42.3 | 0.52 | <0.10 | 19.3 | 16.5 | 0.75 | <0.02 | <0.01 | 2.5 | | | | |
| May-18 | 570 | 7.94 | 290 | 280 | 17.0 | 0.29 | <0.010 | 14.0 | 5.4 | 0.72 | 0.064 | <0.1 | 2.0 | | | | |
| Nov-18 | 616 | 7.96 | 291 | 293 | 20.1 | 0.43 | < 0.05 | 17.3 | 6.68 | 0.87 | 0.22 | <0.01 | 2.3 | | | | |
| Apr-19 | 519 | 7.87 | 253 | 280 | 9.43 | 0.26 | <0.05 | 10.9 | 3.89 | 0.79 | 0.02 | <0.01 | 2.1 | | | | |
| Oct-19 | 573 | 7.90 | 281 | 272 | 25.9 | 0.42 | <0.05 | 15.1 | 9.90 | 0.80 | <0.02 | <0.01 | 2.4 | | | | |
| Apr-20 | 639 | 7.76 | 278 | 266 | 11.7 | 0.35 | <0.10 | 13.5 | 3.91 | 0.66 | <0.02 | <0.010 | 3.0 | | 77.8 | 20.4 | |
| Oct-20 | 582 | 8.04 | 294 | 281 | 22.0 | 0.41 | <0.05 | 16.2 | 8.02 | 0.70 | <0.02 | 0.053 | 2.7 | | 80.3 | 22.6 | |
| May-21 | 579 | 8.03 | 282 | 269 | 10.6 | 0.29 | <0.05 | 14.3 | 3.90 | 0.74 | <0.02 | <0.010 | 1.9 | | 77.5 | 21.6 | |
| Oct-21 | 599 | 7.84 | 285 | 273 | 20.2 | 0.52 | <0.05 | 16.8 | 7.01 | 0.67 | <0.02 | <0.010 | 169 | | | | |
| Apr-22 | 548 | 7.73 | 267 | 277 | 7.99 | 0.28 | <0.05 | 13.7 | 3.74 | 0.81 | <0.02 | 0.021 | 2.4 | | 74.3 | 19.9 | |
| Sep-22 | 785 | 7.92 | 329 | 304 | 54.7 | 0.47 | <0.05 | 22.7 | 18.6 | 0.66 | <0.02 | 0.016 | 2.0 | | 93.5 | 23.2 | |
| Nov-23 | 579 | 7.59 | 303 | 324 | 6.41 | 0.25 | <0.05 | 17.4 | 3.10 | 1.42 | <0.02 | <0.010 | 1.2 | | 82.8 | 23.4 | 0.027 |
| Apr-24 | 642 | 7.99 | 308 | 321 | 8.42 | 0.24 | <0.05 | 13.7 | 3.75 | 0.59 | <0.02 | <0.020 | 2.9 | | 84.6 | 23.6 | <0.010 |
| Nov-24 | 733 | 7.94 | 273 | 332 | 49.8 | 0.44 | <0.05 | 16.6 | 22.8 | <0.50 | <0.02 | <0.020 | 1.6 | | 72.3 | 22.5 | 0.023 |
| | | | 955 | 0.55 | 05.5 | | 0 | | 0 | | 0.65= | 0.5=: | | | 05 : | 05.5 | |
| Average | 572 | 8.02 | 299 | 269 | 25.6 | 0.46 | <0.10 | 16.6 | 6.10 | 0.77 | 0.037 | 0.071 | 5.2 | 0.0007 | 80.4 | 22.2 | 0.03 |
| Std. Dev. | 83.2 | 0.16 | 36.8 | 25.5 | 16.8 | 0.18 | NA | 2.72 | 5.49 | 0.18 | 0.065 | 0.29 | 23.02 | 0.0006 | 6.69 | 1.39 | N/A |


Notes:


- 1. ODWS = Ontario Drinking Water Standards (June 2003, Revised June 2006)
- 2. PWQO = Provincial Water Quality Objectives
- 3. NM = Not Monitored; NV = No value specified; NA = Not Applicable.
- 4. Results presented in mg/L (milligrams per litre) unless otherwise specified. µS/cm = microsiemens per centimetre.
- 5. Samples analyzed by AGAT Laboratories Limited.
- 6. * indicates outlier interpreted as sample or lab error.
- 7. Data prior to 2006 from Annual Monitoring Report (2005), Henderson, Paddon and Associates, Ltd.
- 8. Values reported as less than detection limits used as 1/2 detection limit for calculation of averages and plotting.































Monitoring Well W-3/03




















ECA No. A272002, A273003 & 5854-7DSSDD St. Edmunds Landfill Site: Annual Monitoring Report (2024) Municipality of Northern Bruce Peninsula, Ontario April 30, 2025

Appendix H Historical Surface Water Quality Results (Tables and Graphs)

HISTORICAL SURFACE WATER QUALITY DATA: S-1

| Parameter | CBOD ₅ | Conductivity | pН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
|------------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|------|------------|--------|--------|--------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | NV | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Dec-88 | NM | 394 | NM | 218 | NM | 9.8 | NM | NM | NM | NM | NM | <0.001 | NM | NM | NM | NM | 2.6 | NM | NM | NM | NM | NM | NM |
| Jan-89 | NM | 447 | NM | 219 | NM | 4.3 | NM | NM | NM | NM | 10.6 | 0.0025 | NM | NM | NM | NM | 0.08 | NM | NM | NM | NM | NM | NM |
| Jul-90 | NM | 659 | NM | 367 | NM | 1.7 | NM | NM | NM | NM | NM | 0.0015 | NM | NM | NM | NM | 0.8 | NM | NM | NM | NM | NM | NM |
| Nov-94 | NM | 831 | NM | 512 | NM | 4.1 | NM | NM | NM | NM | 11.4 | 0.0072 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Nov-94 Dup | NM | 834 | NM | 513 | NM | 4.2 | NM | NM | NM | NM | 11.4 | 0.0027 | NM | NM | NM | NM | 0.16 | NM | NM | NM | NM | NM | NM |
| Nov-10 | <5 | 771 | 8.14 | 478 | 312 | 9.3 | <0.05 | < 0.05 | 158 | <0.02 | 15.4 | <0.001 | 0.95 | <0.05 | <0.010 | <0.005 | <0.01 | NM | NM | < 0.0003 | NM | NM | 5.0 |
| Apr-11 | <5 | 513 | 8.07 | 262 | 192 | 17.7 | 0.05 | < 0.05 | 50.9 | 0.02 | 8.9 | <0.001 | 0.73 | <0.05 | <0.010 | <0.005 | <0.01 | NM | NM | 0.0001 | 346 | 7.43 | 11.8 |
| Nov-11 | <5 | 592 | 8.23 | 330 | 280 | 31.4 | < 0.05 | < 0.05 | 57.1 | 0.04 | 13.2 | <0.001 | 0.49 | 0.02 | <0.010 | <0.005 | < 0.01 | NM | NM | 0.0003 | 687 | 7.72 | 7.3 |
| Apr-12 | <5 | 619 | 8.15 | 320 | 282 | 20.5 | <0.05 | < 0.05 | 30.4 | <0.02 | 10.1 | 0.0010 | 0.67 | 0.04 | <0.010 | <0.005 | <0.01 | NM | NM | <0.0001 | 637 | 7.70 | 5.3 |
| Nov-12 | <5 | 662 | 8.21 | 362 | 187 | 22.8 | 0.23 | < 0.05 | 186 | <0.02 | 14.5 | <0.001 | 0.80 | <0.02 | <0.010 | 0.02 | 0.025 | NM | 1.19 | <0.00003 | 716 | 7.01 | 6.0 |
| Apr-13 | <5 | 516 | 8.19 | 214 | 190 | 40.3 | 0.16 | < 0.05 | 18.9 | 0.02 | 8.1 | <0.001 | 0.59 | <0.02 | <0.010 | <0.005 | <0.01 | NM | 0.75 | 0.0004 | 483 | 8.07 | 9.1 |
| Nov-13 | <5 | 676 | 8.30 | 320 | 246 | 23.1 | <0.25 | <0.25 | 69.4 | 0.02 | 14.0 | <0.001 | 0.87 | <0.02 | <0.010 | <0.005 | <0.01 | 14.2 | 0.84 | 0.0002 | 683 | 8.04 | 3.0 |
| May-14 | <5 | 590 | 8.16 | 289 | 259 | 21.9 | <0.10 | <0.10 | 25.0 | 0.15 | 10.6 | <0.001 | 0.60 | <0.02 | 0.01 | <0.005 | <0.01 | NM | 0.78 | 0.0006 | 249 | 7.38 | 9.4 |
| Oct-14 | <5 | 665 | 8.29 | 307 | 277 | 38.6 | 0.4 | <0.10 | 26.4 | 0.03 | 16.7 | <0.001 | 0.76 | 0.06 | 0.01 | <0.005 | 0.05 | 21.3 | 1.17 | 0.0002 | 612 | 7.52 | 9.3 |
| Apr-15 | <5 | 563 | 8.16 | 259 | 247 | 29.5 | <0.25 | <0.25 | 21.4 | <0.02 | 8.9 | <0.001 | 0.92 | 0.03 | <0.010 | <0.005 | 0.01 | NM | 0.86 | 0.0000 | 576 | 7.06 | 1.1 |
| Oct-15 | <5 | 695 | 7.95 | 361 | 226 | 17.9 | <0.25 | <0.25 | 128 | <0.02 | 16.4 | 0.0010 | 0.74 | 0.03 | <0.010 | <0.005 | <0.01 | NM | 6.44 | 0.0000 | 459 | 6.34 | 7.4 |
| Apr-16 | <5 | 572 | 7.95 | 281 | 260 | 25.1 | <0.10 | <0.10 | 31.0 | <0.02 | 11.1 | <0.001 | 1.10 | <0.02 | NM | NM | NM | NM | 0.52 | 0.00010 | 386 | 7.52 | 7.5 |
| Nov-16 | <5 | 868 | 7.45 | 409 | 316 | 24.2 | <0.25 | <0.25 | 164 | <0.02 | 16.2 | <0.001 | 0.85 | 0.04 | <0.010 | <0.005 | <0.01 | NM | 1.29 | 0.00012 | 555 | 7.57 | 7.9 |
| Apr-17 | <5 | 578 | 8.12 | 261 | 237 | 24.8 | <0.05 | <0.05 | 25.1 | <0.02 | 9.8 | <0.001 | 0.50 | <0.02 | 0.01 | <0.005 | 0.03 | NM | 0.66 | 0.00010 | 610 | 7.52 | 7.4 |
| Nov-17 | <5 | 696 | 8.14 | 352 | 322 | 24.6 | 0.32 | <0.10 | 35.1 | 0.02 | 14.8 | <0.001 | 0.76 | 0.02 | <0.010 | <0.005 | <0.01 | 17.4 | 1.01 | 0.00032 | 462 | 8.04 | 7.3 |
| May-18 | <2 | 360 | 8.39 | 180 | 180 | 7.7 | <0.10 | <0.010 | <1.0 | <0.050 | 12.0 | <0.0010 | 0.48 | <0.040 | <0.01 | <0.005 | <0.1 | NM | NM | <0.006 | 250 | 8.82 | 10.5 |
| Nov-18 | <5 | 646 | 8.03 | 289 | 260 | 34.4 | 0.11 | <0.05 | 46.7 | <0.02 | 13.0 | <0.001 | 0.53 | <0.02 | <0.010 | <0.005 | 0.03 | NM | NM | <0.001 | 324 | 7.30 | 0.44 |
| Apr-19 | <5 | 353 | 7.83 | 159 | 184 | 10.6 | 0.06 | <0.05 | 4.39 | <0.02 | 8.3 | <0.001 | 0.23 | <0.02 | <0.010 | 0.005 | 0.02 | 8.44 | 0.73 | <0.001 | 203 | 7.76 | 1.67 |
| Oct-19 | <5 | 621 | 7.98 | 297 | 282 | 24.3 | <0.10 | <0.10 | 39.4 | <0.02 | 15.2 | 0.001 | 0.57 | 0.02 | 0.014 | <0.005 | <0.01 | 15.3 | 1.49 | <0.001 | 516 | 7.89 | 11.1 |
| Oct-20 | <2 | 645 | 8.11 | 358 | 295 | 31.4 | <0.10 | <0.10 | 29.5 | <0.02 | 14.6 | 0.005 | 0.70 | 0.05 | 0.012 | <0.005 | 0.038 | 21.7 | 0.85 | <0.001 | 394 | 7.87 | 5.5 |
| May-21 | <2 | 470 | 8.14 | 215 | 203 | 20.9 | <0.05 | <0.05 | 2.96 | <0.02 | 10.7 | 0.001 | 0.55 | 0.02 | 0.010 | <0.005 | 0.10 | 13.1 | 1.33 | <0.001 | 352 | 7.48 | 7.5 |
| Oct-21 | <2 | 746 | 7.92 | 366 | 348 | 22.9 | <0.05 | <0.05 | 9.88 | <0.02 | 54.7 | 0.030 | 0.84 | <0.02 | 0.018 | <0.020 | 0.050 | NM | NM | <0.001 | 563 | 7.58 | 13.5 |
| Apr-22 | 2 | 515 | 7.81 | 225 | 209 | 30.0 | 0.10 | <0.05 | 12.8 | <0.02 | 10.5 | 0.023 | 0.50 | <0.02 | 0.011 | <0.020 | 0.079 | 20.7 | 1.21 | <0.001 | 366 | 6.72 | 9.8 |
| Apr-23 | <2 | 623 | 7.93 | 272 | 229 | 41.3 | <0.05 | <0.05 | 22.5 | <0.02 | 10.4 | 0.005 | 0.24 | <0.02 | 0.025 | <0.020 | 0.020 | 29.3 | 0.72 | <0.001 | 434 | 7.61 | 7.3 |
| Nov-23 | <2 | 735 | 7.66 | 301 | 322 | 54.7 | <0.05 | <0.05 | 21.0 | <0.02 | 8.7 | 0.005 | 0.60 | 0.03 | 0.015 | <0.020 | 0.26 | 29.4 | <0.50 | <0.001 | 442 | 6.81 | 1.1 |
| Apr-24 | <2 | 593 | 8.14 | 220 | 248 | 42.2 | 0.08 | <0.05 | 4.43 | 0.02 | 14.2 | 0.001 | 0.26 | 0.06 | 0.015 | <0.020 | <0.050 | 30.9 | 0.84 | 0.0005 | 737 | 8.04 | 10 |
| Nov-24 | <20 | 804 | 7.73 | 410 | 345 | 34.0 | <0.05 | <0.05 | 81.3 | <0.02 | 13.1 | <0.001 | 0.24 | <0.02 | <0.010 | <0.020 | 0.22 | 25.4 | 1.76 | <0.001 | 920 | 8.04 | 10 |
| Average | <5 | 620 | 8.04 | 310 | 257 | 23.4 | 0.09 | <0.10 | 50.1 | 0.019 | 13.6 | 0.003 | 0.63 | 0.023 | 0.0087 | <0.005 | 0.15 | 20.6 | 1.29 | 0.00042 | 499 | 7.57 | 7.2 |
| Std. Dev. | NA | 132 | 0.21 | 89.3 | 50.8 | 12.8 | 0.09 | NA | 51.7 | 0.027 | 8.18 | 0.006 | 0.23 | 0.016 | 0.0052 | NA | 0.48 | 7.18 | 1.29 | 0.00055 | 173 | 0.51 | 3.4 |

HISTORICAL SURFACE WATER QUALITY DATA: S-2

| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
|-----------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|------|------------|-------|------|------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Dec-88 | NM | 559 | NM | 303 | NM | 8.4 | NM | NM | NM | NM | NM | 0.0010 | NM | NM | NM | NM | 4.2 | NM | NM | MM | NM | NM | NM |
| Jan-89 | NM | 458 | NM | 227 | NM | 3.0 | NM | NM | NM | NM | 6.1 | 0.0015 | NM | NM | NM | NM | 4.8 | NM | NM | NM | NM | NM | NM |
| Dec-89 | NM | 733 | NM | NM | NM | 9.7 | NM | NM | NM | NM | NM | NM | NM | NM | NM | NM | NM | NM | NM | MM | NM | NM | NM |
| Jul-90 | NM | 656 | NM | 344 | NM | 8.8 | NM | NM | NM | NM | NM | 0.0020 | NM | NM | NM | NM | 19.0 | NM | NM | NM | NM | NM | NM |
| Nov-94 | NM | 777 | NM | 432 | NM | 11.5 | NM | NM | NM | NM | 9.3 | 0.0039 | NM | NM | NM | NM | 0.18 | NM | NM | MM | NM | NM | NM |
| Average | NA | 637 | NA | 327 | NA | 8.28 | NA | NA | NA | NA | 7.70 | 0.0021 | NA | NA | NA | NA | 7.05 | NA | NA | NA | NA | NA | NA |
| Std. Dev. | NA | 130 | NA | 85.4 | NA | 3.18 | NA | NA | NA | NA | 2.26 | 0.0013 | NA | NA | NA | NA | 8.23 | NA | NA | NA | NA | NA | NA |

HISTORICAL SURFACE WATER QUALITY DATA: S-3

| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
|-----------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|------|------------|-------|------|------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Dec-88 | NM | 586 | NM | NM | NM | 5.1 | NM | NM | NM | NM | NM | 0.0065 | NM | NM | NM | NM | 83.5 | NM | NM | NM | NM | NM | NM |
| Jan-89 | NM | 402 | NM | 217 | NM | 3.0 | NM | NM | NM | NM | 9.52 | 0.0035 | NM | NM | MM | NM | 4.8 | NM | NM | NM | NM | NM | NM |
| Jul-90 | NM | 687 | NM | 367 | NM | 9.8 | NM | NM | NM | NM | NM | 0.0015 | NM | NM | NM | NM | 3.3 | NM | NM | NM | NM | NM | NM |
| Average | NA | 558 | NA | 292 | NA | 6.0 | NA | NA | NA | NA | NA | 0.0035 | NA | NA | NA | NA | 30.5 | NA | NA | NA | NA | NA | NA |
| Std. Dev. | NA | 145 | NA | 106 | NA | 3.5 | NA | NA | NA | NA | NA | 0.0025 | NA | NA | NA | NA | 45.9 | NA | NA | NA | NA | NA | NA |

| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
|-----------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|------|------------|-------|------|------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 796 | NM | 484 | MM | 3.9 | NM | NM | NM | NM | 10.7 | 0.0033 | NM | NM | NM | MM | 0.20 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 633 | NM | 377 | NM | 3.7 | NM | NM | NM | NM | 12.8 | <0.001 | NM | NM | NM | MM | 0.12 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 315 | NM | 171 | NM | 2.8 | NM | NM | MM | NM | 3 | <0.001 | NM | NM | NM | MM | 0.23 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM | 510 | NM | 286 | NM | 3.1 | NM | NM | MM | NM | 5 | <0.001 | NM | NM | NM | MM | 0.15 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 711 | NM | 421 | NM | 8.8 | NM | NM | NM | NM | 25 | <0.001 | NM | NM | NM | NM | 0.16 | NM | NM | NM | NM | NM | NM |
| Nov-01 | NM | 430 | NM | 257 | NM | 5.1 | NM | NM | MM | NM | 23 | <0.001 | NM | NM | NM | MM | 0.17 | NM | NM | NM | NM | NM | NM |
| Dec-02 | MM | 522 | NM | 292 | NM | 4.6 | NM | NM | MM | NM | 14.5 | <0.001 | NM | NM | NM | MM | 0.08 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 596 | NM | 350 | NM | 9.7 | NM | NM | NM | NM | 23.7 | <0.001 | NM | NM | NM | MM | 0.10 | NM | NM | NM | NM | NM | NM |
| Oct-06 | NM | 720 | 8.28 | 407 | 208 | 8.83 | <0.05 | < 0.05 | 216 | <0.05 | 13.1 | NM | NM | NM | NM | MM | 0.34 | 1.47 | NM | < 0.0014 | NM | NM | 7.0 |
| Apr-07 | NM | 501 | 8.70 | 305 | 217 | 7.18 | <0.05 | < 0.05 | 45.7 | < 0.05 | 8.3 | NM | NM | NM | NM | NM | 0.21 | 1.33 | NM | NM | NM | NM | NM |
| Average | NA | 573 | 8.49 | 335 | 213 | 5.77 | <0.05 | < 0.05 | 131 | < 0.05 | 13.9 | <0.001 | NA | NA | NA | NA | 0.10 | 1.40 | NA | <0.001 | NA | NA | 7.0 |
| Std. Dev. | NA | 147 | 0.30 | 91.2 | 6.4 | 2.61 | NA | NA | 120 | NA | 7.8 | NA | NA | NA | NA | NA | 0.08 | 0.10 | NA | NA | NA | NA | NA |

| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
|------------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|------|------------|-------|------|------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 744 | NM | 434 | NM | 4.0 | MM | NM | NM | NM | 9.8 | 0.0031 | NM | NM | NM | NM | 0.14 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 653 | NM | 289 | MM | 29.8 | MM | NM | NM | NM | 12.6 | 0.0142 | NM | NM | NM | NM | 1.09 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 372 | NM | 189 | NM | 5.6 | NM | NM | NM | NM | 7 | <0.001 | NM | NM | NM | NM | 0.58 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM | 604 | NM | 311 | NM | 6.4 | NM | NM | NM | NM | 16 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Oct-97 Dup | NM | 608 | NM | 316 | MM | 6.4 | MM | NM | NM | NM | 11 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Oct-98 | NM | 801 | NM | 443 | NM | 11.5 | MM | NM | NM | NM | 9 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Nov-99 | NM | 530 | NM | 311 | NM | 6.2 | NM | NM | NM | NM | 22 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 716 | NM | 419 | NM | 9.8 | NM | NM | NM | NM | 20 | <0.001 | NM | NM | NM | NM | 0.26 | NM | NM | NM | NM | NM | NM |
| Nov-01 | NM | 472 | NM | 260 | NM | 7.4 | NM | NM | NM | NM | 25 | 0.002 | NM | NM | NM | NM | 0.11 | NM | NM | NM | NM | NM | NM |
| Dec-02 | NM | 528 | NM | 291 | NM | 7.5 | NM | NM | NM | NM | 13.3 | <0.001 | NM | NM | NM | NM | 0.33 | NM | NM | NM | NM | NM | NM |
| Oct-03 | NM | 825 | NM | 461 | NM | 19.8 | NM | NM | NM | NM | 20 | <0.001 | NM | NM | NM | NM | 0.30 | NM | NM | NM | NM | NM | NM |
| Nov-04 | NM | 1030 | NM | 657 | NM | 18.8 | NM | NM | NM | NM | 10 | <0.001 | NM | NM | NM | NM | 2.77 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 578 | NM | 328 | NM | 9.5 | NM | NM | NM | NM | 19.5 | <0.001 | NM | NM | NM | NM | 0.41 | NM | NM | NM | NM | NM | NM |
| Apr-06 | NM | 561 | 8.31 | 305 | 265 | 4.89 | <0.05 | <0.05 | 29.0 | <0.05 | 9 | NM | NM | NM | NM | NM | 0.93 | 1.52 | NM | NM | NM | NM | NM |
| Oct-06 | NM | 665 | 8.37 | 400 | 203 | 8.09 | <0.05 | < 0.05 | 193 | <0.05 | 11.9 | NM | NM | NM | NM | NM | 0.32 | 1.60 | NM | < 0.0017 | NM | NM | 7.0 |
| Apr-07 | NM | 514 | 8.55 | 305 | 224 | 6.49 | <0.05 | < 0.05 | 47.6 | 0.08 | 8.8 | NM | NM | NM | NM | NM | 0.22 | 1.35 | NM | NM | NM | NM | NM |
| Average | NA | 638 | 8.41 | 357 | 231 | 10.1 | < 0.05 | < 0.05 | 89.9 | 0.13 | 14.0 | 0.0019 | NA | NA | NA | NA | 0.48 | 1.49 | NA | NA | NA | NA | 7.0 |
| Std. Dev. | NA | 160 | 0.12 | 109 | 31.5 | 6.9 | NA | NA | 89.8 | NA | 5.6 | 0.0038 | NA | NA | NA | NA | 0.69 | 0.13 | NA | NA | NA | NA | NA |

| | | | | | | | | | | | | | | | | | | | | | | 8 | |
|------------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|------|------------|-------|--------|------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | NV | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 777 | NM | 440 | NM | 11.4 | NM | NM | NM | NM | 9.3 | 0.0056 | NM | NM | NM | NM | 0.64 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 1006 | NM | 539 | NM | 35.2 | NM | NM | NM | NM | 8.8 | <0.001 | NM | NM | NM | NM | 0.54 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 707 | NM | 274 | NM | 10.0 | NM | NM | NM | NM | 3 | 0.0010 | NM | NM | NM | NM | 0.15 | NM | NM | NM | NM | NM | NM |
| Dec-96 Dup | NM | 708 | NM | 350 | NM | 9.8 | NM | NM | NM | NM | 3 | <0.001 | NM | NM | NM | NM | 0.16 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM | 967 | NM | 536 | NM | 26.0 | NM | NM | NM | NM | 10 | <0.001 | NM | NM | NM | NM | 0.26 | NM | NM | NM | NM | NM | NM |
| Nov-99 | NM | 1016 | NM | 552 | NM | 24.4 | NM | NM | NM | NM | NM | <0.001 | NM | NM | NM | NM | 0.01 | NM | NM | NM | NM | NM | NM |
| Nov-99 Dup | NM | 1010 | NM | 542 | NM | 24.3 | NM | NM | NM | NM | 5 | <0.001 | NM | NM | NM | NM | 0.01 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 1089 | NM | 616 | NM | 30.6 | NM | NM | NM | NM | 25 | <0.001 | NM | NM | NM | NM | 3.27 | NM | NM | NM | NM | NM | NM |
| Oct-00 Dup | NM | 1090 | NM | 605 | MM | 30.7 | NM | NM | NM | NM | 28 | <0.001 | NM | NM | NM | NM | 2.05 | NM | NM | NM | NM | NM | NM |
| Nov-01 | NM | 958 | NM | 669 | NM | 20.6 | NM | NM | NM | NM | 13 | <0.001 | NM | NM | NM | NM | 0.49 | NM | NM | NM | NM | NM | NM |
| Dec-02 | NM | 1060 | NM | 577 | NM | 22.9 | NM | NM | NM | NM | 7.1 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Nov-04 | NM | 1080 | NM | 581 | NM | 25.7 | NM | NM | NM | NM | 7.7 | <0.001 | NM | NM | NM | NM | 0.06 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 669 | NM | 338 | NM | 17.7 | NM | NM | NM | NM | 13.6 | <0.001 | NM | NM | NM | NM | 0.03 | NM | NM | NM | NM | NM | NM |
| Oct-06 | NM | 902 | 8.33 | 453 | 349 | 25.7 | 0.50 | < 0.05 | 176 | <0.05 | 9.2 | NM | NM | NM | NM | MM | 0.33 | 17.7 | NM | < 0.0015 | NM | NM | 7.0 |
| Apr-07 | NM | 707 | 8.53 | 398 | 328 | 5.37 | 1.04 | < 0.05 | 52.2 | 0.10 | 5.7 | NM | NM | NM | NM | NM | 0.26 | 8.12 | NM | NM | NM | NM | NM |
| Nov-10 | <5 | 1080 | 8.10 | 489 | 551 | 53.9 | 0.15 | < 0.05 | 56.9 | 16.3 | 14.6 | <0.001 | 19.4 | < 0.05 | 0.29 | 0.064 | 0.67 | NM | NM | 0.2727 | NM | NM | 6.0 |
| Apr-11 | <5 | 954 | 8.14 | 407 | 424 | 29.9 | 1.08 | < 0.05 | 56.9 | 7.7 | 9.4 | <0.001 | 10.3 | 0.06 | 0.18 | 0.013 | 3.82 | NM | NM | 0.0467 | 990 | 7.33 | 15.6 |
| Nov-11 | <5 | 871 | 8.25 | 441 | 430 | 50.8 | 0.49 | < 0.05 | 66.2 | 8.99 | 14.8 | <0.001 | 10.6 | 0.04 | 0.22 | 0.021 | 1.44 | NM | NM | 0.0421 | 1012 | 7.49 | 7.5 |
| Apr-12 | <5 | 1090 | 8.23 | 446 | 516 | 47.6 | <0.05 | < 0.05 | 35.2 | 11.9 | 10.9 | 0.0050 | 13.5 | 0.03 | 0.28 | 0.016 | 3.75 | NM | NM | 0.1400 | 1227 | 7.86 | 8.5 |
| Nov-12 | <5 | 881 | 8.21 | 352 | 254 | 67.2 | 0.21 | < 0.05 | 175 | 2.6 | 19.1 | <0.001 | 5.37 | 0.08 | 0.35 | 0.040 | 0.41 | NM | 25.7 | 0.0315 | 899 | 7.98 | 5.4 |
| Apr-13 | <5 | 883 | 8.26 | 363 | 356 | 43.3 | 0.85 | < 0.25 | 42.7 | 4.68 | 11.8 | <0.001 | 8.07 | 0.06 | 0.17 | 0.020 | 0.18 | NM | 17.1 | 0.1078 | 899 | 8.04 | 11.9 |
| Nov-13 | 7 | 1140 | 8.25 | 461 | 405 | 92 | 0.85 | < 0.25 | 75.2 | 4.92 | 17.5 | 0.0020 | 5.91 | <0.02 | 0.29 | 0.020 | 0.19 | 54 | 16.7 | 0.0524 | 1440 | 8.00 | 3.2 |
| May-14 | <5 | 935 | 8.06 | 380 | 422 | 42.4 | <0.25 | <0.25 | 18.7 | 2.79 | 12.7 | <0.001 | 6.44 | 0.15 | 0.22 | 0.012 | 0.34 | NM | 17.5 | 0.0237 | 366 | 7.68 | 9.5 |
| Oct-14 | 8 | 1050 | 8.16 | 373 | 380 | 85.4 | 0.6 | < 0.25 | 56.5 | 4.7 | 23.9 | 0.0030 | 7.02 | 0.13 | 0.37 | 0.033 | 0.45 | 62 | 21.9 | 0.0321 | 890 | 7.59 | 9.4 |
| Apr-15 | <5 | 836 | 8.14 | 316 | 335 | 48.8 | 0.4 | < 0.25 | 50.5 | 4.26 | 13.0 | <0.001 | 5.23 | 0.05 | 0.18 | 0.008 | 0.08 | NM | 13.7 | 0.0009 | 845 | 6.30 | 2.9 |
| Oct-15 | <5 | 770 | 7.87 | 303 | 161 | 47.9 | 0.38 | < 0.25 | 169 | <0.02 | 18.9 | 0.0030 | 1.19 | 0.11 | 0.11 | 0.118 | 0.25 | NM | 33.4 | 0.0001 | 479 | 7.58 | 7.5 |
| Apr-16 | <5 | 807 | 8.11 | 351 | 382 | 34.9 | <0.25 | < 0.25 | 24.4 | 2.11 | 10.4 | <0.001 | 3.40 | <0.02 | NM | NM | NM | NM | 11.3 | 0.0052 | 362 | 7.20 | 7.9 |
| Nov-16 | 6 | 1100 | 7.48 | 365 | 382 | 77.5 | 0.58 | < 0.25 | 92.4 | 4.06 | 33.9 | <0.001 | 8.04 | 0.11 | 0.31 | 0.084 | 0.69 | NM | 28.8 | 0.0151 | 650 | 7.40 | 7.2 |
| Apr-17 | <5 | 985 | 8.23 | 384 | 403 | 53.3 | 2.45 | < 0.25 | 39.9 | 4.5 | 11.9 | <0.001 | 5.13 | <0.02 | 0.24 | 0.014 | 0.04 | NM | 17.5 | 0.0174 | 1180 | 7.40 | 7.7 |
| Nov-17 | <5 | 1260 | 8.05 | 451 | 385 | 131 | 2.19 | < 0.25 | 113 | 0.95 | 14.9 | <0.001 | 2.64 | 0.04 | 0.53 | 0.020 | 0.20 | 74.5 | 22.3 | 0.0025 | 720 | 7.38 | 3.4 |
| May-18 | <2 | 730 | 8.04 | 310 | 300 | 27.0 | 1.01 | 0.035 | 42.0 | 0.55 | 9.8 | <0.0010 | 1.60 | <0.020 | 0.19 | 0.0057 | <0.1 | NM | NM | 0.010 | 690 | 8.03 | 8.4 |
| Nov-18 | <5 | 1130 | 8.10 | 414 | 389 | 73.7 | 5.28 | < 0.25 | 120 | 1.90 | 15.3 | 0.002 | 4.08 | 0.02 | 0.55 | 0.015 | 0.03 | NM | NM | 0.002 | 383 | 7.10 | 0.30 |
| Apr-19 | <5 | 780 | 7.89 | 323 | 336 | 24.2 | 1.86 | <0.25 | 69.7 | 1.25 | 9.6 | 0.001 | 2.55 | 0.03 | 0.25 | 0.146 | 0.02 | 26.6 | 11.3 | 0.004 | 449 | 7.52 | 2.42 |
| Oct-19 | <5 | 884 | 7.99 | 382 | 334 | 48.0 | 0.37 | <0.25 | 102 | 0.13 | 14.6 | 0.003 | 1.14 | 0.03 | 0.43 | 0.012 | 0.10 | 42.3 | 13.6 | 0.001 | 721 | 7.64 | 10.0 |
| Oct-20 | <2 | 1000 | 8.19 | 486 | 390 | 63.1 | 0.79 | <0.25 | 95.7 | 0.48 | 16.4 | 0.006 | 1.76 | 0.05 | 0.69 | 0.015 | 0.08 | 63.1 | 17.3 | 0.004 | 627 | 7.82 | 5.5 |
| May-21 | <2 | 827 | 8.18 | 325 | 286 | 41.6 | 1.23 | <0.25 | 70.8 | 0.09 | 9.4 | 0.002 | 1.56 | 0.02 | 0.42 | 0.006 | 0.17 | 36.1 | 12.6 | 0.001 | 633 | 7.68 | 7.5 |
| Apr-22 | 2.0 | 984 | 7.92 | 419 | 366 | 33.5 | 1.48 | <0.05 | 118 | 1.76 | 15.2 | 0.008 | 4.64 | <0.02 | 0.51 | <0.020 | 0.10 | 35.8 | 15.7 | 0.002 | 702 | 6.76 | 9.2 |
| Apr-23 | <2 | 951 | 7.99 | 410 | 387 | 42.0 | 1.97 | < 0.05 | 39.7 | 1.80 | 13.7 | 0.003 | 2.93 | 0.04 | 0.39 | <0.020 | 0.06 | 45.9 | 15.6 | 0.009 | 659 | 7.59 | 5.6 |
| Apr-24 | <2 | 921 | 8.05 | 351 | 381 | 31.3 | 1.48 | <0.05 | 41.8 | 1.11 | 15.4 | 0.001 | 2.31 | 0.05 | 0.36 | <0.020 | 0.20 | 34.3 | 12.5 | 0.036 | 838 | 8.16 | 10.3 |
| Nov-24 | <20 | 1000 | 7.81 | 414 | 431 | 81.4 | 0.65 | <0.05 | 27.7 | 0.18 | 12.0 | <0.001 | 0.40 | <0.02 | 0.37 | <0.020 | 2.29 | 66.2 | 13.2 | 0.005 | 1140 | 8.16 | 10.3 |
| Average | 3.02 | 940 | 8.09 | 430 | 373 | 42.3 | 1.04 | <0.25 | 75.1 | 3.33 | 13.3 | 0.0015 | 5.41 | 0.047 | 0.328 | 0.034 | 0.63 | 43.6 | 17.8 | 0.035 | 783 | 7.57 | 7.3 |
| Std. Dev. | 2.27 | 142 | 0.20 | 98 | 75.0 | 25.9 | 1.07 | NA | 45.3 | 3.95 | 6.4 | 0.0018 | 4.43 | 0.040 | 0.141 | 0.039 | 1.02 | 19.8 | 6.10 | 0.060 | 285 | 0.44 | 3.3 |

| | | | | | | | | | | | | | | | | | | 11.0 | 01110712 | JO: 11 7 10 L | | | DATA. 3-0A |
|----------------------|-------------------|--------------|--------------|-------------|-------------|--------------|--------------|----------------|--------------|--------------|--------------|-------------------|-------------|----------------|----------|----------|--------------|--------------|--------------|------------------------|-------------------------|------------|------------------------|
| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 810 | NM | 461 | NM | 10.6 | NM | NM | NM | NM | 9.3 | 0.0039 | NM | NM | NM | NM | 0.34 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 688 | NM | 395 | NM | 7.8 | NM | NM | NM | NM | 12.8 | 0.0013 | NM | NM | NM | NM | 0.26 | NM | NM | NM | NM | NM | NM |
| Oct-95 Dup | NM | 687 | NM | 397 | NM | 8.0 | NM | NM | NM | NM | 12.4 | 0.0013 | NM | NM | NM | NM | 0.21 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 435 | NM | 246 | NM | 5.4 | NM | NM | NM | NM | 7 | 0.0010 | NM | NM | NM | NM | 0.21 | NM | NM | NM | NM | NM | NM |
| Dec-96 Dup | NM | 379 | NM | 202 | NM | 3.2 | NM | NM | NM | NM | 9 | <0.001 | NM | NM | NM | NM | 0.18 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM | 657 | NM | 344 | NM | 6.7 | NM | NM | NM | NM | 11 | <0.001 | NM | NM | NM | NM | 0.16 | NM | NM | NM | NM | NM | NM |
| Oct-98 | NM | 760 | NM | 397 | NM | 14.2 | NM | NM | NM | NM | 8 | <0.001 | NM | NM | NM | NM | 0.24 | NM | NM | NM | NM | NM | NM |
| Nov-99 | NM | 549 | NM | 313 | NM | 6.1 | NM | NM | NM | NM | 16 | <0.001 | NM | NM | NM | NM | 0.05 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 795 | NM | 468 | NM | 12.2 | NM | NM | NM | NM | 24 | <0.001 | NM | NM | NM | NM | 0.91 | NM | NM | NM | NM | NM | NM |
| Nov-01 | NM | 487 | NM | 275 | NM | 7.7 | NM | NM | NM | NM | 22 | <0.001 | NM | NM | NM | NM | 0.19 | NM | NM | NM | NM | NM | NM |
| Dec-02 | NM | 582 | NM | 284 | NM | 8.0 | NM | NM | NM | NM | 13.2 | <0.001 | NM | NM | NM | NM | 0.17 | NM | NM | NM | NM | NM | NM |
| Oct-03 | NM | 809 | NM | 441 | NM | 19.3 | NM | NM | NM | NM | 22.0 | <0.001 | NM | NM | NM | NM | 0.13 | NM | NM | NM | NM | NM | NM |
| Nov-04 | NM | 936 | NM | 547 | NM | 20.5 | NM | NM | NM | NM | 8.2 | <0.001 | NM | NM | NM | NM | 1.79 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 534 | NM | 277 | NM | 13.7 | NM | NM | NM | NM | 16.9 | <0.001 | NM | NM | NM | NM | 1.05 | NM | NM | NM | NM | NM | NM |
| Nov-05 Dup | NM | 524 | NM | 281 | NM | 13.2 | NM 0.14 | NM | NM | NM | 15.8 | <0.001 | NM | NM | NM | NM | 0.18 | NM 7.70 | NM | NM | NM | NM | NM |
| Apr-06 | NM | 639 | 8.39 | 336 | 307 | 10.3 | 0.14 | <0.05 | 31.8 | 0.35 | 9.0 | NM | NM | NM | NM | NM | 1.01 | 7.70 | NM | NM | NM | NM | NM |
| Oct-06 | NM | 705 | 8.34 | 386 | 226 | 16.7 | 0.37 | <0.05 | 324 | 0.10 | 11.2 | NM | NM | NM | NM | NM | 0.31 | 7.38 | NM | 0.0031 | NM | NM | 7.0 |
| Apr-07 | NM | 716 | 8.50 | 414 | 341 | 4.86 | 0.76 | <0.05 | 49.9 | 0.46 | 7.4 | NM | NM | NM | NM | NM | 0.26 | 7.45 | NM | NM | NM | NM | NM |
| Nov-07 | NM NM | 907 534 | 8.27 | 475 | 276 | 25.9 | 0.31 | <0.05 | 211 36.3 | 0.19 | 32.8 | NM NM | NM NM | NM NM | NM | NM | 0.10 | 15.9 7.24 | NM NM | 0.0045 | NM NM | NM NM | 5.5 10.5 |
| Apr-08 Apr-09 | NM | 632 | 8.29 8.27 | 284 357 | 250 233 | 11.1 9.18 | 0.29 0.56 | <0.05 <0.05 | 100 | 0.43 0.05 | 8.8 11.0 | NM | NM | NM | NM NM | NM NM | 0.31 0.44 | 7.79 | NM | 0.0156 0.0012 | NM NM | NM | 6.0 |
| Nov-09 | NM | 891 | 8.21 | 489 | 378 | 31.1 | 0.36 | <0.05 | 75.4 | 0.05 | 13.9 | NM | NM | NM | NM | NM | 0.44 | 19.1 | NM | 0.0012 | NM | NM | 6.0 |
| Apr-10 | NM | 514 | 8.29 | 269 | 230 | 14.4 | 0.76 | <0.05 | 37.2 | 0.16 | 12.5 | NM | NM | NM | NM | NM | 0.13 | 7.92 | 4.0 | 0.0039 | NM | NM | 10.0 |
| Nov-10 | NM | 1050 | 8.22 | 469 | 521 | 56.4 | 0.99 | <0.05 | 57.0 | 18.1 | 14.0 | NM | NM | NM | NM | NM | 0.35 | 44.1 | 24.8 | 0.5014 | NM | NM | 9.0 |
| Apr-11 | <5 | 920 | 8.20 | 430 | 412 | 29.8 | 0.75 | <0.05 | 58.7 | 5.72 | 8.9 | <0.001 | 8.84 | <0.05 | 0.18 | 0.008 | 0.63 | NM | NM | 0.0397 | 920 | 7.46 | 13.4 |
| Nov-11 | NM | 741 | 8.23 | 380 | 354 | 36.5 | 0.44 | <0.05 | 67.7 | 5.53 | 11.9 | NM | NM | NM | NM | NM | 0.39 | 25.7 | 11.6 | 0.0588 | 828 | 7.84 | 7.7 |
| Apr-12 | <5 | 774 | 8.18 | 357 | 331 | 29.3 | 0.23 | < 0.05 | 56.9 | 3.95 | 9.6 | 0.003 | 5.14 | 0.03 | 0.088 | 0.007 | 0.27 | NM | NM | 0.0479 | 1128 | 7.97 | 5.7 |
| Nov-12 | <5 | 709 | 8.21 | 357 | 199 | 31.8 | 0.21 | <0.05 | 189 | 0.17 | 13.8 | <0.001 | 1.13 | <0.02 | 0.090 | 0.013 | 0.05 | NM | 7.73 | 0.0012 | 804 | 7.75 | 5.2 |
| Apr-13 | <5 | 813 | 8.28 | 331 | 324 | 40.0 | 0.77 | <0.25 | 40.7 | 3.74 | 10.3 | <0.001 | 6.09 | 0.03 | 0.13 | 0.017 | 0.11 | NM | 13.4 | 0.0807 | 748 | 8.00 | 12.2 |
| Nov-13 | <5 | 672 | 8.28 | 305 | 233 | 23.1 | <0.25 | <0.25 | 83.6 | <0.02 | 11.8 | <0.001 | 0.75 | <0.02 | <0.010 | <0.005 | <0.01 | 13.7 | 1.11 | <0.0002 | 786 | 8.03 | 3.4 |
| May-14 | <5 | 821 | 8.05 | 348 | 347 | 36.7 | <0.25 | <0.25 | 32.6 | 2.78 | 12.3 | <0.001 | 5.34 | 0.09 | 0.15 | <0.005 | 2.92 | NM | 12.3 | 0.0263 | 339 | 7.64 | 12.1 |
| Oct-14 | <5 | 838 | 8.21 | 316 | 319 | 57.6 | <0.25 | < 0.25 | 51.0 | 2.97 | 17.9 | 0.002 | 4.82 | 0.10 | 0.19 | 0.022 | 0.23 | 40.4 | 13.8 | 0.0226 | 452 | 7.63 | 9.6 |
| Apr-15 | <5 | 909 | 8.20 | 345 | 375 | 50.5 | 0.89 | < 0.25 | 51.9 | 3.40 | 13.3 | <0.001 | 5.46 | 0.03 | 0.20 | 0.009 | 0.03 | NM | 15.8 | 0.0075 | 919 | 7.31 | 3.3 |
| Apr-16 | <5 | 749 | 8.08 | 337 | 338 | 33.5 | 0.6 | <0.25 | 32.4 | 3.44 | 11.3 | <0.001 | 4.80 | <0.02 | NM | NM | NM | NM | 10.2 | 0.0088 | 630 | 7.21 | 8.0 |
| Nov-16 | <5 | 1040 | 7.56 | 343 | 368 | 74.2 | <0.25 | <0.25 | 89.9 | 2.27 | 27.3 | <0.001 | 5.22 | 0.03 | 0.29 | 0.012 | 0.07 | NM | 28.0 | 0.0136 | 677 | 7.58 | 8.0 |
| Nov-17 | <5 | 1230 | 8.13 | 451 | 370 | 122 | 2.11 | <0.25 | 127 | 0.45 | 13.9 | <0.001 | 2.17 | 0.03 | 0.56 | 0.007 | <0.01 | 73.3 | 23.4 | 0.0034 | 773 | 7.75 | 5.9 |
| May-18 | <2 | 820 | 8.18 | 340 | 350 | 30 | 1.16 | 0.029 | 38 | 1.9 | 11 | <0.0010 | 3 | <0.040 | 0.24 | 0.011 | <0.1 | NM | NM | 0.06 | 655 | 8.26 | 9.4 |
| Nov-18 | <5 | 1120 | 8.09 | 411 | 376 | 76 | 5.71 | <0.25 | 136 | 1.91 | 15 | 0.003 | 3.64 | <0.02 | 0.63 | 0.014 | 0.01 | NM | NM | 0.002 | 563 | 7.21 | -0.5 |
| Apr-19 | <5 | 469 | 7.82 | 199 | 221 | 16 | 0.59 | <0.05 | 18.1 | 0.30 | 8.4 | <0.001 | 0.76 | <0.02 | 0.076 | 0.005 | 0.02 | 14.2 | 3.25 | 0.001 | 359 | 7.49 | 2.3 |
| Oct-20 | <2 | 965 | 8.19 | 418 | 376 | 58.9 | 0.96 | <0.25 | 95.1 | 0.19 | 15.2 | 0.004 | 1.41 | 0.04 | 0.60 | 0.007 | 0.055 | 51.9 | 13.9 | 0.002 | 604 | 7.93 | 6.1 |
| May-21 | <2 | 863 | 8.20 | 336 | 330 | 40.1 | 1.74 | <0.25 | 49.1 | 1.51 | 10.2 | 0.003 | 3.81 | 0.02 | 0.37 | 0.025 | 0.48 | 34.8 | 13.9 | 0.010 | 652 | 7.65 | 7.5 |
| Apr-22 | <2 | 956 | 7.97 | 430 | 359 | 32.2 | 1.63 | <0.05 | 116 | 1.48 | 15.0 | 0.008 | 3.99 | <0.02 | 0.46 | <0.020 | 0.071 | 35.6 | 15.5 | 0.001 | 368 | 6.70 | 10.1 |
| Nov-23 | <2 | 1040 | 7.94 | 428 | 526 | 54.5 | 2.03 | < 0.05 | 32.0 | 0.79 | 10.4 | 0.006 | 1.90 | <0.02 | 0.45 | <0.020 | 0.17 | 45.2 | 13.2 | 0.003 | 586 | 7.69 | 0.0 |
| Apr-24 | <2 | 825 | 8.06 | 321 | 374 | 28.7 | 1.60 | <0.05 | 38.0 | 0.82 | 15.0 | 0.001 | 1.78 | 0.04 | 0.36 | <0.020 | 0.13 | 35.8 | 11.6 | 0.031 | 560 | 8.24 | 9.9 |
| Nov-24 | <20 | 977 | 7.85 | 409 | 438 | 80.2 | 0.51 | <0.05 | 29.6 | <0.02 | 11.3 | <0.001 | 0.46 | 0.04 | 0.36 | <0.020 | 1.15 | 63.1 | 13.2 | <0.001 | 990 | 8.24 | 9.9 |
| Average | -/5 | 766 | 0.16 | 264 | 226 | 20.2 | 0.00 | <0.2E | 70.5 | 2.14 | 12./ | 0.0014 | 3.53 | 0.020 | 0.302 | 0.011 | 0.27 | 27.0 | 12.2 | 0.0279 | 602 | 7.60 | 7.0 |
| Average Std. Dev. | <5 NA | 766 193 | 8.16 0.19 | 364 76.9 | 336 80.2 | 29.3 24.9 | 0.90 1.08 | <0.25 NA | 78.5 65.8 | 2.14 3.44 | 13.4 5.28 | 0.0014 0.00176 | 2.22 | 0.030 0.025 | 0.302 | 0.011 | 0.37 0.53 | 27.9 | 13.2 6.85 | 0.0378 0.097 | 683 211 | 7.69 | 7.3 3.5 |
| olu. Dev. | L NA | 193 | 0.19 | 10.9 | 00.2 | 24.9 | 1.00 | INA | 0.00 | J.44 | 0.20 | J U.UU1/0 | L.LL | 0.025 | U. 10 I | U.000 | 0.33 | ZU.S | 0.00 | 0.097 | | 0.59 | 5.5 |

| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
|------------|-------------------|--------------|----------|----------|------------|----------|---------|---------|----------|---------|------|---------|-------|------------|-------|-----------|--------|--------|-----------|-----------------------|-------------------------|------------|------------------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 870 | NM | 523 | NM | 9.9 | NM | NM | NM | NM | 9.0 | 0.0070 | NM | NM | NM | NM | 0.18 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 575 | NM | 337 | NM | 4.5 | NM | NM | NM | NM | 13.9 | 0.0063 | NM | NM | NM | NM | 0.58 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 379 | NM | 202 | NM | 3.2 | NM | NM | NM | NM | 9 | <0.001 | NM | NM | MM | NM | 0.18 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM | 604 | NM | 344 | NM | 3.3 | NM | NM | NM | NM | 21 | <0.001 | NM | NM | NM | NM | 0.39 | NM | NM | NM | NM | NM | NM |
| Oct-98 | NM | 1568 | NM | 830 | NM | 2.0 | NM | NM | NM | NM | 10 | <0.001 | NM | NM | NM | NM | 0.13 | NM | NM | NM | NM | NM | NM |
| Oct-98 Dup | NM | 1605 | NM | 888 | NM | 2.0 | NM | NM | NM | NM | 17 | <0.001 | NM | NM | NM | NM | 0.12 | NM | NM | NM | NM | NM | NM |
| Nov-99 | NM | 579 | NM | 330 | NM | 6.0 | NM | NM | NM | NM | 17 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 856 | NM | 511 | NM | 14.0 | NM | NM | NM | NM | 17 | <0.001 | NM | NM | NM | NM | 0.16 | NM | NM | NM | NM | NM | NM |
| Nov-01 | NM | 419 | NM | 217 | NM | 2.6 | NM | NM | NM | NM | 17 | <0.001 | NM | NM | NM | NM | 0.15 | NM | NM | NM | NM | NM | NM |
| Nov-01 Dup | NM | 420 | NM | 236 | NM | 2.7 | NM | NM | NM | NM | 16 | <0.001 | NM | NM | NM | NM | 0.15 | NM | NM | NM | NM | NM | NM |
| Dec-02 | NM | 580 | NM | 315 | NM | 7.9 | NM | NM | NM | NM | 12.5 | <0.001 | NM | NM | NM | NM | 0.09 | NM | NM | NM | NM | NM | NM |
| Dec-02 Dup | NM | 573 | NM | 308 | NM | 7.9 | NM | NM | NM | NM | 131 | <0.001 | NM | NM | NM | NM | 0.09 | NM | NM | NM | NM | NM | NM |
| Oct-03 | NM | 594 | NM | 338 | NM | 8.9 | NM | NM | NM | NM | 21.0 | <0.001 | NM | NM | NM | NM | 0.20 | NM | NM | NM | NM | NM | NM |
| Nov-04 | NM | 689 | NM | 391 | NM | 9.9 | NM | NM | NM | NM | 7.5 | <0.001 | NM | NM | NM | NM | 0.39 | NM | NM | NM | NM | NM | NM |
| Nov-04 Dup | NM | 685 | NM | 404 | NM | 9.7 | NM | NM | NM | NM | 7.6 | <0.001 | NM | NM | NM | NM | 0.80 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 458 | NM | 242 | NM | 5.6 | NM | NM | NM | NM | 21.2 | <0.001 | NM | NM | NM | NM | 0.21 | NM | NM | NM | NM | NM | NM |
| Apr-06 | NM | 319 | 8.51 | 175 | 160 | 1.62 | <0.05 | <0.05 | 3.11 | <0.05 | 11.0 | NM | NM | NM | NM | NM | 0.52 | 1.15 | NM | NM | NM | NM | NM |
| Oct-06 | NM | 341 | 8.44 | 197 | 148 | 1.80 | <0.05 | <0.05 | 45.0 | <0.05 | 22.1 | NM | NM | NM | NM | NM | 0.19 | 1.09 | NM | <0.0019 | NM | NM | 7.0 |
| Apr-07 | NM | 296 | 8.38 | 176 | 142 | 1.44 | <0.05 | < 0.05 | 11.3 | <0.05 | 11.3 | NM | NM | NM | NM | NM | 0.25 | 0.81 | NM | NM | NM | NM | NM |
| Nov-07 | NM | 409 | 8.37 | 224 | 152 | 2.62 | < 0.05 | < 0.05 | 61.5 | 0.16 | 23.1 | NM | NM | NM | NM | NM | <0.005 | 0.49 | NM | 0.0051 | NM | NM | 6.5 |
| Apr-08 | NM | 278 | 8.24 | 155 | 142 | 2.34 | 0.07 | <0.05 | 9.0 | <0.05 | 10.6 | NM | NM | NM | NM | NM | 0.02 | 0.99 | NM | <0.0016 | NM | NM | 10.0 |
| Apr-09 | NM | 263 | 8.23 | 155 | 134 | 1.61 | 0.07 | <0.05 | 5.18 | <0.05 | 11.4 | NM | NM | NM | NM | NM | 0.51 | 1.08 | NM | <0.0010 | NM | NM | 5.0 |
| Nov-09 | NM | 380 | 8.41 | 238 | 199 | 1.45 | <0.05 | <0.05 | 11.1 | <0.05 | 20.9 | NM | NM | NM | NM | NM | 0.08 | 1.33 | NM | <0.0017 | NM | NM | 6.0 |
| Apr-10 | NM | 323 | 8.30 | 187 | 173 | 1.90 | <0.05 | <0.05 | 7.55 | <0.02 | 15.0 | NM | NM_ | NM | NM | NM | 0.04 | 1.33 | 0.83 | <0.0006 | NM | NM | 8.0 |
| Nov-10 | NM | 397 | 8.35 | 258 | 219 | 3.46 | < 0.05 | < 0.05 | 36 | <0.02 | 23.2 | NM | NM | NM | NM | NM | <0.01 | 1.46 | 0.39 | <0.0006 | NM | NM | 6.0 |
| Average | NA NA | 578 | 8.36 | 327 | 163 | 4.73 | <0.05 | <0.05 | 21.1 | <0.05 | 19.9 | 0.0013 | NA NA | NA | NA | NA | 0.22 | 1.08 | 0.61 | <0.005 | NA NA | NA NA | 6.9 |
| Std. Dev. | NA | 347 | 0.09 | 189 | 28.7 | 3.54 | NA | NA | 21.0 | NA I | 23.7 | 0.0021 | NA | NA | NA | <u>NA</u> | 0.20 | 0.30 | 0.31 | NA | NA | NA | 1.6 |

| | | | | | | | | | | | | | | | | | | | | | LWAILK | | Designation of the Control of the Co |
|------------------|-------------------|--------------|--------------|------------|------------|--------------|---------------|----------------|--------------|---------------|--------------|------------------|--------------|----------------------|----------------|-----------------|---------------|--------------|--------------|-----------------------|-------------------------|--------------|--|
| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized Ammonia | Conductivity (field) | pH (field) | Temperature (field) |
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | 500 | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | 0.02 | NV | 6.5-8.5 | NA |
| UNITS | mg/L | uS/cm | Unitless | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 772 | NM | 465 | NM | 7.0 | NM | NM | NM | NM | 8.8 | 0.0047 | NM | NM | NM | NM | 0.12 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 642 | NM | 375 | NM | 6.4 | NM | NM | NM | NM | 12 | 0.0129 | NM | NM | NM | NM | 0.28 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 389 | NM | 215 | NM | 4.0 | NM | NM | NM | NM | 9 | <0.001 | NM | NM | NM | NM | 0.39 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM NM | 651 1376 | NM NM | 364 754 | NM NM | 6.5 1.4 | NM NM | NM | NM NM | NM NM | 13 11 | <0.001 <0.001 | NM NM | NM NM | NM NM | NM NM | 0.04 0.05 | NM NM | NM NM | NM NM | NM NM | NM NM | NM NM |
| Oct-98 Nov-99 | NM | 540 | NM | 308 | NM | 4.6 | NM | NM NM | NM | NM | 16 | <0.001 | NM | NM | NM | NM | 0.05 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 785 | NM | 457 | NM | 7.5 | NM | NM | NM | NM | 13 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Nov-01 | NM | 502 | NM | 283 | NM | 6.8 | NM | NM | NM | NM | 23 | <0.001 | NM | NM | NM | NM | 0.07 | NM | NM | NM | NM | NM | NM |
| Dec-02 | NM | 561 | NM | 315 | NM | 6.2 | NM | NM | NM | NM | 11.2 | <0.001 | NM | NM | NM | NM | 0.07 | NM | NM | NM | NM | NM | NM |
| Oct-03 | NM | 639 | NM | 346 | NM | 10.8 | NM | NM | NM | NM | 18.0 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Nov-04 | NM | 667 | NM | 383 | NM | 9.4 | NM | NM | NM | NM | 6.9 | <0.001 | NM | NM | NM | NM | 0.07 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 447 | NM | 254 | NM | 4.3 | NM | NM | NM | NM | 23.4 | <0.001 | NM | NM | NM | NM | 0.37 | NM | NM | NM | NM | NM | NM |
| Apr-06 | NM | 329 | 8.62 | 185 | 167 | 1.86 | <0.05 | < 0.05 | 4.46 | <0.05 | 10 | NM | NM | NM | NM | NM | 0.53 | 1.35 | NM | NM | NM | NM | NM |
| Oct-06 | NM | 387 | 8.41 | 218 | 156 | 3.02 | <0.05 | <0.05 | 56.1 | <0.05 | 20.8 | NM | NM | NM | NM | NM | 0.18 | 1.72 | NM | <0.0018 | NM | NM | 7.0 |
| Apr-07 | NM | 304 | 8.71 | 178 | 144 | 1.89 | <0.05 | <0.05 | 12.8 | 0.18 | 11.8 | NM | NM | NM | NM | NM | 0.13 | 1.07 | NM | NM | NM | NM | NM |
| Nov-07 | NM | 499 | 8.26 | 271 | 167 | 4.34 | 0.06 | <0.05 | 92.6 | 0.11 | 20.4 | NM | NM | NM | NM | NM | <0.005 | 1.21 | NM | 0.0024 | NM | NM | 5.0 |
| Apr-08 | NM | 286 | 8.33 | 157 | 147 | 2.25 | <0.05 | <0.05 | 10.0 | <0.05 | 10.3 | NM | NM | NM | NM | NM | 0.03 | 1.17 | NM | <0.0015 | NM | NM | 7.0 |
| Oct-08 | NM | 630 | 8.20 | 352 | 254 | 8.48 | <0.05 | <0.05 | 57.4 | <0.05 | 8.5 | NM | NM | NM | NM | NM | 0.04 | 6.23 | NM | <0.0010 | NM | NM | 6.0 |
| Apr-09 | NM | 275 | 8.29 | 167 | 139 | 1.77 | <0.05 | <0.05 | 6.02 | <0.02 | 10.2 | NM | NM | NM | NM | NM | 0.07 | 1.04 | NM | <0.0004 | NM | NM | 4.0 |
| Nov-09 | NM | 431 | 8.16 | 253 | 226 | 3.06 | <0.05 | <0.05 | 17.5 | <0.05 | 19.8 | NM | NM | NM | NM | NM | 0.14 | 2.45 | NM | <0.0009 | NM | NM | 4.5 |
| Apr-10 | NM | 397 | 8.30 | 217 | 206 | 4.17 | 0.11 | <0.05 | 13.7 | 0.45 | 13.3 | NM | NM | NM | NM | NM | 0.02 | 3.34 | 2.15 | 0.0138 | NM | NM | 8.0 |
| Nov-10 | NM | 465 | 8.18 | 285 241 | 223 | 6.82 | 0.87 | <0.05 | 51.6 | 0.09 | 20.4 | NM | NM NM | NM NM | NM | NM NM | 0.04 | 4.23 | 2.04 | 0.0018 | NM | NM 7.04 | 6.0 7.1 |
| Nov-11 Apr-12 | NM <5 | 366 416 | 8.19 8.02 | 223 | 207 208 | 7.31 6.51 | 0.18 1.08 | <0.05 <0.05 | 28.8 9.67 | 0.16 <0.02 | 16.5 10.7 | 0.0010 | 0.70 | 0.03 | NM 0.019 | 0.172 | 0.03 | 4.10 NM | 1.73 NM | 0.0015 <0.0002 | 433 426 | 7.81 7.83 | 5.3 |
| Nov-12 | <5 | 609 | 8.31 | 319 | 186 | 22.4 | 0.44 | <0.05 | 149 | 0.02 | 13.0 | <0.0010 | 0.70 | <0.02 | 0.019 | 0.006 | 0.04 | NM | 5.76 | 0.0002 | 657 | 7.73 | 5.5 |
| Apr-13 | <5 | 335 | 8.13 | 171 | 151 | 6.2 | 0.44 | <0.05 | 14.9 | 0.02 | 9.5 | <0.001 | 0.71 | <0.02 | <0.010 | <0.005 | <0.03 | NM | 0.85 | 0.0001 | 320 | 8.15 | 8.0 |
| Nov-13 | <5 | 432 | 8.28 | 209 | 183 | 6.57 | 0.14 | <0.10 | 32.6 | 0.11 | 18.5 | 0.0010 | 0.92 | <0.02 | 0.016 | <0.005 | 0.01 | 4.13 | 1.24 | 0.0014 | 434 | 8.08 | 3.0 |
| May-14 | <5 | 358 | 8.11 | 189 | 177 | 4.2 | 0.05 | <0.05 | 6.57 | 0.21 | 12.8 | <0.001 | 0.95 | <0.02 | 0.014 | <0.005 | 0.02 | NM | 0.9 | 0.0025 | 144 | 7.83 | 9.3 |
| Oct-14 | <5 | 446 | 8.22 | 236 | 230 | 7.01 | <0.05 | <0.05 | 8.10 | 0.06 | 18.7 | <0.001 | 0.78 | 0.06 | 0.019 | <0.005 | 0.06 | 4.53 | 1.93 | 0.0004 | 408 | 7.58 | 8.6 |
| Apr-15 | <5 | 357 | 8.22 | 184 | 181 | 5.48 | 0.06 | < 0.05 | 7.78 | 0.03 | 10.0 | <0.001 | 0.52 | <0.02 | 0.011 | <0.005 | 0.01 | NM | 1.12 | 0.00001 | 367 | 6.45 | 1.2 |
| Oct-15 | <5 | 921 | 7.94 | 493 | 142 | 51.3 | 1.22 | <0.25 | 285 | <0.02 | 18.1 | 0.002 | 0.97 | 0.03 | <0.010 | <0.005 | <0.01 | NM | 3.64 | 0.00001 | 631 | 6.54 | 9.1 |
| Apr-16 | <5 | 317 | 7.90 | 168 | 161 | 3.66 | 0.06 | <0.05 | 10.8 | <0.02 | 11.5 | <0.001 | 1.10 | <0.02 | NM | NM | NM | NM | 0.71 | 0.00004 | 210 | 7.10 | 6.5 |
| Nov-16 | <5 | 690 | 7.51 | 309 | 277 | 20.9 | <0.25 | <0.25 | 86.0 | <0.02 | 16.2 | <0.001 | 0.70 | <0.02 | 0.023 | 0.005 | <0.01 | NM | 4.19 | 0.00010 | 450 | 7.51 | 7.6 |
| Apr-17 | <5 | 363 | 8.02 | 187 | 175 | 4.17 | <0.05 | <0.05 | 11.8 | <0.02 | 12.7 | <0.001 | 0.49 | <0.02 | 0.019 | <0.005 | 0.02 | NM | 0.95 | 0.00012 | 393 | 7.57 | 8.0 |
| Nov-17 | <5 | 516 | 8.02 | 272 | 234 | 9.65 | <0.10 | <0.10 | 37.2 | <0.02 | 19.0 | <0.001 | 0.82 | 0.02 | 0.034 | 0.007 | <0.01 | 7.08 | 1.72 | 0.00017 | 305 | 7.87 | 4.4 |
| May-18 | 2 | 260 | 8.16 | 130 | 140 | <1.0 | <0.10 | <0.010 | <1.0 | <0.050 | 3.4 | <0.0010 | 0.21 | <0.020 | <0.01 | <0.005 | 0.13 | NM | NM | <0.001 | 201 | 7.78 | 13.6 |
| Nov-18 | <5 | 348 | 7.78 | 166 | 189 | 1.77 | 0.13 | <0.05 | 10.3 | <0.02 | 6.2 | <0.001 | 0.38 | 0.11 | 0.027 | 0.009 | 1.71 | NM 2.55 | NM | <0.001 | 176 | 7.63 | -0.4 |
| Apr-19 Oct-19 | <5 <5 | 309 451 | 7.86 7.87 | 150 240 | 166 228 | 3.31 7.44 | 0.08 <0.05 | <0.05 <0.05 | 4.52 19.6 | 0.02 <0.02 | 7.9 21.6 | <0.001 0.001 | 0.21 0.68 | <0.02 0.03 | 0.014 0.042 | <0.005 0.016 | <0.01 0.01 | 2.55 5.57 | 0.98 1.62 | <0.001 <0.001 | 159 241 | 7.65 7.87 | 0.6 10.2 |
| Oct-19 | <2 | 489 | 8.13 | 294 | 258 | 7.44 | <0.05 | <0.05 | 17.3 | <0.02 | 20.7 | <0.001 | 0.87 | 0.03 | 0.042 | <0.005 | 0.01 | 6.11 | 2.12 | <0.001 | 299 | 7.87 | 5.5 |
| May-21 | <2 | 331 | 8.20 | 170 | 170 | 0.70 | <0.05 | <0.05 | 0.46 | <0.02 | 3.7 | 0.001 | 0.35 | <0.02 | 0.036 | <0.005 | 0.12 | 0.11 | 1.94 | <0.001 | 332 | 7.90 | 9.5 |
| Oct-21 | <2 | 567 | 8.01 | 311 | 282 | 3.87 | <0.05 | <0.05 | 50.8 | <0.02 | 40.4 | 0.001 | 1.22 | <0.02 | 0.010 | <0.003 | 0.12 | NM | NM | <0.001 | 466 | 7.90 | 16.9 |
| Apr-22 | <2 | 378 | 7.96 | 207 | 191 | 4.93 | 0.09 | <0.05 | 7.70 | <0.02 | 13.5 | 0.001 | 0.55 | <0.02 | 0.028 | <0.020 | 0.098 | 3.81 | 2.18 | <0.001 | 183 | 6.38 | 8.5 |
| Sep-22 | 2.0 | 385 | 7.98 | 189 | 173 | 5.44 | <0.05 | <0.05 | 7.67 | <0.02 | 15.8 | 0.006 | 0.43 | <0.02 | 0.015 | <0.020 | 0.092 | 4.71 | 1.10 | <0.001 | 289 | 6.96 | 15.8 |
| Apr-23 | <2 | 424 | 8.06 | 233 | 202 | 5.73 | 0.08 | <0.05 | 6.89 | <0.02 | 12.3 | <0.001 | 0.30 | <0.02 | 0.033 | <0.020 | 0.082 | 4.56 | 1.75 | <0.001 | 214 | 7.74 | 6.4 |
| Nov-23 | 2.0 | 484 | 7.93 | 242 | 285 | 4.95 | 0.14 | <0.05 | 8.65 | <0.02 | 8.8 | 0.003 | 0.27 | 0.04 | 0.033 | <0.020 | 0.24 | 2.51 | 0.64 | <0.001 | 190 | 7.74 | 0.0 |
| Apr-24 | <2 | 363 | 8.15 | 193 | 214 | 4.31 | 0.05 | <0.05 | 2.98 | 0.03 | 17.1 | <0.001 | 0.20 | 0.04 | 0.031 | <0.020 | 0.068 | 4.16 | 1.01 | 0.0015 | 349 | 8.34 | 10.9 |
| Nov-24 | <20 | 492 | 7.97 | 277 | 297 | 6.88 | <0.05 | <0.05 | 12.4 | <0.02 | 16.7 | <0.001 | <0.10 | <0.02 | 0.021 | <0.020 | 0.079 | 5.49 | 2.26 | <0.001 | 540 | 8.34 | 10.9 |
| | | | | | | | | | | | | | | | | | | | | | | | |
| Average | <5 | 487 | 8.12 | 267 | 198 | 6.91 | 0.15 | <0.10 | 33.1 | 0.051 | 14.3 | 0.0020 | 0.63 | 0.024 | 0.023 | 0.013 | 0.133 | 3.50 | 1.86 | 0.0010 | 339 | 7.62 | 7.0 |
| Std. Dev. | NA | 197 | 0.22 | 111 | 44.6 | 7.76 | 0.29 | NA | 53.9 | 0.086 | 6.31 | 0.0047 | 0.30 | 0.025 | 0.014 | 0.034 | 0.263 | 1.88 | 1.20 | 0.0023 | 141 | 0.53 | 3.9 |


| Parameter | CBOD ₅ | Conductivity | рН | Hardness | Alkalinity | Chloride | Nitrate | Nitrite | Sulphate | Ammonia | DOC | Phenols | TKN | Phosphorus | Boron | Zinc | Iron | Sodium | Potassium | Un-ionized | Conductivity | pH (field) | Temperature |
|------------------|-------------------|--------------|--------------|------------|------------|--------------|----------------|----------------|--------------|----------------|--------------|------------------------|--------------|----------------|----------|------------------|---------------|--------------|--------------|------------------------|---------------|---------------------|---------------|
| PWQO | NV | NV | 6.5-8.5 | NV | NV | NV | NV | NV | NV | NV | NV | 0.0010 | NV | 0.02 | 0.2 | 0.03 | 0.3 | NV | NV | Ammonia 0.02 | (field) NV | 6.5-8.5 | (field) NA |
| UNITS | mg/L | uS/cm | Unitless | ma/L | ma/L | ma/L | mg/L | mg/L | mg/L | ma/L | mg/L | mg/L | ma/L | ma/L | ma/L | ma/L | ma/L | mg/L | ma/L | mg/L | uS/cm | Unitless | °C |
| Nov-94 | NM | 587 | NM | 335 | NM | 6.4 | NM | NM | NM | NM | 8.2 | 0.0034 | NM | NM | NM | NM | 0.24 | NM | NM | NM | NM | NM | NM |
| Oct-95 | NM | 571 | NM | 323 | NM | 7.4 | NM | NM | NM | NM | 10.4 | 0.0081 | NM | NM | NM | NM | 0.36 | NM | NM | NM | NM | NM | NM |
| Dec-96 | NM | 410 | NM | 226 | NM | 4.1 | NM | NM | NM | NM | 8 | <0.001 | NM | NM | NM | NM | 0.57 | NM | NM | NM | NM | NM | NM |
| Oct-97 | NM | 509 | NM | 264 | NM | 6.7 | NM | NM | NM | NM | 15 | <0.001 | NM | NM | NM | NM | 0.27 | NM | NM | NM | NM | NM | NM |
| Oct-98 | NM | 454 | NM | 236 | NM | 1.5 | NM | NM | NM | NM | 16 | <0.001 | NM | NM | NM | NM | 0.57 | NM | NM | NM | NM | NM | NM |
| Nov-99 | NM | 497 | NM | 264 | NM | 4.8 | NM | NM | NM | NM | 14 | <0.001 | NM | NM | NM | NM | 0.04 | NM | NM | NM | NM | NM | NM |
| Oct-00 | NM | 490 | NM | 265 | NM | 7.3 | NM | NM | NM | NM | 12 | <0.001 | NM | NM | NM | NM | 1.20 | NM | NM | NM | NM NM | NM | NM |
| Nov-01 Dec-02 | NM NM | 448 579 | NM NM | 232 315 | NM NM | 5.3 5.9 | NM NM | NM NM | NM NM | NM NM | 19 11.5 | <0.001 <0.001 | NM NM | NM NM | NM NM | NM NM | 0.08 | NM NM | NM NM | NM NM | NM | NM NM | NM NM |
| Oct-03 | NM | 496 | NM | 240 | NM | 11.8 | NM | NM | NM | NM | 17 | <0.001 | NM | NM | NM | NM | 0.10 | NM | NM | NM | NM | NM | NM |
| Oct-03 Dup | NM | 490 | NM | 240 | NM | 11.9 | NM | NM | NM | NM | 17 | <0.001 | NM | NM | NM | NM | 0.13 | NM | NM | NM | NM | NM | NM |
| Nov-04 | NM | 453 | NM | 239 | NM | 7.2 | NM | NM | NM | NM | 8.2 | <0.001 | NM | NM | NM | NM | 0.07 | NM | NM | NM | NM | NM | NM |
| Nov-05 | NM | 457 | NM | 265 | NM | 4.8 | NM | NM | NM | NM | 22.2 | <0.001 | NM | NM | NM | NM | 0.32 | NM | NM | NM | NM | NM | NM |
| Apr-06 | NM | 328 | 8.44 | 179 | 168 | 1.81 | <0.05 | <0.05 | 4.33 | <0.05 | 11 | NM | NM | NM | NM | NM | 0.51 | 1.35 | NM | NM | NM | NM | NM |
| Oct-06 | NM | 391 | 8.37 | 221 | 161 | 3.48 | <0.05 | <0.05 | 56.5 | <0.05 | 19.7 | NM | NM | NM | NM | NM | 0.18 | 1.95 | NM | <0.0017 | NM | NM | 7.0 |
| Apr-07 | NM | 314 | 8.47 | 183 | 151 | 1.82 | <0.05 | <0.05 | 12.0 | 0.10 | 11.1 | NM | NM | NM | NM | NM | 0.13 | 1.08 | NM | NM | NM | NM | NM |
| Nov-07 | NM | 461 | 8.31 | 255 | 255 | 3.88 | <0.05 | <0.05 | 80.8 | 0.12 | 22.0 | NM | NM | NM | NM | NM | <0.005 | 1.23 | NM | 0.0029 | NM | NM | 4.5 |
| Apr-08 | NM | 288 | 8.19 | 155 | 141 | 2.17 | 0.05 | <0.05 | 10.1 | <0.05 | 10.6 | NM | NM | NM | NM | NM | 0.04 | 1.17 | NM | <0.0009 | NM | NM | 5.0 |
| Oct-08 | NM | 548 | 8.21 | 292 | 194 | 9.12 | <0.05 | <0.05 | 63.7 | <0.05 | 12.6 | NM | NM | NM | NM | NM | 0.04 | 7.24 | NM | <0.0013 | NM | NM | 8.5 |
| Apr-09 Nov-09 | NM NM | 280 432 | 8.29 8.19 | 168 260 | 142 214 | 1.56 3.34 | <0.05 <0.05 | <0.05 <0.05 | 6.18 18.9 | <0.02 <0.05 | 10.2 20.3 | NM NM | NM NM | NM NM | NM NM | NM NM | 0.03 | 1.02 2.68 | NM NM | <0.0005 <0.0010 | NM NM | NM NM | 5.0 6.0 |
| Apr-10 | NM | 396 | 8.37 | 219 | 206 | 4.10 | 0.03 | <0.05 | 13.6 | 0.3 | 13.1 | NM | NM | NM | NM | NM | 0.00 | 3.30 | 2.16 | 0.0108 | NM | NM | 8.0 |
| Nov-10 | <5 | 509 | 8.29 | 278 | 230 | 12.1 | 0.37 | <0.05 | 58.5 | <0.02 | 17.2 | <0.001 | 0.96 | <0.05 | 0.016 | <0.005 | <0.01 | NM | NM | <0.0004 | NM | NM | 4.0 |
| Apr-11 | <5 | 370 | 8.16 | 199 | 175 | 4.47 | 0.16 | <0.05 | 13.6 | 0.25 | 10.5 | <0.001 | 1.09 | <0.05 | 0.013 | 0.009 | 0.10 | NM | NM | 0.0014 | 405 | 7.57 | 7.3 |
| Nov-11 | <5 | 363 | 8.17 | 234 | 195 | 7.08 | <0.05 | <0.05 | 27.5 | 0.23 | 17.6 | <0.001 | 1.09 | <0.02 | 0.017 | <0.005 | <0.01 | NM | NM | 0.0019 | 426 | 7.76 | 7.1 |
| Apr-12 | <5 | 400 | 8.10 | 220 | 206 | 5.48 | 0.23 | <0.05 | 8.74 | <0.02 | 10.9 | 0.0010 | 0.82 | 0.03 | 0.017 | <0.005 | 0.04 | NM | NM | <0.0004 | 410 | 8.08 | 7.3 |
| Nov-12 | <5 | 586 | 8.29 | 305 | 186 | 22.3 | <0.05 | <0.05 | 133 | 0.04 | 12.1 | <0.001 | 0.70 | <0.02 | 0.055 | 0.006 | 0.03 | NM | 5.93 | 0.0007 | 628 | 8.14 | 5.1 |
| Apr-13 | <5 | 333 | 7.97 | 168 | 152 | 6.69 | 0.1 | <0.05 | 14.4 | 0.09 | 8.5 | <0.001 | 0.75 | <0.02 | <0.010 | <0.005 | <0.01 | NM | 1.01 | 0.0012 | 319 | 8.03 | 5.2 |
| Nov-13 | <5 | 422 | 8.31 | 205 | 180 | 7.01 | 0.11 | <0.10 | 36.1 | 0.08 | 17.6 | 0.0010 | 0.88 | <0.02 | 0.017 | 0.005 | <0.01 | 4.16 | 1.31 | 0.0014 | 418 | 8.22 | 3.1 |
| May-14 | <5 | 348 | 8.16 | 181 | 169 | 4.20 | <0.05 | <0.05 | 6.87 | 0.15 | 12.2 | <0.001 | 0.76 | <0.02 | 0.012 | <0.005 | 0.02 | NM | 0.96 | 0.0033 | 140 | 8.02 | 11.9 |
| Oct-14 | <5 | 458 | 8.26 | 241 | 230 | 8.42 | <0.05 | <0.05 | 10.4 | 0.04 | 16.2 | <0.001 | 0.62 | 0.07 | 0.024 | <0.005 | 0.06 | 5.26 | 2.15 | 0.0003 | 419 | 7.72 | 8.7 |
| Apr-15 Oct-15 | <5 <5 | 361 441 | 8.12 8.17 | 187 233 | 184 211 | 5.36 8.83 | <0.05 <0.10 | <0.05 <0.10 | 6.62 16.4 | <0.02 <0.02 | 9.8 18.1 | <0.001 <0.001 | 0.46 0.86 | <0.02 <0.02 | 0.012 | <0.005 <0.005 | 0.02 <0.01 | NM NM | 1.09 0.87 | 0.00001 | 364 287 | 6.70 6.23 | 3.3 7.1 |
| Apr-16 | <5 | 312 | 8.05 | 163 | 156 | 3.68 | <0.10 | <0.10 | 11.7 | <0.02 | 11.7 | <0.001 | 1.20 | <0.02 | NM | NM | NM | NM | 0.87 | 0.00001 | 97 | 7.14 | 8.5 |
| Nov-16 | <5 | 534 | 7.44 | 247 | 235 | 14.4 | <0.05 | <0.05 | 49.0 | <0.02 | 18.3 | <0.001 | 0.88 | <0.02 | 0.025 | <0.005 | <0.01 | NM | 2.88 | 0.00008 | 461 | 7.38 | 7.9 |
| Apr-17 | <5 | 354 | 8.20 | 189 | 168 | 3.99 | <0.05 | <0.05 | 12.4 | <0.02 | 12.3 | <0.001 | 0.51 | <0.02 | 0.015 | <0.005 | 0.04 | NM | 1.18 | 0.00021 | 385 | 7.75 | 10.5 |
| Nov-17 | <5 | 517 | 8.04 | 265 | 235 | 9.71 | <0.10 | <0.10 | 37.1 | <0.02 | 19.2 | <0.001 | 1.04 | 0.03 | 0.038 | <0.005 | <0.01 | 7.03 | 1.71 | 0.00027 | 323 | 8.04 | 5.2 |
| May-18 | <2 | 300 | 8.12 | 160 | 160 | 2.80 | <0.10 | <0.010 | <1.0 | <0.050 | 11.0 | <0.0010 | 0.39 | <0.020 | 0.015 | <0.005 | <0.1 | NM | NM | <0.001 | 195 | 7.97 | 7.6 |
| Nov-18 | <5 | 468 | 8.05 | 225 | 216 | 9.17 | 0.23 | <0.05 | 30.4 | <0.02 | 16.0 | 0.002 | 0.62 | <0.02 | 0.033 | <0.005 | 0.02 | NM | NM | <0.001 | 238 | 7.58 | 0.0 |
| Apr-19 | <5 | 99 | 7.30 | 44.8 | 55 | 0.52 | <0.05 | <0.05 | 0.80 | <0.02 | 2.9 | 0.001 | 1.03 | 0.11 | <0.010 | <0.005 | <0.01 | 0.32 | 0.66 | <0.001 | 46 | 7.70 | 0.0 |
| Oct-19 | <5 | 455 | 7.93 | 249 | 231 | 7.53 | <0.05 | <0.05 | 19.1 | <0.02 | 21.7 | 0.002 | 0.66 | 0.02 | 0.030 | <0.005 | <0.01 | 5.46 | 1.70 | <0.001 | 375 | 7.78 | 10.7 |
| Apr-20 | <5 | 494 | 7.77 | 220 | 221 | 5.50 | <0.05 | <0.05 | 7.53 | <0.02 | 13.6 | 0.003 | 0.74 | 0.02 | 0.017 | <0.005 | 0.06 | 3.57 | 1.56 | <0.001 | 450 | 7.81 | 4.3 |
| Oct-20 | <2 | 500 | 8.18 | 286 | 264 | 7.63 | <0.05 | <0.05 | 16.8 | <0.02 | 18.2 | 0.003 | 0.74 | 0.10 | 0.031 | <0.005 | 0.05 | 6.20 | 2.01 | <0.001 | 314 | 8.01 | 6.1 |
| May-21 | <2 | 402 | 8.13 | 208 | 196 | 4.82 | <0.05 | <0.05 | 3.66 | <0.02 | 8.4 | 0.001 | 0.25 | 0.02 | 0.018 | <0.005 | 0.082 | 3.41 | 1.50 | <0.001 | 290 | 7.90 | 7.3 |
| Oct-21 Apr-22 | <2 <2 | 593 355 | 8.01 7.89 | 320 190 | 300 181 | 7.33 3.26 | <0.05 <0.05 | <0.05 <0.05 | 4.41 5.75 | <0.02 <0.02 | 55.0 10.6 | 0.026 <0.001 | 1.03 0.57 | <0.02 <0.02 | 0.024 | <0.020 <0.020 | 0.17 0.15 | NM 2.62 | NM 1.88 | <0.001 <0.001 | 452 255 | 7.78 7.01 | 14.0 9.5 |
| Sep-22 | <2 | 464 | 7.89 | 241 | 217 | 5.06 | <0.05 | <0.05 | 7.15 | <0.02 | 23.2 | 0.008 | 0.57 | <0.02 | 0.020 | <0.020 | 0.15 | 4.52 | 0.67 | <0.001 | 350 | 6.73 | 15.9 |
| Apr-23 | <2 | 383 | 7.09 | 218 | 193 | 2.95 | <0.05 | <0.05 | 4.53 | <0.02 | 10.2 | 0.005 | 0.74 | <0.02 | 0.024 | <0.020 | 0.10 | 2.77 | 1.78 | <0.001 | 278 | 7.49 | 7.5 |
| Nov-23 | <2 | 493 | 7.83 | 284 | 292 | 5.52 | 0.10 | <0.05 | 8.82 | <0.02 | 11.6 | 0.003 | 3.03 | 0.17 | 0.039 | <0.020 | 3.96 | 4.31 | 1.00 | <0.001 | 313 | 7.69 | 0.0 |
| Apr-24 | <2 | 328 | 8.16 | 176 | 204 | 0.69 | <0.05 | <0.05 | 0.75 | 0.03 | 7.8 | 0.002 | <0.10 | 0.05 | 0.017 | <0.020 | <0.050 | 1.78 | 1.69 | 0.0012 | 357 | 8.22 | 11.7 |
| Nov-24 | <20 | 471 | 7.91 | 269 | 270 | 5.68 | <0.05 | <0.05 | 10.8 | <0.02 | 17.4 | <0.001 | 0.18 | <0.02 | 0.017 | <0.020 | 0.083 | 4.94 | 2.07 | <0.001 | 540 | 8.22 | 11.7 |
| | | 100 | | | | | | | | | | | | | | | | | 10.000 | | | | |
| Average | <5 | 431 | 8.10 | 231 | 199 | 6.05 | 0.059 | <0.10 | 22.4 | 0.047 | 14.7 | 0.0020 | 0.82 | 0.029 | 0.023 | 0.0048 | 0.21 | 3.36 | 1.68 | 0.0009 | 341 | 7.67 | 7.01 |
| Std. Dev. | NA | 96.4 | 0.24 | 52.5 | 46.4 | 3.81 | 0.074 | NA | 27.0 | 0.072 | 7.32 | 0.0042 | 0.51 | 0.038 | 0.010 | 0.0034 | 0.58 | 2.01 | 1.09 | 0.0018 | 126 | 0.50 | 3.61 |

- Notes:


 1. ODWS = Ontario Drinking Water Standards (June 2003, Revised June 2006)

 2. PWQO = Provincial Water Quality Objectives
- 3. NM = Not Monitored; NV = No value specified; NA = Not Applicable.
- Results presented in mg/L (milligrams per litre) unless otherwise specified. μS/cm = microsiemens per centimeter.
 Samples analyzed by AGAT Laboratories Limited.
- 6. * indicates outlier interpreted as sample or lab error.
- Data prior to 2006 from Annual Monitoring Report (2005), Henderson, Paddon and Associates, Ltd.
 Values reported as less than detection limits used as 1/2 detection limit for calculation of averages and plotting.


Surface Water: S-1 Chloride, Conductivity and Hardness




Surface Water: S-4
Chloride, Conductivity and Hardness




Surface Water: S-5
Chloride, Conductivity and Hardness




Surface Water: S-6 Chloride, Conductivity and Hardness




Surface Water: S-6A Chloride, Conductivity and Hardness



Surface Water: S-7 Chloride, Conductivity and Hardness



Surface Water: S-8 Chloride, Conductivity and Hardness



Surface Water: S-9
Chloride, Conductivity and Hardness

